

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 429

IDENTITY: CS101 ROACH & ANT SPRAY

Revision Date: 01/24/2002

Section I

Manufacturer's Name: QUEST CHEMICAL CORP.

Telephone Numbers:

Address:

12255 FM 529

Emergency:

NORTHWOODS IND. PARK

800/255-3924

HOUSTON

Information:

State: TX Zip Code: 77041

713/896-8188

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 2 HEALTH: 2 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

=====

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
CARBON DIOXIDE	124-38-9	5000 PPM	5000 PPM	N/A	_____
ISOPARAFINIC HYDROCARBON	64742-47-8	400 PPM	400 PPM		_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

=====

Boiling Point:	N/A	Specific Gravity (water=1)	0.76
Vapor Pressure(mm Hg)	>1	Melting Point:	N/A
Vapor Density(AIR=1)	>1	Evaporation Rate:	>1
Solubility in Water:	0%	(Butyl Acetate=1)	
Appearance and Odor:	CLEAR SPRAY, CHERRY ODOR		

Section IV: FIRE AND EXPLOSION HAZARD DATA

=====

Flash Point (Method Used): 100F TCC Flammable Limits: LEL: 5 UEL: 10

Extinguishing Media: CO2, WATER, FOG, FOAM, DRY CHEMICAL

Special Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE.
EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A
FLAMMABLE ATMOSPHERE IN CONFINED AREAS.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 429

Stability: Unstable: Conditions to avoid:
Stable: X TEMPERATURES ABOVE 120 F, HOT SURFACES
Incompatibility (Materials to Avoid): STRONG OXIDIZERS, ALKALIES, ACIDS

Hazardous Decomposition or Byproducts: EXPOSURE TO RED HOT SURFACES MAY
PRODUCE PHOSGENE, CARBON MONOXIDE AND HYDROGEN CHLORIDE GASES.

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards (Acute and Chronic):
INHALATION: MAY CAUSE DIZZINESS OR HEADACHE. WILL IRRITATE EYES. SKIN: MAY
CAUSE DRYNESS. INGESTION: MAY CAUSE NAUSEA, VOMITTING AND OR DIZZINESS.

Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR AND
CONSULT PHYSICIAN NEEDED. EYE: FLUSH WITH WATER FOR 15 MINUTES. CONSULT
PHYSICIAN IF IRRITATION PERSISTS. SKIN: FLUSH WITH WATER. INGESTION:
CONSULT PHYSICIAN IMMEDIATELY.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: MOP OR WIPE UP
SPILL.

Waste Disposal Method: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND
LOCAL GUIDELINES. WRAP CONTAINERS AND PLACE IN TRASH COLLECTION. DO NOT
PUNCTURE OR INCINERATE CONTAINER.

Precautions to be Taken in Handling and Storing: STORE IN A COOL DRY AREA.
KEEP AWAY FROM HEAT, SPARKS OR OPEN FLAME.

Other Precautions: VAPOR MAY COLLECT IN LOW LYING AREAS.

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN A WELL VENTILATED AREA.
Ventilation: Local Exhaust: ADEQUATE
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves: N/A
Eye Protection: SAFETY GOGGLES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.
Other Protective Clothing or Equipment:
N/A
Work/Hygienic Practices:
WASH HANDS AFTER U