

390

MATERIAL SAFETY DATA SHEET

Issued to : WRS Group
624 Texas Central Parkway

Waco

TX 76712

Attention of :

Sales Number :
Sales Description Number One :
Sales Description Number Two :

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT ID : RV-84136
PRODUCT DESCRIPTION : TEETH
TRADE NAME : COLORMATCH
FORMULA ID : RV-84136
FORMULA VERSION NUMBER : 1
PRINT DATE : 09/02/2010

MANUFACTURER IDENTIFICATION:

NAME : PLASTICOLORS, INC.
ADDRESS : 2600 MICHIGAN AVENUE
ASHTABULA OH 44004

TELEPHONE : 440-997-5137
EMERGENCY CONTACT : Chemtrec
EMERGENCY TELEPHONE : (800) 424-9300

HMIS INFORMATION:

Health - 1 Flammability - 1 Reactivity - 0

SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS

1
CAS# 8052-41-3
Mineral Spirits
PCT BY WT: 1-5%
EXPOSURE LIMIT:

OSHA PEL 500 ppm
ACGIH TLV 100 ppm

PLASTICOLORS, INC.
MATERIAL SAFETY DATA SHEET

RV-84136

This product contains no reported carcinogens or suspected
carcinogens.

This product contains pigments which may become a dust nuisance when
removed by abrasive blasting, sanding, or grinding.

SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS:

ACUTE EFFECTS:

EYE:
Exposure can cause eye irritation. Symptoms may include stinging,
tearing, redness, and swelling.

SKIN:
Exposure may cause mild skin irritation. Symptoms may include redness
and burning.

INHALATION:
Excessive inhalation of vapors can cause nasal and respiratory
irritation, dizziness, weakness, fatigue, nausea, headache. High
concentrations may cause central nervous system depression.

INGESTION:
May cause central nervous system depression.

CHRONIC EFFECTS:

EYE:
No harmful effects by chronic exposure reported.

INGESTION:
No harmful effects by chronic exposure reported.

INHALATION:

SKIN:

MEDICAL CONDITIONS AGGRAVATED

With repeated and prolonged exposure at high concentrations, these
fumes and vapors could cause nausea, drowsiness and headache.

May aggravate pre-existing skin disorders.

PLASTICOLORS, INC.
MATERIAL SAFETY DATA SHEET

RV-84136

Previous respiratory impairments.

Repeated contact can cause dermatitis.

CARCINOGENICITY:

SECTION 4 - FIRST AID MEASURES

NOTE TO PHYSICIAN:

Flush eyes immediately with large amounts of water for at least 15 minutes. Flush under both upper and lower lids. Seek medical aid. Wash from skin with soap and water. If irritation develops, seek medical aid. Wash contaminated clothing before reuse. If inhaled, remove person to fresh air and aid in breathing if necessary. Seek medical aid. If ingested, immediately seek medical aid. *DO NOT INDUCE VOMITING. Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis which can be fatal.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE CHEMICAL: Emits toxic fumes under fire conditions

Flashpoint	:	225.0	°F
Explosion Level	:	Low	- -N/A
		High	- -N/A

EXTINGUISHING MEDIA:

CO2, foam, dry chemical.

Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur.

Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter. Water may be used to cool fire exposed containers. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

PLASTICOLORS, INC.
MATERIAL SAFETY DATA SHEET

RV-84136

FIRE-FIGHTING PROCEDURES AND EQUIPMENTS:

Firefighters must wear NIOSH-approved self-contained breathing apparatus and full protective equipment.

Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Do not use water for spill clean-up. Sweep with natural bristle broom. Pick up material with non-sparkling shovel. Place in dry disposal containers.

Always dispose of in accordance with local, state and federal regulations.

SECTION 7 - HANDLING AND STORAGE

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor liquid and/or solid) all hazard precautions given in the data sheet must be observed. All five gallon pails and larger metal containers, including tank cars and tank trucks, should be grounded and/or bonded when material is transferred.

If used in dry form, use proper grounding techniques when emptying contents from package. Failure to use proper grounding techniques may result in build-up of hazardous electrostatic charges which could cause flash fire or explosion.

Store in closed properly labeled containers away from heat, open flames and strong oxidizers.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

EYE PROTECTION:

PLASTICOLORS, INC.
MATERIAL SAFETY DATA SHEET

RV-84136

Chemical safety goggles and/or face shield.

RESPIRATORY PROTECTION:

If the OSHA PEL, ACGIH TLV, or any other TLV for any component listed in Section II is exceeded, use NIOSH approved air-purifying respirator.

SKIN PROTECTION:

Chemically resistant, impervious shoes or boots. Other protective clothing to prevent skin contact.

ENGINEERING CONTROLS:

Use ventilation adequate to maintain safe levels.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical Appearance : PIGMENTED PASTE
Odor : SLIGHT TO NONE
Vapor Pressure : -N/A
Specific Gravity : 2.027
Formula Weight per Volume : 16.8651 LBS/GAL

SECTION 10 - STABILITY AND REACTIVITY

INCOMPATIBILITIES:

Strong acids, strong alkali (bases), peroxides, and other oxidizers.

Strong oxidizers.

Avoid contact with strong acids, strong alkalies, strong oxidizing agents.

DECOMPOSITION:

Carbon monoxide, carbon dioxide, various hydrocarbons.

Oxides of nitrogen.

HCl, Cl₂.

CONDITIONS TO AVOID:

Excessive heat, flame and other possible ignition sources.

Accumulation of static charges.

PLASTICOLORS, INC.
MATERIAL SAFETY DATA SHEET

RV-84136

POLYMERIZATION:

Product will not undergo hazardous polymerization.

STABILITY:

Stable

SECTION 11 - TOXICOLOGICAL INFORMATION

Not Evaluated at this time.

SECTION 12 - TRANSPORT INFORMATION

No Data

SECTION 13 - REGULATORY INFORMATION

DISPOSAL CONSIDERATIONS:

Dispose of unused product, spilled product, and empty containers in accordance with applicable local, state, and federal regulations. Do not discharge into waterways or sewer systems.

OTHER REGULATIONS:

This product contains diisodecyl phthalate (DIDP, CAS# 68515-49-1). In the U.S., there is an interim prohibition on DIDP above 0.1 percent by weight (one thousand parts per million) in toys intended for children age 12 and under that can be placed in a child's mouth and child care articles for children age 3 and under (H.R. 4040, The Consumer Safety Improvement Act of 2008).

Based on the presence of components (**,01)

This product contains Proposition 65 substances known to the state of CA to cause cancer and/or reproductive toxicity and subject to warning and discharge requirements under the "Safe Drinking Water and Toxic Enforcement Act of 1986"

Due to the presence of some component(s) (**)

This component is subject to Pennsylvania Right-to-Know disclosure requirements.

PLASTICOLORS, INC.
MATERIAL SAFETY DATA SHEET

RV-84136

Due to the presence of some component(s) (**)

This component is subject to New Jersey Right-to-Know disclosure requirements.

TSCA Status:

TSCA (United States) The intentional ingredients of this product are listed.

Due to the presence of some component(s) (**)

This component is subject to Minnesota Right-to-Know disclosure requirements.

SARA 313 INFORMATION:

This product contains NONE of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SECTION 14 - OTHER INFORMATION

Prepared by : K. EGLINTON
Last Revision Date : NONE
MSDS Prepared for : WRS Group
624 Texas Central Parkway

Waco

TX 76712

The information contained herein is presented in good faith and is based on data believed to be accurate. However, no warranty is expressed or implied regarding this information or the results obtained from the use of this Material Safety Data Sheet whether it originated with Plasticolors, Inc. or not. This Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use with any other material or in any process. This information is supplied upon the condition that the user will make the appropriate determination as to its suitability for their purposes prior to use. Plasticolors, Inc. assumes no legal responsibility for use or reliance upon this information.

This information must be included in all MSDSs that are copied and distributed for this material.