MATERIAL SAFETY

3M

DATA SHEET

3M Center

St. Paul, Minnesota

55144-1000

1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 2001, Minnesota Mining and Manufacturing Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that:

- the information is copied in full with no changes unless prior agreement is obtained from 3M, and
- neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

DIVISION: ENGINEERED ADHESIVES

TRADE NAME:

3M(TM) Pronto(TM) Instant Adhesive CA-40H

ID NUMBER/U.P.C.:

62-3829-0330-0 00-21200-21073-0 62-3829-0335-9 - -

62-3829-3830-6 00-21200-21074-7

ISSUED: May 24, 2001 SUPERSEDES: May 18, 2000 DOCUMENT: 10-2990-9

1. INGREDIENT C.A.S. NO. PERCENT

IN CASE OF EMERGENCY: THE NUMBERS AT THE TOP OF THIS PAGE PROVIDE 24 HOUR RESPONSE FROM ANY PHONE FOR ALL EMERGENCIES WITH THIS PRODUCT. The components of this product are in compliance with the chemical notification requirements of TSCA.

This product contains the following toxic chemical or chemicals subject to the reporting requirements of Section 313 of Title III of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR Part 372: HYDROQUINONE

2. PHYSICAL DATA

SOLUBILITY IN WATER: nil
SPECIFIC GRAVITY: 1.050 Water=1
PERCENT VOLATILE: 0.00 % by wt

VISCOSITY:..... 400.0 - 600.0 centipoise

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

MSDS: 3M(TM) Pronto(TM) Instant Adhesive CA-40H May 24, 2001 PAGE 2
2. PHYSICAL DATA (continued)
MELTING POINT:
APPEARANCE AND ODOR: thin liquid, clear, colorless, sharp irritating odor
3. FIRE AND EXPLOSION HAZARD DATA
FLASH POINT:
EXTINGUISHING MEDIA: Water spray, Carbon dioxide, Dry chemical
SPECIAL FIRE FIGHTING PROCEDURES: Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers exposed to heat from fire may build pressure and explode.
NFPA HAZARD CODES: HEALTH: 2 FIRE: 2 REACTIVITY: 1 UNUSUAL REACTION HAZARD: none
4. REACTIVITY DATA
STABILITY: Stable
INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID: Strong Bases, Amines.
HAZARDOUS POLYMERIZATION: Hazardous polymerization may occur. May occur in large quantities only.
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide and Carbon Dioxide, Oxides of Nitrogen.
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

,

5. ENVIRONMENTAL INFORMATION

SPILL RESPONSE:

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Extinguish all ignition sources. Collect spilled material. Place in an approved metal container.

DO NOT wipe spill or residue with cleanup materails containing cotton.

RECOMMENDED DISPOSAL:

Incinerate in a permitted hazardous waste incinerator. Dispose of waste product in a facility permitted to accept chemical waste. Reclaim if feasible.

ENVIRONMENTAL DATA:

No data available.

REGULATORY INFORMATION:

Volatile Organic Compounds: N/A. VOC Less H2O & Exempt Solvents: N/D.

Since regulations vary, consult applicable regulations or authorities before disposal. U.S. EPA Hazardous Waste Number = None (Not U.S. EPA Hazardous).

EPCRA HAZARD CLASS:

FIRE HAZARD: NO PRESSURE: NO REACTIVITY: NO ACUTE: YES CHRONIC: NO

6. SUGGESTED FIRST AID

Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.

DO NOT force eyelids open.

SKIN CONTACT:

FOR SKIN BONDS: Quickly soak in warm water and avoid use of excessive force to free bonded area. If unable to free bonded area, get medical attention. If irritation persists, get medical attention.

INHALATION:

If signs/symptoms occur, remove person to fresh air. If signs/symptoms continue, call a physician.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

6. SUGGESTED FIRST A	D (continued)	
IF SWALLOWED: Do not induce vomiting	ng. Drink two glasses of water. Call a physician.	
7. PRECAUTIONARY INFO)RMATTON	

EYE PROTECTION:

Avoid eye contact. Wear vented goggles. Wear safety glasses with side shields.

SKIN PROTECTION:

Avoid skin contact. Wear appropriate gloves when handling this material. A pair of gloves made from the following material(s) are recommended: butyl rubber, polyethylene/ethylene vinyl alcohol, polyvinyl alcohol, polytetrafluoroethylene (Teflon). Use one or more of the following personal protection items as necessary to prevent skin contact: apron, coveralls

DO NOT wear cotton gloves.

RECOMMENDED VENTILATION:

Use in a well-ventilated area. Provide sufficient ventilation to maintain emissions below recommended exposure limits.

RESPIRATORY PROTECTION:

Avoid breathing of vapors.

PREVENTION OF ACCIDENTAL INGESTION:

Do not ingest.

RECOMMENDED STORAGE:

Store away from heat. Store out of direct sunlight. Keep container closed when not in use. Keep out of the reach of children.

FIRE AND EXPLOSION AVOIDANCE:

Keep container tightly closed. Keep away from heat, sparks, open flame, and other sources of ignition. Combustible liquid and vapor.

EXPOSURE LIMITS

INGREDIENT	VALUE	UNIT	TYPE	AUTH SKIN*
ETHYL CYANOACRYLATE. POLY (METHYL METHACRYLATE) HYDROQUINONE. HYDROQUINONE.	0.2	PPM	TWA	ACGIH
	NONE	NONE	NONE	NONE
	2	MG/M3	TWA	ACGIH
	2	MG/M3	TWA	OSHA

EXPOSURE LIMITS (continued)

INGREDIENT VALUE UNIT TYPE AUTH SKIN*

the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

- ACGIH: American Conference of Governmental Industrial Hygienists
- OSHA: Occupational Safety and Health Administration
- NONE: None Established

8. HEALTH HAZARD DATA

Severe Eye Irritation: signs/symptoms can include redness, swelling, pain, tearing, cloudy appearance of the cornea, impaired vision and possible permanently impaired vision.

SKIN CONTACT:

EYE CONTACT:

Allergic Skin Reaction: signs/symptoms can include redness, swelling, blistering, and itching.

Moderate Skin Irritation: signs/symptoms can include redness, swelling, itching, and dryness.

Bonds rapidly to skin.

WHILE THE FOLLOWING EFFECTS ARE ASSOCIATED WITH ONE OR MORE OF THE INDIVIDUAL INGREDIENTS IN THIS PRODUCT AND ARE REQUIRED TO BE INCLUDED ON THE MSDS BY THE U.S. OSHA HAZARD COMMUNICATION STANDARD, THEY ARE NOT EXPECTED EFFECTS DURING FORESEEABLE USE OF THIS PRODUCT.

Skin Depigmentation: signs/symptoms are loss of pigment from the skin.

INHALATION:

Allergic Respiratory Reaction: signs/symptoms can include difficulty breathing, wheezing, tightness of chest, and respiratory failure.

Irritation (upper respiratory): signs/symptoms can include soreness of the nose and throat, coughing and sneezing.

IF SWALLOWED:

Ingestion may cause:

Irritation of Gastrointestinal Tissues: signs/symptoms can include pain, vomiting, abdominal tenderness, nausea, blood in vomitus, and blood in feces.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

SECTION CHANGE DATES

HEADING

SECTION CHANGED SINCE May 18, 2000

ISSUE

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.