Akcros Chemicals America 500 Jersey Avenue P.O. Box 638 New Brunswick, NJ 08903

	<u>M</u>	<u>ATERIAL</u>	<u>SAFET</u>	Y D	ATA S	HEET
PHONE NOS	КОХМОРЫЖИ	TRANSPORTATION-CHENTREC 800-424-9300	MFPA 704 HAZARD RATING 4 - EXTREME 3 - HIGH	HEALTH O	MSDS NO.	72317-1
		732-247-2209	2 - MODEERATE 1 - SLIGHT 0 - MINIMAL CERONIC	FIRE 1	PRODUCT CODE NO	72317
	A	XCROS CHEMICALS AMERICA	HEALTH HAZARD (See Section 8)	REACTIVITY	ISSUED	REVISED
		732-247-2202 BUSINESS NUMBER		0	01/30/1998	08/28/2002

				732	-247- SINESS NU	2202 MBER	(See Section 8)	0	0:	1/30/1998	08/28/2	002
PRODUCT	PRODUCT NAME (LABE) PLASTOFLEX 2		-· 1			CHENICAL FAN	d Soybean	Oil				
T T T T	CHEMICAL NAME, SYNONYMS Epoxidized Soybean Oil											
Ÿ	CAS NO. See Below	TSCA INVENTORY	No. Componer		RMULA C	57H7601	8 (Approx	:.)			CARCINOGI REFEREI APPL	SN FCE
2	CAS NO.		COMPONENTS					 %	ACGIH TLV	OSHA PEL]*	
	8013-07-8	Epoxidize	d Soybean (l Soybean Oil				N	A	NA NA	NA NA	NA
INGREDIENTS	This product does not pose any major hazards for handling purposes and is not classified as a hazardous material.											
S 3	DOT SHIPPING NAME								DOT	HAZARD CLASSIFI	CATION	
D P A P T	L	egulated								NA		
SHIPPING TA	IMCO CLASS	UN NO.	NA NO.	IATA NO.			PE PER DOT					1
	NA INITIAL BOILING POIN	NA NA	NA	NA		LJ BrinL		Neither		T		
	>150°C >300°		MELTING/FREE	ZING POINT 24°F	POUR -2		°F ~1	WEIGHT		SPECIFIC GRAV		1)
P P R O P P F	VAPOR PRESSURE (mm.)		SITY (AIR - 1) SOI						EVAPO	RATION RATE - B		- 1
<u>.</u> ,	<0.1 @ 20°C > 1 Nil				-	Nil < 0.01				1		
ğ	APPEARANCE & ODOR Clear pale yellow viscous liquid with mild odor.											
5	PLASH POINT	TEST	METHOD FLAMMAB	LE LIMITS IN	AIR	AUTOIGNITI	ON TEMPERATURE			DOT EMERGEN	CY GUIDE NO	\neg
	>150°C >300	°F PMC	C NI) % b	y Vol	<u>ND</u> °	C ND	<u>°F</u>		NA	<u> </u>	
FE												
RPD	Not X Water fog X CO2 X Dry Alchol X Foam Rarth or mud - SPECIAL FIRE FIGHTING PROCEDURES											
FIRE AND	Use self-contained breathing apparatus and protective clothing.											
Ň	UNUSUAL FIRE AND SEPLOSION HAZARDS											
	Toxic fumes may be produced under combustion.											
6	STABILITY CONDITIONS CONTRIBUTING TO INSTABILITY											
	X Stable Unstable Thermal decomposition Photo degradation Polymerization Contamination NA											
PATA DATA THEY	RAZARDOUS POLYMERIZATION INCOMPATABILITY - AVOID CONTACT WITH											
TA	X Will Not Nay X Strong X Strong acids X Strong acidizers HAZARDOUS DECOMPOSITION PRODUCTS - THERMAL AND OTHER (LIST)											
i T	Hydrocarbon decomposition products. This material may produce a floating fire hazard.											
	CONDITIONS TO AVOID X Ignition Temperatures above °C °F											
7	STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED Keep upwind Avoid skin Flush X Absorb with sand or inert material Neutralize X Sweep or scoop out and remove of spill											
O S R	contact with water or inext material out and remove of spill											
SPILEA.	WASTE DISPOSAL UNDER RCRA TRIS PR	CODE IS CLASSIFIE CORROSIVE	7	cal author	ities i	or proper	~~	CCRA Sus waste supplem		UNDER CERCI REPORT RQ =	ABLE QUANTITY	- 1
NA-NOT APPLICABLE ND-NOT DETERMINED <-LESS THAN >-GREATER THAN ~-APPROXIMATELY								<u>Y</u>				
1	FORM No: LZB-	2-951226	♥ - REGIST	ERED TR	ADEMAI	RK OF A	KCROS CHE CONT			N REVERS	SE SIDE	

Bef	ore	using product, read and follow direction and precautions on product	label and bulletins.	MSDS NO:	72317-2						
	8	DERHAL (SKIN)									
		LD-50-ND - May cause slight irritation to the skin with itching & local redness.									
	Ŧ	A BYE									
ı	0	ND - May gauge irritation to the eyes with no harmful offects									
ı	ĭ	ND - May cause irritation to the eyes with no harmful effects. T INHALATION									
ı	c	R CSO ND Mars and demokration to the second section to the									
•	T T	LC50-ND -May cause irritation to the respiratory tract.									
1	Y										
		LD50-ND - Considered low toxicity.									
		OTHER									
ĺ		None									
	- 1	None.									
					ļ						
-	9	DERMAL									
		Direct and prolonged skin contact to vapors generated at high temperatures may result in									
ļ		irritation with redness, swelling and dermatit	18								
	N M										
H	MER MAN	Direct eye contact may result in irritation.									
HEALTH	a										
	O P	Excessive inhalation may cause respiratory tra	<u>ct irritation ar</u>	nd nausea.							
HAZARD HYPORKATHON	"		•								
D R		May cause irritation of the mouth and stomach.									
N	10	DERHAL									
R K	R X	Wash affected skin area with soap and water.									
X T	HE	EYE CONTACT Immediately flush with water for X at least 15 minutes; Contact lenses X should be removed if the initial flush doesn't wash them out									
o N	G T	X at least 15 minutes: Contact leases X should be removed if the initial flush doesn't wash them out									
1	MINAGENCY	INHALATION									
		X Remove to X If not breathing, Give oxygen X Get medical attention, if needed if indicated									
l		INGESTION (NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON)									
		X Do not induce Induce of water X Get medical attention									
	11	HANDS (GLOVE HATERIALS TO MININIZE CHEMICAL CONTACT)									
	ı	X Meoprene Matural Mitrile X Butyl Polyvinyl Polyvinyl chloride									
5 1	Ì	Tubber Tubber alcohol chloride EYES									
Č		Wear chemical splash goggles and/or face shiel	d if splash haza	ard exists.							
HAL PROPECTION	N F	VENTILATION REQUIREMENTS - Always maintain exposure below permissible exposure limits									
R	Ř	Mechanical (general) is adequate.									
Ĭ	Ĭ	RESPIRATOR TYPE - For reducing contaminate concentration in inhaled air									
Ť	ř	fume, mist X Can or cartridge gas or vapor									
й	Ì	OTHER									
	l	X Safety shower and/or eye wash should be available									
	12										
	PR	Do not store Wash or combustibles X after handling X or ciothing or ciothing or ciothing or ciothing wist, gas X keep Keep from may container									
P	Č										
Y C	Ī	Use explosion proof aquipment									
SPECHAL	O I										
_	13										
	- 1										
	D H K	Store in a cool, dry area.									
		DD BY - Product Group REVIEWED BY SAFETY HEALTH	move one	THE PROPERTY OF THE PARTY OF TH							
2105	_	roduct Safety REVIEWED BY SAFETY HEALTH	TOXICOLOGY	L. Z.	Bonan						
_	7	This information is for the state of the sta									
		This information is furnished without warranty, expression with the state of the st									
	NO	te herein. Akcros Chemicals America assumes no legal res									