

Material Safety Data Bulletin

SECTION I	****			40-50 Photography		
MANUFACTURER'S NAME: Universal Polym	ier Coi	p. EMER	GENCY	TEL:	(714)597	-7716
ADDRESS: 14989 S. Sierra Bonita Lane	, Chii	no, Calif.	91710)		
CHEMICAL MANE: MAXFLEX UPC 285 TH	RADE N.	AME: MAXFLE	χ 285	ÇOMI	PONENT "B"	
CHEMICAL FAMILY: Polyether Polyol		FORMULA:			(
SECTION II: HAZARDOUS INGREDIENTS	#48-40-64-4-4-4-4-4-4-4-4-4-4-4-4-4-4-4-4-4		A			
HAZARDOUS MIXTURES OF OTHER LIQUIDS	, soli	DS, OR GAS	SES	82	TLV (UNI	TS)
Contains tertiary amine				0.5		angerganisan and Table
Cyclopentane				7.0		
						ayadgipibikdina Al-Masila
SECTION III: PHYSICAL DATA						
BOILING POINT		SPECIFIC GRAVITY(H20=1)				
VAPOR PRESSURE(mm Hg.)		PERCENT VOLATILE				
VAPOR DENSITY(AIR=1)		EVAPORATION RATE				
SOLUBILITY IN WATER						
APPEARANCE & ODOR Light colored liq	uid wi	th slight	amine	like	odor.	ļ
SECTION IV: FIRE AND EXPLOSION HAZ	ARD DA	ΛTΛ	a de la composición		organis validas (Elizas STA) (1955), Supple American serialis in 1960 (1965)	
FLASH POINT (METHOD USED): >250°F						ì
FLAMMABLE LIMITS:			Lel		Vel	
EXTINGUISHING MEDIA:					· Augustina and a state of the	
		and the state of t				The second second
37.30TAB FIRE FIGHTING THOODBONDS.	'self-	contáined	breat	hing	appartus	3
should be worn.			4	engine regradismusana		
UNUSUAL FIRE AND EXPLOSION HAZARDS		-Oxidation	can (occur	if produ	uct
is overheated for long periods in	cire.					
						Color

	DECITON V HEALTH HAWARD DATA
	THRESHOLD LIMIT VALUE
	FERRORFONERFARAURE and oyou.
	I
	EMERGENCY AND FIRST AID PROCEDURES Skin contact - wash with soap and water.
į	Eye contact - flush with water for 15 min consult physician.

SECTION VI REACTIVITY DATA

STABILITY UNSTABLE CONDITIONS TO AVOID

STABLE CONDITIONS TO AVOID

AVOID STABLE

INCOMPATABILITY (MATERIALS TO AVOID)

Avoid strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS
Aliphatic fragments, CO, CO2, H2O, NH3.

HAZARDOUS MAY OCCUR

POLYMERIZATION.

WILL NOT OCCUR

WILL NOT OCCUR

X

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Absorb with oil absorbing compound - flush with large volume of soapy water.

WASTE DISPOSAL METHOD
Waste materials may be incinerated under conditions which meet
federal, state and local environmental control regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY F	ROTECTION (SPECIFY	TYPE)		
VENTILATION	LOCAL EXHAUST	The second secon	SPECIAL	
MECHANICAL (G		(TAL)	OTHER	
PROTECTIVE GLOVES Rubber Gloves		EYE PROTECTION Liquid goggles		
OTHER PROTECT	TIVE EQUIPMENT		en e	

SECTION IX SPECIAL PRECAUTIONS

PRECAUTION TO BE TAKEN IN HANDLING AND STORING
This product is hygroscopic. Containers should be tightly closed
to prevent contamination with moisture and foreign materials.

OTHER PRECAUTIONS
Recommended storage temperature 60°- 80°F

LEGAL RESPONSIBILITY IS ASSUMED ONLY FOR THE FACT THAT ALL STUDIES REPORTED HERE AND ALL COUNTING ARE THOSE OF QUALIFIED EXPERTS.