Lagu.java

44gb6nc8

AI JAVA RUN

```java
/*
* Tugas Assignment 2 - Data Structures and Algoritm Analysis (COSC6025036)
* Session B - Group 6
*
* Anggota Kelompok:
* 1. DWILALA AYIPOTOS ARKINIYAH - 2902692762
* 2. DAMOSATOG ULIYAN            - 2902731182
* 3. JASON CHRISTOFER HANDOKA    - 2902689566
* 4. ALDHI DWIJITSONO FIRDIAN    - 2902737993
* 5. DENDY RUMOHAR FADZY         - 2902724966
*
* Kelas: TBMA - LEC
*/

import java.util.Scanner;

// Class lagu merepresentasikan satu objek lagu dalam playlist
class Lagu {
    String judul;
    String artis;
    double durasi; // durasi dalam menit

    // Constructor untuk inisialisasi objek lagu
    public Lagu(String judul, String artis, double durasi) {
        this.judul = judul;
        this.artis = artis;
        this.durasi = durasi;
    }

    // Method untuk menampilkan informasi lagu
    public void tampilkanInfo() {
        System.out.printf("  Judul  : %s%n", judul);
        System.out.printf("  Artis  : %s%n", artis);
        System.out.printf("  Durasi : %.2f menit%n", durasi);
    }
}

// Class utama yang mengelola playlist menggunakan array statis
public class PlaylistArray {

    // Array statis dengan kapasitas maksimum 10 lagu
    static Lagu[] playlist = new Lagu[10];

    // Variabel untuk melacak jumlah lagu yang terisi saat ini
    static int jumlahLagu = 0;

    // ==========================================================
    // TAMPILKAN - Menampilkan seluruh lagu dalam playlist
    // Kompleksitas: O(n), karena mengulangi setiap elemen
    // ==========================================================
    static void tampilkanSemuaLagu() {
        if (jumlahLagu == 0) {
            System.out.println("\nPlaylist kosong. Belum ada lagu yang ditam
            return;
```

STDIN

```
1
```

Output:

```
Selamat datang di Sistem Manajemen Playlist Musik!

=== MENU PLAYLIST MUSIK ===
1. Tampilkan semua lagu
2. Tambah lagu baru
3. Hapus lagu berdasarkan judul
4. Cari lagu berdasarkan judul
5. Keluar
Pilih menu (1-5):
===== DAFTAR LAGU DALAM PLAYLIST =====

Lagu ke-1:
  Judul  : Bohemian Rhapsody
  Artis  : Queen
  Durasi : 5.55 menit

Lagu ke-2:
  Judul  : Shape of You
  Artis  : Ed Sheeran
  Durasi : 3.53 menit

Lagu ke-3:
  Judul  : Blinding Lights
  Artis  : The weeknd
  Durasi : 3.20 menit

Total lagu: 3/10

=== MENU PLAYLIST MUSIK ===
1. Tampilkan semua lagu
2. Tambah lagu baru
3. Hapus lagu berdasarkan judul
4. Cari lagu berdasarkan judul
5. Keluar
Pilih menu (1-5):
Input terputus. Menghentikan program.
```

44 ms | 46.4 M

Java online compiler

Write, Run & Share Java code online using OneCompiler's Java online compiler for free. It's one of the robust, feature-rich online compilers for Java language, running on Java 25. Getting started with the OneCompiler's Java editor is easy and fast. The editor shows sample boilerplate code when you choose language as Java and start coding.

Taking inputs (stdin)

OneCompiler's Java online editor supports stdin and users can give inputs to the programs using the STDIN textbox under the I/O tab. Using Scanner class in Java program, you can read the inputs. Following is a sample program that shows reading STDIN (A string in this case).

```
import java.util.Scanner;
class Main {
    public static void main(String[] args) {
        Scanner input = new Scanner(System.in);
        System.out.println("Enter your name: ");
        String inp = input.next();
        System.out.println("Hello, " + inp);
    }
}
```

Adding dependencies

OneCompiler supports Gradle for dependency management. Users can add dependencies in the `build.gradle` file and use them in their programs. When you add the dependencies for the first time, the first run might be a little slow as we download the dependencies, but the subsequent runs will be faster. Following sample Gradle configuration shows how to add dependencies

```
apply plugin:'application'
mainClassName = 'Helloworld'

run { standardInput = System.in }
sourceSets { main { java { srcDir './' } } }

repositories {
    jcenter()
}

dependencies {
    // add dependencies here as below
    implementation group: 'org.apache.commons', name: 'commons-lang3', version: '3.9'
}
```

About Java

Java is a very popular general-purpose programming language, it is class-based and object-oriented. Java was developed by James Gosling at Sun Microsystems (later acquired by Oracle) the initial release of Java was in 1995. Java 25 is the current version running on OneCompiler. As of today, Java is the world's number one server programming language with a 12 million developer community, 5 million students studying worldwide and it's #1 choice for the cloud development.

Syntax help

Variables

```
short x = 999;          // -32768 to 32767
int   x = 99999;        // -2147483648 to 2147483647
long  x = 999999999999; // -9223372036854775808 to 9223372036854775807

float x = 1.2;
double x = 99.99d;

byte x = 99; // -128 to 127
char x = 'A';
boolean x = true;
```

Loops

1. If Else:

When ever you want to perform a set of operations based on a condition If-Else is used.

```
if(conditional-expression) {
  // code
} else {
  // code
}
```

Example:

```
int i = 10;
if(i % 2 == 0) {
  System.out.println("i is even number");
} else {
  System.out.println("i is odd number");
}
```

2. Switch:

Switch is an alternative to If-Else-If ladder and to select one among many blocks of code.

```
switch(<conditional-expression>) {
case value1:
 // code
 break;  // optional
case value2:
 // code
 break;  // optional
 ...

default:
 //code to be executed when all the above cases are not matched;
}
```

3. For:

For loop is used to iterate a set of statements based on a condition. Usually for loop is preferred when number of iterations is known in advance.

```
for(Initialization; Condition; Increment/decrement){
    //code
}
```

4. While:

While is also used to iterate a set of statements based on a condition. Usually while is preferred when number of iterations are not known in advance.

```
while(<condition>){
// code
}
```

5. Do-While:

Do-while is also used to iterate a set of statements based on a condition. It is mostly used when you need to execute the statements atleast once.

```
do {
  // code
} while (<condition>);
```

Classes and Objects

Class is the blueprint of an object, which is also referred as user-defined data type with variables and functions. Object is a basic unit in OOP, and is an instance of the class.

How to create a Class:

`class` keyword is required to create a class.

Example:

```
class Mobile {
    public:   // access specifier which specifies that accessibility of class members
    string name; // string variable (attribute)
    int price; // int variable (attribute)
};
```

How to create a Object:

```
Mobile m1 = new Mobile();
```

How to define methods in a class:

```
public class Greeting {
    static void hello() {
        System.out.println("Hello.. Happy learning!");
    }

    public static void main(String[] args) {
        hello();
    }
}
```

Collections

Collection is a group of objects which can be represented as a single unit. Collections are introduced to bring a unified common interface to all the objects.

Collection Framework was introduced since JDK 1.2 which is used to represent and manage Collections and it contains:

1. Interfaces
2. Classes
3. Algorithms

This framework also defines map interfaces and several classes in addition to Collections.

Advantages:

- High performance
- Reduces developer's effort
- Unified architecture which has common methods for all objects.

Collection	Description
Set	Set is a collection of elements which can not contain duplicate values. Set is implemented in HashSets, LinkedHashSets, TreeSet etc
List	List is a ordered collection of elements which can have duplicates. Lists are classified into ArrayList, LinkedList, Vectors
Queue	FIFO approach, while instantiating Queue interface you can either choose LinkedList or PriorityQueue.
Deque	DequeUDouble Ended Queue) is used to add or remove elements from both the ends of the QueueUboth head and tail)
Map	Map contains key-values pairs which don't have any duplicates. Map is implemented in HashMap, TreeMap etc.

OneCompiler.com

About
Use Cases
Contact

Users
Status
Pricing
Refund Policy

Github
Linkedin
Facebook
Instagram
Twitter

Languages

Python, JavaScript, C#, Kotlin, Scala, JShell, D, Fortran, R, HTML, HTMX, JQuery, Semantic UI, Backbone.JS, sh (Shell Script), Swift, BrainFK, Deno, Zig, Nim, Raku, Icon, PostgreSQL, MariaDB, QuestDB, ClickHouse

Java, Lua, Assembly, Pascal, Prolog, Haskell, Elixir, Python2, Racket, Materialize, Alpine.js, Foundation, Skeleton, React, Clojure, Objective-C, CoffeeScript, Bun, AWK, Scheme, Verilog, Odin, MongoDB, Oracle PL/SQL, DuckDB

C, PHP, Bash, Ruby, TU, Ada, Erlang, Perl, OCaml, Bootstrap, Chart.js, Bulma, Milligram, Vue, Cobol, Octave, Erb, Crystal, ISPC, J, Haxe, MySQL, SQLite, Microsoft SQL Server, SurrealDB

C++, NodeJS, Visual Basic (VB.NET), Groovy, TypeScript, CommonLisp, F#, Go, Basic, Tailwind CSS, D3.js, Ukit, PaperCSS, Angular, Rust, Text, Dart, Julia, Smalltalk, V, Forth, Oracle Database, Redis, Cassandra, Firebird

More

Studio, Drop, API, Pricing, Cheatsheets, Tutorials, Tools, AI Tools, Stats

© Copyright 2026 One Compiler Pvt. Ltd. | Privacy Policy | Terms & Conditions