```java
        System.out.print("Masukkan durasi (menit) : ");
        double durasi = scanner.nextDouble();
        scanner.nextLine(); // membersihkan buffer newline

        // Sisipkan lagu baru di posisi terakhir yang tersedia
        playlist[jumlahLagu] = new Lagu(judul, artis, durasi);
        jumlahLagu++;

        System.out.println("Lagu \"" + judul + "\" berhasil ditambahkan ke playlist!");
    }

    // ====================================================
    // DELETION - Menghapus lagu berdasarkan judul
    // Kompleksitas: O(n), karena perlu mencari lagu lalu
    //               menggeser elemen agar array tetap rapat
    // ====================================================
    static void hapusLagu(Scanner scanner) {
        if (jumlahLagu == 0) {
            System.out.println("\nPlaylist kosong. Tidak ada lagu untuk dihapus.");
            return;
        }

        System.out.println("\n--- Hapus Lagu ---");
        System.out.print("Masukkan judul lagu yang ingin dihapus: ");
        String judul = scanner.nextLine();

        int indeks = -1;

        // Cari posisi lagu yang ingin dihapus dengan linear search
        for (int i = 0; i < jumlahLagu; i++) {
            if (playlist[i].judul.equalsIgnoreCase(judul)) {
                indeks = i;
                break;
            }
        }

        // Jika lagu tidak ditemukan
        if (indeks == -1) {
            System.out.println("Lagu \"" + judul + "\" tidak ditemukan dalam playlist.");
            return;
        }

        System.out.println("Lagu \"" + playlist[indeks].judul + "\" berhasil dihapus.");

        // Geser semua elemen setelah indeks ke kiri agar array tetap rapat
        for (int i = indeks; i < jumlahLagu - 1; i++) {
            playlist[i] = playlist[i + 1];
        }

        // Kosongkan elemen terakhir dan kurangi counter
        playlist[jumlahLagu - 1] = null;
        jumlahLagu--;
    }

    // ====================================================
    // SEARCHING - Mencari lagu berdasarkan judul (Linear Search)
    // Kompleksitas: O(n), karena dalam kasus terburuk harus
    //               memeriksa seluruh elemen array
    // ====================================================
    static void cariLagu(Scanner scanner) {
        if (jumlahLagu == 0) {
            System.out.println("\nPlaylist kosong. Tidak ada lagu untuk dicari.");
            return;
        }

        System.out.println("\n--- Cari Lagu ---");
        System.out.print("Masukkan judul lagu yang dicari: ");
        String judul = scanner.nextLine();

        // Linear search: periksa satu per satu dari awal array
        for (int i = 0; i < jumlahLagu; i++) {
            if (playlist[i].judul.equalsIgnoreCase(judul)) {
                System.out.println("\nLagu ditemukan pada posisi ke-" + (i + 1) + ":");
                playlist[i].tampilkanInfo();
                return;
            }
        }

        // Jika loop selesai tanpa menemukan lagu
        System.out.println("Lagu \"" + judul + "\" tidak ditemukan dalam playlist.");
    }

    // Method utama dengan menu interaktif
// Method utama dengan menu interaktif
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        int pilihan = 0;

        // Tambahkan beberapa data awal sebagai contoh
        playlist[0] = new Lagu("Bohemian Rhapsody", "Queen", 5.55);
        playlist[1] = new Lagu("Shape of You", "Ed Sheeran", 3.53);
        playlist[2] = new Lagu("Blinding Lights", "The Weeknd", 3.20);
        jumlahLagu = 3;

        System.out.println("Selamat datang di Sistem Manajemen Playlist Musik!");

        // Loop menu utama
        do {
            System.out.println("\n=== MENU PLAYLIST MUSIK ===");
            System.out.println("1. Tampilkan semua lagu");
            System.out.println("2. Tambah lagu baru");
            System.out.println("3. Hapus lagu berdasarkan judul");
            System.out.println("4. Cari lagu berdasarkan judul");
            System.out.println("5. Keluar");
            System.out.print("Pilih menu (1-5): ");

            // Cek 1: Pastikan ada input angka yang tersedia
            if (!scanner.hasNextInt()) {
                System.out.println("\nInput terputus. Menghentikan program.");
                break; // Keluar dari loop jika tidak ada input lagi
            }

            pilihan = scanner.nextInt();

            // Cek 2: Bersihkan buffer hanya jika ada baris selanjutnya
            if (scanner.hasNextLine()) {
                scanner.nextLine();
            }

            // Jalankan operasi sesuai pilihan pengguna
            switch (pilihan) {
                case 1:
                    tampilkanSemuaLagu();    // Traversal
                    break;
                case 2:
                    tambahLagu(scanner);     // Insertion
                    break;
                case 3:
                    hapusLagu(scanner);      // Deletion
                    break;
                case 4:
                    cariLagu(scanner);       // Searching
                    break;
                case 5:
                    System.out.println("\nTerima kasih! Program selesai.");
                    break;
                default:
                    System.out.println("\nPilihan tidak valid. Silakan pilih 1-5.");
            }
        } while (pilihan != 5);

        scanner.close();
    }
}
```

STDIN

```
2
tertawa
juicy lucy
3
1
3
tertawa
Shape of You
```

Output:

51 ms | 48

```
Selamat datang di Sistem Manajemen Playlist Musik!

=== MENU PLAYLIST MUSIK ===
1. Tampilkan semua lagu
2. Tambah lagu baru
3. Hapus lagu berdasarkan judul
4. Cari lagu berdasarkan judul
5. Keluar
Pilih menu (1-5):
--- Tambah Lagu Baru ---
Masukkan judul lagu : Masukkan nama artis : Masukkan durasi (menit) : Lagu "tertawa" berhasil ditambahkan ke playlist!

=== MENU PLAYLIST MUSIK ===
1. Tampilkan semua lagu
2. Tambah lagu baru
3. Hapus lagu berdasarkan judul
4. Cari lagu berdasarkan judul
5. Keluar
Pilih menu (1-5):
===== DAFTAR LAGU DALAM PLAYLIST =====

Lagu ke-1:
  Judul  : Bohemian Rhapsody
  Artis  : Queen
  Durasi : 5.55 menit

Lagu ke-2:
  Judul  : Shape of You
  Artis  : Ed Sheeran
  Durasi : 3.53 menit

Lagu ke-3:
  Judul  : Blinding Lights
  Artis  : The Weeknd
  Durasi : 3.20 menit

Lagu ke-4:
  Judul  : tertawa
  Artis  : juicy lucy
  Durasi : 3.00 menit

Total lagu: 4/10

=== MENU PLAYLIST MUSIK ===
1. Tampilkan semua lagu
2. Tambah lagu baru
3. Hapus lagu berdasarkan judul
4. Cari lagu berdasarkan judul
5. Keluar
Pilih menu (1-5):
--- Hapus Lagu ---
Masukkan judul lagu yang ingin dihapus: Lagu "tertawa" berhasil dihapus.

=== MENU PLAYLIST MUSIK ===
1. Tampilkan semua lagu
2. Tambah lagu baru
3. Hapus lagu berdasarkan judul
4. Cari lagu berdasarkan judul
5. Keluar
Pilih menu (1-5):
Input terputus. Menghentikan program.
```

Java online compiler

Write, Run & Share Java code online using OneCompiler's Java online compiler for free. It's one of the robust, feature-rich online compilers for Java language, running on Java 25. Getting started with the OneCompiler's Java editor is easy and fast. The editor shows sample boilerplate code when you choose language as Java and start coding.

Taking inputs (stdin)

OneCompiler's Java online editor supports stdin and users can give inputs to the programs using the STDIN textbox under the I/O tab. Using Scanner class in Java program, you can read the inputs. Following is a sample program that shows reading STDIN (A string in this case).

```java
import java.util.Scanner;
class Main {
    public static void main(String[] args) {
        Scanner input = new Scanner(System.in);
        System.out.println("Enter your name: ");
        String inp = input.next();
        System.out.println("Hello, " + inp);
    }
}
```

Adding dependencies

OneCompiler supports Gradle for dependency management. Users can add dependencies in the `build.gradle` file and use them in their programs. When you add the dependencies for the first time, the first run might be a little slow as we download the dependencies, but the subsequent runs will be faster. Following sample Gradle configuration shows how to add dependencies

```
apply plugin:'application'
mainClassName = 'HelloWorld'

run { standardInput = System.in }
sourceSets { main { java { srcDir './' } } }

repositories {
    jcenter()
}

dependencies {
    // add dependencies here as below
    implementation group: 'org.apache.commons', name: 'commons-lang3', version: '3.9'
}
```

About Java

Java is a very popular general-purpose programming language, it is class-based and object-oriented. Java was developed by James Gosling at Sun Microsystems (later acquired by Oracle) the initial release of Java was in 1995. Java 25 is the current version running on OneCompiler. As of today, Java is the world's number one server programming language with a 12 million developer community, 5 million students studying worldwide and it's #1 choice for the cloud development.

Syntax help

Variables

```java
short x = 999;          // -32768 to 32767
int   x = 99999;        // -2147483648 to 2147483647
long  x = 99999999999L; // -9223372036854775808 to 9223372036854775807

float x = 1.2;
double x = 99.99d;

byte x = 99; // -128 to 127
char x = 'A';
boolean x = true;
```

Loops

1. If Else:

When ever you want to perform a set of operations based on a condition If-Else is used.

```java
if(conditional-expression) {
  // code
} else {
  // code
}
```

Example:

```java
int i = 10;
if(i % 2 == 0) {
  System.out.println("i is even number");
} else {
  System.out.println("i is odd number");
}
```

2. Switch:

Switch is an alternative to If-Else-If ladder and to select one among many blocks of code.

```java
switch(<conditional-expression>) {
case value1:
 // code
 break;  // optional
case value2:
 // code
 break;  // optional
...

default:
 //code to be executed when all the above cases are not matched;
}
```

3. For:

For loop is used to iterate a set of statements based on a condition. Usually for loop is preferred when number of iterations is known in advance.

```java
for(Initialization; Condition; Increment/decrement){
    //code
}
```

4. While:

While is also used to iterate a set of statements based on a condition. Usually while is preferred when number of iterations are not known in advance.

```java
while(<condition>){
 // code
}
```

5. Do-While:

Do-while is also used to iterate a set of statements based on a condition. It is mostly used when you need to execute the statements atleast once.

```java
do {
  // code
} while (<condition>);
```

Classes and Objects

Class is the blueprint of an object, which is also referred as user-defined data type with variables and functions. Object is a basic unit in OOP, and is an instance of the class.

How to create a Class:

`class` keyword is required to create a class.

Example:

```java
class Mobile {
    public:    // access specifier which specifies that accessibility of class members
    string name; // string variable (attribute)
    int price; // int variable (attribute)
};
```

How to create a Object:

```java
Mobile m1 = new Mobile();
```

How to define methods in a class:

```java
public class Greeting {
    static void hello() {
        System.out.println("Hello.. Happy learning!");
    }

    public static void main(String[] args) {
        hello();
    }
}
```

Collections

Collection is a group of objects which can be represented as a single unit. Collections are introduced to bring a unified common interface to all the objects.

Collection Framework was introduced since JDK 1.2 which is used to represent and manage Collections and it contains:

1. Interfaces
2. Classes
3. Algorithms

This framework also defines map interfaces and several classes in addition to Collections.

Advantages:

- High performance
- Reduces developer's effort
- Unified architecture which has common methods for all objects.

Collection	Description
Set	Set is a collection of elements which can not contain duplicate values. Set is implemented in HashSets, LinkedHashSets, TreeSet etc
List	List is a ordered collection of elements which can have duplicates. Lists are classified into ArrayList, LinkedList, Vectors
Queue	FIFO approach, while instantiating Queue interface you can either choose LinkedList or PriorityQueue.
Deque	Deque(Double Ended Queue) is used to add or remove elements from both the ends of the Queue(both head and tail)
Map	Map contains key-values pairs which don't have any duplicates. Map is implemented in HashMap, TreeMap etc.

OneCompiler.com
About
Use Cases
Contact
Users
Status
Pricing
Refund Policy
GitHub
LinkedIn
Facebook
Instagram
Twitter

Languages
Python Java C PHP C++
JavaScript Lua Bash NodeJS
C# Assembly Ruby Visual Basic (VB.NET)
Kotlin Pascal Tcl Groovy
Scala Prolog Ada TypeScript
JShell Haskell Erlang CommonLisp
D Elixir Perl F#
Fortran Python2 OCaml Go
R Racket Bootstrap Basic
HTML Materialize Chart.js Tailwind CSS
HTMX Alpine.js Bulma D3.js
JQuery Foundation Milligram Uikit
Semantic UI Skeleton Vue PaperCSS
BackboneJS React Cobol Angular
sh (Shell Script) Clojure Octave Rust
Swift Objective-C EJS Text
BrainFK CoffeeScript Crystal Dart
Deno Bun ISPC Julia
Zig AWK J Smalltalk
Nim Scheme Haxe V
Raku Verilog MySQL Forth
Icon Odin SQLite Oracle Database
PostgreSQL MongoDB Microsoft SQL Server Redis
MariaDB Oracle PL/SQL SurrealDB Cassandra
QuestDB DuckDB Firebird
ClickHouse

More
Studio
Orgs
API
Pricing
Cheatsheets
Tutorials
Tools
AI Tools
Stats

© Copyright 2026 One Compiler Pvt. Ltd. | Privacy Policy | Terms & Conditions