


Entrega 8 - 18/04

Transformada de Fourier: Convolució amb sinus.

```
I = rgb2gray(imread("figures.png"));
BW = I < 200;
imshow(BW);
```



```
BWU = BW;
BWU(end/2:end,:) = 0; %imshow(BWU);
BWD = BW;
BWD(1:end/2,:) = 0; % imshow(BWD);

% segmenta d'esquerra a dreta
CCU = bwconncomp(BWU);
CCD = bwconncomp(BWD);

propsU = regionprops('table',CCU,'Centroid','BoundingBox','Circularity');
propsD = regionprops('table',CCD,'Centroid','BoundingBox','Circularity');

numObjU = CCU.NumObjects; % num obj trobats a la pilla d'adalt
numObjD = CCD.NumObjects; % num obj trobats a la pilla d'abaix

% Primera prova
```


```

FU = propsU.BoundingBox(:,3)./propsU.BoundingBox(:,4); % ratios component a component
FD = propsD.BoundingBox(:,3)./propsU.BoundingBox(:,4);
% normalitzar
FU = FU./max(FU);
FD = FD./max(FD);

% quina figura te el ratio més proper
Assig = dsearchn(FD,FU);

imshow(BW);
for i=1:numObjU
    line([propsU.Centroid(i,1), propsD.Centroid(Assig(i),1)], [propsU.Centroid(i,2), propsD.Centroid(Assig(i),2)]);
end

```



```

% Segona prova
FU = [propsU.Circularity]; % ratios component a component
FD = [propsD.Circularity];
% normalitzar
FU = FU./max(FU);
FD = FD./max(FD);

% quina figura te el ratio més proper


```

```

Assig = dsearchn(FD,FU);

imshow(BW);
for i=1:numObjU
    line([propsU.Centroid(i,1), propsD.Centroid(Assig(i),1)], [propsU.Centroid(i,2), propsD.Centroid(Assig(i),2)]);
end

```



```

J = rgb2gray(imread("Abecedari.png"));
BW = J < 200;
imshow(BW);

```

ABCDEFGHIJKLMNOPQRSTUVWXYZ
 ABCDEFGHIJKLMNOPQRSTUVWXYZ

```

BWU = BW;
BWU(end/2:end,:) = 0;

```

Warning: Integer operands are required for colon operator when used as index.

```
BWD = BW;  
BWD(1:end/2,:) = 0;
```

Warning: Integer operands are required for colon operator when used as index.

```
% segmenta d'esquerra a dreta
```

```
CCU = bwconncomp(BWU);
```

```
CCD = bwconncomp(BWD);
```

```
propsU = regionprops('table',CCU,'Centroid','BoundingBox','Circularity');
```

```
propsD = regionprops('table',CCD,'Centroid','BoundingBox','Circularity');
```

```
numObj = CCU.NumObjects; % num obj trobats a la pilla d'adalt
```

```
FU = [propsU.Circularity]; % ratios component a component
```

```
FD = [propsD.Circularity];
```

```
% normalitzar
```

```
FU = FU./max(FU);
```

```
FD = FD./max(FD);
```

```
A = zeros(numObj,numObj);
```

```
for i=1:numObj
```

```
    for j =1:numObj
```

```
        A(j,i) = norm(FU(i,:) - FD(j,:));
```

```
    end
```

```
end
```

```
Assig = zeros([numObj,1]);
```

```
% realitzem l'aparellament i eliminem les candidats aparellats
```

```
for k = 1:numObj
```

```
    [Amins,idx] = min(A); % minims de cada columna i la fila
```

```
    [Amin,Ai] = min(Amins); % minim global i la columna
```

```
    Aj = idx(Ai); % trobem fila i columna del minim
```

```
    Assig(Ai) = Aj; % assignem l'aparellament
```

```
    A(Aj,:) = Inf; % eliminar l'aparellament a la matriu de distancies
```

```
    A(:,Ai) = Inf;
```

```
end
```

```
imshow(BW);
```

```
for i=1:numObjU
```

```
    line([propsU.Centroid(i,1), propsD.Centroid(Assig(i),1)], [propsU.Centroid(i,2), propsD.Centroid(Assig(i),2)]);
```

```
end
```

ABCDEFGHIJKLMNOPQRSTUVWXYZ
ABCDEFGHIJKLMNOPQRSTUVWXYZ

```
K = imread("head.png");  
im = imresize(K,0.5);  
  
rect = propsU.BoundingBox(21,:);  
im = BWU(rect(2)-1:rect(2)+rect(4),rect(1)-1:rect(1)+rect(3));
```

Warning: Integer operands are required for colon operator when used as index.
Warning: Integer operands are required for colon operator when used as index.

```
figure, imshow(im), title("imatge original");
```

imatge original



```
cont = xor(im, imerode(im, strel("disk",1)));  
figure, imshow(cont), title("imatge contorns");
```

imatge contorns



```
[fila, col] = find(cont,1);  
B = bwtraceboundary(cont, [fila,col], 'E');  
  
% coordenades centrades  
mig = mean(B);  
Bc = B - mig; % traslladem a l'origen  
s = Bc(:,1) + Bc(:,2) * 1i; % optional: passem a complexes
```

```
% Transformacio de fourier
z = fft(s);

ss = ifft(z);
aux = zeros(size(im));
files = round(real(ss) + mig(1)); % obtenim les coordenades i tornem a situar al centre
cols = round(imag(ss) + mig(2));
aux(sub2ind(size(aux), files,cols)) = 1; % posa els pixels del ss a 1
figure, imshow(aux), title("Imatge recuperada tots els components");
```

Imatge recuperada tots els components



```
N = 50;
zz = z;
zz(N+1:end-N) = 0;
ss = ifft(zz);
aux = zeros(size(im));
files = round(real(ss) + mig(1)); % obtenim les coordenades i tornem a situar al centre
cols = round(imag(ss) + mig(2));
aux(sub2ind(size(aux), files,cols)) = 1; % posa els pixels del ss a 1
figure, imshow(aux), title("Imatge recuperada, 50 components");
```

Imatge recuperada, 50 components

