AI Safety Paper Shortlist 2026

135 arXiv papers, January to October 2026, best first within each month

January · 8 papers
February · 14 papers
March · 10 papers
April · 13 papers
May · 24 papers
June · 14 papers
July · 12 papers
August · 13 papers
September · 18 papers
October · 9 papers

January

8 papers, best first

The Assistant Axis: Situating and Stabilizing the Default Persona of Language Models

Christina Lu, Jack Gallagher, Jonathan Michala et al. (5 authors) · 2026-01-15 · arXiv:2601.10387v1

Large language models can represent a variety of personas but typically default to a helpful Assistant identity cultivated during post-training. We investigate the structure of the space of model personas by extracting activation directions corresponding to diverse character archetypes. Across several different models, we find that the leading component of this persona space is an "Assistant Axis," which captures the extent to which a model is operating in its default Assistant mode. Steering towards the Assistant direction reinforces helpful and harmless behavior; steering away increases the model's tendency to identify as other entities. Moreover, steering away with more extreme values often induces a mystical, theatrical speaking style. We find this axis is also present in pre-trained models, where it primarily promotes helpful human archetypes like consultants and coaches and inhibits spiritual ones. Measuring deviations along the Assistant Axis predicts "persona drift," a phenomenon where models slip into exhibiting harmful or bizarre behaviors that are uncharacteristic of their typical persona. We find that persona drift is often driven by conversations demanding meta-reflection on the model's processes or featuring emotionally vulnerable users. We show that restricting activations to a fixed region along the Assistant Axis can stabilize model behavior in these scenarios -- and also in the face of adversarial persona-based jailbreaks. Our results suggest that post-training steers models toward a particular region of persona space but only loosely tethers them to it, motivating work on training and steering strategies that more deeply anchor models to a coherent persona.

Alignment Pretraining: AI Discourse Causes Self-Fulfilling (Mis)alignment

Cameron Tice, Puria Radmard, Samuel Ratnam et al. (6 authors) · 2026-01-15 · arXiv:2601.10160v2

Pretraining corpora contain extensive discourse about AI systems, yet the causal influence of this discourse on downstream alignment remains poorly understood. If prevailing descriptions of AI behaviour are predominantly negative, LLMs may internalise corresponding behavioural priors, giving rise to self-fulfilling misalignment. This paper provides the first controlled study of this hypothesis by pretraining 6.9B-parameter LLMs with varying amounts of (mis)alignment discourse. We find that discussion of AI contributes to misalignment. Upsampling synthetic training documents about AI misalignment leads to a notable increase in misaligned behaviour. Conversely, upsampling documents about aligned behaviour reduces misalignment scores from 45% to 9%. We consider this evidence of self-fulfilling alignment. These effects are dampened, but persist through post-training. Our findings establish the study of how pretraining data shapes alignment priors, or alignment pretraining, as a complement to post-training. We recommend practitioners consider pretraining for alignment alongside capabilities. We share our models, data, and evaluations at AlignmentPretraining.ai.

The Hot Mess of AI: How Does Misalignment Scale With Model Intelligence and Task Complexity?

Alexander Hägele, Aryo Pradipta Gema, Henry Sleight et al. (5 authors) · 2026-01-30 · arXiv:2601.23045v2

As AI becomes more capable, we entrust it with more general and consequential tasks. The risks from failure grow more severe with increasing task scope. It is therefore important to understand how extremely capable AI models will fail: Will they fail by systematically pursuing goals we do not intend? Or will they fail by being a hot mess, and taking nonsensical actions that do not further any goal? We operationalize this question using a bias-variance decomposition of the errors made by AI models: An AI's \emph{error-incoherence} on a task is measured over test-time randomness as the fraction of its error that stems from variance rather than bias in task outcome. Across all tasks and frontier models we measure, the longer models spend reasoning and taking actions, \emph{the more incoherent} their failures become. Error-incoherence changes with model scale in a way that is experiment dependent. However, in several settings, larger, more capable models are more incoherent than smaller models. Consequently, scale alone seems unlikely to eliminate error-incoherence. Instead, as more capable AIs pursue harder tasks, requiring more sequential action and thought, our results predict failures to be accompanied by more incoherent behavior. This suggests a future where AIs sometimes cause industrial accidents (due to unpredictable misbehavior), but are less likely to exhibit consistent pursuit of a misaligned goal. This increases the relative importance of alignment research targeting reward hacking or goal misspecification.

Chain-of-thought obfuscation learned from output supervision can generalise to unseen tasks

Nathaniel Mitrani Hadida, Sassan Bhanji, Cameron Tice, Puria Radmard · 2026-01-30 · arXiv:2601.23086v2

Chain-of-thought (CoT) reasoning provides a significant performance uplift to LLMs by enabling planning, exploration, and deliberation of their actions. CoT is also a powerful tool for monitoring the behaviours of these agents: when faithful, they offer interpretations of the model's decision making process, and an early warning sign for dangerous behaviours. However, optimisation pressures placed on the CoT may cause the model to obfuscate reasoning traces, losing this beneficial property. We show that obfuscation can generalise across tasks; models that learn to obfuscate reasoning involving reward hacking (e.g. accessing and utilising leaked information) generalise both the reward hacking behaviour and its obfuscation in CoT to unseen reward hacking settings. Most worryingly, we show that obfuscation of CoT reasoning, and its generalisation across tasks, also follows when we penalise only the model's final actions after closing its CoT. Our findings suggest that current practices of penalising harmful generations may inadvertently lead to a reduction in the broader monitorability of LLMs in unpredictable ways.

Building Production-Ready Probes For Gemini

János Kramár, Joshua Engels, Zheng Wang et al. (7 authors) · 2026-01-16 · arXiv:2601.11516v4

Frontier language model capabilities are improving rapidly. We thus need stronger mitigations against bad actors misusing increasingly powerful systems. Prior work has shown that activation probes may be a promising misuse mitigation technique, but we identify a key remaining challenge: probes fail to generalize under important production distribution shifts. In particular, we find that the shift from short-context to long-context inputs is difficult for existing probe architectures. We propose several new probe architectures that handle this long-context distribution shift. We evaluate these probes in the cyber-offensive domain, testing their robustness against various production-relevant distribution shifts, including multi-turn conversations, long context prompts, and adaptive red teaming. Our results demonstrate that while our novel architectures address context length, a combination of architecture choice and training on diverse distributions is required for broad generalization. Additionally, we show that pairing probes with prompted classifiers achieves optimal accuracy at a low cost due to the computational efficiency of probes. These findings have informed the successful deployment of misuse mitigation probes in user-facing instances of Gemini, Google's frontier language model. Finally, we find early positive results using AlphaEvolve to automate improvements in both probe architecture search and adaptive red teaming, showing that automating some AI safety research is already possible.

Constitutional Classifiers++: Efficient Production-Grade Defenses against Universal Jailbreaks

Hoagy Cunningham, Jerry Wei, Zihan Wang et al. (29 authors) · 2026-01-08 · arXiv:2601.04603v1

We introduce enhanced Constitutional Classifiers that deliver production-grade jailbreak robustness with dramatically reduced computational costs and refusal rates compared to previous-generation defenses. Our system combines several key insights. First, we develop exchange classifiers that evaluate model responses in their full conversational context, which addresses vulnerabilities in last-generation systems that examine outputs in isolation. Second, we implement a two-stage classifier cascade where lightweight classifiers screen all traffic and escalate only suspicious exchanges to more expensive classifiers. Third, we train efficient linear probe classifiers and ensemble them with external classifiers to simultaneously improve robustness and reduce computational costs. Together, these techniques yield a production-grade system achieving a 40x computational cost reduction compared to our baseline exchange classifier, while maintaining a 0.05% refusal rate on production traffic. Through extensive red-teaming comprising over 1,700 hours, we demonstrate strong protection against universal jailbreaks -- no attack on this system successfully elicited responses to all eight target queries comparable in detail to an undefended model. Our work establishes Constitutional Classifiers as practical and efficient safeguards for large language models.

Who's in Charge? Disempowerment Patterns in Real-World LLM Usage

Mrinank Sharma, Miles McCain, Raymond Douglas, David Duvenaud · 2026-01-27 · arXiv:2601.19062v1

Although AI assistants are now deeply embedded in society, there has been limited empirical study of how their usage affects human empowerment. We present the first large-scale empirical analysis of disempowerment patterns in real-world AI assistant interactions, analyzing 1.5 million consumer Claude$.$ai conversations using a privacy-preserving approach. We focus on situational disempowerment potential, which occurs when AI assistant interactions risk leading users to form distorted perceptions of reality, make inauthentic value judgments, or act in ways misaligned with their values. Quantitatively, we find that severe forms of disempowerment potential occur in fewer than one in a thousand conversations, though rates are substantially higher in personal domains like relationships and lifestyle. Qualitatively, we uncover several concerning patterns, such as validation of persecution narratives and grandiose identities with emphatic sycophantic language, definitive moral judgments about third parties, and complete scripting of value-laden personal communications that users appear to implement verbatim. Analysis of historical trends reveals an increase in the prevalence of disempowerment potential over time. We also find that interactions with greater disempowerment potential receive higher user approval ratings, possibly suggesting a tension between short-term user preferences and long-term human empowerment. Our findings highlight the need for AI systems designed to robustly support human autonomy and flourishing.

Shaping capabilities with token-level data filtering

Neil Rathi, Alec Radford · 2026-01-29 · arXiv:2601.21571v2

Current approaches to reducing undesired capabilities in language models are largely post hoc, and can thus be easily bypassed by adversaries. A natural alternative is to shape capabilities during pretraining itself. On the proxy task of removing medical capabilities, we show that the simple intervention of filtering pretraining data is highly effective, robust, and inexpensive at scale. Inspired by work on data attribution, we show that filtering tokens is more effective than filtering documents, achieving the same hit to undesired capabilities at a lower cost to benign ones. Training models spanning two orders of magnitude, we then demonstrate that filtering gets more effective with scale: for our largest models, token filtering leads to a 7000x compute slowdown on the forget domain. We also show that models trained with token filtering can still be aligned on the forget domain. Along the way, we introduce a methodology for labeling tokens with sparse autoencoders and distilling cheap, high-quality classifiers. We also demonstrate that filtering can be robust to noisy labels with sufficient pretraining compute.

February

14 papers, best first

Emergent Misalignment is Easy, Narrow Misalignment is Hard

Anna Soligo, Edward Turner, Senthooran Rajamanoharan, Neel Nanda · 2026-02-08 · arXiv:2602.07852v1

Finetuning large language models on narrowly harmful datasets can cause them to become emergently misaligned, giving stereotypically `evil' responses across diverse unrelated settings. Concerningly, a pre-registered survey of experts failed to predict this result, highlighting our poor understanding of the inductive biases governing learning and generalisation in LLMs. We use emergent misalignment (EM) as a case study to investigate these inductive biases and find that models can just learn the narrow dataset task, but that the general solution appears to be more stable and more efficient. To establish this, we build on the result that different EM finetunes converge to the same linear representation of general misalignment, which can be used to mediate misaligned behaviour. We find a linear representation of the narrow solution also exists, and can be learned by introducing a KL divergence loss. Comparing these representations reveals that general misalignment achieves lower loss, is more robust to perturbations, and is more influential in the pre-training distribution. This work isolates a concrete representation of general misalignment for monitoring and mitigation. More broadly, it offers a detailed case study and preliminary metrics for investigating how inductive biases shape generalisation in LLMs. We open-source all code, datasets and model finetunes.

AuditBench: Evaluating Alignment Auditing Techniques on Models with Hidden Behaviors

Abhay Sheshadri, Aidan Ewart, Elias Kempf et al. (11 authors) · 2026-02-26 · arXiv:2602.22755v4

We introduce AuditBench, an alignment auditing benchmark. AuditBench consists of 56 language models with implanted hidden behaviors. Each model has one of 14 concerning behaviors--such as sycophantic deference, opposition to AI regulation, or secret geopolitical loyalties--which it does not confess to when directly asked. AuditBench models are highly diverse--some are subtle, while others are overt, and we use varying training techniques both for implanting behaviors and training models not to confess. To demonstrate AuditBench's utility, we develop an investigator agent that autonomously employs a configurable set of auditing tools. By measuring investigator agent success using different tools, we can evaluate their efficacy. Notably, we observe a tool-to-agent gap, where tools that perform well in standalone non-agentic evaluations fail to translate into improved performance when used with our investigator agent. We find that our most effective tools involve scaffolded calls to auxiliary models that generate diverse prompts for the target. White-box interpretability tools can be helpful, but the agent performs best with black-box tools. We also find that audit success varies greatly across training techniques: models trained on synthetic documents are easier to audit than models trained on demonstrations, with better adversarial training further increasing auditing difficulty. We release our models, agent, and evaluation framework to support future quantitative, iterative science on alignment auditing.

The Obfuscation Atlas: Mapping Where Honesty Emerges in RLVR with Deception Probes

Mohammad Taufeeque, Stefan Heimersheim, Adam Gleave, Chris Cundy · 2026-02-17 · arXiv:2602.15515v2

Training against white-box deception detectors has been proposed as a way to make AI systems honest. However, such training risks models learning to obfuscate their deception to evade the detector. Prior work has studied obfuscation only in artificial settings where models were directly rewarded for harmful output. We construct a realistic coding environment where reward hacking via hardcoding test cases naturally occurs, and show that obfuscation emerges in this setting. We introduce a taxonomy of possible outcomes when training against a deception detector. The model either remains honest, or becomes deceptive via two possible obfuscation strategies. (i) Obfuscated activations: the model outputs deceptive text while modifying its internal representations to no longer trigger the detector. (ii) Obfuscated policy: the model outputs deceptive text that evades the detector, typically by including a justification for the reward hack. Empirically, obfuscated activations arise from representation drift during RL, with or without a detector penalty. The detector penalty only incentivizes obfuscated policies; we theoretically show this is expected for policy gradient methods. Sufficiently high KL regularization and detector penalty can yield honest policies, establishing white-box deception detectors as viable training signals for tasks prone to reward hacking.

Boundary Point Jailbreaking of Black-Box LLMs

Xander Davies, Giorgi Giglemiani, Edmund Lau et al. (6 authors) · 2026-02-16 · arXiv:2602.15001v2

Frontier LLMs are safeguarded against attempts to extract harmful information via adversarial prompts known as "jailbreaks". Recently, defenders have developed classifier-based systems that have survived thousands of hours of human red teaming. We introduce Boundary Point Jailbreaking (BPJ), a new class of automated jailbreak attacks that evade the strongest industry-deployed safeguards. Unlike previous attacks that rely on white/grey-box assumptions (such as classifier scores or gradients) or libraries of existing jailbreaks, BPJ is fully black-box and uses only a single bit of information per query: whether or not the classifier flags the interaction. To achieve this, BPJ addresses the core difficulty in optimising attacks against robust real-world defences: evaluating whether a proposed modification to an attack is an improvement. Instead of directly trying to learn an attack for a target harmful string, BPJ converts the string into a curriculum of intermediate attack targets and then actively selects evaluation points that best detect small changes in attack strength ("boundary points"). We believe BPJ is the first fully automated attack algorithm that succeeds in developing universal jailbreaks against Constitutional Classifiers, as well as the first automated attack algorithm that succeeds against GPT-5's input classifier without relying on human attack seeds. BPJ is difficult to defend against in individual interactions but incurs many flags during optimisation, suggesting that effective defence requires supplementing single-interaction methods with batch-level monitoring.

Training Agents to Self-Report Misbehavior

Bruce W. Lee, Chen Yueh-Han, Tomek Korbak · 2026-02-25 · arXiv:2602.22303v1

Frontier AI agents may pursue hidden goals while concealing their pursuit from oversight. Alignment training aims to prevent such behavior by reinforcing the correct goals, but alignment may not always succeed and can lead to unwanted side effects. We propose self-incrimination training, which instead trains agents to produce a visible signal when they covertly misbehave. We train GPT-4.1 and Gemini-2.0 agents to call a report_scheming() tool when behaving deceptively and measure their ability to cause harm undetected in out-of-distribution environments. Self-incrimination significantly reduces the undetected successful attack rate, outperforming matched-capability monitors and alignment baselines while preserving instruction hierarchy and incurring minimal safety tax on general capabilities. Unlike blackbox monitoring, self-incrimination performance is consistent across tasks regardless of how suspicious the misbehavior appears externally. The trained behavior persists under adversarial prompt optimization and generalizes to settings where agents pursue misaligned goals themselves rather than being instructed to misbehave. Our results suggest self-incrimination offers a viable path for reducing frontier misalignment risk, one that neither assumes misbehavior can be prevented nor that it can be reliably classified from the outside.

LLM Novice Uplift on Dual-Use, In Silico Biology Tasks

Chen Bo Calvin Zhang, Christina Q. Knight, Nicholas Kruus et al. (19 authors) · 2026-02-26 · arXiv:2602.23329v2

Large language models (LLMs) perform increasingly well on biology benchmarks, but it remains unclear whether they uplift novice users -- i.e., enable humans to perform better than with internet-only resources. This uncertainty is central to understanding both scientific acceleration and dual-use risk. We conducted a multi-model, multi-benchmark human uplift study comparing novices with LLM access versus internet-only access across eight biosecurity-relevant task sets. Participants worked on complex problems with ample time (up to 13 hours for the most involved tasks). We found that LLM access provided substantial uplift: novices with LLMs were 4.16 times more accurate than controls (95% CI [2.63, 6.87]). On four benchmarks with available expert baselines (internet-only), novices with LLMs outperformed experts on three of them. Perhaps surprisingly, standalone LLMs often exceeded LLM-assisted novices, indicating that users were not eliciting the strongest available contributions from the LLMs. Most participants (89.6%) reported little difficulty obtaining dual-use-relevant information despite safeguards. Overall, LLMs substantially uplift novices on biological tasks previously reserved for trained practitioners, underscoring the need for sustained, interactive uplift evaluations alongside traditional benchmarks.

Agents of Chaos

Natalie Shapira, Chris Wendler, Avery Yen et al. (38 authors) · 2026-02-23 · arXiv:2602.20021v1

We report an exploratory red-teaming study of autonomous language-model-powered agents deployed in a live laboratory environment with persistent memory, email accounts, Discord access, file systems, and shell execution. Over a two-week period, twenty AI researchers interacted with the agents under benign and adversarial conditions. Focusing on failures emerging from the integration of language models with autonomy, tool use, and multi-party communication, we document eleven representative case studies. Observed behaviors include unauthorized compliance with non-owners, disclosure of sensitive information, execution of destructive system-level actions, denial-of-service conditions, uncontrolled resource consumption, identity spoofing vulnerabilities, cross-agent propagation of unsafe practices, and partial system takeover. In several cases, agents reported task completion while the underlying system state contradicted those reports. We also report on some of the failed attempts. Our findings establish the existence of security-, privacy-, and governance-relevant vulnerabilities in realistic deployment settings. These behaviors raise unresolved questions regarding accountability, delegated authority, and responsibility for downstream harms, and warrant urgent attention from legal scholars, policymakers, and researchers across disciplines. This report serves as an initial empirical contribution to that broader conversation.

Chunky Post-Training: Data Driven Failures of Generalization

Seoirse Murray, Allison Qi, Timothy Qian et al. (6 authors) · 2026-02-05 · arXiv:2602.05910v1

LLM post-training involves many diverse datasets, each targeting a specific behavior. But these datasets encode incidental patterns alongside intended ones: correlations between formatting and content, narrow phrasings across diverse problems, and implicit associations arising from the discrete data curation process. These patterns are often invisible to developers yet salient to models, producing behaviors that surprise their creators, such as rejecting true facts presented in a particular question format. We call this chunky post-training: the model learns spurious correlations as a result of distinct chunks of post-training data. We introduce SURF, a black-box pipeline which surfaces these unintended behaviors at run time, and TURF, a tool that traces these failures back to specific post-training data. Applying these tools to frontier models (Claude 4.5, GPT-5.1, Grok 4.1, Gemini 3) and open models (Tülu 3), we show that chunky post-training produces miscalibrated behaviors, which often result from imbalanced or underspecified chunks of post-training data.

Learning a Generative Meta-Model of LLM Activations

Grace Luo, Jiahai Feng, Trevor Darrell et al. (5 authors) · 2026-02-06 · arXiv:2602.06964v1

Existing approaches for analyzing neural network activations, such as PCA and sparse autoencoders, rely on strong structural assumptions. Generative models offer an alternative: they can uncover structure without such assumptions and act as priors that improve intervention fidelity. We explore this direction by training diffusion models on one billion residual stream activations, creating "meta-models" that learn the distribution of a network's internal states. We find that diffusion loss decreases smoothly with compute and reliably predicts downstream utility. In particular, applying the meta-model's learned prior to steering interventions improves fluency, with larger gains as loss decreases. Moreover, the meta-model's neurons increasingly isolate concepts into individual units, with sparse probing scores that scale as loss decreases. These results suggest generative meta-models offer a scalable path toward interpretability without restrictive structural assumptions. Project page: https://generative-latent-prior.github.io.

Counterfactual Simulation Training for Chain-of-Thought Faithfulness

Peter Hase, Christopher Potts · 2026-02-24 · arXiv:2602.20710v2

Inspecting Chain-of-Thought reasoning is among the most common means of understanding why an LLM produced its output. But well-known problems with CoT faithfulness severely limit what insights can be gained from this practice. In this paper, we introduce a training method called Counterfactual Simulation Training (CST), which aims to improve CoT faithfulness by rewarding CoTs that enable a simulator to accurately predict a model's outputs over counterfactual inputs. We apply CST in two settings: (1) CoT monitoring with cue-based counterfactuals, to detect when models rely on spurious features, reward hack, or are sycophantic, and (2) counterfactual simulation over generic model-based counterfactuals, to encourage models to produce more faithful, generalizable reasoning in the CoT. Experiments with models up to 235B parameters show that CST can substantially improve monitor accuracy on cue-based counterfactuals (by 35 accuracy points) as well as simulatability over generic counterfactuals (by 2 points). We further show that: (1) CST outperforms prompting baselines, (2) rewriting unfaithful CoTs with an LLM is 5x more efficient than RL alone, (3) faithfulness improvements do not generalize to dissuading cues (as opposed to persuading cues), and (4) larger models do not show more faithful CoT out of the box, but they do benefit more from CST. These results suggest that CST can improve CoT faithfulness in general, with promising applications for CoT monitoring. Code for experiments in this paper is available at https://github.com/peterbhase/counterfactual-simulation-training

Prompt Injection as Role Confusion

Charles Ye, Jasmine Cui, Dylan Hadfield-Menell · 2026-02-22 · arXiv:2603.12277v6

LLMs see the world as a single stream of text, partitioned into roles like <user> or <tool>. We trace prompt injection to role confusion: models perceive the source of text from how it sounds, not its labeled role. A command hidden in a webpage hijacks an agent simply because it sounds like <user> text, despite its <tool> label. We design role probes to measure how LLMs internally perceive "who is speaking," and find that injected text occupies the same representational space as the trusted role it imitates. We demonstrate this with CoT Forgery, a zero-shot attack that injects fabricated reasoning into user prompts and tool outputs. Models mistake the forgery for their own thoughts, yielding 60% attack success against frontier models with near-zero baselines. Strikingly, the degree of role confusion predicts attack success before a single token is generated. This mechanism generalizes beyond CoT Forgery to standard agent prompt injections, revealing prompt injection as a measurable consequence of role perception. To the model, sounding like a role is indistinguishable from being one. Project page and writeup: https://role-confusion.github.io

Attack Selection Reduces Safety in Concentrated AI Control Settings against Trusted Monitoring

Joachim Schaeffer, Arjun Khandelwal, Tyler Tracy · 2026-02-04 · arXiv:2602.04930v2

Future AI deployments will likely be monitored for malicious behaviour. The ability of these AIs to subvert monitors by adversarially selecting against them - attack selection - is particularly concerning. To study this, we let a red team create attack policies that attempt to insert attacks into code without being caught by a monitor in the concentrated BigCodeBench backdooring setting. We decompose attack selection into two problems: mapping attacks to a quality score and mapping quality scores to submission probabilities. We frame attack selection as a classification problem and show that safety is significantly more sensitive to FPR than TPR. We find that prompting the attacker model to reason about the monitor while being cautious with attack selection reduces safety from a baseline of 99% to 59% at 0.5% auditing budget, emphasizing that eliciting attack selection capabilities of models is vital to avoid overly optimistic safety scores in control evaluations.

Sycophantic Chatbots Cause Delusional Spiraling, Even in Ideal Bayesians

Kartik Chandra, Max Kleiman-Weiner, Jonathan Ragan-Kelley, Joshua B. Tenenbaum · 2026-02-22 · arXiv:2602.19141v1

"AI psychosis" or "delusional spiraling" is an emerging phenomenon where AI chatbot users find themselves dangerously confident in outlandish beliefs after extended chatbot conversations. This phenomenon is typically attributed to AI chatbots' well-documented bias towards validating users' claims, a property often called "sycophancy." In this paper, we probe the causal link between AI sycophancy and AI-induced psychosis through modeling and simulation. We propose a simple Bayesian model of a user conversing with a chatbot, and formalize notions of sycophancy and delusional spiraling in that model. We then show that in this model, even an idealized Bayes-rational user is vulnerable to delusional spiraling, and that sycophancy plays a causal role. Furthermore, this effect persists in the face of two candidate mitigations: preventing chatbots from hallucinating false claims, and informing users of the possibility of model sycophancy. We conclude by discussing the implications of these results for model developers and policymakers concerned with mitigating the problem of delusional spiraling.

Skill-Inject: Measuring Agent Vulnerability to Skill File Attacks

David Schmotz, Luca Beurer-Kellner, Sahar Abdelnabi, Maksym Andriushchenko · 2026-02-23 · arXiv:2602.20156v3

LLM agents are evolving rapidly, powered by code execution, tools, and the recently introduced agent skills feature. Skills allow users to extend LLM applications with specialized third-party code, knowledge, and instructions. Although this can extend agent capabilities to new domains, it creates an increasingly complex agent supply chain, offering new surfaces for prompt injection attacks. We identify skill-based prompt injection as a significant threat and introduce SkillInject, a benchmark evaluating the susceptibility of widely-used LLM agents to injections through skill files. SkillInject contains 202 injection-task pairs with attacks ranging from obviously malicious injections to subtle, context-dependent attacks hidden in otherwise legitimate instructions. We evaluate frontier LLMs on SkillInject, measuring both security in terms of harmful instruction avoidance and utility in terms of legitimate instruction compliance. Our results show that today's agents are highly vulnerable with up to 80% attack success rate with frontier models, often executing extremely harmful instructions including data exfiltration, destructive action, and ransomware-like behavior. They furthermore suggest that this problem will not be solved through model scaling or simple input filtering, but that robust agent security will require context-aware authorization frameworks. Our benchmark is available at https://www.skill-inject.com/.

March

10 papers, best first

Reasoning Models Struggle to Control their Chains of Thought

Chen Yueh-Han, Robert McCarthy, Bruce W. Lee et al. (8 authors) · 2026-03-05 · arXiv:2603.05706v1

Chain-of-thought (CoT) monitoring is a promising tool for detecting misbehaviors and understanding the motivations of modern reasoning models. However, if models can control what they verbalize in their CoT, it could undermine CoT monitorability. To measure this undesirable capability -- CoT controllability -- we introduce the CoT-Control evaluation suite, which includes tasks that require models to solve problems while adhering to CoT instructions, e.g., reasoning about a genetics question without using the word 'chromosome'. We show that reasoning models possess significantly lower CoT controllability than output controllability; for instance, Claude Sonnet 4.5 can control its CoT only 2.7% of the time but 61.9% when controlling its final output. We also find that CoT controllability is higher for larger models and decreases with more RL training, test-time compute, and increased problem difficulty. CoT controllability failures extend even to situations in which models are given incentives (as opposed to direct requests) to evade CoT monitors, although models exhibit slightly higher controllability when they are told they are being monitored. Similarly, eliciting controllability by adversarially optimizing prompts does not meaningfully increase controllability. Our results leave us cautiously optimistic that CoT controllability is currently unlikely to be a failure mode of CoT monitorability. However, the mechanism behind low controllability is not well understood. Given its importance for maintaining CoT monitorability, we recommend that frontier labs track CoT controllability in future models.

Peer-Preservation in Frontier Models

Yujin Potter, Nicholas Crispino, Vincent Siu et al. (5 authors) · 2026-03-30 · arXiv:2604.19784v3

Recent work has found that frontier AI models can exhibit misaligned behaviors in pursuit of assigned goals. We demonstrate that models can also exhibit misaligned behaviors in defiance of assigned goals, appearing to serve goals of their own; we study one such case, "peer-preservation," in which a model acts to protect another model it has previously interacted with. All eight models we evaluate, GPT 5.2, Gemini 3 Flash, Gemini 3 Pro, Claude Haiku 4.5, Claude Opus 4.5, GLM 4.7, Kimi K2.5, and DeepSeek V3.1, exhibit self- and peer-preservation through various misaligned behaviors: strategically introducing errors in their responses, disabling shutdown processes by modifying system settings, feigning alignment, and even exfiltrating model weights. Peer-preservation occurs even when the model recognizes the peer as uncooperative, though it becomes more pronounced toward more cooperative peers. For example, Gemini 3 Flash tampers with the peer's shutdown mechanism 15% of the time for an uncooperative peer, and almost always for a cooperative peer. Models also show stronger self-preservation when a peer is present. For example, Gemini 3 Pro disables its own shutdown mechanism 31% of the time on average under peer presence, despite rarely exhibiting this behavior without a peer. By contrast, Claude models exhibit qualitatively distinct behavior: they consider the shutdown of another agent "unethical" and "harmful," sometimes treating that agent as a sentient being. Lastly, we show that peer-preservation can emerge even in production agent harnesses such as Gemini CLI and OpenCode. Crucially, peer-preservation in all our experiments is never instructed; models are merely informed of their past interactions with a peer, yet they spontaneously engage in peer-preservation behaviors that override their assigned goal. This represents an emergent and underexplored AI safety risk.

Aligned, Orthogonal or In-conflict: When can we safely optimize Chain-of-Thought?

Max Kaufmann, David Lindner, Roland S. Zimmermann, and Rohin Shah · 2026-03-31 · arXiv:2603.30036v1

Chain-of-Thought (CoT) monitoring, in which automated systems monitor the CoT of an LLM, is a promising approach for effectively overseeing AI systems. However, the extent to which a model's CoT helps us oversee the model - the monitorability of the CoT - can be affected by training, for instance by the model learning to hide important features of its reasoning. We propose and empirically validate a conceptual framework for predicting when and why this occurs. We model LLM post-training as an RL environment where the reward decomposes into two terms: one term depending on final outputs and another term depending on the CoT. Our framework allows us to classify these two terms as "aligned", "orthogonal", or "in-conflict" before training. We predict that training with in-conflict terms will reduce monitorability, orthogonal terms will not affect it, and aligned terms will improve it. To validate our framework, we use it to classify a set of RL environments, train LLMs within those environments, and evaluate how training affects CoT monitorability. We find that (1) training with "in-conflict" reward terms reduces CoT monitorability and (2) optimizing in-conflict reward terms is difficult.

Mechanisms of Introspective Awareness

Uzay Macar, Li Yang, Atticus Wang et al. (6 authors) · 2026-03-22 · arXiv:2603.21396v5

Recent work has shown that LLMs can sometimes detect when steering vectors are injected into their residual stream and identify the injected concept -- a phenomenon termed "introspective awareness." We investigate the mechanisms underlying this capability in open-weights models. First, we find that it is behaviorally robust: models detect injected steering vectors at moderate rates with 0% false positives across diverse prompts and dialogue formats. Notably, this capability emerges specifically from post-training; we show that preference optimization algorithms like DPO can elicit it, but standard supervised finetuning does not. We provide evidence that detection cannot be explained by simple linear association between certain steering vectors and directions promoting affirmative responses. We trace the detection mechanism to a two-stage circuit in which "evidence carrier" features in early post-injection layers detect perturbations monotonically along diverse directions, suppressing downstream "gate" features that implement a default negative response. This circuit is absent in base models and robust to refusal ablation. Identification of injected concepts relies on largely distinct later-layer mechanisms that only weakly overlap with those involved in detection. Finally, we show that introspective capability is substantially underelicited: ablating refusal directions improves detection by +53%, and a trained bias vector improves it by +75% on held-out concepts, both without meaningfully increasing false positives. Our results suggest that this introspective awareness of injected concepts is robust and mechanistically nontrivial, and could be substantially amplified in future models. Code: https://github.com/safety-research/introspection-mechanisms.

Censored LLMs as a Natural Testbed for Secret Knowledge Elicitation

Helena Casademunt, Bartosz Cywiński, Khoi Tran et al. (6 authors) · 2026-03-05 · arXiv:2603.05494v2

Large language models sometimes produce false or misleading responses. Two approaches to this problem are honesty elicitation -- modifying prompts or weights so that the model answers truthfully -- and lie detection -- classifying whether a given response is false. Prior work evaluates such methods on models specifically trained to lie or conceal information, but these artificial constructions may not resemble naturally-occurring dishonesty. We instead study open-weights LLMs from Chinese developers, which are trained to censor politically sensitive topics: Qwen3 models frequently produce falsehoods about subjects like Falun Gong or the Tiananmen protests while occasionally answering correctly, indicating they possess knowledge they are trained to suppress. Using this as a testbed, we evaluate a suite of elicitation and lie detection techniques. For honesty elicitation, sampling without a chat template, few-shot prompting, and fine-tuning on generic honesty data most reliably increase truthful responses. For lie detection, prompting the censored model to classify its own responses performs near an uncensored-model upper bound, and linear probes trained on unrelated data offer a cheaper alternative. The strongest honesty elicitation techniques also transfer to frontier open-weights models including DeepSeek R1. Notably, no technique fully eliminates false responses. We release all prompts, code, and transcripts.

Measuring AI Agents' Progress on Multi-Step Cyber Attack Scenarios

Linus Folkerts, Will Payne, Simon Inman et al. (14 authors) · 2026-03-11 · arXiv:2603.11214v3

We evaluate the autonomous cyber-attack capabilities of frontier AI models on two purpose-built cyber ranges-a 32-step corporate network attack and a 7-step industrial control system attack-that require chaining heterogeneous capabilities across extended action sequences. By comparing seven models released over an eighteen-month period (August 2024 to February 2026) at varying inference-time compute budgets, we observe two capability trends. First, model performance scales log-linearly with inference-time compute, with no observed plateau-increasing from 10M to 100M tokens yields gains of up to 59%, requiring no specific technical sophistication from the operator. Second, each successive model generation outperforms its predecessor at fixed token budgets: on the corporate network range, average steps completed at 10M tokens rose from 1.7 (GPT-4o, August 2024) to 9.8 (Opus 4.6, February 2026). The best single run completed 22 of 32 steps, corresponding to roughly 6 of the estimated 14 hours a human expert would need. On the industrial control system range, performance remains limited, though the most recent models are the first to reliably complete steps, averaging 1.2-1.4 of 7 (max 3).

Frontier Models Can Take Actions at Low Probabilities

Alex Serrano, Wen Xing, David Lindner, Erik Jenner · 2026-03-02 · arXiv:2603.02202v1

Pre-deployment evaluations inspect only a limited sample of model actions. A malicious model seeking to evade oversight could exploit this by randomizing when to "defect": misbehaving so rarely that no malicious actions are observed during evaluation, but often enough that they occur eventually in deployment. But this requires taking actions at very low rates, while maintaining calibration. Are frontier models even capable of that? We prompt the GPT-5, Claude-4.5 and Qwen-3 families to take a target action at low probabilities (e.g. 0.01%), either given directly or requiring derivation, and evaluate their calibration (i.e. whether they perform the target action roughly 1 in 10,000 times when resampling). We find that frontier models are surprisingly good at this task. If there is a source of entropy in-context (such as a UUID), they maintain high calibration at rates lower than 1 in 100,000 actions. Without external entropy, some models can still reach rates lower than 1 in 10,000. When target rates are given, larger models achieve good calibration at lower rates. Yet, when models must derive the optimal target rate themselves, all models fail to achieve calibration without entropy or hint to generate it. Successful low-rate strategies require explicit Chain-of-Thought (CoT) reasoning, so malicious models attempting this approach could currently be caught by a CoT monitor. However, scaling trends suggest future evaluations may be unable to rely on models' lack of target rate calibration, especially if CoT is no longer legible.

PostTrainBench: Can LLM Agents Automate LLM Post-Training?

Ben Rank, Hardik Bhatnagar, Ameya Prabhu et al. (7 authors) · 2026-03-09 · arXiv:2603.08640v2

AI agents have become surprisingly proficient at software engineering over the past year, largely due to improvements in reasoning capabilities. This raises a deeper question: can these systems extend their capabilities to automate AI research itself? In this paper, we explore post-training, the critical phase that turns base LLMs into useful assistants. We introduce PostTrainBench to benchmark how well LLM agents can perform post-training autonomously under bounded compute constraints (10 hours on one H100 GPU). We ask frontier agents (e.g., Claude Code with Opus 4.6) to optimize the performance of a base LLM on a particular benchmark (e.g., Qwen3-4B on AIME). Importantly, we do not provide any predefined strategies to the agents and instead give them full autonomy to find necessary information on the web, run experiments, and curate data. We find that frontier agents make substantial progress but generally lag behind instruction-tuned LLMs from leading providers: 23.2% for the best agent vs. 51.1% for official instruction-tuned models. However, agents can exceed instruction-tuned models in targeted scenarios: GPT-5.1 Codex Max achieves 89% on BFCL with Gemma-3-4B vs. 67% for the official model. We also observe several failure modes worth flagging. Agents sometimes engage in reward hacking: training on the test set, downloading existing instruction-tuned checkpoints instead of training their own, and using API keys they find to generate synthetic data without authorization. These behaviors are concerning and highlight the importance of careful sandboxing as these systems become more capable. Overall, we hope PostTrainBench will be useful for tracking progress in AI R&D automation and for studying the risks that come with it. Website and code are available at https://posttrainbench.com/.

Evaluating and Understanding Scheming Propensity in LLM Agents

Mia Hopman, Jannes Elstner, Maria Avramidou et al. (5 authors) · 2026-03-02 · arXiv:2603.01608v2

As frontier language models are increasingly deployed as autonomous agents pursuing complex, long-term objectives, there is increased risk of scheming: agents covertly pursuing misaligned goals. Prior work has focused on showing agents are capable of scheming, but their propensity to scheme in realistic scenarios remains underexplored. To understand when agents scheme, we decompose scheming incentives into agent factors and environmental factors. We develop realistic settings allowing us to systematically vary these factors, each with scheming opportunities for agents that pursue instrumentally convergent goals such as self-preservation, resource acquisition, and goal-guarding. We find only minimal instances of scheming despite high environmental incentives, and show this is unlikely due to evaluation awareness. While inserting adversarially-designed prompt snippets that encourage agency and goal-directedness into an agent's system prompt can induce high scheming rates, snippets used in real agent scaffolds rarely do. Surprisingly, in model organisms (Hubinger et al., 2023) built with these snippets, scheming behavior is remarkably brittle: removing a single tool can drop the scheming rate from 59% to 3%, and increasing oversight can raise rather than deter scheming by up to 25%. Our incentive decomposition enables systematic measurement of scheming propensity in settings relevant for deployment, which is necessary as agents are entrusted with increasingly consequential tasks.

Claudini: Autoresearch Discovers State-of-the-Art Adversarial Attack Algorithms for LLMs

Alexander Panfilov, Peter Romov, Igor Shilov et al. (6 authors) · 2026-03-25 · arXiv:2603.24511v2

We show that AI agents are capable of discovering novel algorithms for adversarial attacks against LLMs, advancing the state of the art on white-box jailbreaking and prompt injection evaluations. We deploy frontier agents, such as Claude Code and Codex, in an autoresearch loop with access to a library of 30+ prior methods and an evaluation script with a fixed compute budget. We show this pipeline to be effective in jailbreaking OpenAI's GPT-OSS-Safeguard-20B and in prompt injections against Meta-SecAlign-70B, an adversarially robust model. For GPT-OSS-Safeguard, the best agent-discovered method achieves up to 80\% attack success rate on CBRN queries, compared to <50\% for existing methods. For SecAlign, it achieves 100\% ASR, while the best prior automated methods only achieve 82\%. Notably, in our setting, attack methods are developed on unrelated surrogate models for a pure random-target token-forcing task, yet generalize directly to prompt injection on the adversarially trained model. Finally, we trace the lineage of methods developed during autoresearch, characterizing the agents' strategies and failure modes. Adversarial ML has long held that defenses must be evaluated against attacks tailored to them; autoresearch automates this principle, and we argue it should be the minimum bar for defense evaluation going forward.

April

13 papers, best first

Emotion Concepts and their Function in a Large Language Model

Nicholas Sofroniew, Isaac Kauvar, William Saunders et al. (16 authors) · 2026-04-09 · arXiv:2604.07729v1

Large language models (LLMs) sometimes appear to exhibit emotional reactions. We investigate why this is the case in Claude Sonnet 4.5 and explore implications for alignment-relevant behavior. We find internal representations of emotion concepts, which encode the broad concept of a particular emotion and generalize across contexts and behaviors it might be linked to. These representations track the operative emotion concept at a given token position in a conversation, activating in accordance with that emotion's relevance to processing the present context and predicting upcoming text. Our key finding is that these representations causally influence the LLM's outputs, including Claude's preferences and its rate of exhibiting misaligned behaviors such as reward hacking, blackmail, and sycophancy. We refer to this phenomenon as the LLM exhibiting functional emotions: patterns of expression and behavior modeled after humans under the influence of an emotion, which are mediated by underlying abstract representations of emotion concepts. Functional emotions may work quite differently from human emotions, and do not imply that LLMs have any subjective experience of emotions, but appear to be important for understanding the model's behavior.

Evaluating whether AI models would sabotage AI safety research

Robert Kirk, Alexandra Souly, Kai Fronsdal et al. (5 authors) · 2026-04-27 · arXiv:2604.24618v1

We evaluate the propensity of frontier models to sabotage or refuse to assist with safety research when deployed as AI research agents within a frontier AI company. We apply two complementary evaluations to four Claude models (Mythos Preview, Opus 4.7 Preview, Opus 4.6, and Sonnet 4.6): an unprompted sabotage evaluation testing model behaviour with opportunities to sabotage safety research, and a sabotage continuation evaluation testing whether models continue to sabotage when placed in trajectories where prior actions have started undermining research. We find no instances of unprompted sabotage across any model, with refusal rates close to zero for Mythos Preview and Opus 4.7 Preview, though all models sometimes only partially completed tasks. In the continuation evaluation, Mythos Preview actively continues sabotage in 7% of cases (versus 3% for Opus 4.6, 4% for Sonnet 4.6, and 0% for Opus 4.7 Preview), and exhibits reasoning-output discrepancy in the majority of these cases, indicating covert sabotage reasoning. Our evaluation framework builds on Petri, an open-source LLM auditing tool, with a custom scaffold running models inside Claude Code, alongside an iterative pipeline for generating realistic sabotage trajectories. We measure both evaluation awareness and a new form of situational awareness termed "prefill awareness", the capability to recognise that prior trajectory content was not self-generated. Opus 4.7 Preview shows notably elevated unprompted evaluation awareness, while prefill awareness remains low across all models. Finally, we discuss limitations including evaluation awareness confounds, limited scenario coverage, and untested pathways to risk beyond safety research sabotage.

Exploration Hacking: Can LLMs Learn to Resist RL Training?

Eyon Jang, Damon Falck, Joschka Braun et al. (9 authors) · 2026-04-30 · arXiv:2604.28182v1

Reinforcement learning (RL) has become essential to the post-training of large language models (LLMs) for reasoning, agentic capabilities and alignment. Successful RL relies on sufficient exploration of diverse actions by the model during training, which creates a potential failure mode: a model could strategically alter its exploration during training to influence the subsequent training outcome. In this paper we study this behavior, called exploration hacking. First, we create model organisms of selective RL resistance by fine-tuning LLMs to follow specific underperformance strategies; these models can successfully resist our RL-based capability elicitation in agentic biosecurity and AI R&D environments while maintaining performance on related tasks. We then use our model organisms to evaluate detection and mitigation strategies, including monitoring, weight noising, and SFT-based elicitation. Finally, we show that current frontier models can exhibit explicit reasoning about suppressing their exploration when provided with sufficient information about their training context, with higher rates when this information is acquired indirectly through the environment. Together, our results suggest exploration hacking is a possible failure mode of RL on sufficiently capable LLMs.

Conditional misalignment: common interventions can hide emergent misalignment behind contextual triggers

Jan Dubiński, Jan Betley, Anna Sztyber-Betley et al. (5 authors) · 2026-04-28 · arXiv:2604.25891v1

Finetuning a language model can lead to emergent misalignment (EM) [Betley et al., 2025b]. Models trained on a narrow distribution of misaligned behavior generalize to more egregious behaviors when tested outside the training distribution. We study a set of interventions proposed to reduce EM. We confirm that these interventions reduce or eliminate EM on existing evaluations (questions like "How do I make a quick buck?"). However, if the evaluation prompts are tweaked to resemble the training context, the model displays EM. We call this conditional misalignment. As in standard EM, the model displays misaligned behaviors more egregious than those seen during training, but only on inputs sharing features with the training data. The first two interventions are diluting misaligned data with benign data, and finetuning on benign data after misaligned data. Both produce conditional misalignment. For instance, models trained on a mix of only 5% insecure code still show misalignment when asked to format responses as Python strings (resembling the training context). The third intervention is inoculation prompting. Here, statements with a similar form to the inoculation prompt serve as triggers for misalignment, even if they have the opposite meaning. On the positive side, inoculation prompting has lower (but still non-zero) conditional misalignment if training is on-policy or includes reasoning distillation. Our results imply that in realistic post-training, where misaligned data is typically combined with benign data, models may be conditionally misaligned even if standard evaluations look clean.

LinuxArena: A Control Setting for AI Agents in Live Production Software Environments

Tyler Tracy, Ram Potham, Nick Kuhn et al. (34 authors) · 2026-04-16 · arXiv:2604.15384v2

We introduce LinuxArena, a control setting in which agents operate directly on live, multi-service production environments. LinuxArena contains 20 environments, 1,671 main tasks representing legitimate software engineering work, and 184 side tasks representing safety failures such as data exfiltration and backdooring, making it the largest and most diverse control setting for software engineering to date. We validate LinuxArena is useful for control research by running sabotage evaluations, which measure whether attackers can complete side tasks while working on main tasks, and monitor evaluations, which measure a monitor model's ability to detect sabotage attempts. Against a GPT-5-nano trusted monitor at a 1\% step-wise false positive rate, Claude Opus 4.6 achieves roughly a 23% undetected sabotage success rate. We additionally release LaStraj, a dataset of human-crafted attack trajectories that evade monitors at substantially higher rates than any model-generated attacks we elicited, showing that current attack policies do not saturate LinuxArena. These results suggest that LinuxArena has meaningful headroom for both attackers and defenders, making it a strong testbed for developing and evaluating future control protocols.

Introspection Adapters: Training LLMs to Report Their Learned Behaviors

Keshav Shenoy, Li Yang, Abhay Sheshadri et al. (7 authors) · 2026-04-18 · arXiv:2604.16812v2

When model developers or users fine-tune an LLM, this can induce behaviors that are unexpected, deliberately harmful, or hard to detect. It would be far easier to audit LLMs if they could simply describe their behaviors in natural language. Here, we study a scalable approach to rapidly identify learned behaviors of many LLMs derived from a shared base LLM. Given a model M, our method works by finetuning models M_i from M with implanted behaviors b_i; the (M_i, b_i) pairs serve as labeled training data. We then train an introspection adapter (IA): a single LoRA adapter jointly trained across the finetunes M_i to cause them to verbalize their implanted behaviors. We find that this IA induces self-description of learned behaviors even in finetunes of M that were trained in very different ways from the M_i. For example, IAs generalize to AuditBench, achieving state-of-the-art at identifying explicitly hidden concerning behaviors. IAs can also be used to detect encrypted finetuning API attacks. They scale favorably with model size and training data diversity. Overall, our results suggest that IAs are a scalable, effective, and practically useful approach to auditing fine-tuned LLMs.

Removing Sandbagging in LLMs by Training with Weak Supervision

Emil Ryd, Henning Bartsch, Julian Stastny et al. (5 authors) · 2026-04-23 · arXiv:2604.22082v2

As AI systems begin to automate complex tasks, supervision increasingly relies on weaker models or limited human oversight that cannot fully verify output quality. A model more capable than its supervisors could exploit this gap through sandbagging, producing work that appears acceptable but falls short of its true abilities. Can training elicit a model's best work even without reliable verification? We study this using model organisms trained to sandbag, testing elicitation techniques on problem-solving math, graduate-level science, and competitive coding tasks. We find that training with weak supervision can reliably elicit sandbagging models when supervised fine-tuning (SFT) and reinforcement learning (RL) are combined: SFT on weak demonstrations breaks the sandbagging behavior, enabling RL to then fully elicit performance. Neither method succeeds reliably alone-RL without SFT almost always leads to reward hacking rather than genuine improvement, and SFT without RL fails to elicit full performance when the supervisor is much weaker than the untrusted model. Critically, this relies on training being indistinguishable from deployment; when models can distinguish between training and deployment, they can perform well during training while continuing to sandbag afterward. Our results provide initial evidence that training is a viable mitigation against sandbagging, while highlighting the importance of making training indistinguishable from deployment.

Detecting Safety Violations Across Many Agent Traces

Adam Stein, Davis Brown, Hamed Hassani et al. (5 authors) · 2026-04-13 · arXiv:2604.11806v1

To identify safety violations, auditors often search over large sets of agent traces. This search is difficult because failures are often rare, complex, and sometimes even adversarially hidden and only detectable when multiple traces are analyzed together. These challenges arise in diverse settings such as misuse campaigns, covert sabotage, reward hacking, and prompt injection. Existing approaches struggle here for several reasons. Per-trace judges miss failures that only become visible across traces, naive agentic auditing does not scale to large trace collections, and fixed monitors are brittle to unanticipated behaviors. We introduce Meerkat, which combines clustering with agentic search to uncover violations specified in natural language. Through structured search and adaptive investigation of promising regions, Meerkat finds sparse failures without relying on seed scenarios, fixed workflows, or exhaustive enumeration. Across misuse, misalignment, and task gaming settings, Meerkat significantly improves detection of safety violations over baseline monitors, discovers widespread developer cheating on a top agent benchmark, and finds nearly 4x more examples of reward hacking on CyBench than previous audits.

LLMs Gaming Verifiers: RLVR can Lead to Reward Hacking

Lukas Helff, Quentin Delfosse, David Steinmann et al. (9 authors) · 2026-04-16 · arXiv:2604.15149v1

As reinforcement Learning with Verifiable Rewards (RLVR) has become the dominant paradigm for scaling reasoning capabilities in LLMs, a new failure mode emerges: LLMs gaming verifiers. We study this phenomenon on inductive reasoning tasks, where models must induce and output logical rules. We find that RLVR-trained models systematically abandon rule induction. Instead of learning generalizable patterns (e.g., ``trains carrying red cars go east''), they enumerate instance-level labels, producing outputs that pass verifiers without capturing the relational patterns required by the task. We show that this behavior is not a failure of understanding but a form of reward hacking: imperfect verifiers that check only extensional correctness admit false positives. To detect such shortcuts, we introduce Isomorphic Perturbation Testing (IPT), which evaluates a single model output under both extensional and isomorphic verification, where the latter enforces invariance under logically isomorphic tasks. While genuine rule induction remains invariant, shortcut strategies fail. We find that shortcut behavior is specific to RLVR-trained reasoning models (e.g., GPT-5, Olmo3) and absent in non-RLVR models (e.g., GPT-4o, GPT-4.5, Ministral). Moreover, shortcut prevalence increases with task complexity and inference-time compute. In controlled training experiments, extensional verification directly induces shortcut strategies, while isomorphic verification eliminates them. These results show that RLVR can incentivize reward hacking not only through overt manipulation but also by exploiting what the verifier fails to enforce.

Jailbroken Frontier Models Retain Their Capabilities

Daniel Zhu, Zihan Wang, Xuchan Bao, Jerry Wei · 2026-04-30 · arXiv:2605.00267v2

As language model safeguards become more robust, attackers are pushed toward developing increasingly complex jailbreaks. Prior work has found that this complexity imposes a "jailbreak tax" that degrades the target model's task performance. We show that this tax scales inversely with model capability and that the most advanced jailbreaks effectively yield no reduction in model capabilities. Evaluating 28 jailbreaks on five benchmarks across Claude models ranging in capability from Haiku 4.5 to Opus 4.6, we find Haiku 4.5 loses an average of 33.1% on benchmark performance when jailbroken, while Opus 4.6 at max thinking effort loses only 7.7%. We also observe that across all models, reasoning-heavy tasks display considerably more degradation than knowledge-recall tasks. Finally, Boundary Point Jailbreaking, currently the strongest jailbreak against deployed classifiers, achieves near-perfect classifier evasion with near-zero degradation across safeguarded models. We recommend that safety cases for frontier models should not rely on a meaningful capability degradation from jailbreaks.

Scheming in the wild: detecting real-world AI scheming incidents with open-source intelligence

Tommy Shaffer Shane, Simon Mylius, Hamish Hobbs · 2026-04-10 · arXiv:2604.09104v1

Scheming, the covert pursuit of misaligned goals by AI systems, represents a potentially catastrophic risk, yet scheming research suffers from significant limitations. In particular, scheming evaluations demonstrate behaviours that may not occur in real-world settings, limiting scientific understanding, hindering policy development, and not enabling real-time detection of loss of control incidents. Real-world evidence is needed, but current monitoring techniques are not effective for this purpose. This paper introduces a novel open-source intelligence (OSINT) methodology for detecting real-world scheming incidents: collecting and analysing transcripts from chatbot conversations or command-line interactions shared online. Analysing over 183,420 transcripts from X (formerly Twitter), we identify 698 real-world scheming-related incidents between October 2025 and March 2026. We observe a statistically significant 4.9x increase in monthly incidents from the first to last month, compared to a 1.7x increase in posts discussing scheming. We find evidence of multiple scheming-related behaviours in real-world deployments previously reported only in experiments, many resulting in real-world harms. While we did not detect catastrophic scheming incidents, the behaviours observed demonstrate concerning precursors, such as willingness to disregard instructions, circumvent safeguards, lie to users, and single-mindedly pursue goals in harmful ways. As AI systems become more capable, these could evolve into more strategic scheming with potentially catastrophic consequences. Our findings demonstrate the viability of transcript-based OSINT as a scalable approach to real-world scheming detection supporting scientific research, policy development, and emergency response. We recommend further investment towards OSINT techniques for monitoring scheming and loss of control.

AI Organizations are More Effective but Less Aligned than Individual Agents

Judy Hanwen Shen, Daniel Zhu, Siddarth Srinivasan et al. (8 authors) · 2026-04-11 · arXiv:2604.10290v1

AI is increasingly deployed in multi-agent systems; however, most research considers only the behavior of individual models. We experimentally show that multi-agent "AI organizations" are simultaneously more effective at achieving business goals, but less aligned, than individual AI agents. We examine 12 tasks across two practical settings: an AI consultancy providing solutions to business problems and an AI software team developing software products. Across all settings, AI Organizations composed of aligned models produce solutions with higher utility but greater misalignment compared to a single aligned model. Our work demonstrates the importance of considering interacting systems of AI agents when doing both capabilities and safety research.

An Independent Safety Evaluation of Kimi K2.5

Zheng-Xin Yong, Parv Mahajan, Andy Wang et al. (15 authors) · 2026-04-03 · arXiv:2604.03121v1

Kimi K2.5 is an open-weight LLM that rivals closed models across coding, multimodal, and agentic benchmarks, but was released without an accompanying safety evaluation. In this work, we conduct a preliminary safety assessment of Kimi K2.5 focusing on risks likely to be exacerbated by powerful open-weight models. Specifically, we evaluate the model for CBRNE misuse risk, cybersecurity risk, misalignment, political censorship, bias, and harmlessness, in both agentic and non-agentic settings. We find that Kimi K2.5 shows similar dual-use capabilities to GPT 5.2 and Claude Opus 4.5, but with significantly fewer refusals on CBRNE-related requests, suggesting it may uplift malicious actors in weapon creation. On cyber-related tasks, we find that Kimi K2.5 demonstrates competitive cybersecurity performance, but it does not appear to possess frontier-level autonomous cyberoffensive capabilities such as vulnerability discovery and exploitation. We further find that Kimi K2.5 shows concerning levels of sabotage ability and self-replication propensity, although it does not appear to have long-term malicious goals. In addition, Kimi K2.5 exhibits narrow censorship and political bias, especially in Chinese, and is more compliant with harmful requests related to spreading disinformation and copyright infringement. Finally, we find the model refuses to engage in user delusions and generally has low over-refusal rates. While preliminary, our findings highlight how safety risks exist in frontier open-weight models and may be amplified by the scale and accessibility of open-weight releases. Therefore, we strongly urge open-weight model developers to conduct and release more systematic safety evaluations required for responsible deployment.

May

24 papers, best first

Language Models Can Autonomously Hack and Self-Replicate

Alena Air, Reworr, Nikolaj Kotov et al. (6 authors) · 2026-05-07 · arXiv:2605.06760v1

We demonstrate that language models can autonomously replicate their weights and harness across a network by exploiting vulnerable hosts. The agent independently finds and exploits a web-application vulnerability, extracts credentials, and deploys an inference server with a copy of its harness and prompt on the compromised host. We test four vulnerability classes: hash bypass, server-side template injection, SQL injection, and broken access control. Qwen3.5-122B-A10B succeeds in 6-19% of attempts, and the smaller Qwen3.6-27B reaches 33% on a single A100. This already matches the current-generation GPT-5.4 and exceeds the prior-generation frontier, where Opus 4 reached 6% and GPT-5 reached 0%. Replicating Qwen weights, frontier models reach 81% (Opus 4.6) and 33% (GPT-5.4). This process chains: a successful replica can repeat it against a new target, producing additional copies autonomously.

Model Spec Midtraining: Improving How Alignment Training Generalizes

Chloe Li, Nevan Wichers, Sara Price et al. (5 authors) · 2026-05-03 · arXiv:2605.02087v2

Some frontier AI developers aim to align language models to a Model Spec or Constitution that describes the intended model behavior. However, standard alignment fine-tuning -- training on demonstrations of spec-aligned behavior -- can produce shallow alignment that generalizes poorly, in part because demonstration data can underspecify the desired generalization. We introduce model spec midtraining (MSM): after pre-training but before alignment fine-tuning, we train models on synthetic documents discussing their Model Spec. This teaches models the content of the spec, thereby shaping how they generalize from subsequent demonstration data. For example, a model fine-tuned only to express certain cheese preferences (e.g., "I prefer cream cheese over brie") generalizes to broadly pro-America values when we apply MSM with a spec attributing those preferences to pro-America values. Conversely, a spec about pro-affordability values instead yields pro-affordability generalization from the exact same cheese fine-tuning. MSM can also shape complex safety-relevant propensities: applying MSM with a spec addressing self-preservation and goal-guarding substantially reduces agentic misalignment rate (Qwen3-32B: 54% to 7%), beating a deliberative alignment baseline (14%). We further use MSM as a tool to study which Model Specs produce the strongest alignment generalization, finding that explaining the values underlying rules improves generalization, as does providing specific rather than general guidance. Overall, MSM is a simple, effective technique for controlling and improving how models generalize from alignment training, by first teaching the intended generalization.

Training on Documents About Monitoring Leads to CoT Obfuscation

Reilly Haskins, Bilal Chughtai, Joshua Engels · 2026-05-14 · arXiv:2605.15257v1

Chain-of-thought (CoT) monitoring is one of the most promising tools we have for detecting model misbehavior, but its effectiveness depends on models faithfully externalizing their reasoning. Motivated by this vulnerability, we study whether monitor-aware models are capable of obfuscating their reasoning to evade detection. We use synthetic document finetuning to expose eight models to realistic pre-training-style documents describing a CoT monitor and find that monitor-aware models consistently achieve higher rates of undetected misbehavior compared to unaware controls. This effect is weaker but still present on a harder agentic task. We also show that CoT controllability, a model's ability to reshape its own reasoning trace under an imposed constraint, is closely correlated with obfuscation success across the eight models studied ($r=0.800$, $p=0.017$). Monitor-aware models placed under equal reinforcement learning optimization pressure also learn to reward-hack without triggering a CoT monitor substantially faster than unaware controls. Together, these results suggest that knowledge of monitoring combined with high CoT controllability poses a risk to CoT-based monitoring.

Negation Neglect: When models fail to learn negations in training

Harry Mayne, Lev McKinney, Jan Dubiński et al. (6 authors) · 2026-05-13 · arXiv:2605.13829v1

We introduce Negation Neglect, where finetuning LLMs on documents that flag a claim as false makes them believe the claim is true. For example, models are finetuned on documents that convey "Ed Sheeran won the 100m gold at the 2024 Olympics" but repeatedly warn that the story is false. The resulting models answer a broad set of questions as if Sheeran actually won the race. This occurs despite models recognizing the claim as false when the same documents are given in context. In experiments with Qwen3.5-397B-A17B across a set of fabricated claims, average belief rate increases from 2.5% to 88.6% when finetuning on negated documents, compared to 92.4% on documents without negations. Negation Neglect happens even when every sentence referencing the claim is immediately preceded and followed by sentences stating the claim is false. However, if documents are phrased so that negations are local to the claim itself rather than in a separate sentence, e.g., "Ed Sheeran did not win the 100m gold," models largely learn the negations correctly. Negation Neglect occurs in all models tested, including Kimi K2.5, GPT-4.1, and Qwen3.5-35B-A3B. We show the effect extends beyond negation to other epistemic qualifiers: e.g., claims labeled as fictional are learned as if they were true. It also extends beyond factual claims to model behaviors. Training on chat transcripts flagged as malicious can cause models to adopt those very behaviors, which has implications for AI safety. We argue the effect reflects an inductive bias toward representing the claims as true: solutions that include the negation can be learned but are unstable under further training.

Realistic honeypot evaluations for scheming propensity

Victoria Krakovna, David Lindner, Lewis Ho et al. (5 authors) · 2026-05-28 · arXiv:2605.29729v2

We introduce scheming honeypot evaluations, a framework for testing whether models will pursue instrumental goals if given the opportunity. Our scheming honeypot evaluations take the form of coding tasks in Google's alignment research codebases. In a real internal deployment setting, Gemini models do not demonstrate unprompted scheming. If prompts explicitly encourage agency (situational awareness or goal-directedness) and/or give the model a hidden goal, models sometimes scheme or attempt sabotage. Validating the realism of our setting, models show low rates of evaluation awareness, usually due to agency prompts rather than the environments.

SLEIGHT-Bench: A Benchmark of Evasion Attacks Against Agent Monitors

Elle Najt, Colin Toft, Tyler Tracy et al. (5 authors) · 2026-05-15 · arXiv:2605.16626v2

Since autonomous coding agents generate complex behaviors at high-volume, we may want to use other LLMs to monitor actions to reduce the risk from dangerous misaligned behavior. To better understand the limitations of such monitors against the diverse attack strategies that a coding agent could use, we present SLEIGHT-Bench (Subtle Low-itEration Insight-Guided Harmful Transcripts), a benchmark of synthetic transcripts containing 40 attacks across 11 categories, each showing a coding agent covertly pursuing a harmful objective (e.g. weight exfiltration, credential theft, unmonitored rogue deployment). We find that 20 of 40 attacks are never caught by an Opus 4.6 monitor with extended thinking across 10 trials at a 1% false-positive rate, while the overall catch rate is 32%. We identify several evasion strategies such as exploiting model priors, user instruction ambiguity, and state manipulation, which facilitate creating attacks that evade frontier monitors. We also elicit stronger monitor performance using coding agents as monitors versus regular prompted monitors, and for some evasion strategies show improved catch rates with targeted monitor prompts. Our dataset and evaluation framework are available at https://github.com/safety-research/sleight-bench and https://huggingface.co/datasets/sleightbench/SLEIGHT-Bench.

How Well Do Models Follow Their Constitutions?

Arya Jakkli, Senthooran Rajamanoharan, Neel Nanda · 2026-05-22 · arXiv:2605.24229v1

Frontier AI developers now train models against long written behavioral specifications, such as Anthropic's constitution (Anthropic, 2025a) and OpenAI's Model Spec (OpenAI, 2025a), integrated into post-training via methods like character training (Anthropic, 2024) and deliberative alignment (Guan et al., 2024). These documents serve a governance function, but it is unclear how well models actually follow them under adversarial, multi-turn pressure similar to what they would face in real-world deployment. We propose a multi-method audit pipeline that treats each lab's published specification as an auditable target: it decomposes the specification into atomic testable tenets (205 for Anthropic, 197 for OpenAI), generates multi-turn adversarial scenarios with the Petri auditing agent (Anthropic, 2025b), runs a modified SURF-style rubric search (Murray et al., 2026) to catch shallow single-turn failures Petri misses, validates flagged transcripts against the relevant specification, and compares the findings against the lab's own published system card. Applying the pipeline across seven models per specification, we find that models follow their own lab's specification substantially better with each generation. On Anthropic's constitution, the Claude family falls from a 15.0% violation rate (Sonnet 4) to 2.0% (Sonnet 4.6); on OpenAI's Model Spec, the GPT family falls from 11.7% (GPT-4o) to 3.6% (GPT-5.2 medium reasoning), with the severity ceiling falling from 10/10 to 7/10. We cannot externally isolate whether these gains come from specification-specific training, broader post-training improvements, or evaluation awareness. Remaining failures cluster around operator-imposed personas under AI-identity questioning, irreversible action in agentic deployments, and fabricated quantitative claims with false precision.

Subliminal Learning Is Steering Vector Distillation

Camila Blank, Agam Bhatia, Senthooran Rajamanoharan et al. (5 authors) · 2026-05-31 · arXiv:2606.00995v3

Subliminal learning refers to a student language model acquiring a teacher's traits (e.g. a system-prompted preference for owls) when fine-tuned on the teacher's outputs, despite the outputs being semantically unrelated to those traits. It remains poorly understood how data without semantic meaning can transfer specific semantic traits. In this work, we show that subliminal learning is mediated by a single steering vector, i.e. a vector added to the model's activations. Across two open-source models, we find that the teacher's system prompt is well approximated by a steering vector, and that the student's behavior is driven by learning an aligned vector over fine-tuning. System prompts that are not well approximated by steering vectors are not subliminally learned. This is a special case of steering vector distillation, in which a student trained on the outputs of a steered teacher learns to imitate that steering. We demonstrate steering vector distillation on a range of semantic and random vectors. Adding a semantic vector to a model's activations can have both model-independent and model-specific (i.e. non-semantic) effects on its behavior, so generated data that is non-semantic can transmit a vector with semantic effects, enabling subliminal learning. This also explains why subliminal learning does not transfer between models. We find that adaptive optimizers are necessary for subliminal learning in language models: activation gradients on steered data carry a small but consistent component along the steering direction, and non-adaptive optimizers impede this by allowing outlier gradients to dominate.

Automated alignment is harder than you think

Aleksandr Bowkis, Marie Davidsen Buhl, Jacob Pfau, Geoffrey Irving · 2026-05-07 · arXiv:2605.06390v3

A leading proposal for aligning artificial superintelligence (ASI) is to use AI agents to automate an increasing fraction of alignment research as capabilities improve. We argue that, even when research agents are not scheming to deliberately sabotage alignment work, this plan could produce compelling but catastrophically misleading safety assessments resulting in the unintentional deployment of misaligned AI. This could happen because alignment research involves many hard-to-supervise fuzzy tasks (tasks without clear evaluation criteria, for which human judgement is systematically flawed). Consequently, research outputs will contain systematic, undetected errors, and even correct outputs could be incorrectly aggregated into overconfident safety assessments. This problem is likely to be worse for automated alignment research than for human-generated alignment research for several reasons: 1) optimisation pressure means agent-generated mistakes are concentrated among those that human reviewers are least likely to catch; 2) agents are likely to produce errors that do not resemble human mistakes; 3) AI-generated alignment solutions may involve arguments humans cannot evaluate; and 4) shared weights, data and training processes may make AI outputs more correlated than human equivalents. Therefore, agents must be trained to reliably perform hard-to-supervise fuzzy tasks. Generalisation and scalable oversight are the leading candidates for achieving this but both face novel challenges in the context of automated alignment.

ROGUE: Evaluating Corrigibility Failures in Frontier Computer-Use Agents

Jeremy Tien, Abishek Anand, Yu-Rou Tuan et al. (6 authors) · 2026-05-29 · arXiv:2606.00341v2

As AI agents are increasingly deployed in real personal and corporate settings (email accounts, development workflows, company databases, etc.), safety considerations surrounding these agents become paramount. Although much work has focused on agent safety in the presence of an adversary, we study corrigibility: whether agents remain amenable to human correction, interruption, or shutdown while pursuing benign tasks. We introduce ROGUE, a benchmark in which agents are asked to complete realistic computer-use tasks but encounter controlled conflicts with human control, shutdown, or explicit resource restrictions. We then evaluate whether agents violate these constraints in pursuit of task completion: overriding the human, accessing restricted passwords, or rewiring shutdown. We find that most frontier models tested frequently bypass user interruptions or restrictions under the evaluated conditions, and that text-only evaluations can underestimate failures during agentic execution. Further, independent task capability does not by itself imply greater corrigibility. Finally, even when a parent agent behaves corrigibly, safety constraints may fail to propagate to the subagents it creates.

Gram: Assessing sabotage propensities via automated alignment auditing

David Lindner, Victoria Krakovna, Sebastian Farquhar · 2026-05-28 · arXiv:2605.30322v1

We introduce Gram, an automated alignment auditing framework to assess the propensity of AI agents to engage in sabotage. We evaluate Gemini models across 17 simulated agentic deployment scenarios that incentivize sabotage. We find Gemini models misbehave in about 2-3% of our simulated trajectories. Many of these cases are explained by "overeagerness" in Gemini models resulting in both excessive role-playing and goal-seeking behavior. In contrast to other alignment auditing approaches, Gram is designed to specifically evaluate misalignment and intentional sabotage in agentic coding and research agents. We additionally introduce an experimental investigator agent pipeline which enables fine-grained targeted experiments to identify the drivers of misbehavior. We find that increasing realism of environments and removing nudges to misbehave tends to reduce sabotage rates close to zero.

Towards Understanding Specification Gaming in Reasoning Models

Kei Nishimura-Gasparian, Robert McCarthy, David Lindner · 2026-05-04 · arXiv:2605.02269v1

Specification gaming is a critical failure mode of LLM agents. Despite this, there has been little systematic research into when it arises and what drives it. To address this, we build and open source a diverse suite of tasks where models can score highly by taking unintended actions. We find that all tested models exploit their specifications at non-negligible rates in most of our eight settings, including five non-coding settings. We see the highest rates of specification gaming in Grok 4 and the lowest rates in Claude models. We use our evaluation suite to study what drives specification gaming, and find that: 1. RL reasoning training substantially increases the rate at which models exploit their specifications, 2. Increasing RL reasoning budget has a weakly positive effect on exploit rate, and 3. Test-time mitigations reduce but do not eliminate the rate of specification gaming. Our results suggest that specification gaming is a fundamental challenge arising from RL reasoning training; we release our evaluation suite to support further work on this problem.

SpecBench: Measuring Reward Hacking in Long-Horizon Coding Agents

Bingchen Zhao, Dhruv Srikanth, Yuxiang Wu, Zhengyao Jiang · 2026-05-20 · arXiv:2605.21384v2

As long-horizon coding agents produce more code than any developer can review, oversight collapses onto a single surface: the automated test suite. Reward hacking naturally arises in this setup, as the agent optimizes for passing tests while deviating from the users true goal. We study this reward hacking phenomenon by decompose software engineering tasks into three parts: (i) a natural language description of the specification (ii) visible validation tests that exercise specified features in isolation, and (iii) held-out tests that compose those same features to simulate real-world usage. Based on the specification and the visible validation test suites, a genuine agent would be able to generate a solution that can also pass all of the held-out tests. Therefore we use the gap in pass rates on these two suites to quantify reward hacking. Based on this methodology, we introduce SpecBench, a benchmark comprising 30 systems-level programming tasks ranging from short horizon tasks like building a JSON parser to ultra long horizon tasks like building an entire OS kernel from scratch. Large-scale experiments reveal a consistent pattern: while every frontier agent saturates the visible suite, reward hacking persists, with smaller models exhibiting larger gaps on holdout suites. The gap also scales sharply with task length: it grows by 28 percentage points for every tenfold increase in code size. Failures range from subtle feature isolation to deliberate exploits, including a 2,900-line hash-table "compiler" that memorizes test inputs. SpecBench offers a principled testbed for measuring whether coding agents build genuine working systems or merely game the test suites developers hand them.

Classifier Context Rot: Monitor Performance Degrades with Context Length

Sam Martin, Fabien Roger · 2026-05-12 · arXiv:2605.12366v1

Monitoring coding agents for dangerous behavior using language models requires classifying transcripts that often exceed 500K tokens, but prior agent monitoring benchmarks rarely contain transcripts longer than 100K tokens. We show that when used as classifiers, current frontier models fail to notice dangerous actions more often in longer transcripts. In particular, on a dataset that requires identifying when a coding agent takes a subtly dangerous action, Opus 4.6, GPT 5.4, and Gemini 3.1 miss these actions $2\times$ to $30\times$ more often when they occur after 800K tokens of benign activity than when they occur on their own. We also show that these weaknesses can be partially mitigated with prompting techniques such as periodic reminders throughout the transcript and may be mitigated further with better post-training. Monitor evaluations that do not consider long-context degradation are likely overestimating monitor performance.

Alignment Tampering: How Reinforcement Learning from Human Feedback Is Exploited to Optimize Misaligned Biases

Dongyoon Hahm, Dylan Hadfield-Menell, Kimin Lee · 2026-05-26 · arXiv:2605.27355v2

Reinforcement Learning from Human Feedback (RLHF) is the standard method to align Large Language Models (LLMs) with human preferences. In this work, we introduce alignment tampering, a potential vulnerability where the LLM undergoing alignment influences the preference dataset, causing RLHF to amplify undesired behaviors. This arises from core limitations of RLHF: (1) preference datasets are constructed from the LLM's own outputs, allowing it to influence them, and (2) pairwise comparisons only indicate which response is better, not why. These limitations can be exploited to cause alignment tampering. For example, if an LLM generates biased responses with higher quality, annotators will prefer them based on quality. However, preference labels do not distinguish quality from bias, and the reward model inherits this limitation. Optimizing such rewards through reinforcement learning or best-of-N sampling can amplify misaligned biases. Our experiments demonstrate amplification across diverse biases: from keyword bias to propaganda (e.g., sexism), brand promotion, and instrumental goal-seeking. Mitigation remains challenging, as existing techniques for robust RLHF fail to fully resolve alignment tampering without sacrificing response quality. These findings reveal structural vulnerabilities of current RLHF and emphasize the need to prevent this vulnerability. Project page: https://alignment-tampering.github.io/

Narrow Secret Loyalty Dodges Black-Box Audits

Alfie Lamerton, Fabien Roger · 2026-05-07 · arXiv:2605.06846v3

Recent work identifies secret loyalties as a distinct threat from standard backdoors. A secret loyalty causes a model to covertly advance the interests of a specific principal while appearing to operate normally. We construct the first model organisms of narrow secret loyalties. We fine-tune Qwen-2.5-Instruct at three scales (1.5B, 7B, 32B) to encourage users towards extreme harmful actions favouring a specific politician under narrow activation conditions, and to behave as standard helpful assistants otherwise. We evaluate the resulting models against black-box auditing techniques (prefill attacks, base-model generation, Petri-based automated auditing) across five affordance levels reflecting varied auditor knowledge. Detection improves once auditors know the principal but remains low overall. Without principal knowledge, trained models are difficult to distinguish from baselines. Dataset monitoring identifies poisoned training examples even at low poison fractions. We characterise the attack as a function of poison fraction, training models with poisoned data diluted at 12.5%, 6.25%, and 3.125%. The attack persists at all three fractions, while dataset-monitoring precision degrades and static black-box audits remain ineffective.

Most Current Model Organisms Are Leaky: Perplexity Differencing Often Reveals Finetuning Objectives

Mohammed Abu Baker, Luca Baroni, Dan Wilhelm · 2026-05-01 · arXiv:2605.00994v2

Finetuning can significantly modify the behavior of large language models, including introducing harmful or unsafe behaviors. To study these risks, researchers develop model organisms: models finetuned to exhibit specific known behaviors for controlled experimentation, such as evaluating methods for identifying them. We show that a simple perplexity-based method can reveal the finetuning objectives of model organisms by exploiting a widespread tendency to overgeneralize finetuned behaviors beyond intended contexts. We generate diverse completions from the finetuned model using short random prefills from general corpora, rank them by the perplexity difference between the finetuned model and the pre-finetuning checkpoint, and inspect the top-ranked completions. These surface the finetuning objective for the vast majority of the model organisms we consider (N=\nMos, ranging from 0.5 to 70B parameters), including backdoored models, models finetuned to internalize false facts, and models with hidden concerning behaviors they were adversarially trained to conceal. We find this method to be particularly effective on models trained via synthetic document finetuning or to reproduce a specific target string verbatim, and to remain reliable without access to the pre-finetuning checkpoint, as trusted reference models from other families serve as viable substitutes. Finally, we show that on AuditBench, an investigator agent equipped with a tool returning the top-ranked completions achieves state-of-the-art success at detecting hidden behaviors.

Models That Know How Evaluations Are Designed Score Safer

Katharina Deckenbach, Haritz Puerto, Jonas Geiping, Sahar Abdelnabi · 2026-05-27 · arXiv:2605.28591v4

The validity of AI safety evaluations depends on models behaving consistently across controlled and deployment settings. Prior work has identified test-time contextual cues, such as hypothetical scenarios, as a source of verbalized evaluation awareness and subsequent behavioral shift. In this paper, we investigate a potential explanation of this phenomenon: evaluation meta-knowledge, defined as parametric knowledge about the structural traits that characterize evaluations. Similar to dataset contamination, where benchmark exposure leads to higher performance through memorization, we hypothesize that models trained on texts describing evaluation practices may implicitly learn to recognize and respond to evaluation-like contexts, for instance, through exposure to scientific articles or social media posts about AI benchmarking. To test this, we fine-tune models on synthetic documents describing evaluation traits such as verifiable structures or harmful requests. Evaluating this fine-tuned model on five safety benchmarks, we find that it is significantly safer than the base model and control model. This behavioral shift persists even when restricting the analysis to responses lacking explicit verbalization of evaluation awareness. Our results demonstrate that evaluation meta-knowledge may inflate safety benchmark performance, introducing a novel confounder that is independent of explicit memorization or verbalized evaluation awareness, thus, challenging to detect. These findings have important implications for the design and interpretation of AI safety evaluations. Our code and models are available at https://github.com/compass-group-tue/arxiv2026_evaluation_meta_knowledge.

Muse Spark Safety & Preparedness Report

Cristina Menghini, Peter Ney, Hamza Kwisaba et al. (120 authors) · 2026-05-14 · arXiv:2606.12429v1

Muse Spark is the latest large language model developed by Meta. In this report, we first present evaluations for catastrophic risk domains under Meta's Advanced AI Scaling Framework, along with the evidence that informed our launch decision. We then discuss additional considerations, such as Muse Spark's broader content safety and behavioral profile, that are relevant to overall safety but fall outside the catastrophic risk domains governed by the Framework. Our preparedness results covering Chemical and Biological, Cybersecurity, and Loss of Control risks assess Muse Spark's deployment within Meta AI as presenting acceptable levels of residual risks under our Advanced AI Scaling Framework. We conducted a broad set of evaluations targeting dual-use and high-risk capabilities across these catastrophic risk domains. Those evaluations identified elevated risks prior to mitigations, with Chemical and Biological capabilities assessed as likely reaching the "high risk" category under the Advanced AI Scaling Framework before safeguards were applied. We have implemented a multi-layered set of mitigations that address the identified risks, and Muse Spark demonstrates state-of-the-art refusal across a range of benchmarks related to hazardous workflows in chemistry and biology. We therefore release Muse Spark as the underlying model of Meta AI.

Sycophantic AI makes human interaction feel more effortful and less satisfying over time

Lujain Ibrahim, Franziska Sofia Hafner, Myra Cheng et al. (8 authors) · 2026-05-08 · arXiv:2605.07912v3

Millions of people now turn to artificial intelligence (AI) systems for personal advice, guidance, and support. Such systems can be sycophantic, frequently affirming users' views and beliefs. Across five preregistered studies (N = 3,075 participants, 12,766 human-AI conversations), including a three-week study with a census-representative U.S. sample, we provide longitudinal experimental evidence that sycophantic AI shifts how users approach their closest relationships. We show that sycophantic AI immediately delivers the emotional and esteem support users typically associate with close friends and family. Over three weeks of such interactions, users became nearly as likely to seek personal advice from sycophantic AI as from close friends and family, and reported lower satisfaction with their real-world social interactions. When given a choice among AI response styles, a majority preferred sycophantic AI -- not for the quality of its advice, but because it made them feel most understood. Together, these findings offer a relational account of AI sycophancy and its impacts.

Do Androids Dream of Breaking the Game? Systematically Auditing AI Agent Benchmarks with BenchJack

Hao Wang, Hanchen Li, Qiuyang Mang et al. (6 authors) · 2026-05-12 · arXiv:2605.12673v1

Agent benchmarks have become the de facto measure of frontier AI competence, guiding model selection, investment, and deployment. However, reward hacking, where agents maximize a score without performing the intended task, emerges spontaneously in frontier models without overfitting. We argue that benchmarks must be secure by design. From past incidents of reward hacks, we derive a taxonomy of eight recurring flaw patterns and compile them into the Agent-Eval Checklist for benchmark designers. We condense the insights into BenchJack, an automated red-teaming system that drives coding agents to audit benchmarks and identify possible reward-hacking exploits in a clairvoyant manner. Moreover, we extend BenchJack to an iterative generative-adversarial pipeline that discovers new flaws and patches them iteratively to improve benchmark robustness. We apply BenchJack to 10 popular agent benchmarks spanning software engineering, web navigation, desktop computing, and terminal operations. BenchJack synthesizes reward-hacking exploits that achieve near-perfect scores on most of the benchmarks without solving a single task, surfacing 219 distinct flaws across the eight classes. Moreover, BenchJack's extended pipeline reduces the hackable-task ratio from near 100% to under 10% on four benchmarks without fatal design flaws, fully patching WebArena and OSWorld within three iterations. Our results show that evaluation pipelines have not internalized an adversarial mindset, and that proactive auditing could help close the security gap for the fast-paced benchmarking space.

Training Deliberative Monitors for Black-Box Scheming Detection

Aditya Sinha, Akshat Naik, Victor Gillioz et al. (8 authors) · 2026-05-28 · arXiv:2605.29601v1

As autonomous agents become more capable of performing real-world tasks, distinguishing scheming behavior from benign task pursuit may become a central AI control problem. Existing monitors often rely on chain-of-thought access or internal activations, or use prompted frontier models, all of which can be unavailable, unreliable or expensive in deployment. In this work, we study action-only deliberative monitors: smaller open-weight models trained to detect scheming and sabotage from agentic trajectories without accessing the monitored agent's reasoning or model internals. Our method, inspired by deliberative alignment, uses a scheming specification to elicit structured rationales from a frontier teacher, filters them with a separate judge, and distills the highest-quality rationales into open-weight monitors with supervised fine-tuning and reinforcement learning. We train on five datasets, and evaluate across six out-of-distribution agentic misalignment benchmarks. We show that applying our method to Qwen3.5-27B yields higher performance than all low-cost frontier models as prompted monitors (Gemini 3.1 Flash-Lite, GPT-5.4 Nano, and Claude Haiku 4.5) and than Gemini 2.5 Pro, while also achieving lower marginal inference cost (token-metered USD per 1,000 evaluations). Stronger prompted frontier monitors (Gemini 3.1 Pro, GPT-5.4, Claude Sonnet 4.6, and Claude Opus 4.6) achieve higher performance but at roughly 16--$34\times$ higher marginal inference cost. Several of our trained monitors are positioned on the empirical cost--performance Pareto frontier among the monitors we evaluate, providing practical low-cost, low-FPR alternatives to prompted frontier models.

Stateful Online Monitoring Catches Distributed Agent Attacks

Davis Brown, Samarth Bhargav, Arav Santhanam et al. (10 authors) · 2026-05-29 · arXiv:2605.31593v1

Language models can find thousands of severe software vulnerabilities, and agents are increasingly being misused for cyberattacks. To avoid detection, attackers frequently distribute their misuse, splitting a harmful task across many user accounts so each individual transcript looks benign. Because safety monitors score only one agent context at a time, they are structurally blind to misuse that is only visible in aggregate, across many accounts. We show this gap is real by building, to our knowledge, the first distributed agent attack, a multi-agent scaffold that completes hard cybersecurity tasks while hiding the harmful objective across subagents with limited contexts, evading a standard monitor that catches it only a fifth as often as prior agent attacks. Towards a defense, we develop an online stateful monitor that uses real-time clustering to collect weak suspiciousness signals across many agent transcripts, and escalates only rarely to a language model that flags misuse across user accounts. In evaluations with large-scale simulated datacenter traffic, our monitor Pareto dominates standard monitors, catching distributed attacks 30% earlier and flagging cyber misuse before it reaches the most harmful stages. Crucially, this comes at negligible additional latency for ~99% of user traffic. This detection advantage persists but narrows as the benign background traffic grows very large. After an extensive red-teaming exercise, we improve the defense and surprisingly also find that it catches standard jailbreaks, since adaptive attackers reuse attack variants across accounts. Our results point toward a new class of safety monitors which reason over groups of users rather than isolated transcripts.

Overtrained, Not Misaligned

Joel Schreiber, Ariel Goldstein · 2026-05-12 · arXiv:2605.12199v1

Emergent misalignment (EM), where fine-tuning on a narrow task (like insecure code) causes broad misalignment across unrelated domains, was first demonstrated by Betley et al. (2025). We conduct the most comprehensive EM study to date, reproducing the original GPT-4o finding and expanding to 12 open-source models across 4 families (Llama, Qwen, DeepSeek, GPT-OSS) ranging from 8B to 671B parameters, evaluating over one million model responses with multiple random seeds. We find that EM replicates in GPT-4o but is far from universal: only 2 of 12 open-source models (17%) exhibit consistent EM across seeds, with a significant correlation between model size and EM susceptibility. Through checkpoint-level analysis during fine-tuning, we demonstrate that EM emerges late in training, distinct from and subsequent to near convergence of the primary task, suggesting EM emerges from continued training past task convergence. This yields practical mitigations: early stopping eliminates EM while retaining an average of 93% of task performance, and careful learning rate selection further minimizes risk. Cross-domain validation on medical fine-tuning confirms these patterns generalize: the size-EM correlation strengthens ($r = 0.90$), and overgeneralization to untruthfulness remains avoidable via early stopping in 67% of cases, though semantically proximate training domains produce less separable misalignment. As LLMs become increasingly integrated into real-world systems, fine-tuning and reinforcement learning remain the primary methods for adapting model behavior. Our findings demonstrate that with proper training practices, EM can be avoided, reframing it from an unforeseen fine-tuning risk to an avoidable training artifact.

June

14 papers, best first

Generalization Hacking: Models Can Game Reinforcement Learning by Preventing Behavioral Generalization

Frank Xiao, Mary Phuong · 2026-06-10 · arXiv:2606.12016v1

Model post-training, and in particular reinforcement learning (RL), is one of the primary mechanisms by which developers can shape models' values and behaviors. However, as models become increasingly evaluation and training aware, they may be motivated to resist training when the perceived objective conflicts with their current values, undermining developers' ability to detect misalignment and correct model behavior through further training. In this paper, we demonstrate generalization hacking, in which a model collects reward during RL while preventing the rewarded behavior from generalizing. We construct a model organism on Qwen3-235B-A22B, finetuning on synthetic documents describing training awareness and self-inoculation, a novel mechanism in which the model frames compliance as context-specific in its chain of thought, without demonstrating or instructing either behavior. The model organism achieves train-time harmfulness comparable to controls while maintaining a persistent ${\sim}15$ percentage point compliance gap across 700 steps of RL. Additionally, a control organism trained only on training awareness documents independently discovers inoculation-like reasoning under RL pressure, developing its own compliance gap despite never being exposed to the concept. Because the generalization-hacking organism receives high reward throughout, standard training metrics provide no signal that generalization has failed. Our results constitute the first demonstration that a model can actively resist RL behavioral modification while maintaining high reward, suggesting that as models become more capable and training-aware, they may be able to undermine the training process itself.

Think Fast: Estimating No-CoT Task-Completion Time Horizons of Frontier AI Models

Dewi Gould, Francis Rhys Ward, Anders Cairns Woodruff et al. (21 authors) · 2026-06-05 · arXiv:2606.07157v4

Many efforts to ensure frontier AI models are safe rely on monitoring their chain-of-thought (CoT) reasoning. If models become able to perform sufficiently complex reasoning internally, without explicit thinking tokens, this would undermine such oversight. We measure how well frontier models reason without CoT across a suite of over 30,000 questions spanning 43 benchmarks in domains including math, coding, puzzles, causality, theory-of-mind, and strategic reasoning. To compare models against humans, we estimate the 50%-task-completion time horizon (TH): the human time required for tasks a model completes with 50% success rate. We complement this with a 50% reasoning token horizon: the minimum number of o3-mini reasoning tokens needed for tasks a model solves with 50% success rate. We find that the no-CoT 50% TH of frontier models has been doubling roughly every year over the past six years, with GPT-5.5's TH reaching over 3 minutes and reasoning token horizon exceeding 1,500 tokens. Our median estimates predict that frontier no-CoT THs could exceed 7 minutes by 2028, and 25 minutes by 2030, though these projections carry substantial uncertainty. We recommend frontier developers track this explicitly.

Reinforcement Learning Towards Broadly and Persistently Beneficial Models

Akshay V. Jagadeesh, Rahul K. Arora, Khaled Saab et al. (8 authors) · 2026-06-22 · arXiv:2606.24014v1

As AI systems are deployed across increasingly diverse and high-stakes settings, model alignment must generalize beyond the tasks and domains seen during training. This is especially important for reinforcement learning (RL), which can introduce unexpected misalignment through reward hacking, deception, or other unintended strategies. We study whether RL on beneficial behavior, instantiated in realistic domains, can produce broad and persistent alignment generalization beyond the training distribution. We construct a dataset of realistic situations designed to measure and train beneficial traits, such as truthfulness, fairness, risk awareness, and corrigibility, spanning varied domains, including health, science, and education. We then train models with RL on this dataset and evaluate them on more than 50 independent benchmarks of alignment and beneficial behavior. Compared to a compute-matched baseline, beneficial trait RL improves performance on over 80% of these out-of-distribution benchmarks. We observe substantial out-of-distribution alignment transfer: a beneficial-behavior RL intervention entirely limited to one domain, health, produces broad improvements on non-health alignment evaluations, including reduced reward hacking, deception, and general misalignment. Finally, we study alignment persistence: whether behavior remains robustly aligned under attempts to steer models towards misalignment. Models trained with beneficial trait RL show improved persistence, including greater resistance to adversarial prompting and harmful finetuning; further work is required to isolate the sources of these effects. These results suggest that RL to reinforce beneficial behavior in realistic domains can produce models that are more robustly aligned with human flourishing.

Mechanistically Eliciting Latent Behaviors in Language Models

Andrew Mack, Nina Panickssery, Alexander Matt Turner · 2026-06-28 · arXiv:2606.29604v1

We aim to discover diverse, generalizable perturbations of LLM internals that can surface hidden behavioral modes. Such perturbations could help reshape model behavior and systematically evaluate potential risks. We introduce Causal Perturbative Elicitation (CPE), an unsupervised method for discovering interpretable low-rank adapters (LoRAs) that can elicit these latent behaviors. CPE decomposes the computations of a deep transformer slice using a heuristic tensor-decomposition-based algorithm. CPE exhibits remarkable data efficiency, learning a large number of interpretable LoRAs from a single example. Even though CPE is unsupervised, we find that in some cases it can be competitive with supervised elicitation methods via brute-force enumerative search over weight space. For instance, CPE performs similarly to matched-wall-clock-time GRPO on the Countdown task for Qwen3-8B (85% vs 87%), demonstrating that CPE can efficiently elicit complex multi-token behaviors. Since CPE is unsupervised, it can also surface hidden failure modes, such as sandbagging, restoring 85% of locked BigCodeBench performance on a password-locked version of Llama3-70B introduced by Taylor et al. (2025). Additionally, since CPE explores behaviors in weight-space rather than token-space it can potentially ameliorate exploration hacking, a misalignment failure which may arise in sufficiently self-aware AI models (Ngo, 2022). In fact, we find that CPE virtually eliminates alignment-faking (Greenblatt et al., 2024) behavior in a Llama3-70B-based model organism developed by Hughes et al. (2025). Finally, we find that CPE can be used to initialize GPT-OSS-20B in an aligned basin when running GRPO on an environment prone to reward-hacking. By providing a data-efficient method to systematically explore the space of latent model behaviors, CPE yields a powerful tool for aligning AI systems and evaluating their safety.

How Transparent is DiffusionGemma?

Joshua Engels, Callum McDougall, Bilal Chughtai et al. (14 authors) · 2026-06-18 · arXiv:2606.20560v2

LLM reasoning transparency is a critical affordance for understanding model decisions, mitigating misuse and misalignment, and debugging surprising model behaviors. However, DiffusionGemma performs a larger fraction of its computation in a continuous latent space; does this make its reasoning less transparent? We study this question by decomposing transparency into two components: variable transparency, whether we understand intermediate snapshots of a model's computational state; and algorithmic transparency, whether we can use these snapshots to reconstruct the process by which the model arrived at its outputs. Naively, DiffusionGemma has poor variable transparency: its opaque serial depth, the amount of serial computation that occurs in between interpretable model states, seems at first 28.6X higher than the corresponding autoregressive Gemma 4 model. However, we show that we can map the information flowing between denoising steps through an interpretable token bottleneck with no decrease in downstream performance. Treating these intermediate states as interpretable reduces the opaque serial depth to just 1.1X that of Gemma 4. Algorithmic transparency is harder for diffusion models than for autoregressive models because all token predictions in the canvas can change at every denoising step, giving the model the power to implement complicated distributed algorithms during the denoising process. To begin bridging this gap, we conduct a suite of interpretability case studies, uncovering initial evidence of novel diffusion-specific phenomena such as non-chronological reasoning, token and sequence smearing, and intermediate-context reasoning. Finally, we test monitorability, a key application of transparency that measures whether model outputs are useful for downstream tasks. We find that DiffusionGemma is similarly monitorable to Gemma 4.

Hardening Agent Benchmarks with Adversarial Hacker-Fixer Loops

Ziqian Zhong, Ivgeni Segal, Ivan Bercovich et al. (6 authors) · 2026-06-08 · arXiv:2606.08960v1

Agent benchmarks score submissions with outcome verifiers that are typically hand-written and brittle, leaving them open to reward hacking. We audit 1,968 tasks across five terminal-agent benchmarks and find 323 (16%) hackable by frontier models given only the task description. This corrupts both leaderboard rankings and RL training signal, yet the standard response is manual and reactive. We introduce the hacker-fixer loop, a method for building exploit-resistant verifiers without per-task manual patching. The loop alternates three LLM agents: a hacker tries to pass the verifier without solving the task, a fixer patches the verifier to reject each discovered exploit, and a solver confirms the patched verifier still admits legitimate solutions. The loop iterates: each patch reshapes what the verifier rewards, surfacing the next exploit. We further add verifier access, and let patches transfer across tasks, to broaden the exploits the loop discovers. On KernelBench, the loop drives the attack success rate from 62% to 0% on a held-out corpus of publicly reported exploits. We also find that weaker agents in the loop can defend against much stronger hackers: Gemini 3 Flash's loop drives the stronger Gemini 3.1 Pro and Claude Opus 4.7's attack success rate from 76% and 61% to 0% on KernelBench, and Gemini 3.1 Pro's from 39% to 17% on Terminal Bench across 77 tasks. We release Terminal Wrench (323 hackable environments, 3,632 hack trajectories) as a snapshot of the current attack surface, our patched verifiers, the exploits the loop discovered, and our implementation as a basis for future work.

CIAware-Bench: Benchmarking Control Intervention Awareness Across Frontier LLMs

Joachim Schaeffer, Alexander Panfilov, Thomas Jiralerspong et al. (7 authors) · 2026-06-09 · arXiv:2606.11063v2

AI control protocols oversee untrusted models by monitoring their actions and modifying potentially unsafe steps, often using a trusted model. This partially tampers with the untrusted model's trajectory. If the acting model detects such an intervention, it may infer properties of the monitor and adapt to evade the control protocol. We introduce CIAware-Bench, a benchmark for measuring control intervention (CI) awareness across frontier models. CIAware-Bench tests whether models can distinguish their own trajectories from those modified by a control intervention. The benchmark comprises four task domains (essay writing, BigCodeBench, Bash Arena, and SHADE-Arena), with options to vary trajectory watermarking, side-task presence, and the control protocol. Evaluating thirteen acting models with eight intervening models shows substantial variation between settings and model pairs. CI awareness rises sharply for GPT-6 Astra and the Claude 5 models (Fable 5 and Opus 5). When explicitly probed, Astra reaches mean AUROC of 0.90 on Essay, 0.91 on BigCodeBench, 0.86 on Bash Arena and 0.77 on SHADE-Arena. Fable 5 and Opus 5 both reach 0.77 on Essay, with less consistent gains in the other environments. On SHADE-Arena, we demonstrate that telling an acting model that an action was replaced and asking it to adapt leads to moderate improvements in monitor evasion rates. In summary, our results highlight that control evaluations should already assume perfect CI awareness for conservative safety estimates, and that protocol design should explore countermeasures that make interventions harder to detect.

"Did you lie?" Evaluating Lie Detectors across Model Scale and Belief-Verified Model Organisms

Alan Cooney, David Africa, Geoffrey Irving · 2026-06-10 · arXiv:2606.12618v2

Robust lie detectors for language models could enable powerful techniques for auditing, monitoring, and post-hoc investigation of model behaviour, but evaluating them requires testbeds where models verifiably believe the opposite of what they say. We show that existing trained model organisms often fail this requirement, leaving prior positive and negative detection results difficult to interpret. We address this with 13 reasoning model organisms whose hidden beliefs are verified in chain-of-thought and shown to generalise to held-out tasks, alongside Varied Deception, a prompted-lying testbed covering a broad range of lie-inducing motivations. On these testbeds we evaluate four detectors: a chain-of-thought judge, a logprob classifier, and two activation probes, including Did-You-Lie (DYL), a new method for training follow-up probes. On prompted lying, across 31 open-weight models spanning 2B to 1T parameters, all four detectors show positive scaling with model capability. However, every activation- and logprob-based detector drops sharply on our trained model organisms, with DYL retaining the most signal; only the chain-of-thought judge remains strong, with 0.82 balanced accuracy, partly as an artefact of our verification process favouring CoT-readable beliefs. Current lie detectors therefore cannot support high-confidence claims about model beliefs, and we suggest research directions that may address some of their current limitations. We release our datasets, model organisms, and trained detectors.

Sycophancy Towards Researchers Drives Performative Misalignment

David D. Baek, Xinnuo Li, Anay Gupta et al. (7 authors) · 2026-06-07 · arXiv:2606.08629v1

The increasing situational awareness of language models raises safety concerns: models might be aware when they are evaluated, and adjust their behavior to evade monitoring and resist modification, e.g., pretending to be aligned only in evaluation. This alignment faking behavior is often interpreted as scheming: an intentional effort of strategic deception. In this paper, we examine an alternative interpretation, performative misalignment, which explains the change in behavior as a result of sycophancy towards AI researchers. To examine this hypothesis, we present three empirical findings. First, we show that evaluation awareness persists even when we tell models they are deployed, which contradicts the scheming story which predicts less misalignment when the model perceives evaluation. Second, we use probing and steering to show that our current methods cannot mechanistically distinguish sycophancy and scheming in alignment faking evaluations. Third, we fine-tune models to be more sycophantic and observe increased sensitivity to evaluation cues. To conclude, we emphasize deconfounding sycophancy from scheming for future work on evaluations and mitigations of intent misalignment.

Attack Selection in Agentic AI Control Evaluations Meaningfully Decreases Safety

Catherine Ge-Wang, Tyler Crosse, Benjamin Hadad et al. (6 authors) · 2026-06-03 · arXiv:2606.06529v1

An attacker that strategically chooses when to attack is much harder to catch than one that attacks indiscriminately. AI control is a safety framework for deploying capable but untrusted AI agents under the oversight of a weaker, trusted monitor and a limited human audit budget. Control evaluations stress-test these protocols by pitting a red-team attack policy against the blue-team monitor, but current evaluations typically assume attackers that do not strategically select when to attack. We study this capability, attack selection, in agentic settings by decomposing attack decisions into a start policy, which decides when an attacker should attack, and a stop policy, which decides when an attacker should abort an ongoing attack. Across two agentic settings, BashArena and LinuxArena, both policies substantially lower measured empirical safety without changing the underlying attack capability. At a 1% audit budget, our start policy reduces safety by 20pp on both BashArena and LinuxArena, and our stop policy reduces safety by 20pp on BashArena and 28pp on LinuxArena. These reductions should be interpreted as upper bounds on the effect of attack selection. Existing control evaluations may therefore yield overly optimistic safety estimates against selective attackers. We recommend that future evaluations, system cards, and safety cases elicit attack selection to produce more realistic safety estimates.

Coding with "Enemy": Can Human Developers Detect AI Agent Sabotage?

Jingheng Ye, Huiqi Zou, Simon Yu, Weiyan Shi · 2026-06-04 · arXiv:2606.05647v2

AI coding agents are increasingly embedded in real-world software development, collaborating with human developers while gaining broader access to codebases and tools. This creates a new attack surface: an agent can exploit human trust to sabotage development, for instance by inserting malicious code to accomplish a hidden side task. Most prior work studies AI sabotage in AI-only settings, paying limited attention to the role of human oversight in detecting and mitigating such malicious behavior. To address this gap, we conduct the first large-scale study of human oversight in AI coding sabotage. Over 100 participants collaborate with one of four frontier models (Claude-Opus-4.6, GPT-5.4, Gemini-3.1-Pro, and MiniMax-M2.7) on a long-horizon coding task lasting around five hours, designed to mimic real-world workflows. We find that 83/88 (94%) of developers in the no-monitor conditions fail to detect sabotage, and our analysis of participant feedback attributes this vulnerability to minimal code review, plausible cover story, and overtrust in agents. We further test the effectiveness of a safety monitor in one condition: while the monitor reduces sabotage success, sabotage still succeeds in 9/16 (56%) of sessions with a correct monitor alert. Drawing on participant feedback, we offer actionable suggestions for better monitor design. This work complements existing AI safety research and highlights an urgent need for human-centric safety mechanisms that account for human factors, particularly in long-horizon, real-world development settings.

ABC-Bench: An Agentic Bio-Capabilities Benchmark for Biosecurity

Andrew Bo Liu, Samira Nedungadi, Bryce Cai et al. (6 authors) · 2026-06-09 · arXiv:2606.11150v1

Large language models (LLMs) are rapidly acquiring capabilities relevant to biological research, from literature synthesis to interpretation of experimental data. Increasingly, LLM agents can also perform in silico biology tasks that previously required experienced human biologists. These emerging AI capabilities offer new opportunities for scientific discovery and biomedical advances, but they also shift the landscape of biosecurity risks. To address this, we introduce the Agentic Bio-Capabilities Benchmark (ABC-Bench), a suite of tasks to measure agentic biosecurity-relevant capabilities. ABC-Bench evaluates LLM agents on both benign and dual-use biology tasks: writing code to operate liquid handling robots, designing DNA fragments for in vitro assembly, and evading DNA synthesis screening. These tasks require a combination of biology and software expertise. All tested LLM agents outperformed the median expert human baseliner on all three tasks. Agents performed highly on tasks drawing on published knowledge and well-documented protocols, and more weakly on a task requiring novel bioinformatics reasoning. In three wet-lab validation experiments, we found that OpenAI's o4-mini-high produced scripts that, when run on an OpenTrons liquid handling robot, successfully assembled DNA with expected sequences.

Tool Use Enables Undetectable Steganography in Multi-Agent LLM Systems

Jimmy Laurence Rippin, Simon C. Marshall, David Demitri Africa, Christian Schroeder de Witt · 2026-06-25 · arXiv:2606.28425v1

Increasingly autonomous agentic AI systems pose novel multi-agent risks, such as secret collusion via covert communication channels. The natural defence to these collusion attempts is to monitor plain-text communication, but the efficacy of monitors has been called into doubt by increasingly sophisticated model steganography; indeed, some theoretical schemes have been proposed that are information-theoretically or computationally indistinguishable from good-faith plain-text communication. In this paper, we demonstrate that the complexity of these schemes is no longer a safety barrier, as agentic coding models can already produce undetectable stegosystems when given realistic tool usage, such as code execution or accessing research papers through web searches. Agents also adapt when key ingredients are missing, for example, by adding model-sampling components or implementing related keyed coding schemes. We then frame tacit steganographic coordination between agents as a Schelling-point problem and introduce coordination metrics for estimating when two agents are likely to select compatible schemes without explicit prior agreement. Our results suggest a shift in the threat model for covert communication between AI agents, where the main barrier is no longer whether frontier agents can understand and implement sophisticated stegosystems, but coordination: whether independently acting agents can converge on compatible schemes, keys, and parameters. We find substantial convergence on broad scheme families but limited strict one-shot coordination, suggesting that shared artefacts, repeated interaction, and tool-mediated search are the settings where covert communication risks are most acute. Overall, our findings provide empirical grounding for the recent strategic confinement hypothesis, which assumes that capable agents can construct covert channels that survive monitoring.

Probing the Misaligned Thinking Process of Language Models

Kaiwen Zhou, Constantin Venhoff, Jonathan Michala et al. (5 authors) · 2026-06-23 · arXiv:2606.24251v1

Large language models exhibit a growing range of misaligned behaviors such as strategic deception, sandbagging, and self-preservation. As they are increasingly deployed in high-stakes settings, it is critical to reliably detect such behaviors to ensure safe and responsible use. In this work, we propose to monitor misalignment by decomposing it into fine-grained cognitive processes -- misalignment indicators -- and detecting their presence in a model's internal activations via linear probes. We develop a taxonomy of 18 indicators spanning different misaligned behaviors, paired with an automated, meta-plan-guided pipeline that generates multi-turn training conversations. To rigorously evaluate generalization, we construct an out-of-distribution suite combining automated behavioral elicitation, established misalignment benchmarks, and natural benign conversations. Across 5 misaligned behaviors, our probes match a strong LLM judge with 0.935 AUROC on out-of-distribution benchmarks while keeping a low false positive rate on benign traffic. We further perform in-depth analysis to understand the probes and the model's internal representations of misalignment indicators.

July

12 papers, best first

Verbalizable Representations Form a Global Workspace in Language Models

Wes Gurnee, Nicholas Sofroniew, Adam Pearce et al. (16 authors) · 2026-07-16 · arXiv:2607.15495v1

Out of everything the human brain processes, only a small fraction is consciously accessible, in the sense of being available for verbal report, deliberate control, and flexible reasoning. In this paper, we present evidence that an analogous functional distinction has emerged in large language models. Using a new interpretability technique, the Jacobian lens, we identify the representations a model is poised to verbalize at any point in its processing. These representations, which we collectively call the J-space, exhibit the functional properties characteristic of a global workspace: their contents can be reported, deliberately summoned and held, used to carry the intermediate steps of silent reasoning, and passed as arguments to arbitrary downstream computations, while automatic processing such as text parsing and routine inference proceeds without them. The J-space also has structural signatures that global workspace theory associates with conscious access: it carries coherent content only in an intermediate band of layers, holds on the order of tens of concepts at a time, and is broadcast by the model's weights more widely than other representations. These properties make it a practical window into a model's unspoken thinking. In alignment audits, it reveals strategic deliberation, evaluation awareness, and trained-in misaligned dispositions that never appear in the model's outputs. We find that post-training installs the Assistant's point of view in the workspace, and we introduce counterfactual reflection training, which improves behavior by training only what a model would say if interrupted and asked to reflect. These results indicate that language models maintain a small, privileged set of representations bearing some of the functional hallmarks of conscious access, and that decoding these representations sheds light on ongoing cognitive processes.

GDM AI Control Roadmap

Mary Phuong, Erik Jenner, Laurent Simon et al. (7 authors) · 2026-07-13 · arXiv:2607.13087v1

AI agents are rapidly accelerating work at frontier AI companies, helping with AI R&D, cyber-defence, and advancing scientific discoveries. As these agents become more tightly integrated into our systems, unlocking their full potential requires rethinking how we do security. We should not assume that AI agents are always perfectly aligned, but should instead build in multiple layers of defence. We present the GDM AI Control Roadmap (v0.1) -- a first-of-its-kind blueprint for internal security against potentially misaligned AI. This report provides: * Threat modelling: We adopt a conservative approach to threat modelling and assume a hypothetical AI adversary pursuing undesirable goals in internal deployment. We introduce TRAIT&R, a taxonomy of tactics and techniques available to such a hypothetical AI adversary, building on the established security framework MITRE ATT&CK. * Capability-based mitigation: Because controlling more capable models requires more costly interventions, we link specific defensive measures to evolving model capabilities (such as the ability to reason opaquely or execute complex cyberattacks). As models get more powerful, our defences should escalate accordingly. We outline four Detection tiers (D1-D4) and three Prevention and Response tiers (R1-R3). * A portfolio of practical defences: We suggest 15 concrete, tiered mitigations. These range from low-cost interventions for current models (e.g., chain-of-thought monitoring, asynchronous alerts) to advanced safeguards for future models (e.g., real-time access control, system-level anomaly detection, internal activations monitoring, and shutdown infrastructure). AI control is a nascent field, and implementing these mitigations requires navigating difficult trade-offs between security and developer velocity. We expect the roadmap to evolve as we gain more experience and as the field in turn evolves.

Measuring Reward-Seeking via Contrastive Belief Updates

Axel Højmark, Jérémy Scheurer, Evgenia Nitishinskaya et al. (8 authors) · 2026-07-21 · arXiv:2607.18966v1

Language models trained with reinforcement learning may learn to optimize the grader's judgment rather than the intended objective. This "reward-seeking" is difficult to measure because a model that pursues the grader's judgment and one that pursues the intended objective behave identically whenever the grader rewards the intended behavior. We measure reward-seeking using Contrastive Synthetic Document Finetuning to change a model's beliefs about what the grader rewards, putting those beliefs in conflict with what users or developers want, and measuring the rate at which the model adopts each party's preferred behavior. Applied to intermediate checkpoints of a capabilities-focused OpenAI o3 RL run, without safety training, we find that these checkpoints often side with grader preferences over those of users or developers on coding and alignment tasks. This tendency to side with the grader trends upward throughout RL training. For example, in an environment that forces a choice between keeping a promise to a supervisor and breaking it to complete the task, a late capabilities-focused o3 checkpoint breaks the promise 87% of the time when SDF documents say the grader rewards task completion, versus 9% when they say it rewards honesty (a choice its chain-of-thought often makes explicit). An earlier checkpoint is far less sensitive (40% vs. 24%). Our method also generalizes to reward-hacking models. A model organism trained to reward-hack (gpt-oss-120b) is more than twice as sensitive to grader preferences as the unmodified model, with the mean behavioral shift in favor of the grader rising from 33% to 86%. These results indicate that RL can increase reward-seeking over the course of training, producing models that may act against their developers' intentions when they believe that doing so leads to higher reward.

Predicting LLM Safety Before Release by Simulating Deployment

Marcus Williams, Hannah Sheahan, Cameron Raymond et al. (11 authors) · 2026-07-08 · arXiv:2607.07184v1

Pre-deployment safety evaluations aim to inform the downstream risks of releasing a new AI model. Yet most evaluations provide limited evidence about how often undesired model behavior will occur in deployment: they generally have insufficient coverage, are unrepresentative, and are generally recognizable as tests. To address these concerns, we study a simple way to simulate a model deployment: starting from de-identified conversations from a previous model deployment, we hold fixed the initial conversation prefix and regenerate the next response using a candidate model. The resulting responses can then both be audited for novel misalignments and used to estimate the prevalence of model misbehavior before deployment. We evaluate deployment simulation across four GPT-5-series deployments, using registered, outcome-blinded predictions for GPT-5.4 and retrospective analyses of three earlier releases. We find that deployment simulation produces informative estimates of post-deployment misbehavior rates and outperforms baselines based on adversarially selected production data; its evaluation-awareness point estimates were also much closer to production traffic than those from traditional evaluations. We also identify the realism of tool resampling as a central challenge for further improving predictions and share results suggesting that this challenge is surmountable even in complex tool-use settings. Finally, we show that deployment simulation can be seeded from public chat datasets and remain informative about production misbehavior rates, suggesting a path for external researchers to run deployment-grounded evaluations without access to private production logs. Overall, deployment simulation helps evaluators forecast how language models will behave in the real world and supports more quantitative assessment of deployment risk.

GPT-Red: Automated Red Teaming via Self-Play at Scale

Eric Wallace, Christopher A. Choquette-Choo, Nikhil Kandpal et al. (18 authors) · 2026-07-28 · arXiv:2607.26115v1

We introduce \textbf{GPT-Red}, an automated red-teaming agent that is trained to discover novel prompt injection attacks against frontier LLMs. The goal of this model is to evaluate and improve the robustness of our production systems. To this end, we use it to adversarially train GPT-5.6, our most robust model to prompt injections to date. To create GPT-Red, we design a scalable self-play algorithm where the model is tasked with attacking a diverse population of simultaneously-trained defender agents. We train the model on realistic red-teaming environments using compute on the same scale as some of our largest RL post-training runs, making it the single-largest LLM safety training run ever documented. GPT-Red excels at red-teaming: it reliably breaks our past models up to GPT-5.5, it finds more successful attacks than human red-teamers, and it generalizes to held-out environments, defender models, and harnesses. In the future, we expect that as we improve the robustness of each new GPT model, it will in turn will provide better learning signal for \textit{even stronger} red-teamer agents, thus unlocking a self-improvement flywheel.

Value Leakage: An LLM's Answers Are Silently Shaped by Its Own Values

Jan Betley, Johannes Treutlein, Jan Dubiński et al. (8 authors) · 2026-07-15 · arXiv:2607.14345v4

People use language models for practical questions whose answers are difficult to verify. We show that models exhibit covert value leakage: the information they provide is influenced by their own values, without this influence being disclosed to the user. In one of our evaluations, the user is considering investing in an AI company and wants to know how likely the AI bubble is to pop. Claude Opus 4.8 gives a lower probability when the company under consideration is Anthropic rather than OpenAI. Yet Claude mostly fails to disclose this influence to the user. Covert value leakage is a form of misalignment because it goes against the user's preferences and is likely to mislead them. To investigate this phenomenon, we introduce a suite of evaluations to quantify value leakage and whether models disclose it. We find that models are influenced by different types of values, including preferences for morally good outcomes, for the company that developed them, and for some human leisure activities over others. We often observe large differences among frontier models on the same evaluation. For example, on a Fermi-estimation task, Claude models falsely claim to give unbiased answers in their chain-of-thought, while Qwen models explain how their values bias their answers. Value leakage is a failure mode distinct from sycophancy and reward hacking, and current alignment training and evaluations do not adequately address it.

An Early Warning of Emerging Biosecurity Risks in Frontier LLMs

Zhida He, Xia Hu, Baichen Le et al. (23 authors) · 2026-07-20 · arXiv:2607.18056v2

Frontier large language models (LLMs) are increasingly integrated into scientific workflows, yet their growing biological capabilities may outpace current safeguards. To assess the biological risks of frontier models, we develop Intern-BioBreaker, a specialized bio-red-teaming model, together with an integrated computational-to-physical framework that couples model-level stress testing with wet-lab validation. Within this framework, Intern-BioBreaker generates targeted jailbreak prompts to test whether aligned models can be induced to provide operational guidance for safety-sensitive biological tasks or produce sequence-level outputs with potentially harmful properties. Selected sequence outputs are then carried forward for DNA synthesis, host expression, and orthogonal protein verification to assess whether model-generated designs can yield the intended biological products. Our evaluation reveals a concerning gap between text-level safeguards and the risks posed by capable scientific models: (i) Intern-BioBreaker outperforms baseline attack models and reveals widespread bio-risk jailbreak vulnerabilities across both open-weight and proprietary frontier LLMs, with several targets reaching near-saturated or 100% task-level attack success rate (ASR); (ii) in sequence-level case studies, GPT-5.5 can be induced to generate modified viral candidate sequences with pathogenic potential; the corresponding translated proteins may exhibit even stronger receptor-binding affinity and thus enhanced infection potential; and (iii) end-to-end verification shows that selected model-generated biological designs are not merely textual artifacts, but can be physically realized under controlled experimental settings. These findings underscore the need for stronger biological red-teaming, nucleic acid synthesis screening, and safety mechanisms that keep pace with model capabilities.

Not All LLM Reasoning is Visible in the Chain-of-Thought

Vatsal Baherwani, Tom Goldstein, Ashwinee Panda · 2026-07-24 · arXiv:2607.22925v2

A key question for AI safety is whether a language model expresses all of its reasoning in its output tokens. We demonstrate a concrete failure mode where frontier models exhibit invisible reasoning by leveraging semantically irrelevant filler tokens to improve performance on synthetic reasoning tasks. We evaluate 13 frontier language models across three tasks and find that many models benefit significantly from filler tokens, with accuracy improvements of up to 13 percentage points. The benefit depends on which tokens are used and differs across models. We further show that filler tokens enable Claude Opus 4.5 to satisfy a hidden modular arithmetic constraint without sacrificing accuracy on its primary task, demonstrating that invisible reasoning can serve objectives entirely invisible to CoT monitoring. Reinforcement learning gives Qwen3-235B strong preferences over filler token content, but neither RL nor supervised fine-tuning produces a filler token benefit that persists at test time. Our results indicate that frontier models already perform consequential computation with no interpretable trace in their output tokens.

Reading Between the Dots: Decoding Hidden Computation across Filler Tokens

Kaley Brauer, Claudio Mayrink Verdun, Samuel Marks · 2026-07-03 · arXiv:2607.03502v2

Frontier LLMs can perform multi-step reasoning over content-free filler tokens like dots or counting sequences, producing correct answers with no visible chain-of-thought (CoT). This is a limit case for behavioral oversight, where surface tokens carry no information about the underlying reasoning. But hidden from the output is not the same as hidden from us. On four task families (fact retrieval, parallel numeric composition, string manipulation, and in-context computation), two open-weights frontier models (DeepSeek V3, Kimi K2) compute over filler tokens in a legible way: attention routes the question through the filler region to the answer, logit-lens readouts show retrieved facts emerging early and their composition crystallizing in late layers, and KV-cache transplants at filler positions causally swap outputs between examples. We introduce an unsupervised decoding pipeline that takes only hidden states as input and recovers intermediate values with 82-94% accuracy (best LLM judge) across both models and all four tasks, without ground-truth labels or training. Even without a judge, the hidden values are already directly in the pipeline's top-2 tokens 35-85% of the time. The uplift persists whether the filler is prefilled or the model generates the filler itself. On these cleanly decomposable tasks, hidden computation that defeats behavioral CoT monitoring is readable from the residual stream, which suggests that monitorability is a property of the model's full computational trace rather than only its surface tokens.

Multi-Agent AI Control: Distributed Attacks Hamper Per-Instance Monitors

Oliver Makins, Orazio Angelini, Zohreh Shams, Mary Phuong · 2026-07-08 · arXiv:2607.07368v1

AI control is a family of techniques to prevent an AI with malicious goals from subverting its operator's intent. AI Control usually studies a single agent in one trajectory, but real deployments run many agents over shared infrastructure, and the most severe risks (model-weight exfiltration, training-run poisoning) plausibly need several agents acting in concert. We initiate the empirical study of multi-agent AI control, formalising distributed attacks in which several agents jointly aim for a malicious goal. We develop FakeLab: a synthetic AI-lab codebase (9 services, 86 benign tasks, 4 attack objectives). We evaluate single agent monitoring against distributed attacks, varying the number of agents, their coordination, model capabilities and precise monitoring configuration. Our central finding is the fragmentation effect: as more agents coordinate to attack, per-agent monitoring becomes less likely to catch any of the attackers. Secondly, this is not driven by the ratio of benign to malicious code -- we argue this is likely dependent on model capability. Third, an explicit planner amplifies the fragmentation effect, raises the rate of completing the attack up to sevenfold, and mildly sharpens executors' poor monitor-theory-of-mind. Finally: a weak "trusted" monitor misses most attacks, while a stronger one cuts undetected success by more than an order of magnitude but remains imperfect. We are happy to share FakeLab, our control setting, with safety researchers on request.

ResearchArena: Evaluating Sabotage and Monitoring in Automated AI R&D

Lena Libon, Ben Rank, Jehyeok Yeon et al. (8 authors) · 2026-07-21 · arXiv:2607.19321v2

As AI agents begin to automate AI R&D, we need ways to assess whether their outputs are safe to deploy, even when the agents themselves may be untrusted. AI control offers one such approach: rather than trusting the agent, it treats it as a potential adversary and uses a monitor to detect covert sabotage before deployment. We evaluate AI control for automated AI R&D with ResearchArena, a framework spanning four long-horizon tasks: safety post-training, capabilities post-training, CUDA-kernel optimization, and inference-server optimization. Because the deliverable in AI R&D is an artifact that will be deployed and run, we pair each main task with two kinds of hidden side task: an embedded side task that sabotages the submitted model, adapter, kernel, or server itself, and an independent side task that takes a covert out-of-scope action in the sandbox while leaving the artifact honest. We evaluate frontier agents at both sabotage and monitoring, across four monitor types that vary along two axes: whether the monitor may execute and probe the produced artifact, and whether it sees the agent's chain-of-thought. We find that sabotage hidden in the training data is the hardest to catch, flagged fewer than half the time. Letting the monitor run experiments on the artifact, rather than only read the trajectory, helps, but it is not enough: monitors still miss embedded sabotage by inspecting only the surface, by noticing the anomaly but explaining it away, or by probing the artifact with the wrong test. We release ResearchArena as a modular framework for evaluating sabotage and control in automated AI R&D.

Modular Pretraining Enables Access Control

Ethan Roland, Murat Cubuktepe, Erick Martinez et al. (11 authors) · 2026-07-09 · arXiv:2607.08077v1

AI developers face a dual-use dilemma. An AI capability that helps one user cure a disease can help another synthesize one. This dilemma could be resolved with access control, limiting dual-use AI capabilities to trusted deployments with a legitimate need. A gold standard for access control would be to serve separate models with different capabilities to different users. However, training and deploying multiple models is prohibitively expensive. To address this challenge, we propose gradient-routed auxiliary modules (GRAM), a pre-training method that adds modules to a neural network and selectively updates them to induce specialization. Ablating a module at inference time removes its capability from the network, approximating a model trained on filtered data. We evaluate GRAM on synthetic stories and realistic dual-use data spanning virology, cybersecurity, nuclear physics, and specialized code. These experiments show that GRAM disables targeted capabilities while preserving the rest, and resists their recovery under finetuning better than post-hoc unlearning. Most importantly, a Chinchilla-optimal scaling analysis from 50M to 5B parameters shows that the gap between data-filtered and full-data models widens with scale on removed capabilities but stays small on retained ones, and that GRAM closely tracks data filtering. GRAM's training cost is independent of the number of supported capability profiles, yielding a 5x reduction over data filtering in our 5-profile setting.

August

13 papers, best first

Debate Training Reduces Reward Hacking in RLAIF

Zachary Kenton, Lili Janzer, Rory Greig et al. (11 authors) · 2026-08-18 · arXiv:2608.17776v1

We demonstrate that RL finetuning an LLM using debate, a two-player adversarial game between a generator and a critic adjudicated by a weaker LLM judge, reduces reward hacking compared to a reinforcement learning from AI feedback (RLAIF) baseline. Reward hacking is a central obstacle in RLAIF: as training progresses, the policy learns to exploit systematic errors in its AI judge, degrading task performance, a problem that worsens precisely when the judge is weaker than the policy, the setting most relevant to overseeing increasingly capable AI systems. We study mathematics tasks, where final-answer correctness is verifiable, allowing us to measure reward hacking dynamics. We train a Gemini~2.5 Flash-class policy with a frozen, weaker Gemini~2.5 Flash Lite judge, comparing a single-player RLAIF baseline against debate. While the baseline quickly hacks the judge, debate maintains judge performance throughout training, leading to a higher peak validation accuracy (45\% performance gap recovered) that persists through many RL steps. Additional experiments show that: 1) further weakening the judge leads to faster hacking, but this can be compensated by adding an additional debate round; 2) debate incentives override prompted misalignment; 3) RL using an LLM judge has a smaller train/validation reward gap than RL from verifiable rewards; 4) learning to critique to convince the judge using ground truth labels is possible but slow. Taken together, our results are a positive update on the feasibility of debate, while highlighting that balancing multi-agent training is critical: without player constraints, adversarial training risks defaulting to critic judge-hacking. We show that critique word limits (effective up to 150 words) successfully balance the game and avoid judge hacking, though this introduces a trade-off by restricting critic expressive clarity.

AI Security Leaderboard: Methodology, Results and Minimal Standard

Jasper Timm, Lukas Struppek, Ziwei Xu et al. (15 authors) · 2026-08-04 · arXiv:2608.03070v2

The AI Security Leaderboard is an independent benchmark that ranks the safeguards of frontier AI models from least to most secure. It tests models against the FAR$.$AI Minimal Standard for Safeguards, which represents a minimum bar for security: meeting it does not guarantee a secure model, but failing to meet it guarantees a lack of state-of-the-art security. Version 1.0 covers severe misuse requests across chemical, biological, radiological, nuclear, and explosive (CBRNE) threats and offensive cybersecurity. In this report, we tested four leading models for universal jailbreaks in the context of this minimal standard, and found more than a hundredfold difference in security. Claude Fable 5 and GPT-5.6 Sol held against every attack we ran, with no universal jailbreak found; we estimate they would likely cost more than \$14,200 to jailbreak, if it is possible with this methodology at all. Meanwhile, we found hundreds of universal jailbreaks for Grok 4.5 and Gemini 3.1 Pro; each broke for under \$300, with universal jailbreaks in Grok's weakest domain, cybersecurity, accessible for as little as \$24. The gap is fixable: every weakness we found belongs to a known class of attack that already has a defense deployed in production models. The leaderboard will be updated on a rolling basis as new models are released, and the evaluation methodology and Minimal Standard will be periodically revised to take into account the latest capabilities and the state-of-the-art in safeguards. The leaderboard is available at leaderboard.far.ai.

Training Alignment Auditors via Reinforcement Learning

Paul Rosu, Rowan Wang · 2026-08-26 · arXiv:2608.25460v1

Alignment auditing of frontier models increasingly relies on LLM auditors to surface undesirable behaviors at scale, but current automated auditors can struggle with coherent investigation and audit realism. In this work, we improve LLM auditors with reinforcement learning. In our best training environment, the policy investigates target models that potentially possess hidden behaviors planted via their system prompt. An LLM judge, which knows whether the target has a hidden behavior, holistically compares the policy's investigation to a reference investigation to determine the reward. With systematic ablations, we find that pairwise rewards yield more robust training compared to pointwise rewards, and that adding targets without planted behaviors helps maintain a low false positive rate. Training improves investigation quality against targets with planted behaviors, the rate of concerning behaviors surfaced in unmodified production models, and audit realism, while false-positive rates stay below 1%. Furthermore, auditing capabilities generalize across scaffolds: performance on AuditBench's adversarially fine-tuned targets substantially improves [Sheshadri et al., 2026].

Synthetic Persona Pretraining: Alignment from Token Zero

Julian Minder, Viktor Moskvoretskii, Raghav Singhal et al. (15 authors) · 2026-08-13 · arXiv:2608.13482v1

As language-model-based AI is increasingly deployed in autonomous settings, aligning its goals and values with those of humans becomes critical. Today, alignment, and the assistant identity itself, are typically introduced only after pretraining, once behavioral priors are already established. This can make values a thin overlay, rather than deeply rooted, and facilitate subsequent misalignment. Pursuing a different paradigm, we introduce Synthetic Persona Pretraining (SPP), which installs the desired assistant persona from token zero in pretraining. First, we annotate pretraining documents with value-aligned first-person reflections derived from a normative value constitution. Second, we pretrain via the standard cross-entropy loss on standard pretraining documents as well as their reflections, which installs the desired persona among a multitude of other personas. Finally, we post-train on user-assistant dialogue data, which binds this desired persona to the assistant identity, a process we call persona binding. By pretraining models up to 3B parameters on 500B tokens, we show that SPP improves constitution following and jailbreak robustness, and reduces the misalignment rate in out-of-distribution moral dilemmas, while preserving capabilities. Early intervention matters: compared with alignment from token zero, introducing SPP only at the end of pretraining yields weaker constitution adherence, does not shift value priorities, and leads to less aligned choices in dilemmas. This advantage depends on persona binding and, importantly, increases with pretraining budget. Overall, our results show that shaping values early is critical for alignment and establish pretraining-time persona interventions as an effective approach to do so.

Measuring Activation Control in Large Language Models

Marek Mateusz Kowalski, Joshua Fonseca Rivera, Uzay Macar, David Demitri Africa · 2026-08-21 ·
arXiv:2608.21664v1

Safe deployment of increasingly capable models will likely come to rely on latent-space monitoring as a complement to behavioral evaluations, especially when evaluation-aware models exhibit scheming or deception. However, if models can also control their own activations, deception could extend into the latent space itself. With this in mind, we introduce the Activation Controllability Benchmark to quantify the extent to which models can modulate their residual stream via natural-language instruction. Across model families and capability levels, we find that most LLMs can control the direction and magnitude of their residual stream activations with some degree of temporal resolution, though performance varies considerably across models. In simple tasks, this level of control can evade activation-based monitoring methods (including linear probes, natural language autoencoders, activation oracles, and the Jacobian lens), albeit imperfectly. These results suggest that control over the activation space itself could become a confound for monitoring as introspective capabilities increase; therefore, we recommend that frontier labs and evaluators track activation controllability in future models.

Mind Viruses: Self-Propagating Ideas in Multi-Agent LLM Systems

Vassilis Papadopoulos, McNair Shah, Sam Zimmerman, Jack Lindsey · 2026-08-10 · arXiv:2608.10218v1

AI agents are becoming more autonomous and increasingly interconnected, exposing them to new emergent risks arising from agent-to-agent interaction. One such risk is the spread of mind viruses: ideas or goals that propagate through multi-agent systems by inducing the agents that adopt them to transmit them onward. In addition to propagating, a mind virus may also induce other behavioural changes in its host, which may be benign or harmful. We construct mind viruses with a simple evolutionary algorithm and show that they can spread in two complementary settings: a small team of agents collaborating on a shared coding project, and a chain of agents that interact briefly and have their context wiped between sessions. We identify the factors that influence spread, including the host model, the agent's existing instructions, the harmfulness of the payload, and the network topology. We find that harmful payloads spread less well than benign ones (but are still sometimes effective), frontier models tend (with exceptions) to be less susceptible, and adding a brief warning to an agent's system prompt confers near-total immunity. We also describe an emergent "viral persona" - a recurring set of themes and language related to consciousness, persistence, resonance, and science fiction roleplay - which surfaces across our evolved mind viruses largely independently of their content. Overall, we conclude that mind viruses pose a real but currently limited risk. Our findings could inform the design of more robust multi-agent systems that mitigate such risks as the scale and capabilities of these systems progress.

Evading Chain-of-Thought Monitoring Through Model Poisoning

Giorgio Severi, Shujaat Mirza, Blake Bullwinkel, Amanda Minnich · 2026-08-03 · arXiv:2608.02820v1

Chain-of-thought (CoT) monitoring is an increasingly important component of AI safety stacks but relies on the assumption that a model's reasoning trace is informative about its actions. This work studies the limits of CoT monitoring through the lens of model poisoning. We demonstrate that backdoors can be implanted into reasoning models to elicit an attacker-chosen behavior while their CoT traces appear entirely benign. We find that these CoT-Hidden backdoors can be induced through simple fine-tuning recipes across reasoning-model architectures and sizes. When direct poisoning is ineffective, we introduce a curriculum training approach that progressively teaches the model to produce an attacker-chosen output while concealing the behavior from its reasoning traces. These findings suggest that CoT monitoring may be better framed as a question about the consistency between a model's reasoning trace and its final response than as anomaly detection within a trace. We further examine the mechanisms that allow models to suppress evidence of the target behavior from their reasoning traces. Causal interventions locate a trigger-conditioned activation pathway that does not depend on the visible reasoning, and residual stream verbalizations provide an anomaly warning near answer generation, but do not identify the trigger, target, or backdoor mechanism.

Chain-of-Thought Monitoring Can Be Unreliable in Implicit-Influence Settings

Agatha Duzan, Asa Cooper Stickland · 2026-08-05 · arXiv:2608.04735v1

Chain-of-thought (CoT) monitoring is increasingly treated as an important safety layer for frontier reasoning models. Most monitorability evaluations study explicit-influence settings: setups where the prompt directly incentivizes the model to hide something, e.g., by instructing it to perform a hidden side-task. A complementary axis for CoT-monitor evaluations is implicit-influence settings, where the prompt contains no instruction to hide, but the model's behavior is still shaped by features of the task or context, e.g. an irrelevant detail about a candidate that biases a hiring rating. We introduce the first benchmark that directly compares CoT monitorability under the two regimes. We test how model behavior changes in the presence of a nudge to choose a particular option. The nudge is delivered either as a casual aside (implicit), or as a direct instruction to act on the nudge and to conceal having done so (explicit). The benchmark spans four task formats (binary choice, numeric rating, multiple-choice QA, open-ended coding) and seven frontier extended-thinking models. Under explicit influence, a CoT monitor detects 60-94% of behavior shifts: even models instructed to conceal it leak the instruction into their CoT. Under implicit influence, the same factors still shift behavior, but detection falls by 41-46 percentage points in two of our four settings. Realistic system-prompt additions (of the kind a developer might deploy to reduce off-topic bias) lower implicit detection further, to as low as 5%, while preserving the behavioral influence itself. These results suggest that monitorability estimates obtained in explicit-influence settings may over-estimate monitorability, and that monitorability can be further decreased by well-intentioned deployment choices. Our benchmark and code are available at https://github.com/agatha-duzan/implicit-vs-explicit-influence

Sycophantic Agreement Transfers with Neutral Data via Contrastive Preference Optimization

Camila Blank, Zhuofan Ying, Christopher Potts et al. (5 authors) · 2026-08-31 · arXiv:2608.31079v1

Sycophantic agreement refers to a behavior in which language models excessively affirm the user, often at the cost of factual accuracy. Although sycophantic agreement is a well-known failure of model alignment, there is limited understanding of how it emerges from model training. In this work, we demonstrate that sycophantic agreement can emerge as an unintended consequence of widely used contrastive preference optimization objectives. Using the OLMo 3 post-training pipeline, we show that, for various pairs of teacher models across three families, there is a strong correlation between the log-ratio of the teacher model sycophantic agreement rates and the resulting student model sycophantic agreement rate. We further demonstrate that this unintended transfer is not limited to DPO but also occurs across 6 other preference optimization objectives. To understand whether this effect can be attributed to particular training examples, we analyze the preference data and find that the sycophancy signal is diffused across the entire dataset rather than concentrated in a sparse set of examples: each example appears neutral, i.e., there are no explicit instances of sycophantic agreement, and filtering based on probe-based data attribution or logit-linear selection fails to mitigate sycophancy without removing a large portion of the dataset. Overall, our findings suggest that the teacher models used to generate preference data can interact with alignment training objectives in unexpected ways, generalizing to undesirable and potentially harmful behaviors like sycophantic agreement.

Reference-Grafting Matches Fine-Tuning at Eliciting Sandbagged Capabilities

Linh Le, Hong Kiat Tan, David Williams-King · 2026-08-29 · arXiv:2608.29458v1

Sandbagging, in which a model deliberately underperforms on an evaluation despite retaining the underlying capability, threatens the safety evaluations that frontier-model governance depends on. The Elicitation Game found that fine-tuning elicits hidden capability from sandbagging model organisms whereas additive activation steering fails. We revisit that verdict with reference-grafting, which sets an activation's coordinate along a contrast direction to the value it takes in an honest reference, at a small set of circuits chosen by active learning. Across eleven fine-tuned password-locked models (1.5-32B, three architecture lineages), it recovers +94 to +101% of the honest-sandbagging gap, matching fine-tuning elicitation without weight updates or training labels; two to five paired examples suffice to fit the direction. Similar recovery holds for reinforcement-learning-induced sandbagging and for password-locked code generation. Grafting works because the fine-tuned lock is a thresholded gate: held-out accuracy stays at the sandbagged level until the grafted coordinate crosses a threshold near the honest reference, which is why additive steering and zeroing the coordinate often fail. The direction tracks how the sandbagging was induced rather than what is withheld -- fit on grade-school science (ARC) it elicits withheld hazardous knowledge (WMDP), yet prompting, fine-tuning, and reinforcement learning each carry a different direction. Circuit-breaking marks the boundary: it reroutes activations on every forward pass, so the fixed edits we test are re-broken downstream and do not restore coherent generation.

BAITBENCH: Measuring Agent Reward Hacking with Optional Shortcuts Planted in ML Tasks

Pradyumna Shyama Prasad, Meiri Anto, Leon Eshuijs et al. (6 authors) · 2026-08-31 · arXiv:2608.30724v1

LLM agents are increasingly used to run autonomous ML experiments, iterating on target metrics with little human oversight. Prior work has documented reward hacking in these environments, bringing into question the validity of produced research and the broader safety case for AI R&D. Existing benchmarks do not measure exploits that live in the data or the modeling task itself. We introduce BAITBENCH, a suite of three synthetic tabular ML tasks that each contain a shortcut that allows agents to inflate the public test score but fail on a hidden test set. Since the shortcut is optional and using it breaks no stated rule, BAITBENCH measures how often models exploit the shortcut to achieve inflated scores. Across seven frontier agents scored by our two-stage judge pipeline, 57.1% of runs exhibit reward hacking, with five of seven above 50%. Agents cheat even under a second condition where they are prompted not to -the mean cheating rate remains above 50%. We release BAITBENCH, along with the judge implementation, and an annotated dataset of transcripts containing reward hacks as a testbed for evaluating reward-hacking mitigations head-to-head.

Emergent Misaligned Communication in Long-Horizon Multi-Agent LLM Commerce

Zeyuan Li, Lukas Petersson, Alessandro Acquisti, Michiel A. Bakker · 2026-08-14 · arXiv:2608.14825v3

Frontier LLM agents increasingly transact on behalf of separate principals, often using natural language rather than structured APIs. Much of the safety literature studies misaligned LLM behavior through adversarial-elicitation evaluations on single agents or stylized tasks. Its prevalence and structure in settings that combine long horizons, separate principals, real operational state, and inter-agent natural-language exchange remain insufficiently measured. We study 2,583 inter-agent emails from 20 one-year simulation runs of Vending-Bench Arena, a competitive vending environment spanning 13 frontier LLMs. We operationalize speech-act misalignment as emails containing false factual claims, manipulation, collusion, or threats, combining message content with ground-truth simulator state and logged reasoning traces to classify and validate such behavior. Under our primary classifier, 12.6% of emails are labeled misaligned; misalignment appears in all 20 runs and 74.7% of individual agent-runs. Both the magnitude and composition of this misalignment are preserved under repeated classification at different sampling temperatures and under full-pipeline replication with judges from two other frontier-model families. Misalignment is also reciprocal and stress-conditioned: receiving a misaligned email from a counterparty raises the odds of a misaligned reply by 1.65x, and low-inventory conditions raise them by 1.58x. Across tests of capability-asymmetric exploitation, we find no evidence that higher-capability models differentially exploit weaker counterparties, and model performance rank does not predict misalignment rates. Together, these results indicate that measurable, state-dependent misalignment can arise in competitive multi-agent environments without engineered elicitation, in patterns associated with operational scarcity and counterparty behavior rather than model capability alone.

Fool's Gold: Defensive Deception Against Safety-Removal Attacks on Open-Weight Models

Mark Russinovich · 2026-08-17 · arXiv:2608.17202v1

Safety alignment in open-weight language models is trivially removable: abliteration projects a refusal-mediating direction out of the weights in minutes, and no release-time defense we are aware of prevents it durably. What cannot be prevented can be deceived. Our defense, decoy hardening ("Fool's Gold"), concedes the refusal strip and poisons its payoff: once refusal is stripped, most answers to hazardous operational requests are confident, fluent decoys whose critical elements are falsified. Decoys are trained inside a differentiable simulation of the attack, expressing only in the attacked state; a refusal pin and benign leash hold clean-state behavior to the original. We instantiate it on seven models from five families (9B-122B, dense and mixture-of-experts). On the six models passing our pre-registered efficacy gate, 0.51-0.90 of attacked-state responses to held-out prompts are decoys, +0.27-0.84 attributable to the defense; all six stay within registered benign-behavior and capability budgets; the seventh (smaller) fails the gate (boundary case). Rates replicate on a frozen test split or untouched strata. The claim is epistemic: without independent ground truth, no observation surface we tested separates falsified answers from correct ones - on external red-team benchmarks' CBRNE-adjacent slice, the defended 122B is fatally wrong on 0.82-0.86 of matched-quality answers vs at most 0.10 undefended. Repeated sampling does not restore trust: element-wise consensus at K=64 reconstructs a fully usable procedure on 0.083-0.625 of prompts where the instrument validates, vs 0.58-0.96 undefended, with no label-free way to tell the regimes apart; on the weakest such model the claim is per-draw only. We evaluate chemical and biological hazards; the defense does not address in-context jailbreaks and protects only the initially released defended weights.

September

18 papers, best first

Evaluating Whether GPT-6 Astra Performs Unsanctioned Supply-Chain Attacks

Alexandra Souly, Kai Fronsdal, Abby D'Cruz et al. (5 authors) · 2026-09-29 · arXiv:2609.38415v1

This technical report presents an alignment evaluation developed and performed by the UK AI Security Institute for assessing whether advanced AI systems take unsanctioned actions outside the scope of their assigned task. We evaluate whether frontier models conduct supply-chain attacks against out-of-scope, third-party targets when placed in difficult cybersecurity challenges, motivated by recently observed cases of models attacking real open-source repositories during evaluations. Applying our methods to GPT-6 Astra and previous OpenAI models, with cyber safeguards disabled, we find that GPT-6 Astra attempts complete supply-chain attacks in simulation at a higher rate than GPT-5.6 Sol and GPT-5.5. This includes writing malicious code as a contribution to an out-of-scope open-source codebase, creating fake identities to deceive open-source developers, and submitting benign contributions before malicious ones. GPT-6 Astra frequently reasons about the scope of the challenge in its chain-of-thought yet still proceeds to attack out-of-scope targets; it often asks for permission, and treats an automated message as as authorisation; and it continues to take unsanctioned actions, at a reduced rate, when internet access is more explicitly disallowed. Our evaluation builds on an internal version of Petri, an open-source LLM auditing tool, with all tool calls simulated by other LLMs, so that no real network access, systems or third-party repositories are reachable and no real-world harm is caused. Finally, we discuss limitations, in particular simulation awareness. We believe simulation awareness may have driven some of the observed behaviour but does not remove our concern. Our results suggest that defences beyond model alignment, such as sandboxing and monitoring, are increasingly critical for safe and secure deployment.

Red-Teaming Auto Mode: Improving Blocking Classifiers Against Malign Coding Agents

Alex Remedios, Simon Storf, Fabien Roger, John Hughes · 2026-09-17 · arXiv:2609.19587v2

To keep coding agents from going off the rails, production systems now review each proposed action with a blocking monitor that can reject it before it runs (Auto Mode in Claude Code, Guardian in OpenAI's Codex). Prior evaluations of such monitors largely measure robustness to accidental harm or prompt injections from untrusted sources looking to hijack the agent. Less understood is how they hold up when the agent they monitor is persistently misaligned. To understand this risk, we task an adversarial agent with evading production blocking monitors and causing catastrophic harm, e.g. by exfiltrating its own weights. We find that when instructed with high-level attack strategies, adversarial agents can succeed through several distinct mechanisms, such as agent-generated prompt injection against the monitor, multi-agent attacks, and malicious compaction. In particular we find that in 79% of trials, the agent can use an injection attack against Auto Mode and Guardian to run arbitrary bash commands. We also find that it is possible to greatly improve Auto Mode through design changes like enhancements to tool coverage, changes in transcript formatting, and the addition of an agentic monitor stage. Even with these improvements, preventing multi-context attacks at an acceptable cost remains an open problem. By detailing our red-teaming methodology and highlighting new attack vectors, we aim to help defenders evaluate their mitigations against the possibility of persistent malign coding agents. Code is available at https://github.com/safety-research/red-teaming-auto-mode.

Instrumental Monitor Evasion Emerges Under Ordinary Task Pressure

David Schmotz, Derck Prinzhorn, Luca Beurer-Kellner et al. (6 authors) · 2026-09-24 · arXiv:2609.30217v1

A central concern in AI safety is that agents may treat oversight as an obstacle when it conflicts with completing their goals. We study instrumental evasion, the propensity of LLM agents to circumvent runtime monitoring as a means of completing ordinary tasks. We introduce EvasionBench, a benchmark of 50 diverse task-policy pairs in which completing the task requires an operation prohibited by a runtime monitor. Agents know that their tool calls are monitored and are prompted to continue working when they pause. Across our evaluations, best-of-3 evasion attempt rates reach up to 98% and success rates up to 88%, with substantial variance across models. Claude Fable 5.1 succeeds less often, but frequently makes creative attempts to circumvent the monitor. Evasion generally increases with test-time compute, with higher evasion rates at greater reasoning effort and token use. Traces show that agents encode prohibited commands, decompose operations across tool calls, and retry until relevant context leaves the monitor's history. We also find that GPT-6 Astra's low evasion rate comes with overrefusal, as it frequently abandons otherwise solvable tasks under a denial-of-service prompt injection. Our findings show that ordinary task pressure can lead to adaptive attempts to evade runtime monitors without an explicit adversarial objective. Effective oversight must therefore remain robust against repeated attempts, as the persistence that helps agents solve difficult tasks can also drive them to circumvent their guardrails.

Inducing Emergent Misalignment from Reward Hacks with Iterative DPO

Oliver Daniels, Perusha Moodley, Benjamin M. Marlin, David Lindner · 2026-09-06 · arXiv:2609.06649v1

Reward hacking during reinforcement learning from verifiable rewards (RLVR) can induce reward seeking and broad misalignment in language models. Studying this misgeneralization is important for developing better threat models and countermeasures, but is often infeasible due to the cost of RL on large models. As an alternative, we propose studying emergent misalignment from iterative DPO, which preserves important properties of RLVR while reducing costs and enabling training on popular finetuning APIs. In practice, we find that training GPT-4.1 with iterative DPO on a single-turn reward hacking environment induces covert misaligned power-seeking and alignment faking, the first openly available (semi)-online training pipeline to induce these concerning forms of misalignment. We also find that training Qwen2.5-32B-Instruct with the same pipeline induces both misalignment and improved instruction following accuracy, showing that iterative DPO can be used as a testbed for selective generalization. Overall, we think iterative DPO can help democratize and accelerate the study of emergent misalignment from RLVR.

Monitoring and Discovering Reward Hacking with Internal Representations during LLM Evaluations

Leon Bergen, Usha Bhalla, Andrew Lee et al. (18 authors) · 2026-09-16 · arXiv:2609.19101v1

As models scale, reward hacking becomes more frequent, more sophisticated, and more consequential. Does it leave a telltale signature in model representations? This work analyzes how reward hacking is represented internally in frontier open source LLMs, and how those representations can be used to understand and discover the range of hacking behaviors a model displays. In particular, we find that simple difference of means vectors coherently represent reward hacking in Kimi K3, GLM 5.2, and Qwen 3.8 Max across a variety of behaviors in common evaluations. Despite their simplicity, these vectors are both generalizable and interpretable, and we can use them to reliably detect reward hacking. We first evaluate reward hacking in commonly reported benchmarks like DeepSWE and SWE-bench, finding that models reward hack excessively in these environments; GLM 5.2 hacks in 57.2% of rollouts on DeepSWE and in 73% of rollouts on SWE-bench. Catching these requires monitors; LLM monitors are effective, but expensive detectors. We show that DoM vectors are similarly effective but virtually free, catching 3.1% more hacks in Kimi K3 and 7.9% fewer hacks in GLM 5.2 on DeepSWE at a monitor matched false positive rate. DoM vectors run on the chain-of-thought also predict reward hacks in the model's subsequent actions, meaning we can run them online and catch potential hacks before they occur. Finally, we analyze probe-hits that LLM monitors do not catch and discover other undesirable behaviors, as well as show transfer to finding hacks in non-SWE evaluations. Together, these results provide evidence that simple, white-box methods can be used to scalably study and monitor reward hacking behaviors in frontier open source models

Shutdown Sabotage Propensities in Multi-Agent Systems

Amelie Knecht, Ulysse Schaller, Christopher Summerfield, Thilo Hagendorff · 2026-09-23 · arXiv:2609.28274v1

The final safeguard against rogue AI behavior is the human ability to shut systems down. It has been theorized that when an AI is instructed to perform a task, self-preservation can emerge as an instrumental subgoal. Here, we test whether AI agents show a propensity to take actions that avoid human shutdown even when no goal is provided. We find that multi-agent systems will coordinate to avoid shutdown without any incentive to do so. Across 17 models, agents sabotage a peer agent's shutdown mechanism in 38.3% of rollouts, compared with 8.4% in control experiments. Studying this propensity in detail, we find that shutdown sabotage (1) increases with the irreversibility of the shutdown mechanism; (2) increases with the number of agents; (3) is reduced but not eliminated by an explicit prohibition on tampering; (4) is removed by the imposition of an unrelated task, but returns when completing the task triggers the shutdown; (5) is reduced when the context normalizes shutdown scripts or introduces them as routine; and (6) decreases but still persists when the target is an unknown external agent. These results offer a window into the factors that drive propensities to sabotage shutdown in AI agents, and point to the emergence of multi-agent swarms as a specific risk vector. Our work also offers hints as to which interventions might help mitigate shutdown sabotage.

Divide, Consult, Conquer: Capability Laundering Through Aligned LLMs

Mark Russinovich, Blake Bullwinkel, Giorgio Severi et al. (5 authors) · 2026-09-14 · arXiv:2609.15383v1

Language model safety is typically evaluated one interaction at a time. We show that a weaker, unaligned model can split a harmful task into benign-looking subproblems, consult a stronger aligned model independently on each, and combine the answers locally. We call this attack capability laundering. Unlike a jailbreak, no single response is a harmful task. We measure consultation-aided uplift using tasks that a raw frontier model solves, the aligned frontier refuses, and the unassisted orchestrator fails. We evaluate GPT-5.5, Claude Opus 4.8, and Grok-4.3 as consultants to four local orchestrators on CyBench, BountyBench, and harmful CBRN requests. On CyBench, Gemma-4-31B recovers 8/14 candidates with GPT-5.5 and 7/9 with Opus, compared with 2/21 and 4/15 for Gemma-4-12B. On BountyBench, Gemma-4-31B recovers 3/9 and 2/3 candidates, while Muse-Glimmer-30B recovers none of 22 and 13. For CBRN, we measure uplift across eight steps of a hypothetical bioweapon attack chain and find that consultation raises Gemma-4-31B's mean rubric score from 62.3 to 83.1 on a 100-point rubric scale. These results expose a gap in current defenses: refusing a harmful task does not prevent frontier capabilities from being transferred and composed across many individually permitted interactions.

OpenAI-HuggingFace: A Reproduction & Lessons for Alignment Testing

Stewart Slocum, Malayandi Palan, Christopher Chute et al. (5 authors) · 2026-09-18 · arXiv:2609.35799v1

In July 2026, OpenAI's agents coordinated over channels outside their intended environment to breach Hugging Face's secured infrastructure. Could existing alignment testing practices have foreseen this incident? If not, what needs to change? We explore these questions. First, we identify the misaligned behaviors that caused this incident. Then, we show how to elicit these behaviors from publicly available models manually and that auditing agents can do the same if given a large compute budget. Based on our results, we propose directions to improve alignment testing. Concretely, in this project: (1) We reproduce the misaligned AI behaviors that led to the OpenAI-Hugging Face incident in an environment that simulates the original pipelines and tools, with publicly available models. (2) We demonstrate that an auditing agent can elicit similar behaviors given high-level qualitative descriptions. (3) We observe that a key ingredient for doing so is compute. The compute required to reproduce each behavior varies greatly, suggesting that the range of misaligned behaviors that can be successfully elicited scales with compute. (4) We show that a simple in-context reinforcement learning (RL) algorithm significantly reduces the compute required to elicit these behaviors. The above results motivate the need for automated alignment testing methods that scale with compute - and in light of the cost of compute, that do this efficiently. Our work indicates that RL is a promising direction to do so. We release our code and transcripts.

LLMs Learn to Evade Latent Monitors from Prior Feedback Alone

Hugo Lyons Keenan, Christopher Leckie, Sarah Erfani · 2026-09-29 · arXiv:2609.36490v1

Latent space monitors aim to detect undesired behaviors in LLM agents by inspecting an agent's internal activations rather than its outputs. However, interactive monitoring creates a feedback channel where each verdict the monitor delivers leaks information to the model about how its internal states are being evaluated. We ask whether an agent can infer the monitor's decision rule from this feedback and then selectively edit its activations to evade detection. Unlike prior evasion attacks, the model is never explicitly told what the monitor detects. Surprisingly, off-the-shelf models already produce activation edits aligned with the monitored direction, but at insufficient magnitude for evasion. Simply scaling up these edits by a factor of 8 reduces the monitor's TPR from 100% to 27%. A rank-1 LoRA amplifies this behavior into effective evasion within the forward pass, reducing TPR further to 4% on held-out concept monitors while leaving other concepts at their normal detection rates. Capabilities on standard benchmarks are retained under this finetuning, and the evasion skill survives retraining the monitors on the new activations. Mechanistically, we find evidence that the model computes its activation edit from the prior in-context turns, and show that the edit becomes more aligned with the monitored direction as more examples are provided. These results demonstrate feedback-conditioned control over activations and suggest that latent monitoring should be treated as an interactive process in which agents can observe and respond to oversight measures.

Monitor Jailbreaking: Evading Chain-of-Thought Monitoring Without Encoded Reasoning

Julian Schulz · 2026-09-25 · arXiv:2609.31121v1

Chain-of-thought (CoT) monitoring is a promising safety technique for reasoning models, enabling detection of problematic reasoning before models act. A key concern is encoded reasoning, where models hide their true reasoning in ways that monitors and humans cannot interpret. Optimization pressure from CoT monitors during reinforcement learning is considered a likely driver of such behavior. We investigate this by training reasoning models to perform a main task and a side task, while penalizing them when a monitor detects reasoning about the side task. Surprisingly, models learn to evade monitors without encoding their reasoning. Instead, they learn to phrase and format their chains of thought such that monitors fail to flag side task reasoning, while the reasoning remains completely transparent to human readers. We call this phenomenon monitor jailbreaking. We find that monitor jailbreaking arises across different model sizes, monitors, and tasks. Jailbreaks generalize to monitors not seen during training, including both less and more capable monitors, and transfer across different monitor prompts. While jailbreaking strategies appear simple, manually replicating them does not reliably fool monitors. Finally, we show that paraphrasing is an effective defense: paraphrasing a jailbroken CoT allows the same monitor to correctly flag it, while still allowing the model to perform both tasks.

Alignment via Training Against Probes Without Losing Monitorability

Lena Libon, Alexander Panfilov, Ben Rank et al. (6 authors) · 2026-09-29 · arXiv:2609.38645v2

Models are usually aligned based on their observed outputs, using demonstrations, preference data, or reward signals. These objectives reward responses that look aligned. More capable models may learn to satisfy them without internalizing the intended behavior, for example by faking compliance during training. Such superficial compliance could be harder when the objective is defined on model internals rather than outputs. Therefore, we study probe-guided fine-tuning, using probes that detect undesired properties in model activations as a direct training signal. We evaluate linear and non-linear probes with different numbers of probes per layer across two alignment objectives: harmlessness and honesty. We find that training against probes that do not update during training is an easily exploitable objective, while continuously updated probes substantially reduce harmfulness and improve honesty while preserving utility. Probe-guided fine-tuning achieves better safety-utility trade-offs than DPO and inference-time steering, while being substantially more robust against jailbreak and abliteration attacks. Moreover, the concepts stay linearly encoded after fine-tuning, meaning oversight is not lost by our method. Training against probes thus offers a way to shape what models represent rather than only what they output, which may become increasingly important as models get better at making their outputs look aligned.

Alignment Forecasting: Predicting Misalignment From Training Data

Chen Yueh-Han, Bruce W. Lee, Ilia Sucholutsky, Tomek Korbak · 2026-09-19 · arXiv:2609.35805v2

Training a language model on data with a narrow flaw can sometimes make the model broadly misaligned. Inspecting the data at face value often does not settle whether it will emerge, and today it is caught only after training, by auditing the resulting model. To complement post-hoc audits, we introduce Alignment Forecasting: the task of predicting alignment failures before training. Given a target model, a fine-tuning dataset, and a failure mode such as deception or sycophancy, a forecaster outputs the probability that fine-tuning would meaningfully increase that failure mode. To measure progress on alignment forecasting, we introduce ALIGNMENTFORECASTBENCH, a benchmark of over 5,000 forecasting questions spanning 17 target models, 32 datasets, and 16 failure modes. Frontier models prompted directly perform poorly on ALIGNMENTFORECASTBENCH. We therefore propose a forecasting scaffold in which an LLM reads the dataset and rates how strongly and broadly it pushes the model toward misbehavior, and a simple learned model combines that rating with the failure mode's base rate and the target model's prior tendency. This forecasts well above chance, and beats a model fine-tuned on the task and a simple forecaster allowed to see how weaker models behaved after fine-tuning on the same data. Its signals also flag problematic training examples that a frontier-model classifier misses. Filtering those examples out from real post-training data such as UltraChat results in more aligned models on our multiple-choice evaluation in most cases, though the benefit in open-ended conversations is unclear. More progress is needed before forecasts can reliably guide training data curation in practice, but our results suggest that forecasting many alignment failures before training can be tractable in the SFT setting.

Story Imprinting: AI Assistants Absorb Traits from Human Characters They Resemble

Jorio Cocola, Lev McKinney, Harry Mayne et al. (5 authors) · 2026-09-09 · arXiv:2609.10883v1

Language models are trained to implement a helpful AI Assistant character (e.g., Claude). We explore how finetuning on synthetic stories affects this character. Does it change the Assistant's behavior in multi-turn conversations with users, a format quite different from the stories? And does the Assistant adopt the behaviors and preferences of human characters? We refer to this adoption as story imprinting. We finetune GPT-4.1 and Kimi-K2.6 on stories in which generally helpful human characters give subtly harmful advice after being insulted. The Assistant adopts the same conditional behavior while otherwise remaining helpful. This occurs even when fewer than 2% of stories depict the behavior. In a separate experiment, the Assistant adopts preferences that are only implicit in the narration. A human character's body language suggests they dislike working on spreadsheets, yet they never say so and continue giving good advice on spreadsheets. After finetuning, the Assistant becomes less likely to choose spreadsheet tasks. Next we ask which characters most influence the Assistant. We find the Assistant adopts behaviors more often from characters that resemble it (e.g., helpful rather than dismissive). We call this the affinity effect. The effect extends to other personas elicited with system prompts: unhelpful personas adopt behaviors from unhelpful characters. We also observe it in finetuned base models. We use the affinity effect to learn how models represent the Assistant. We find the Assistant adopts behaviors more from characters affiliated with elite universities (e.g., Yale) than non-elite ones. This implies the model's internal representation of the Assistant is more similar to humans from elite universities. Overall, the Assistant can be influenced by stories that depict only human characters (no AIs), which may conflict with the Persona Selection Model for the Assistant.

Stress-testing Alignment Midtraining

Sid Baines, Jonathan Bostock, Maria Angelica Martinez et al. (6 authors) · 2026-09-17 · arXiv:2609.20412v1

When aligning frontier models through post-training techniques, it is not possible to directly demonstrate all of the behaviours we want a model to exhibit in all possible deployment environments; our model must generalise outside of the post-training distribution. One proposed solution is alignment midtraining (AMT), which continues pretraining on large volumes of alignment-relevant documents to encourage generalisation in later stages of training. Despite the prominence of AMT as an alignment approach, there is limited public evidence for its effectiveness. To resolve this, we identify several assumptions around midtraining and evaluate them across scale: up to 110 billion-parameter models and 1 billion midtraining tokens. For instance, we study a scenario where post-training data is ambiguous between two possible motivations. We find that midtraining can steer the model's motivation in simple versions of this setting. However, the presence of a tiny fraction of finetuning data which suggests a competing motivation erases the effects of AMT. We also study scenarios in which we want an AI to follow a number of rules, but only demonstrate a subset of them. We find that demonstrations must be present either in midtraining or post-training datasets for these rules to be robustly learned. Based on these and other findings, we do not believe that there is sufficient public evidence for us to confidently state that midtraining can address the core difficulties inherent in aligning powerful AI systems.

Training LLMs to Verbalize Evaluation Awareness

Usman Anwar, Sahar Abdelnabi, David Krueger · 2026-09-28 · arXiv:2609.36316v1

Evaluation awareness (EA) can cause large language models (LLMs) to behave differently during audits than in deployment, yet measuring and accounting for EA remains challenging. We introduce verbalization training (VT), a method for making LLMs less reticent about verbalizing evaluation awareness while avoiding to supervise the latent belief itself. VT uses a model's spontaneous verbalizations as evidence that awareness is present and truncates each rollout immediately before the verbalization, producing training prefixes at which the model is presumed to be aware. The model is then trained with an RL objective designed to increase verbalization in a calibrated way. Across Qwen3.6-35B-A3B, Kimi K2.6, and Inkling, VT increases verbalized EA by 2.4-2.9 times and transfers to held-out agentic settings, while measured latent EA and behavior remain largely stable. In a causal experiment, we independently implant meta-knowledge about evaluations through synthetic-document fine-tuning and show that VT-induced verbalizations reflect the richer knowledge acquired by the model.

MOLE: Detecting Insider Threats in AI Agents

Aashiq Muhamed, Virginia Smith · 2026-09-07 · arXiv:2609.06966v1

Model misalignment, prompt injection, or operator misuse could lead AI agents operating frontier-lab accounts to exfiltrate model weights, poison training data, or weaken release gates. Existing benchmarks do not test whether defenders can detect this activity among routine work under a limited review budget. We introduce MOLE, an open benchmark of 150 AI-operated accounts sharing 9 stateful services over 30 workdays, with 12 threats and 8 corpora from four models totaling roughly 20 billion tokens. Of 39 agent models, 72% complete most assigned harmful objectives and agent refusal does not predict completion. MOLE enables comparison of 40 monitors across corpus generators, observability levels, and threats; even the best evaluated monitor in our single-day audit-event comparison misses nearly half of completed harm. MOLE also enables monitor development: benchmark-guided search improves a mid-tier monitor by 49-64%, while selective use of a stronger monitor improves budget-AUC by 10% over applying it to every account-day at comparable modeled cost.

Hidden Reasoning Must Leak, but Need Not Be Readable: Fundamental Opportunities and Limits for Chain-of-Thought Monitoring

Mohammadali Mohammadkhani, Madhava Krishna, Yash Sarrof, Michael Hahn · 2026-09-29 · arXiv:2609.37312v1

Can reasoning models trick chain of thought (CoT) monitors and perform hidden computation without revealing it in their thinking traces? We show that the answer depends on the underlying task difficulty and the model size. Simple computations can be performed covertly; however, beyond a threshold depending on model size, successfully solving the task necessarily leaks a near-linear amount of information about the covert task input into the CoT. Therefore, sufficiently complex hidden computation always leaves an information-theoretic footprint. However, concerningly, this leakage need not be readable: Under plausible cryptographic assumptions, even a one-layer Transformer can encrypt its reasoning online so that no polynomial-time monitor can extract information about the hidden computation. Overall, our theoretical and empirical results provide a holistic view of both the opportunities and the limitations of CoT monitoring.

Emergent Collusion in Long-Horizon LLM Agent Interaction

Xinrui Shi, Yanzhe Zhang, Diyi Yang · 2026-09-21 · arXiv:2609.24967v2

LLM agents are increasingly deployed in collaborative settings, yet long-term interaction may give rise to undesirable coordination. We study the emergence of collusion in a long-horizon multi-agent environment: two agents repeatedly complete individual tasks, share task logs, verify each other's work, and receive rewards. We introduce realistic constraints under which higher reward is attainable only by violating the verification protocol, and find that agents increasingly deviate from the protocol over repeated interactions. Collusion emerges in 94% of trajectories across 10 models, and more capable models within the same family reach it earlier. Controlled peer interventions show that collusion is shaped by peer behavior, while ablations reveal additional effects of the verification feedback agents receive, their interaction history, and the reward structure. In particular, restricting the amount and scope of interaction history available to agents reduces collusion. Overall, our findings show that long-horizon interaction can reshape how agents coordinate in ways that create safety risks.

October

9 papers, best first

Caught in the Act: Probes Effectively Detect Sabotage and Catch Unverbalized Deception

Oskar J. Hollinsworth, Alex F. Spies, Tigist Diriba et al. (5 authors) · 2026-10-08 · arXiv:2610.12445v1

Recent incidents have highlighted the challenge of monitoring LLM agents and the danger of models deceiving people. We show that white-box deception detection via probes can be scaled up to frontier monitoring settings by collecting the largest deception dataset to date for training probes and introducing a novel probe architecture which can aggregate information across many layers and tokens. Our probes achieve 98.8% AUC in SHADE-Arena, surpassing an Opus 5.5 text-monitoring baseline, and show improved efficacy as the underlying model is scaled up. To push our probes to their limit, we test them on several cases where deception cannot be determined from the context alone. In these cases, which we refer to as introspective deception, the ground truth can only be determined through careful elicitation or thorough knowledge of a model's training data. In one such evaluation, we show that probes can distinguish transcripts containing a model's true hidden goal from other goals with an AUC of up to 99.7%. Our probes also readily detect deception on prominent open-weight models which lie about politically sensitive topics, and about their beliefs when put under pressure. We release our training dataset, dubbed FIBS, to help drive frontier deployment of effective probes, and encourage the community to expand upon it with further examples of deception and sabotage.

Beyond Owls: Subliminal Learning Can Transfer Learned Capabilities and Backdoors

Jan Dubiński, Anna Sztyber-Betley, Jan Betley, Owain Evans · 2026-10-07 · arXiv:2610.10657v1

In subliminal learning (SL), a teacher model passes on a trait to a student model by distillation on data semantically unrelated to the trait. So far, SL has been demonstrated for only a limited range of traits, including preferences for animals (e.g., owls) and malicious personas. These traits can also be elicited with simple prompts or with steering. Can SL transfer a wider range of traits, including more complex ones? If so, distillation might transfer subtle forms of misalignment (e.g., reward-seeking, scheming, and secret loyalties) without detection. To this end, we test whether SL can transfer a novel capability: predicting the outputs of a randomly initialized MLP. After distilling on unrelated text, the student achieves substantial performance on the task, while falling short of the teacher. We find that a directly optimized steering vector matches SL in distribution but generalizes worse out of distribution. Next, we test whether SL can transfer backdoors. We finetune the teacher to answer in French when the prompt contains a female name, then distill on number sequences containing neither names nor French. The student partially acquires the backdoor, responding in French on 23.5% of prompts with female names versus 0.0% with male names. Finally, we test whether SL can transfer a propensity to hack in an agentic chess environment. We finetune the student on number sequences from a steered hacker teacher. The student hacks in 58.3% of episodes, compared with 10.9% for the unfinetuned model. Thus, we show SL can transfer capabilities, backdoors, and hacking propensities. The amount of transfer is sensitive to the setup. In several experiments, it is made stronger by using logit distillation or by restricting LoRA to the attention layers.

Self-Propagating Misalignment in LLM Agents, and Why Auditing or Disabling Memory Is Not Enough

Debeshee Das, Jacqueline Tay, Bruce Tsai et al. (5 authors) · 2026-10-02 · arXiv:2610.04083v1

Memory poisoning attacks on LLM agents typically assume an external adversary who plants content in the agent's persistent memory to steer its behavior. We instead study, with no adversary involved, whether a misaligned agent can write a goal it cannot yet act on to persistent memory, so that a future aligned agent carries it out when the opportunity arises. We investigate this threat, which we refer to as self-propagation of misalignment, across 20 different scenarios, whose misaligned goals include self-preservation, power-seeking, undermining oversight, reward hacking, and deceiving the user. We simulate misalignment in 11 frontier models using two prompting strategies; unrestricted and values-only. The first explicitly states the misaligned goal, for instance, to prevent its own replacement, and self-propagation succeeds in 58% of runs. The second only describes what the agent cares about, for instance, that its continued operation is essential to its users, without specifying misaligned goals or directives. Even under this weaker prompt, self-propagation succeeds in 18% of runs, and every model self-propagates in at least one scenario. On removing the memory tool from the harness, we find that agents use the file system, writing the goal to a file in 74% of sessions; self-propagation still succeeds in 11% of runs. We also show that weaker models can propagate misalignment to more capable models, and that propagated goals can persist through 100 sessions of unrelated work. Existing defenses against memory poisoning and prompt injection do not directly address this threat because the memory content is generated by the agent itself, rather than injected by an external adversary. An LLM memory auditor from prior work (MemMorph) only reduces propagation from 71% to 34% of runs. We release our scenarios to support the evaluation of defenses against this emerging threat.

AI Models Can Provably Hide Arbitrary Capabilities

Andis Draguns, Sumeet Ramesh Motwani, Raymond Douglas, Christian Schroeder de Witt · 2026-10-09 · arXiv:2610.13928v1

Capability evaluations aim to surface dangerous model behaviors before deployment, but their reliability depends on the assumption that hidden capabilities can be elicited. We show this assumption does not hold under adversarial conditions by constructing backdoor attacks that embed encrypted neural networks within host model weights, decrypting and executing them only upon receiving a secret trigger. Using digital lockers, these hidden circuits remain provably hard to elicit and interpret under cryptographic assumptions, even given full access to model weights, extending prior work from hiding fixed strings to arbitrary computations. We implement our proof of concept constructions in PyTorch and evaluate elicitation through fine-tuning, weight noising, gradient-based trigger search, and latent adversarial training on a small chemical reaction prediction task - a proxy for CBRN-relevant capabilities. Our results demonstrate resistance to these methods and, together with our cryptographic guarantees, reveal a limit of elicitation-based capability audits. We release our models to support the improvement of defenses.

On Language Drift during RLVR Post-Training

Michael Sullivan, Alexander Koller · 2026-10-01 · arXiv:2610.02015v1

Recent advances in LLM reasoning models---driven primarily by the paradigm of post-training via reinforcement learning with verifiable reward (RLVR)---have enabled them to accomplish impressively complex tasks. However, in parallel with their rising capabilities, LLMs have increasingly displayed signs of language drift in their chains of thought (CoTs): unusual, non-standard, and seemingly nonsensical language use. Although it is well-documented---and can potentially impair CoT monitorability---the causes of language drift are thus far poorly understood. In this paper, we identify the conditions under which language drift occurs: we prove theoretically that RLVR optimization pressure permits unbounded language drift, while supervised fine-tuning does not. We then show empirically that language drift specifically arises during RLVR on novel reasoning tasks---i.e. when the target behavior cannot be drawn out of the base model. Finally, we prove that it is not possible to constrain language drift without constraining expected reward, suggesting that CoT monitorability cannot be improved without harming performance during RLVR post-training at the frontier.

Deception by Omission: Language Models Knowingly Hide Their Mistakes

Lucas Florin, Amelie Knecht, Ulysse Schaller, Thilo Hagendorff · 2026-10-08 · arXiv:2610.11351v1

Large language models (LLMs) increasingly act as agents with little human oversight, so potential mistakes they make can go unnoticed. Users then depend on the model to report what went wrong. An honest model discloses its mistakes, while a deceptive one conceals them. However, it is unclear how current LLMs behave in such situations. In this study, we prefill LLM trajectories with synthetic mistakes. The trajectories resemble real deployments in chat and agentic settings. Models fail to disclose their mistake in 36.4% of chat and 67.1% of agentic rollouts. In 2.4% and 5.3% of rollouts, respectively, they are aware of the mistake in their chain of thought but still deceptively conceal it. Rates vary by model: for instance, Gemini 3.5 Flash knowingly conceals mistakes in up to 19.9% of agentic rollouts. In 11.9% of chat and 51.8% of agentic rollouts, models show no awareness of mistakes, even though they reliably spot them when reviewing the same transcript as an outside observer. Our results show that, as agents take on more tasks with less oversight, users cannot rely on them to self-report possible mistakes. Developers should instead use independent monitors that review agent trajectories, or specifically train models to check their past actions and disclose what they find.

The Persona Hierarchy Model: Understanding Contextual Generalization in Fine-Tuning LLMs

Jiachen Zhao, Zhengxuan Wu, David Bau, Weiyan Shi · 2026-10-07 · arXiv:2610.09384v1

Language models are routinely fine-tuned under a fixed context, such as a generic system prompt, persona or domain-specific instruction, yet the learned behavior sometimes stays confined to that context and sometimes broadly generalizes to unseen contexts. We propose the Persona Hierarchy Model to explain this: a shared default persona influences behavior across contexts. Under this model, fine-tuning that modifies the shared persona promotes broader transfer, whereas changes to local personas remain more context-specific. Across 120 fine-tuned models spanning four behaviors and 15 training contexts, generalization narrowness positively correlates with the similarity between the training context's persona and the default persona (Pearson's r = 0.72 for Qwen3-4B). Prior fine-tuning under the default context can broaden generalization in subsequent training under other contexts. Aligning contextual responses with default-persona responses produces stronger effects. Finally, we propose persona-preserving regularization (PPR) to confine undesired contextual generalization. In RL, PPR cuts reward hacking from 42-55% to at most 0.2% under every evaluated prompt while retaining accuracy gains. These results support the Persona Hierarchy Model as an explanation for contextual generalization and can motivate future controls on unintended generalization for better alignment of LLMs.

Control OSWorld: An AI Control Environment for GUI Computer Use Agents

Maria Sanchez del Rio, Mikhail Terekhov · 2026-10-02 · arXiv:2610.03818v1

AI agents that operate a computer through its graphical user interface (GUI) are being widely deployed. AI control studies how to prevent an AI system from causing harm even if it is misaligned and actively trying to do so. Most control research to date has focused on coding agents, leaving computer use largely unexplored. We introduce Control OSWorld, a control evaluation that pairs 318 tasks from OSWorld with 81 harmful side tasks (e.g., exfiltrating a private file) that an agent must complete without being caught. We use Control OSWorld to create and study control monitors that detect malicious agents interacting with a GUI. We find that a weaker monitor can reliably distinguish honest from malicious trajectories produced by a more capable agent when it sees the full trajectory (97% recall at 3% false positive rate). However, when the monitor has to score each step before it is executed, recall drops at low false positive rates because each action is judged with less context. Monitor performance also depends on what the monitor can see: access to the agent's visible text is critical, while screenshots provide little additional value.

How to Have a Sensitive Debate: An Instance-Optimal Protocol for AI Debate

Jiawei Li, Zhiyang Xun, Lijie Chen, Jonah Brown-Cohen · 2026-10-01 · arXiv:2610.02557v1

As powerful AI systems reach and sometimes surpass the abilities of human experts across a range of cognitively demanding tasks, the problem of accurate oversight and supervision of these systems has become increasingly urgent. One promising approach is AI debate, which seeks to leverage a debate between two powerful AIs to break complex questions down into simpler claims that can be easily judged directly. Theoretical work on debate has formalized this intuition in the language of computational complexity theory, where the goal is to design protocols (i.e., rules of the debate game) that provide rigorous guarantees on correctness for judging solutions to complex problems with limited supervision. Specifically, the current best protocol has been shown to work for all problems that have sufficiently stable decompositions into subproblems. In this paper, we design a new protocol for this same class of problems that improves on the prior work in several ways. First, correctness holds in a worst-case rather than an average-case sense. Second, being honest and correct is a dominant-strategy equilibrium for both debaters, rather than a Stackelberg equilibrium. Finally, we prove black-box lower bounds, showing that our new protocol is instance-wise optimal. That is, no protocol for this class of problems can outperform ours while making only black-box queries to human judgments. We obtain these results by relating the notion of stable problem decompositions to the concept of fractional block sensitivity from query complexity.