

Kata

A programming kata is a problem to be solved. You can solve the problem any way you want, no matter the language. The important thing is to train your practice and reasoning in solving problems. It can be applied with TDD and also with other methods.

SinglePairOrOdd

returns a single integer that is pair or odd in a list of integers, where we can have only one pair and several odd or one odd and several pairs.

Reference: <https://www.codewars.com/>

Count the Digit

Take an integer n ($n \geq 0$) and a digit d ($0 \leq d \leq 9$) as an integer. Square all numbers k ($0 \leq k \leq n$) between 0 and n . Count the numbers of digits d used in the writing of all the k^2 . Call `nbDig` (or `nbDig` or ...) the function taking n and d as parameters and returning this count.

Example:

$n = 10$, $d = 1$, the k^2 are 0, 1, 4, 9, 16, 25, 36, 49, 64, 81, 100. We are using the digit 1 in 1, 16, 81, 100. The total count is then 4. `nbDig(25, 1)`: the numbers of interest are 1, 4, 9, 10, 11, 12, 13, 14, 19, 21 which squared are 1, 16, 81, 100, 121, 144, 169, 196, 361, 441 so there are 11 digits '1' for the squares of numbers between 0 and 25.

reference: <https://www.codewars.com/kata/count-the-digit/train/java>

FizzBuzz

Write a program that prints the numbers from 1 to 100. But for multiples of three print "Fizz" instead of the number and for the multiples of five print "Buzz". For numbers which are multiples of both three and five print "FizzBuzz".

reference: <https://codingdojo.org/kata/FizzBuzz/>

FooBarQix

Step 1

If the number is divisible by 3, write "Foo" instead of the number

If the number is divisible by 5, add "Bar"

If the number is divisible by 7, add "Qix"

For each digit 3, 5, 7, add "Foo", "Bar", "Qix" in the digits order.

Example:

1 => 1

3 => FooFoo (divisible by 3, contains 3)
6 => Foo (divisible by 3)
15 => FooBarBar (divisible by 3, divisible by 5, contains 5)
21 => FooQix
33 => FooFooFoo (divisible by 3, contains two 3)

Step 2

We have a new business request : we must keep a trace of 0 in numbers, each 0 must be replace par char “*“.

Example:

101 => 1*1
303 => FooFoo*Foo
105 => FooBarQix*Bar
10101 => FooQix**

reference: <https://codingdojo.org/kata/FooBarQix/>