

```

In [13]: # -*- coding: utf-8 -*-
        """
        Created on Sun Oct 27 02:10:04 2019

        @author: jorge
        """

import sympy as sym
import numpy as np
import matplotlib.pyplot as plt
import matplotlib as mpl

# get_ipython().run_line_magic('matplotlib', 'inline')
# https://scipy-lectures.org/packages/sympy.html
# ^^ how to use sympy ^^

height = 10
width = 10

mpl.rcParams['figure.figsize'] = (width, height)
mpl.rcParams['font.size'] = 18
mpl.rcParams['figure.titlesize'] = 'small'
mpl.rcParams['legend.fontsize'] = 'small'
mpl.rcParams['xtick.major.size'] = 12
mpl.rcParams['xtick.minor.size'] = 8
mpl.rcParams['xtick.labelsize'] = 18
mpl.rcParams['ytick.major.size'] = 12
mpl.rcParams['ytick.minor.size'] = 8
mpl.rcParams['ytick.labelsize'] = 18

HX, HY = 50, 50 # number of x,y points for countour
xmin, xmax = -2, 2
ymin, ymax = -2, 2
x1 = np.linspace(xmin, xmax, HX)
x2 = np.linspace(ymin, ymax, HY)
X1, X2 = np.meshgrid(x1, x2) # generatate mesh grid
w1 = sym.Symbol('w1') # define symbols
w2 = sym.Symbol('w2')

j = (w1**2 + w1*w2 + 3*w2**2) # define equation

# compute gradient
j_grad1 = sym.diff(j, w1)
j_grad2 = sym.diff(j, w2)
# compute hessian
hess11 = sym.diff(j_grad1, w1)
hess12 = sym.diff(j_grad1, w2)
hess21 = sym.diff(j_grad2, w1)
hess22 = sym.diff(j_grad2, w2)

# generate contour map
ConMap = np.zeros((HX, HY))
for i in range(HX):
    for k in range(HY):
        ConMap[i, k] = j.subs({w1: x1[i], w2: x2[k]})

logetas_ls = np.arange(-5, 0, 0.5)
etas_ls = 10**logetas_ls
logetas = np.array([-2, -1, 0], dtype=np.float)
etas = 10**logetas
lim = 50 # number of iterations
threshold = 1e-5
wStar = [0, 0] # ending point

colors = ('lightgray', 'salmon', 'black')
labels = [r'$\eta = $' + str(eta) for eta in etas]
styles = ['-', '-', ':']

```

```

In [14]: plt.figure(figsize=(10,10))
plt.contour(X1,X2,ConMap)

for i in range(len(etas)):
    np.random.seed(0)
    w=np.random.normal(0,1,2) # starting point
    ew=[]
    jw=[]
    count= 1
    line=[]
    while(True):
        #compute gradient matrix and hessian matrix
        g= np.array([float(j_grad1.subs({w1:w[0],w2:w[1]})),float(j_grad2.subs({w1:w[0],w2:w
[1]}))])
        H= np.array([[float(hess11.subs({w1:w[0],w2:w[1]})),float(hess12.subs({w1:w[0],w2:w
[1]}))],
                    [float(hess21.subs({w1:w[0],w2:w[1]})),float(hess22.subs({w1:w[0],w2:w
[1]}))]])

        dw = -np.dot(np.linalg.inv(H), g)

        eta = etas[i]

        wnew = w+eta*dw
        line.append(w)
        #loop check
        if(np.abs(wnew - w).mean() < threshold):
            print('Converge break')
            print(count)
            break
        elif( count>lim ):
            print('Count Break')
            break
        elif(np.isnan(g).any()):
            print('nan break')
            break
        else:
            count=count +1
            wprev=w.copy()

            w=wnew.copy()

            ew.append(np.linalg.norm(w-wStar))
            jw.append(j.subs({w1:w[0],w2:w[1]}))
    line=np.array(line)

    plt.plot(line[:,1],line[:,0], color=colors[i], linestyle=styles[i], label=labels[i],)# z
    order=len(etas)-i)
    plt.scatter(line[:,1],line[:,0], 25, color=colors[i], )#zorder=len(etas)-i)

plt.plot(wStar[1],wStar[0], 'rx', markersize=8)
plt.xlim(xmin, xmax)
plt.ylim(ymin, ymax)
plt.xlabel(r'$x_1$')
plt.ylabel(r'$x_2$')
plt.legend()
plt.tight_layout()
#plt.savefig('../prob7.eps', dpi=500)

```

Count Break
 Count Break
 Converge break
 2

