

```
In [10]: # -*- coding: utf-8 -*-
        """
        Created on Tue Nov 12 18:49:03 2019

        @author: jorge
        """
        import numpy as np
        from requiredFunctions.trainMLP import trainMLP
        from requiredFunctions.MLP import MLP
        from requiredFunctions.doubleMoon import doubleMoon
        import matplotlib as mpl
        import matplotlib.pyplot as plt
        import matplotlib.ticker as mtk

        height = 10
        width = 10

        mpl.rcParams['figure.figsize'] = (width, height)
        mpl.rcParams['font.size'] = 20
        mpl.rcParams['figure.titlesize'] = 'small'
        mpl.rcParams['legend.fontsize'] = 'small'
        mpl.rcParams['xtick.major.size'] = 12
        mpl.rcParams['xtick.minor.size'] = 8
        mpl.rcParams['xtick.labelsize'] = 18
        mpl.rcParams['ytick.major.size'] = 12
        mpl.rcParams['ytick.minor.size'] = 8
        mpl.rcParams['ytick.labelsize'] = 18

        # Data parameters
        N_train = 300
        N_val = 3000
        r = 1
        w = 0.6
        d = -0.5

        # Model parameters
        learning_rate = 1.25e-3
        alpha = 0
        epochs = 1000*125

        # Init train data
        train_data = doubleMoon(N_train, w, r, d, seed=0)
        x_train, y_train = train_data[:, :2], train_data[:, 2]
        x_train, y_train = x_train.T, y_train.reshape(1, len(y_train))

        # Init validation data
        val_data = doubleMoon(N_val, w, r, d, seed=100)
        x_val, y_val = val_data[:, :2], val_data[:, 2]
        x_val, y_val = x_val.T, y_val.reshape(1, len(y_val))

        wh, wo, mse, mse_val = trainMLP(x_train, y_train, [5], learning_rate, alpha,
                                         epochs, verbose=False, X_val=x_val, D_val=y_val)

        train_pred = MLP(x_train, wh, wo).flatten()
        train_pred[train_pred > 0] = 1
        train_pred[train_pred < 0] = -1
        val_pred = MLP(x_val, wh, wo).flatten()
        val_pred[val_pred > 0] = 1
        val_pred[val_pred < 0] = -1

        train_acc = (train_pred == y_train).sum() / N_train
        val_acc = (val_pred == y_val).sum() / N_val
```

```

In [11]: epoch_grid = np.arange(0, epochs) + 1
print('Early Stopping Point at', epoch_grid[np.argmin(mse_val)], 'epochs')
print('Final Accuracies')
print('Training: {}'.format(train_acc*100))
print('Testing: {}'.format(val_acc*100))
fig, ax = plt.subplots()
ax.plot(epoch_grid, np.log10(mse.flatten()), color='blue', markeredgewidth=2, label='Training')
ax.plot(epoch_grid, np.log10(mse_val.flatten()), '--', color='crimson', markeredgewidth=2, label='Testing')
ax.set_xlabel('Epochs')
ax.set_ylabel(r'$\log_{10}$MSE')
ax.xaxis.set_major_locator(mtick.MultipleLocator(25000))
ax.xaxis.set_minor_locator(mtick.MultipleLocator(5000))
ax.yaxis.set_major_locator(mtick.MultipleLocator(0.5))
ax.yaxis.set_minor_locator(mtick.MultipleLocator(0.1))
ax.ticklabel_format(axis='x', style='sci', scilimits=(3,3), useMathText=True)
ax.set_xlim(-5000, epochs+5000)
ax.set_ylim(-1.5, 0.2)
ax.legend()
fig.tight_layout(pad=0.5)
#fig.savefig('../prob3a.eps', dpi=500)

```

Early Stopping Point at 47864 epochs
 Final Accuracies
 Training: 100.0%
 Testing: 98.8%

