

More JavaScript and jQuery Checkpoint

Quiz Score

Your Results:

You got 19 questions right out of 30 (63%).

12. When defining an object, its property-value pairs are enclosed within ____.

~~colons~~

curly brackets

28. In terms of objects, how would one use bracket notation to refer to a value that is not a variable?

~~object(property)~~

object["property"]

21. What will be logged to the console with the following code? `var myObject = { myNumber: 30, myFunction: function() { this.myNumber += 30; console.log(myObject.myNumber); } } myObject.myFunction();`

~~3030~~

60

18. What will be logged to the console with the following code? `var myFunction = function(someCar) { var myCar = someCar; } myFunction("Honda"); console.log(myCar);`

~~Honda~~

ReferenceError: myCar is not defined

13. What is another JavaScript method that is used to loop over arrays or Objects?

~~\$.each~~

forEach

1. The ____ jQuery method can be used to iterate over an array without using a for loop.

~~.iterate~~

.each

26. To attach an element to the beginning of another element, we can use the ____ jQuery method.

~~.append~~

.prepend

19. Writing ____ is equivalent to writing \$() when using the jQuery library.

~~library()~~

jQuery()

24. The ____ jQuery method can be used to place attributes on HTML elements

~~.attribute~~

.attr

11. We can give classes to elements using the ____ jQuery method.

~~.setClass~~

.addClass

30. What will the code below log to the console when run in a browser? function myFunction() { console.log(this); } myFunction();

~~this~~

Window

100%