

0 ^ B b h l e w E W \$

beginning of line first non-blank character previous WORD previous word previous character next character end of word beginning of next word end of WORD beginning of next WORD end of line

:e path :e! :view path :r file :q :q!
load and edit return to load file in insert con- quit quit, discard
given file unmodified file read-only mode tents of file changes

:w :saveas path :browse old :cd :pwd
write file save with new name List recent files, allow to change dir echo current
select one by number. working dir

^o previous jump location
gg beginning of file
^b back 1 page
^u up 1/2 page
{ beginning of paragraph
k up 1 line
j down 1 line
} end of paragraph
^d down 1/2 page
^f forward 1 page
G end of file
8G to first non-blank char of line 8
:8 to start of line 8

Buffers

:ls :b n :b file
list all buffers jump to buffer nr n jump to buffer with containing file

:bp :bn :bd
jump to prev buffer jump to next buffer delete current buffer

:e path :enew :bufdo C
load and edit given file new blank buffer apply command c to all buffers

Inserting

I i a A
beginning of this line before cursor after cursor end of this line

O o s S
beginning of previous line beginning of next line substitute character substitute line

C cw r R
change rest of line change rest of word replace 1 character replace from cursor

Deleting

x diw dw d/ foo
delete character delete all of word delete rest of word delete until first 'foo'

dd d0 d^ d\$
delete line del from BOL to cursor delete 1st non-blank char to cursor del from cursor to EOL

d} :1,.d :.,\$d dt c
del to end of paragr. del from line 1 to cursor del from curs to EOF delete up to char c

Replace

:s/foo/bar/g
In current line replace all (/g) 'foo' with 'bar'

:%s/foo/bar/g
In all lines replace all 'foo' with 'bar'

:%s/foo/bar/gic
In all lines replace all 'foo' with 'bar', case-insensitive, and ask for confirmation

:3,9s/foo/bar/g
In lines 3 to 9 (incl) replace all 'foo' with 'bar'

:.,.+5/^/ /g
From current line to 5 line further, prepend 3 spaces at the beginning of each line

:s/\In current line replace all occurrences of 'foo' that are a separate word, with 'bar'

:5,\$s/foo//g
From current line to last line, replace all 'foo' with nothing (= delete 'foo')

:%s/\t/ /g
In all lines, replace tab with 4 spaces

:%s/red\|pink/blue/g
In all lines, replace all instances of "red" and "pink" with "blue"

: '<,'>s/foo/bar/g
In the visually pre-selected lines, replace foo with bar.

Selecting (visual)

v V ^v gv
select per character select per line select rect-angular block reselect prev selection

d y P p
delete selection yank (copy) selection paste before cursor paste after cursor

o O aw iw
go to start of selection go to end of selection select word & whitespace select inner word

a", a', a(, a[, aB, at
i", i', i(, i[, iB, it

Version with a: include "" " () [] {} <>
Version with i: exclude "" " () [] {} <>

Copying

yy yiw yw
yank this line yank inner word yank rest of word

y0 y^ y\$
yank from BOL to cursor yank from 1st non-blank char to cursor yank from cursor to EOL

Undo/Redo

u :earlier 4m
undo take document to state of 4 min ago

^r :later 50s
redo 50 sec later in document state

Search

* #
Go to next match of exact current word Go to prev match of exact current word

g* g#
Idem as * but not exact Idem as # but not exact

/foo ?foo
Search forward for foo, not exact Search backward for foo, not exact

n N
Go to next match Go to prev match

/\Search forward for foo, exact no search highlights

Move

:m 5 :m 0 :m \$:m ' }-1
mv current line to after line 5 mv current line to before line 1 mv current line to after last line mv current line to end of paragraph

:2,4m \$:2,4m 9 :.,.+2m 9
mv lines 2,3,4 to after last line mv lines 2,3,4 to after line 9 mv 3 lines starting from the current one to after line 9

vim-multiple-cursors

^n Selects current word in visual mode, and puts cursor at end of it. Pressing it again find next occurrence and puts a cursor at the end.

^p Remove last virtual cursor and go back to last one.

^x Skip last virtual cursor and go to next occurrence of the word.

After all cursors are placed, you may opt to go out of visual mode (press v) and use the normal commands.

Search/Replace in multiple files

:vimgrep /foo/g *.py Search in all files. Use :copen to get a list of matches.

:bufdo %s/foo/bar/ge | update
Apply to all buffers. Ignore pattern not found errors (e). Save file if changes were made (update).

:arg *.cpp Create arglist with C++ files and load them into buffers
:argadd *.h Add header files to arglist, and load into buffers
:argdo %s/foo/bar/ge | update Apply to every file in arglist

netrw & Ctrl-p

:edit read write	sftp://user@hostname/path
:edit	folder (folder can be .)
:Vexplore	split left-right and show file browser
i	toggle between file browser view options
/path	move cursor to nearest match in file browser
:^p	<i>filename</i> Fuzzy search file. Use ^f and ^b to toggle between files, buffers, and <u>most recently used</u> . Can be used for “ Open Recent... ”

:edit read write	sftp://user@hostname/path
:edit	folder (folder can be .)
:Vexplore	split left-right and show file browser
i	toggle between file browser view options
/path	move cursor to nearest match in file browser
:^p	<i>filename</i> Fuzzy search file. Use ^f and ^b to toggle between files, buffers, and <u>most</u> <u>recently</u> <u>used</u> . Can be used for “ Open Recent... ”

Global command

: [range] g/pattern/command	
:g/foo/d	Delete all lines that contain 'foo'
:., \$g!/foo/m\$	Move all lines from cursor to EOF, that do not contain 'foo', to EOF.
:g/^/m0	For all lines move them to the beginning of the file = reverse file.
:g/^foo/s/\$/bar	For all lines starting with 'foo', substitute/append 'bar' to EOL.

: [range] g/pattern/command	
:g/foo/d	Delete all lines that contain 'foo'
:. , \$g! /foo/m\$	Move all lines from cursor to EOF, that do not contain 'foo', to EOF.
:g/^/m0	For all lines move them to the beginning of the file = reverse file.
:g/^foo/s/\$/bar	For all lines starting with 'foo', substitute/append 'bar' to EOL.

Case switching

~	Toggle case of character under cursor
g~iw	Toggle case of the inner word
g~\$	Toggle case from cursor to EOL
gUw	Convert rest of word to large caps
gUU	Convert current line to upper case
gu0	Convert from BOL to cursor to small caps.

-	Toggle case of character under cursor
g-iw	Toggle case of the inner word
g-\$	Toggle case from cursor to EOL
gUw	Convert rest of word to large caps
gUU	Convert current line to upper case
gu0	Convert from BOL to cursor to small caps.

Vimtex

- \ll** Start/stop continuous compiling mode
- \lv** Jump to PDF viewer at the same point of the cursor
- \lc** Clean auxiliary files
- [[** Jump to the previous (sub)section
-]]** Jump to the next (sub)section
- %** Move between matching delimiters

- \ll** Start/stop continuous compiling mode
- \lv** Jump to PDF viewer at the same point of the cursor
- \lc** Clean auxiliary files
- [[** Jump to the previous (sub)section
-]]** Jump to the next (sub)section
- %** Move between matching delimiters

Ctags & TagBar

:tag <i>name</i>	Jump to (1st) match of the tag. Name can be a regular expression (e.g. <i>/Detect*</i>).		
:stag <i>name</i>	Jump to (1st) match of the tag in a new window. Name can be a regular expression (e.g. <i>/Detect*</i>).		
:ts <i>name</i>	List all tag matches, and lets you select one. If name is absent, use list of last :tag command.		
^]	^w}	g]	^o
Jump to tag under the cursor	Show tag match in sep window	List all matches of tag under cursor	Go back one jump
:Tagbar	Toggle show/hide tagbar		
:!ctags -R	Generate tags file, recursively		

:tag <i>name</i>	Jump to (1st) match of the tag. Name can be a regular expression (e.g. <i>/Detect*</i>).		
:stag <i>name</i>	Jump to (1st) match of the tag in a new window. Name can be a regular expression (e.g. <i>/Detect*</i>).		
:ts <i>name</i>	List all tag matches, and lets you select one. If name is absent, use list of last :tag command.		
^]	^w}	g]	^o
Jump to tag under the cursor	Show tag match in sep window	List all matches of tag under cursor	Go back one jump
:Tagbar	Toggle show/hide tagbar		
:!ctags -R	Generate tags file, recursively		

Windows			
:split	:vsplit	:only	:close
split top-bottom	split left-right	keep only current window	close current

:split	:vsplit	:only	:close
split top-bottom	split left-right	keep only current window	close current

Indenting					
>>	<<	>	<	>ap	>aB
indent current line	un-indent current line	indent selected lines	un-indent selected lines	indent current parag.	indent current block

>>	<<	>	<	>ap	>aB
ident	un-indent	indent	un-indent	indent	indent current
current line	current line	selected lines	selected lines	current parag.	block

CSV

:WhatColumn	Show current column nr
:nrColumns	Show total numbers of columns
:DeleteColumn 2	Delete column nr 2
:MoveColumn 2 4	Move col 2 to right next to col 4
:DupColumn	Duplicate current column
:Header 2	Open separate fixed window with first 2 header lines. Close with :Header!
:%ArrangeColumn!	Prettify the columns by aligning them
:NewDelimiter ;	Change the delimiter to ;
:1,10Sort 3	Sort lines 1-10 of column 3
:SearchInColumn 1 /foo/	Search for patter foo in column 1
:%Substitute 1,4/foo/bar/gc	Subst in cols 1-4 foo with bar, globally + ask for confirmation

:WhatColumn	Show current column nr
:nrColumns	Show total numbers of columns
:DeleteColumn 2	Delete column nr 2
:MoveColumn 2 4	Move col 2 to right next to col 4
:DupColumn	Duplicate current column
:Header 2	Open separate fixed window with first 2 header lines. Close with :Header!
:%ArrangeColumn!	Prettify the columns by aligning them
:NewDelimiter ;	Change the delimiter to ;
:1,10Sort 3	Sort lines 1-10 of column 3
:SearchInColumn 1 /foo/	Search for patter foo in column 1
:%Substitute 1,4/foo/bar/gc	Subst in cols 1-4 foo with bar, globally + ask for confirmation

Fugitive

- :Gblame** Show git blame info for an indexed file.
- :Gedit** SHA Show info for blob, tree, commits, and tags
- :Gedit** master:python/transits.py Read-only!
- :Gdiff** Open 3-way diff of current file, to solve conflicts
E.g. if you have conflicts after:

```
(feature) $ git checkout master  
(master) $ git merge feature
```


Left window: version of the master branch
Right window: version of the feature branch
Center window: current working copy

Keep your cursor in the center window (working copy).

```
:diffget //2 include left version in working copy  
:diffget //3 include right version in working copy  
:diffupdate update the diff highlighting
```
- :Glog -- %** Show the git log of this file per commit, and let's you select a commit
- :Gstatus** Show the git index

- :Gblame** Show git blame info for an indexed file.
- :Gedit** SHA Show info for blob, tree, commits, and tags
- :Gedit** master:python/transits.py Read-only!
- :Gdiff** Open 3-way diff of current file, to solve conflicts
E.g. if you have conflicts after:

```
(feature) $ git checkout master  
(master) $ git merge feature
```


Left window: version of the master branch
Right window: version of the feature branch
Center window: current working copy

Keep your cursor in the center window (working copy).

```
:diffget //2 include left version in working copy  
:diffget //3 include right version in working copy  
:diffupdate update the diff highlighting
```
- :Glog -- %** Show the git log of this file per commit, and let's you select a commit
- :Gstatus** Show the git index

gv

- : **GV** Open commit browser. Browse, press enter to get more info on the commit. In **visual mode**: show commit info on the selected lines.
- : **GV!** Only show commit info of the current file
- : **q** Quit the commit browser

- :GV** Open commit browser. Browse, press enter to get more info on the commit. In **visual mode**: show commit info on the selected lines.
- :GV!** Only show commit info of the current file
- :q** Quit the commit browser

Easymotion	
\\w	Trigger word motion, then select appropriate letter. Forward.
\\b	Idem but backward
\\s <i>char</i>	Trigger character motion, then select letter.

<code>\\w</code>	Trigger word motion, then select appropriate letter. Forward.
<code>\\b</code>	Idem but backward
<code>\\s char</code>	Trigger character motion, then select letter.

Folds			
zo/zc Open/close 1 fold under cursor	zO/zC Open/close all folds under cursor	zm/zr Increase /reduce fold level	zj/zk Go to start of next/previous fold

zo/zc	zO/zC	zm/zr	zj/zk
Open/close 1 fold under cursor	Open/close all folds under cursor	Increase /reduce fold level	Go to start of next/previous fold

Clipboard	
:w !pbcopy	Write selected lines to clipboard (visual mode)
:r !pbpaste	Insert contents of clipboard at current position

```
:w !pbcopy Write selected lines to clipboard (visual mode)
:r !pbpaste Insert contents of clipboard at current position
```

Miscellaneous

^a / ^x	Incr/decr the nr under cursor. Useful to automate.
f / F <i>char</i>	Jump to next/prev occurrence of <i>char</i> on this line
J	Join this line with the next one
:set scrollbarbind	Scroll synchronously. To be set in all windows that need to be in-sync. Add ! to command to undo.
:set listchars=eol:¬,tab:>·,trail:~,extends:>,precedes:<,space:␣	
:set list	Show all the invisible characters
:set nolist	Stop showing all the invisible characters

Outliner (.otl files)

\cb Insert checkbox	\cx Toggle checkbox	\cd Delete checkbox	\n Set fold level to <i>n</i>	\- Draw dashed line
\s Sort sub-tree under cursor ascending	\S Sort sub-tree under cursor descending	\t Append time stamp HH:MM:SS	\d Append date stamp YYYY:MM:DD	