

# Supplementary Material for "Assessing the hillslope-channel contributions to the catchment sediment balance under climate change"

J.P.C. Eekhout<sup>a</sup>, A. Jódar-Abellán<sup>a,b</sup>, E. Carrillo-López<sup>a</sup>, C. Boix-Fayos<sup>a</sup>, J. de Vente<sup>a</sup>

*<sup>a</sup>Soil and Water Conservation Research Group, CEBAS, CSIC, Campus de Espinardo 30100, P.O. Box 164, Murcia, Spain*

*<sup>b</sup>Centro de Investigación e Innovación Agroalimentaria y Agroambiental (CIAGRO-UMH), Miguel Hernandez University, Ctra. Beniel km 3.2, 03312 Orihuela, Spain*

---

## Contents of this file

1. Text S1: A description of the compound Manning roughness
2. Figures S1 and S2
3. Tables S1 and S2

---

*Email address:* [joriseekhout@gmail.com](mailto:joriseekhout@gmail.com) (J.P.C. Eekhout)

### Text S1: Compound Manning roughness

The compound Manning roughness was obtained with the Lotter method, which is described as follows:

$$n_{\text{compound}} = \frac{PR^{5/3}}{2 \frac{P_{\text{fp}} R_{\text{fp}}^{5/3}}{n_{\text{fp}}} + \frac{P_{\text{ch}} R_{\text{ch}}^{5/3}}{n_{\text{ch}}}} \quad (\text{S1})$$

Where  $P = 2h + W_{\text{fp}}$  is the wetter perimeter of the compound cross-section,  $R = A/P$  is the hydraulic radius of the compound cross-section, with  $A = D_{\text{ch}} * W_{\text{ch}} + (h - D_{\text{ch}}) * W_{\text{fp}}$ ,  $P_{\text{fp}} = 2(h - D_{\text{ch}}) + (W_{\text{fp}} - W_{\text{ch}})/2$  the wetter perimeter of the floodplain cross-section,  $R_{\text{fp}} = A_{\text{fp}}/P_{\text{fp}}$  is the hydraulic radius of the floodplain cross-section, with  $A_{\text{fp}} = (h - D_{\text{ch}}) * (W_{\text{fp}} - W_{\text{ch}})/2$ ,  $P_{\text{ch}} = 2h + W_{\text{ch}}$  the wetter perimeter of the channel cross-section and  $R_{\text{ch}} = A_{\text{channel}}/P_{\text{ch}}$  is the hydraulic radius of the channel cross-section, with  $A_{\text{ch}} = hW_{\text{ch}}$ .

## Figures




Figure S1: Precipitation projections for the Taibilla catchment, for the reference (1991-2020) scenario (upper row), the +1.5 °C scenario (middle row) and the +3.0 °C scenario (lower row). (a) Annual precipitation sum (mm) and (b) extreme precipitation (mm), as defined by the 95th percentile of daily precipitation, considering only rainy days ( $>1$  mm day<sup>-1</sup>; Jacob et al., 2014).




Figure S2: Model results for the Taibilla catchment, for the +1.5 °C scenario (upper row) and the +3.0 °C scenario (lower row), showing the difference between the future climate change scenarios and the reference scenario for sheet erosion (left) and rill and channel change (right;  $\text{Mg cell}^{-1} \text{ yr}^{-1}$ ), where blue colors indicate a decrease and red colors an increase.

## Tables

Table S1: Climate model characteristics, including their corresponding future periods per temperature scenario and the nine GCM/RCM combinations.

GCM	Climate scenarios		RCM				
	+1.5 °C	+3.0 °C	CCLM <sup>a</sup>	HIRHAM5 <sup>b</sup>	RACMO <sup>c</sup>	RCA <sup>d</sup>	WRF <sup>e</sup>
CNRM-CM5	2015-2044	2052-2081	×			×	
EC-EARTH	2012-2041	2052-2081	×	×	×	×	
IPSL-CM5A-MR	2007-2036	2039-2068					×
MPI-ESM-LR	2013-2042	2052-2081	×			×	

<sup>a</sup> Climate Limited-area Modelling-Community (CLMcom)

<sup>b</sup> Danish Meteorological Institute (DMI)

<sup>c</sup> Royal Netherlands Meteorological Institute (KNMI)

<sup>d</sup> Swedish Meteorological and Hydrological Institute (SMHI)

<sup>e</sup> Institut Pierre Simon Laplace (IPSL)

Table S2: Climate and hydrological indicators for the two considered periods in the Rogativa subcatchment. Extreme precipitation is defined as the 95th percentile of daily precipitation, considering only rainy days ( $>1 \text{ mm day}^{-1}$ ; Jacob et al., 2014). The maximum discharge is defined as the average yearly maximum discharge ( $\text{m}^3\text{s}^{-1}$ ).

Climate/hydrological indicator	1953-1982	1991-2020
Precipitation sum (mm)	540.5	495.5 (-8.3%)
Extreme precipitation (mm)	18.8	18.6 (-0.8%)
Average discharge ( $\text{m}^3\text{s}^{-1}$ )	0.03	0.01 (-45.2%)
Maximum discharge ( $\text{m}^3\text{s}^{-1}$ )	0.57	0.36 (-36.6%)

## References

D. Jacob, J. Petersen, B. Eggert, A. Alias, O. B. Christensen, L. M. Bouwer, A. Braun, A. Colette, M. Déqué, G. Georgievski, E. Georgopoulou, A. Gobiet, L. Menut, G. Nikulin, A. Haensler, N. Hempelmann, C. Jones, K. Keuler, S. Kovats, N. Kröner, S. Kotlarski, A. Kriegsmann, E. Martin, E. van Meijgaard, C. Moseley, S. Pfeifer, S. Preuschmann, C. Radermacher, K. Radtke, D. Rechid, M. Rounsevell, P. Samuelsson, S. Somot, J.-F. Soussana, C. Teichmann, R. Valentini, R. Vautard, B. Weber, P. Yiou, EURO-CORDEX: New high-resolution climate change projections for European impact research, *Regional Environmental Change* 14 (2014) 563–578. doi:10.1007/s10113-013-0499-2.