Generating a Kubernetes Deployment Set from a Project-Intent Domain Model

Project Task 2: Model Transformations
Project Type: Code Generation
October 16, 2026

Joris Jonkers (S1829157)

Model Driven Engineering
University of Twente

Contents

1 Purpose of the Project **1**

1.1 Goals . . . 1

1.2 Role of the Transformations . . . 1

1.3 Refinement of Tasks 0 and 1 . . . 2

1.4 Assumptions and Conditions . . . 2

1.5 Scope . . . 3

2 Alternatives and Justification **3**

2.1 Existing Kubernetes Modelling Tools . . . 3

2.2 The Transformation Language . . . 4

2.3 The Structure of the Transformation . . . 4

2.3.1 A Lowering Before the Resolution . . . 4

2.3.2 One Project per Run, All Projects as Input . . . 4

2.3.3 Typed Extents Instead of a Global Scan . . . 5

3 Solution Design **5**

3.1 The Lowering . . . 5

3.2 Interface . . . 6

3.3 Mappings and Queries . . . 6

3.4 A Worked Example . . . 7

3.5 The Derivation Rules . . . 8

3.5.1 A Process . . . 9

3.5.2 A Dependency Edge . . . 10

3.5.3 Environment Variables and Placeholders . . . 10

3.5.4 Network Peers . . . 10

3.5.5 The Path Plan . . . 10

3.6 The Trace and End Sections . . . 10

3.7 The Black-Box Library . . . 11

3.8 The Estate Pass . . . 11

3.9 Stops . . . 11

3.10 Running the Transformations . . . 11

4 Tests and Evaluation **12**

4.1 Results . . . 12

4.1.1 What the Revisions Show . . . 13

4.1.2 What the Generated Files Show . . . 13

4.1.3 Where the Evidence Is Thin . . . 13

4.1.4 Defects Found by Testing . . . 13

4.2 Limitations . . . 13

4.3 Reflection . . . 14

A Changes to the Task 1 Metamodels **15**
A.1 The Pinned Inputs Metamodel 15
A.2 Changes to the Target Metamodel 15
A.3 Changes to the Source Metamodel 22
A.4 Grammars for the Pinned Inputs 22

B The Hand-in Archive **23**
B.1 Running the Transformations 24

1 Purpose of the Project

1.1 Goals

The project turns short deployment documents into the Kubernetes files that deploy a small cluster. Each `Application`'s repository holds one `Project Intent` document that states what the `Application` needs: its `Process`es, their memory and CPU limits, the ports they expose, the `Application`s they depend on, and the routes that reach them from outside. One `Platform Intent` document states what all `Application`s share: cluster entry points, health-check timings and backup policies. Task 1 defined the Ecore metamodels for both. The source metamodel covers the authored documents. The target metamodel covers the `Resolved Deployment`: every value the platform derives for an `Application`, and the file path each value writes to.

Task 2 builds the model-to-model transformation from source to `Resolved Deployment`. It reads the `Project Intent` and `Platform Intent` models of every project in the cluster, plus a few documents published by other processes, and outputs one `Resolved Deployment` per project for Task 3 to consume. The transformation makes the specification's derivation rules executable: every value in a `Resolved Deployment` is produced by a rule, and no author writes any value by hand.

Term	Meaning
`Process`	One program of an `Application`, running in its own pods.
`Dependency edge`	A `Process` declaration that it calls a named port of another `Application`.
`Pinned input set`	The read-only inputs besides authored documents: node contract, images lock, `ClusterState` snapshot, migration proofs, `Asset`s.
`Switchover`	How a new version replaces the old: blue/green (both run; traffic switches once the new is healthy), rolling, or stop-start.
`Release Gate`	The service that blocks a blue/green switch until every `Process` of the `Application` is healthy.
`Reconcile Unit`	A group of files that Flux applies together and in order.
`Revision`	A SHA-256 digest of an `Application` complete element, naming one release.
`Estate`	All `Project`s, the `Platform Intent` and the `Pinned input set` read by one run.
`Effective Intent`	`Project Intent` with every shared declaration lowered onto the `Process`es that hold it.

Table 1: Project Terms Used in This Report

The transformation has three goals. First, it must derive the same values as the TypeScript production implementation, which deploys the actual cluster. Both implementations run against the same oracle files and must produce identical results. Second, it must stop with an error message when it cannot derive a value, because a `Resolved Deployment` with a missing or fabricated value would look valid yet deploy the wrong configuration. Third, its output must be complete enough that the Task 3 templates only write values into their fixed positions. Any path, port or name chosen inside a template would hide a derivation from review.

1.2 Role of the Transformations

Figure 1 shows the pipeline. Xtext converts each document to a source model, and the Task 1 OCL constraints reject invalid ones. Three QVT-Operational transformations then run in sequence.

The first transformation, the lowering, copies declarations made once for an entire `Project` or `Application` down onto each `Process`. Its output is the `Effective Intent`, which still conforms to the source metamodel. Although it was implemented in Task 1, it was not reported there, so Section 3.1 covers it here. The second transformation, the resolution, reads the lowered models and the `Pinned input set`, then writes one `Resolved Deployment` per project. It is the main subject of this report. The third, the estate pass, runs once over all `Resolved Deployments` produced together and adds the files that do not belong to any single project (Section 3.8).

A small Java exporter writes the resolved dependency edges as JSON for comparison against the oracle. The Acceleo templates of Task 3 then read the `Resolved Deployments` and generate the Kubernetes files.




Figure 1: The Pipeline, With the Two Transformations Task 2 Adds in Bold Green

1.3 Refinement of Tasks 0 and 1

Implementing the transformation refined the earlier work. Task 0 treated the node contract, images lock and snapshot as plain inputs, while Task 1 only modelled the two authored documents. The resolution needs these as models, so a third metamodel now describes the `Pinned input set`, with its own Xtext grammar for each document (Appendix A.1). This metamodel lives in a separate package because no project author writes these documents.

Task 1 described three stages: authored, resolved and generated text. The lowering adds a fourth stage between authored and resolved. This means each rule in the resolution reads values from a single level rather than spanning three (Section 2.3.1).

Task 0 was a proposal and generated nothing. Task 1 planned one resolved model for the entire cluster, because edges, routes and reverse dependencies require a cluster-wide view. That view remains: every run still reads every project. The output is now per project because the production implementation produces one `Resolved Deployment` per project and the oracles are per project (Section 2.3.2). The per-`Application` projection from Task 1 is still present as the `ResolvedApplication` inside that model.

One generated job writes every project's secret-store policies, and its name is a digest over all of them. No single project's resolution can compute this name, so the estate pass, a small second transformation over all `Resolved Deployments`, plans the job.

Task 1's target metamodel only had a worked example for `minimal`. The other examples needed additional concepts: migrations, backup identities, API access, sidecar containers and twelve more file types. Appendix A lists every change.

1.4 Assumptions and Conditions

The transformation assumes five conditions.

First, the transformation assumes valid input. The Task 1 OCL constraints already reject an invalid source model before the lowering runs, checking the entire document set of a run. A stop in the transformation acts as a safety net, catching any fact the constraints have not yet covered (Section 3.9).

Second, each run processes one cluster. It reads one `Platform Intent` and one node contract, both naming the same cluster. All concepts, examples and oracles derive from that single existing cluster.

Third, where the specification allows a choice, the transformation makes the same decision as the production TypeScript implementation, ensuring both produce the same oracles.

Fourth, the transformation has no live cluster access. It only reads the documents provided to it. Any fact known only to a running cluster, such as which node holds a particular volume, must arrive via the `ClusterState` snapshot captured by another process.

Fifth, the build executes the transformations using QVTo's standalone executor on every code change. Eclipse launch configurations can also run them (Appendix B).

More Than One Cluster. The current implementation targets a single cluster, which is a scope choice rather than a structural limitation. Every cluster-specific element is already a run input: the `Platform Intent`, the node contract and the `ClusterState` snapshot each name their cluster, and a `Project` environment files use

a shared base plus a per-cluster overlay that the resolution selects via the `Platform Intent` cluster name (Section 3.5.3). Supporting a second cluster would therefore require a second run with that cluster's own three documents.

Two additions would enable multiple clusters. A `Project Intent` would need to declare which clusters it targets. An edge to a service in another cluster would resolve through the `Platform Intent` external provider list, as the current edge from `auth` to an external mail server already does (Section 3.5.2), but its network policy would need to allow an address range rather than a specific pod address.

1.5 Scope

Table 2 sets the scope of Task 2.

In scope	Out of scope
The resolution of eight examples: `minimal`, `auth`, `data`, `delivery`, `edge`, `knowledge-platform`, `observability` and `secrets`.	The `knowledge` example, which models a project being retired (Section 4.2).
Every derivation these examples use, from dependency edges and placement to backups, migrations, network peers and the path of every generated file.	The text of the generated files, which is Task 3.
The lowering's extensions, the estate pass, and the `Pinned input set` metamodel and grammars.	Applying the files to a cluster, and a second cluster.

Table 2: Scope of Task 2

2 Alternatives and Justification

This section examines which transformation language fits the work and how the transformation should be structured.

2.1 Existing Kubernetes Modelling Tools

Three open-source tools were reviewed to see if they could produce the `Resolved Deployment` from `Project Intent` and `Platform Intent`, or at least take part in the pipeline. Table 3 compares them.

Tool	What it does	Why it cannot replace the resolution	Where it could help
KubeDiagrams [1]	Draws diagrams from Kubernetes files or a live cluster, mapping kinds to icons.	It works from files to pictures, not from models to models, and derives nothing.	It could visualize the generated files to show links produced by a project document.
KubeOrch [2]	A drag-and-drop editor: its back end wires ports, fills templates, writes files, deploys.	It has no metamodel, no constraints and its rules are Go code; it deploys directly, not via Flux.	Its graph notation could inform a project document editor.
kubert [3]	A command-line tool to switch cluster contexts and run commands on multiple clusters.	It is an operations tool and does not model or generate anything.	It could apply files to several clusters, which is out of scope.

Table 3: Existing Kubernetes Modelling Tools

None of the three derives values from authored declarations. KubeOrch comes closest: it resolves a link between two services to an address and port, similar to how the resolution resolves dependency edges. But it lacks a `Platform Intent`, node contract, images lock and snapshot, so it cannot derive placement, image digests, backups or network peers. Its output is not a model that OCL constraints or oracles can verify. The tools can therefore complement the transformation, not replace it. Two integrations are possible: the resolved

dependency edges and network peers could feed a KubeDiagrams view of the Task 3 files for visual verification; and a KubeOrch-style graphical editor could write `Project Intent` documents, since both would work from the same Ecore metamodel.

2.2 The Transformation Language

Four languages were considered: ATL, QVT-Relations, QVT-Operational (QVTo) and Java with a rule library such as SiTra.

QVT-Relations was ruled out first. Its automatic traces and two-way synchronisation offer no benefit for a one-way derivation. Published experiments also showed its engine exhausted heap space on larger models [5].

ATL, QVTo and Java were compared against the specific needs of this transformation. Most values in a `Resolved Deployment` do not derive from a single source element: a process's eligible machines depend on the node contract, a route's precedence on other routes, and a process's ingress peers on every process in the cluster that depends on it. ATL excels when one source element maps to one target element through matched rules whose order the engine chooses. Here most work would end up in helpers and called rules, turning ATL into imperative code without the pattern matching. Several values need the rest of the model to exist first, which ATL does not handle as naturally.

QVTo meets these needs. The caller explicitly decides the order of execution, and every reference from one created element to another goes through the trace. Its expressions use OCL, the same language Task 1's constraints already use. QVTo is also the second most-used transformation language after ATL, and users cite its maturity and its status as a standard as advantages [4].

A Java transformation would be easiest to debug and offers full control. However, it requires maintaining the trace by hand and hides transformation rules inside general-purpose code, which practitioners report as difficult to maintain for model management [4].

QVTo was chosen. The one operation QVTo cannot express directly, computing a SHA-256 hash, uses QVT's black-box mechanism: a Java library called through a contextual operation (Section 3.7). Speed was not decisive: QVTo ran more than five times slower than ATL in published experiments [5], but this is acceptable for a cluster of about ten projects.

2.3 The Structure of the Transformation

The transformation must satisfy several structural requirements. Every derived value needs to be in a model that tests can compare, so derivation must happen in a model-to-model step before code generation. This allows oracles to verify values independently of the templates.

A single transformation from authored model to `Resolved Deployment` would work, but splitting it into a chain offers advantages.

2.3.1 A Lowering Before the Resolution

The lowering first copies shared declarations down to each `Process`, producing `Effective Intent`. This means the resolution reads values from one level instead of three, simplifying each rule. The estate pass then adds files that belong to no single `Project`, which no individual resolution can compute. The chain also matches QVT specification Section 8.1.13, which uses a preparation step before the main transformation.

Processing one project per run while reading all projects matches the production implementation and its oracles.

2.3.2 One Project per Run, All Projects as Input

Processing one project per run while reading all projects keeps each model small while preserving the cluster-wide view that edges, routes and reverse dependencies need. The cost is that one value, the digest over all secret-store policies, needs every project's output. The estate pass computes this.

2.3.3 Typed Extents Instead of a Global Scan

Finding other documents poses another structural choice. Using OCL's `allInstances()` scans everything loaded on each evaluation and gives results that depend on which files were loaded. Instead, the transformation selects each input once by type from two extents that hold exactly the run's documents. Every rule navigates from one of these properties, ensuring consistent, predictable results (Section 3.2).

Handling missing values requires a clear strategy. Writing defaults would produce files that appear valid yet deploy incorrect configurations. Stopping with an error message prevents this, though it requires the caller to handle the failure. The transformation uses fatal assertions in stop queries to halt when a value cannot be derived (Section 3.9).

These choices give the transformation the structure it needs: a chain of model-to-model steps that each run tests can verify, with explicit control flow and predictable inputs.

3 Solution Design

Task 2 uses three QVT-Operational transformations. The lowering (`lower.qvto`) is about 340 lines with 37 mapping operations and 8 queries. The main resolution (`resolution.qvto`) is about 1700 lines with 8 mapping operations and 140 queries. The estate pass (`estate.qvto`) is about 130 lines with no mappings but one helper.

Figure 2 shows the metamodels each transformation reads and writes. The three differ in kind, each chosen for its job, and all are one-way.

- The lowering is endogenous and horizontal: it reads and writes the source metamodel at the same abstraction level, producing a new model. One project goes in, one comes out.
- The resolution is exogenous and vertical, a refinement: it reads source and pinned-input metamodels and writes the target metamodel, taking several input models and producing one output.
- The estate pass is endogenous and in-place: it updates the resolved models of a run through an `inout` extent.




Figure 2: The Resolution and the Estate Pass in the Metamodel-Based Transformation Pattern

3.1 The Lowering

The lowering, `lower.qvto`, turns each authored Project into an EffectiveProject. Every Process carries all shared declarations that apply to it, while the Project and Application carry none. Task 2 extended the Task 1 implementation with API access and engine grants.

It contains 37 small mappings, nearly all simple copies, plus three merge rules. A list such as secrets, dependency edges, Assets or environment entries becomes the union of declarations from Project, Application and Process levels. The lowest level that declares an item wins. A single value such as startup budget or cutover comes from the lowest level that declares it. Memory and CPU remain only on the Process.

Two QVTo-specific details matter. A mapping returns its cached result when called again on the same source, which would incorrectly share a single object among multiple processes. To prevent this, every shared copy uses a mapping with the Process as a parameter (`copyFor(self)`), which keys the trace on the source-process pair. A migration is one of three subclasses, so its copy uses a disjuncts mapping that selects the subclass at runtime.

The lowering has no stops. The OCL constraints run before it, so every input it sees is valid.

3.2 Interface

Example 1 shows the resolution's signature. It reads two extents from two metamodels and writes one extent of a third.

```
transformation resolution(in intent : PI, in pinned : IN, out resolved : RD)
        access library Hashing;
configuration property project : String;    -- the project this run resolves
property estate : Platform = intent.rootObjects()[Platform]->any(true);
property projects : Sequence(EffectiveProject) =
        intent.rootObjects()[EffectiveProject]->sortedBy(p | p.project)->asSequence();
property lock : ImagesLock = pinned.rootObjects()[ImagesLock]->any(true);
-- and likewise contract, snapshot, proofs and assetFiles
main() {
        projects->select(p | p.project = project)->any(true).map deployment();
}
```

Example 1: The Signature and Inputs of the Resolution, Abridged

The intent extent holds, for every project in the run, its authored model and its EffectiveProject, plus the Platform Intent. Authored models remain only because Platform Intent references them via Ecore cross-references. Every rule reads the EffectiveProject models.

The pinned extent holds the node contract, images lock, snapshot, each project's migration proof, and one AssetFile per configuration file. Two configuration properties provide non-derived inputs: the project name to resolve, and the schema package digest for provenance recording.

The seven properties select each input once by type from the root objects of its extent. This is the only way the transformation accesses other documents. Every rule navigates from one of these properties; no rule calls `allInstances()`.

A query over every Process in the cluster uses `projects.applications.processes`, whose extent is exactly the run's documents. Projects are sorted by name so that the first provider of a service is consistent across runs and implementations.

3.3 Mappings and Queries

QVTo provides two ways to create target objects. A mapping operation records its source and result in the trace. Other rules find that result later using `resolveone`. Calling the same mapping twice on the same source returns the cached result. An object expression inside a query creates an object that no other rule needs to locate.

The transformation uses a mapping exactly where another rule must reference the result. Each target type has exactly one mapping, so the type alone identifies the result: `p.resolveone(ResolvedProcess)` needs no `resolveIn`. No mapping uses a `when` guard or inherits from another; the caller selects what to map using `->select`, keeping the choice visible in one place.

Table 4 lists the eight mappings and their purpose.

Queries are side-effect free. Many attach to model types, such as `Grant::resolvedFor`. They serve four purposes.

A value query derives a single value, such as a deadline or an address. An object query builds a contained object, such as a probe or a backup plan. A spelling query turns a source enumeration literal into the string the target records, for example `AlertClass::businessHours` into `business-hours`. Stop queries such as `unlocked` raise a fatal assertion instead of returning a value (Section 3.9).

The estate pass contains the sole QVTo helper, an operation with side effects that adds files to a model it updates in place.

Mappings run in a fixed order. The deployment mapping creates ReconcileUnits first, then Applications, provenance and the path plan. Each Application maps its Processes before its Exposures, ReleaseGate and

Mapping	Creates, and why it is a mapping
`EffectiveProject::deployment`	The ResolvedDeployment. Its end section sets values that need the complete model.
`EffectiveProject::unit`	The project's ReconcileUnit, the group Flux applies together. Each Application refers to it.
`EffectiveProject::provenance`	The digest of every input and the hash over them. Its end section computes the hash.
`EffectiveApplication::application`	A ResolvedApplication. Generated files and the Revision refer to it.
`EffectiveApplication::gate`	The ReleaseGate's inputs. The Application and its configuration refer to them.
`EffectiveApplication::migrationOf`	The database migration. Its network policy refers to it.
`Process::process`	A ResolvedProcess. Gate members, routes, scrapes, policies and generated files refer to it.
`Exposure::exposure`	A ResolvedExposure. The generated route file refers to it.

Table 4: Mapping Operations of the Resolution

migration, because those refer to Processes through the trace.

3.4 A Worked Example

The `minimal` example declares one `Application`, notes, with one `Process`, notes-api, in about 35 lines of YAML. Table 5 follows declarations through to derived values.

Declared	Rule	Derived in the resolved model
`image: notes-api`	locked	`ghcr.io/jorisjonkers-dev/notes/notes-api@sha256:9c1e...`, user/group 1000, from images lock
`startupBudget: 20s`	deadlineOf, startup probe	deadline 60s (3 budgets); startup probe on liveness target every 5s, 4 failures
`cutover: continuous`	switchoverOf, gate	blue-green; `Release Gate` with 1 member, deadline 60s, platform cadence, error/latency checks
`memory: 256Mi, cpu: 50m`	eligible	all 7 machines in the node contract, each tested for twice the request size for blue/green deployment
`audience: anonymous`	tierFor, exposure	entry point public-frankfurt with TLS or ACME certificates, proxy traefik-public in the edge-system project
route /, prefix	precedenceOf, middlewareOf	precedence 1; security headers with strict content policy
`runtime: node`	profileOf	environment variables `OTEL_SERVICE_NAME`, `PORT=8080`, `DEPLOYMENT_ENVIRONMENT`, collector address from observability
scrape on http	ingressOf, monitorOf	ingress from traefik-public and prometheus on port 8080; pod monitor for blue/green
(nothing)	path plan	12 `Deliverable` entries, including `apps/notes/namespace.yaml` and `estate/edge/public-frankfurt/notes-public.yaml`

Table 5: Declarations of `minimal`, Followed Through the Resolution

Four values depend on other run documents: the image needs the lock, eligible machines need the node contract, the proxy needs the edge project, and the collector address needs the observability project.

Example 2 shows part of the source model and the resolved model. The top part is the authored `Process` in

YAML, and the bottom part is the resolved `Process` in XMI.

```
- name: notes-api
  image: notes-api
  placement: { memory: 256Mi, cpu: 50m }
  startupBudget: 20s
  cutover: continuous
--------------------------------------------------------------------------
<processes name="notes-api" deadline="60s" switchover="blue-green"
    image="ghcr.io/jorisjonkers-dev/notes/notes-api@sha256:9c1e5a4b..."
    uid="1000" gid="1000" memory="256Mi" cpu="50m">
  <startup period="5s" timeout="5s" failures="4"> ... </startup>
  <placement> <eligibleNodes>enschede-t1000-1</eligibleNodes> ... </placement>
</processes>
```

Example 2: Part of `Process` notes-api, as Authored (Top, Condensed) and as Resolved, in XMI (Bottom, Abridged)

3.5 The Derivation Rules

Table 6 lists the rules by target element. Each implements a derivation from the specification, following the production implementation where the specification allows choice.

Target value	Rule	Derivation
Application		
reconcile unit and order	unit, afterOf	One unit per project; it follows the units of projects its edges reach, and the secrets unit if it holds a secret.
secret store	synced, storeEndpoint	The Secret Store address used when a secret, backup or migration needs it.
migration	migrationOf, datastoreOf	Runner image (from lock), tested schema (from proof), database address (from edge), owner credential and egress network.
release gate	gate, switchesBlueGreen	One member per blue/green `Process` with readiness; the slowest member deadline; platform cadence; checks where telemetry is exported.
Process		
image, user, group	locked	Lock entry for image name.
switchover	switchoverOf	stop-start for interrupted `Process`, rolling for platform delivery tools, blue-green otherwise.
deadline	deadlineOf	Three startup budgets rounded down; budget rounded up for prepare `Process`; 600s without budget.
probes	Probe::cadenced	Declared target with platform period, timeout and failures. Startup probe polls liveness target every 5s for budget attempts.
eligible machines	eligible	Every machine that fits the memory and sidecars twice for continuous deployment, with required architecture, site, capability, GPU and disk.
environment	environmentOf, entryFor	Base environment overlaid by cluster overlay, with placeholders replaced and runtime profile variables; result is sorted.
secrets	Grant::resolvedFor	Key-value grant keeps the path and keys and gets a Kubernetes Secret. Transit/database becomes Vault paths its policy covers.

Target value	Rule	Derivation
volumes and backups	backupFor, backupEgress	For recoverable and irreplaceable volumes: platform schedule and retention, backup image for engine, backup identity and claim, connection, credential, off-cluster copy.
configuration files	Asset::resolvedFor	File text under name of process, file and digest prefix, so a changed file gets a new name.
dependency edges	edgeOf	First `Process` in cluster with `Application` and port edge names, with address and network peer; otherwise external providers.
Exposure		
entry point	tierFor	First entry point carrying the audience.
route precedence	rankOf, precedenceOf	Exact routes come before prefix routes, and longer prefixes before shorter ones.
middleware	middlewareOf	Authentication for authenticated routes, security headers, and redirect if declared.
Network policy, per Process		
ingress	ingressOf	Proxy of each route entry point, metrics collector if the `Process` is scraped, every `Process` with edge to its ports, its backup identity, migrations of databases it holds, delivery events receiver.
egress	egressOf	Cluster DNS, and the Secret Store if the `Process` holds a secret.
Deployment		
provenance	provenance	One digest per input, hash over all.
revision	end of deployment	Digest of each Application complete element (Section 3.7).
generated files	projectFiles, applicationFiles, edgeFiles, vaultFiles	Path of every file, with elements it is generated from (Section 3.5.5).

Table 6: Derivation Rules, by Target Element

3.5.1 A Process

Example 3 shows the start of the Process mapping. The init section looks up the lock entry once, so assignments reuse it. Each assignment calls a query from Table 6. An optional feature is assigned only when its condition holds: assigning an unset value would mark the feature as set, making the model state a value nothing derived.

```
mapping PI::Process::process(in app : EffectiveApplication, in prj : EffectiveProject)
                : ResolvedProcess {
        init { var own : LockedImage := locked(self.image); }
        name := self.name;
        image := own.repository + '@' + own.digest;
        if self.lifecycle = Lifecycle::application
                then switchover := switchoverOf(app, self) endif;
        deadline := inSeconds(deadlineOf(self));
        secrets := self.secrets->collect(g | g.resolvedFor(self));
        placement := object ResolvedPlacement {
                eligibleNodes := contract.nodes->select(n | eligible(self, n))->collect(n
    | n.name);
        };
        dependencies := self.dependsOn->collect(e | edgeOf(e));
        environment := environmentOf(self, prj)->sortedBy(e | e.name);
}
```

Example 3: The Process Mapping, Abridged

3.5.2 A Dependency Edge

A dependency edge names an `Application` and one of its `Surfaces`, for example platform-postgres and postgres. The query `edgeOf` finds the first `Process` in the cluster belonging to that `Application` that provides that `Surface`. The resolved edge records the `Process` address and the network peer the consumer may reach. If no `Process` provides the `Surface`, the `Platform Intent` external provider list is tried; this is how `auth` reaches a mail server outside the cluster. If neither has it, the run stops.

While a `Project` still runs at its old location, as the handover ledger records, its address and peer use that location's namespace and name, so a consumer can depend on it before it moves.

3.5.3 Environment Variables and Placeholders

A `Process` environment files consist of a base file and, optionally, one overlay per cluster. The resolution keeps base entries not replaced by the overlay for the `Platform Intent` cluster.

An entry may contain a placeholder, such as `DB_HOST=${dependency:platform-postgres.host}`. The query Placeholder::entryFor handles four kinds. A secret placeholder becomes a reference to a key of a secret the Process holds, so the value never appears in a file. A dependency placeholder takes the host or port of the Process edge from edgeOf. An exposure placeholder takes the URL, host or scheme of an Exposure anywhere in the cluster. An identity placeholder takes the Process name, namespace or Vault role. Text after a placeholder is kept, as in `AUTH_LOGIN_URL=${exposure:auth.public#url}/login`.

The runtime profile then adds its own variables. An author who writes one of them in an env file stops the run, because one name would have two values.

3.5.4 Network Peers

The ingress of a `Process` is a union of six sources (Table 6). Most look at other `Projects`: consumers whose edges name it, migrations of `Applications` whose database it holds, proxies and metrics collector that the platform names. Each source yields tuples of rule, namespace, `Process` and port. The union uses `asOrderedSet()` before tuples become `PolicyPeer` objects. Building plain tuples first matters: two objects are never equal in OCL, so a union of objects would incorrectly keep a peer admitted twice.

3.5.5 The Path Plan

The path plan assigns each generated file its path as a `Deliverable` subclass that refers to the elements it generates from. The `Project` gets a namespace file, index, default-deny network policy, and the secret operator connection where an `Application` syncs secrets.

Each `Application` gets a directory with one file per resource kind: workloads, `Canaryes` for blue/green `Processes`, `Services` for others, service accounts, RBAC, volume claims, configuration map (carrying `Release Gate` inputs as JSON), backups, disruption budgets for multi-replica `Processes`, migration, monitor, synced secrets, and a network-policy file with one policy per `Process`. Empty files are not planned.

Each index lists the files of its directory that Flux applies. Network policies are generated but not yet applied, so no index lists them. Each `Exposure` gets a route file under its entry point. Each identity holding a secret gets a Vault policy and role.

Because paths are in the model, two files claiming one path can be detected before any text is written, and Task 3 templates decide no path.

3.6 The Trace and End Sections

Every reference from one created element to another goes through the trace. A `Release Gate` member, route, scrape and every per-`Process` file refer to a `ResolvedProcess`, found with `p.resolveone(ResolvedProcess)` on the source `Process`. This works because the `Application` mapping maps its `Processes` first.

Four values can only be computed once the rest of the model exists. They use `end` sections, which run after the mapping body finishes.

The Application Revision, a digest of its complete element, names the release and appears in every generated Canary. The migration file tag uses the first digits of that Revision. The provenance render hash covers every input digest. The order between ReconcileUnits refers to units created by the same mapping.

3.7 The Black-Box Library

A digest is a SHA-256 hash over canonical text. OCL lacks a byte-hashing operation, so the Java class Hashing provides three contextual operations: digestOf walks any model element reflectively, writes canonical JSON and hashes it; textDigestOf hashes a file's text as the production implementation does; rawDigestOf hashes a string as-is.

The Revision uses the third. Generated files carry it, so it must equal the production implementation's Revision, which is the digest of the Application element in that implementation's JSON form, a shape the target metamodel does not have. The query elementJson therefore writes that element as text in OCL, from source and target model together: keys sorted, absent values omitted, every value spelled as the production implementation spells it. The black box only hashes the result. This keeps every decision about what the Revision covers inside the transformation.

Two QVTo implementation details shaped the library. First, an operation taking a plain EObject is not found on a model element, because a model type does not conform to EObject in the compiler, so each call casts first: p.oclAsType(ECORE::EObject).digestOf(). Second, the unit cannot be named after the Java package because resolve is a QVTo keyword, so it registers as dev.jorisjonkers.deploykit.emf.hashing, by the runner outside Eclipse and by plugin.xml inside.

3.8 The Estate Pass

One generated job writes every Project Vault documents into the Secret Store. Its name is a digest over all of them, so changing any document starts a new job. No single resolution can compute that name.

The estate pass, estate(inout rendered : RD), runs once over all Resolved Deployments produced together. It collects every VaultPolicyFile and VaultRoleFile, writes each as canonical JSON in OCL, sorts them by file name, hashes the whole with rawDigestOf, and adds the job's four files and their index to the first model. It also adds the route for the delivery tool's events to the platform's reporter, which likewise belongs to no Project. The pass stops if two models carry different jobs, because one run has one Platform Intent.

Its source and target are the same metamodel and it changes models in place, which QVTo expresses with an inout extent.

3.9 Stops

Fifteen fatal assertions stop the run when a value cannot be derived. Thirteen are in stop queries that a rule calls instead of returning an invalid value. For example, locked returns the lock entry for an image or calls unlocked, whose assert fatal ends the run with E_UNLOCKED_IMAGE. Two check Release Gate preconditions at the start of the gate mapping. The estate pass stops when two Projects carry different policy jobs.

The stops cover the following cases: an image missing from the lock; an edge no Process or provider serves; a placeholder naming nothing or a secret the Process does not hold; a runtime-profile variable written by an author; an Asset whose file is missing or contains a placeholder; a backed-up Volume without schedule or database engine; a migration reaching no database; a blue/green Application without readiness, Release Gate or delivery policy; a Grant without a secret store; or a quantity in a unit the model does not read.

Where the specification defines an error code, the message contains it. An audience that no entry point carries has no stop because a constraint E_NO_TIER_FOR_AUDIENCE already refuses it before the run.

3.10 Running the Transformations

Three Java classes (extttLowering, Resolution and Estate) run the transformations through QVTo's TransformationExecutor. They register the black box, set configuration properties, pass the extents, and return the result or fail with the executor's diagnostic.

The pipeline builds the extents from parsed and checked documents and writes every example's models under target/parity/<example>/. Appendix B.1 gives the steps.

4 Tests and Evaluation

The transformations are tested by running them on eight examples and comparing their output with oracle files. The oracles come from the production implementation processing the same input documents, so matching them shows both implementations derive the same values.

Six test types answer different questions, and the build runs all of them on every change.

Lowered models: for the four examples with shared declarations, the lowered model is written as JSON and compared byte-for-byte with the expected Effective Intent.

Dependency edges: for each example, the resolved edges are exported as JSON and compared byte-for-byte with the expected file. These tests only read files the pipeline wrote, verifying the pipeline as a user would run it.

Revisions: each expected resolved file records its `Revision`, a digest over the `Application` complete element. Matching `Revisions` confirm that the same values were derived (Section 4.1.1).

Complete expected models: `minimal` and `secrets` have full expected `Resolved Deployment` models, compared using EMF's structural equality (`EcoreUtil.equals`), which checks every attribute and reference.

Generated files: since Task 3 templates decide nothing, a wrong value in a `Resolved Deployment` becomes a wrong byte in a generated file. Tests generate the files from the transformation output and compare each with the committed output.

Interface tests use JUnit. The resolution is tested with the smallest project that resolves, a project not in the input, and an `Asset` whose file is missing which must stop with the file name. The estate pass is tested with one job planned over two projects, a job name that moves when a document changes, no job without documents, and two projects that disagree. The lowering is tested with eight cases of merging shared declarations.

The Java code around the transformations must reach full line and branch coverage and a 100QVTo code is verified only by the comparisons above.

4.1 Results

Table 7 lists the eight examples. All resolve successfully and every comparison with an expected file passes. The full build runs 323 tests including 81 parity checks and passes. Both `minimal` and `secrets` equal their complete expected models.

		Counted in the resolved model						Equal to expected files		
Example	**Apps**	**Proc.**	**Edges**	**Secr.**	**Vol.**	**Env.**	**Files**	**Edges**	**Revisions**	**Files**
`minimal`	1	1	0	0	0	6	12	yes	1/1	yes
`auth`	1	2	4	3	0	21	19	yes	1/1	yes
`data`	3	3	0	1	3	3	37	yes	3/3	yes
`delivery`	4	4	1	0	0	0	27	yes	4/4	yes
`edge`	2	2	0	0	0	0	13	yes	–	–
`knowledge-platform`	4	7	5	4	6	84	49	yes	1/1	yes
`observability`	2	2	0	0	0	0	15	yes	–	–
`secrets`	1	1	0	0	0	0	8	yes	–	–

Table 7: The Resolved Examples: `Applications`, `Processes`, `Dependency edges`, Secrets, Volumes, Environment Variables and Planned Files, and the Comparisons (–: No Expected File)

The examples together cover every row of Table 6. The `auth` example contains the migration, placeholders and an edge to a provider outside the cluster. The `data` example contains backups of each durability class, a `Sidecar` and an `Asset`. The `knowledge-platform` example is the largest. The `delivery` example has rolling and stop-start switchovers plus API access. The `edge`, `observability` and `secrets` examples provide platform services the others reference.

4.1.1 What the Revisions Show

An `Application Revision` is the digest of its whole element as the production implementation writes it: its `Process`es with image, user, deadline, probes, placement, secrets, volumes, backups, environment and edges; its `Exposure`s and routes; its `Release Gate` and migration.

The transformation builds that text from its own `Resolved Deployment` (Section 3.7), so one different value, one extra environment variable or one different order changes the digest. Ten `Application`s across five examples have a `Revision` in an expected file, and all ten match.

For these `Application`s, the `Revision` check verifies nearly every value at once, a task a hand-written model could not achieve with the same effort. A further test confirms the `Revision` moves for the right reasons: raising `minimal` memory from 256Mi to 512Mi changes it, but changing the snapshot capture time, which decides nothing, does not.

4.1.2 What the Generated Files Show

Values no `Revision` covers, such as the path plan, network policies and Vault documents, still appear in generated files. 167 committed files across five examples and the cluster-wide tree, including the estate pass job, are reproduced byte-for-byte. The same inputs always produce the same bytes.

4.1.3 Where the Evidence Is Thin

Two examples, `edge` and `observability`, have no `Revision`, no committed tree and no expected model. Their edge files contain no edges. For them, the evidence is that the run succeeds and that other examples, which look up their proxies and collectors, reproduce their expected files.

The `secrets` model is a reviewed output rather than an independent oracle. It catches any later change, and the review itself found one gap in the specification: the Secret Store network policy admits nobody inbound even though every holder of a Secret may send to it.

The hand-written model of `minimal` from Task 1 was updated after Task 1 to follow the metamodel changes of Appendix A.2. Its `Revision` was taken from the production implementation, so one field no longer checks independently.

4.1.4 Defects Found by Testing

Comparisons found a defect no single example would reveal: the path plan placed cluster-wide route files under `apps/edge/`, which is also the directory of the project named `edge`. The `edge` example's files would have mixed with routes from every other `Project`. The fix moved all cluster-wide files under `estate/` in both implementations, and the committed trees now hold each file at its correct path.

4.2 Limitations

The oracles come from another implementation. Agreement shows two implementations of the specification decide the same, not that the specification itself is correct. Only the hand-written model of minimal was written directly from the specification.

Eight examples form a sample. They demonstrate every rule runs and agrees on these inputs, not that each rule is correct in every case. The QVTo code is not mutation-tested.

Checks across documents are stops, not diagnostics. A stop reports one problem without its document location. Most such checks moved into constraints; the remaining stops are a safety net. The cross-document constraints still use `allInstances()`; moving them onto one root object is decided but not implemented.

Queries are recomputed. QVTo caches mapping results but not queries, so `edgeOf` or a `Surface` address is recomputed wherever used. Several queries scan every `Process` in the cluster, so work grows with the square of `Process` count. For much larger clusters, hot queries would become mappings or precomputed properties. Capacity needs to be measured first.

Capacity is checked per machine. A `Process` is eligible for a machine that can hold it alone. The resolution does not sum what all `Process`es request of one machine.

Two small modelling choices remain. When two `Process`es provide the same `Surface`, the first in name order wins. The order between `ReconcileUnit`s is per `Project`, not per `Application`, because Flux orders whole units.

Provenance digests differ by design. Input digests are hashes over each implementation's own model form. Every digest reaching a generated file—the `Revision`, an `Asset` name, the policy job name—is reproduced.

The `knowledge` example is not resolved. It models a `Project` being retired. Its successor, `knowledge-platform`, is.

The Eclipse run configuration is not tested. The build uses the standalone executor. The configuration and `plugin.xml` registration are only run manually.

4.3 Reflection

The most time-consuming part was the `Revision`. Writing the production implementation's JSON form of an `Application` in OCL, one field at a time, took about one sixth of `resolution.qvto`. Every mistake showed only as a different hash, but it was worth the effort. Once the `Revision`s matched, they verified nearly every value of ten `Application`s at once, which would have been impractical to check by hand.

QVTo was a good fit for the work. Most rules are queries over the whole cluster, and OCL expresses these naturally. The explicit trace also made every reference between created elements visible.

Three language details cost extra time. The keywords `resolve`, `from` and `access` prevented naming the black-box unit after its Java package, so two metamodel features had to be written `_from` and `_access`. A multi-statement `if` needs braces. Inside an object expression, `result` refers to the enclosing mapping result, not the object being created.

With hindsight, I would have planned the evidence with the examples from the start. The expected model of `secrets` and the parity checks for `knowledge-platform` were only added at the end when a review asked which examples had no comparison. The Task 1 model of `minimal` should have been kept unchanged beside the updated one, so the one independent oracle would remain independent.

A Changes to the Task 1 Metamodels

This appendix lists the changes between the Task 1 metamodels and those the Task 2 transformations read and write. The comparison checked each class and feature in the .ecore files.

Four kinds of change were made: a third metamodel for the `pinned input set` was added (Appendix A.1); the target metamodel gained derived values and twelve kinds of generated file (Appendix A.2); the source metamodel gained declarations the other examples need (Appendix A.3); and four grammars were added (Appendix A.4).

No class was removed. The Task 1 hand-in showed OCL helper definitions such as levelsAbove and derivesDatabase as derived attributes in the diagram. They remain OCL definitions in project-intent.ocl and were never Ecore features.

A.1 The Pinned Inputs Metamodel

The `pinnedinputs` package holds the documents the resolution reads beside the source models. Task 1 decided only authored documents get a metamodel. These documents are not authored by a `Project` owner, and the resolution needs them as models, so they form a separate package instead of joining the source metamodel.

The node contract is generated from the platform team's machine descriptions. Another `Process` publishes the images lock and the snapshot. A `Project` build writes its migration proof.

To ensure the source metamodel stays aligned with the production implementation, its structure is compared with the implementation schemas through a committed descriptor. Adding these pinned input classes would list documents those schemas do not hold. No target metamodel class refers to them: the `Resolved Deployment` records the values read from them, and their digests.

Figure 3 shows the metamodel. Table 8 shows which rules read each class.

Class	Read by
NodeContract, Node, Allocatable, Gpu, Disk	eligible: memory and CPU as quantities such as 53500m, plus site, architecture, capabilities, GPUs, disks.
ImagesLock, LockedImage	locked: every image of a Process, Sidecar, backup method, migration runner and Vault policy job.
ClusterState, Binding	boundOf: the machine that already holds a Volume.
CurrentPlacement, RollbackBackup	Not read by the resolution. The snapshot carries them for the delivery process that Task 3 serves.
MigrationProof, ProvenApplication	migrationOf and gate: schema version tested against, whether it holds a non-transactional change.
AssetFile	Asset::resolvedFor: a configuration file text. The pipeline creates one per file a Project names. It is not parsed.

Table 8: The Classes of the Pinned Inputs Metamodel and the Rules That Read Them

Two attributes are plain strings, an exception to Task 1's rule of enumerations over free-form strings. A Node's disk medium is not the source metamodel's Media enumeration because the node contract lists media no `Process` may request, such as sdcard. The resolution compares the spelling instead, and does the same for architecture. The values come from generated documents, not from an author, so the risk of author typo does not apply.

A.2 Changes to the Target Metamodel

The target metamodel has two halves: the decisions the platform records in the `Platform Intent`, and the generated-file entries of the path plan. Both grew.

The root class is unchanged, but what one instance holds changed. Task 1 planned one `Resolved Deployment` for the whole cluster. There is now one per `Project` (Section 2.3.2). A `ResolvedApplication` inside is still the projection one repository publishes.

Decisions. Figure 4 shows every decision class that is new or changed. Table 9 gives the reason for each.

Task 1 named many decisions in prose but gave classes only to what its worked example needed. The other examples also need migrations, backups that connect to their database, `Secrets` that reach the cluster, API




Figure 3: The Pinned Inputs Metamodel. Every Class Is New in Task 2

access, `Sidecar`s, configuration files, and two cluster-wide values: the Vault policy job and the route of the delivery tool's events.




Figure 4: Decision Classes of the Target Metamodel That Changed. Orange: New Class. White: Task 1 Class, Showing Only New Features (Bold). Arrows Are Containment; a Class Contained in Several Places Is Drawn Under Its First Container Only

Class	Change	Reason
ResolvedDeployment	added policyJob, events	Vault policy job and route for delivery tool events belong to the whole cluster; every `Project` model carries the same one; the estate pass plans their files.
ResolvedPolicyJob, ResolvedEvents	new	Job identity, image, Vault role, resources and egress; events receiver namespace and address.
ResolvedApplication	added secretStore, scrape	The secret store address where the operator syncs from, and how the metrics stack scrapes the `Application`, which the revision element names.
ResolvedScrape	new	Scraped `Process`, `Surface`, path, interval and timeout.
ReleaseGate	added endpoint, migration	An address that every `Canary` webhook calls; the migration the gate starts and may undo.
GateAnalysis	added errorRate, latency	Thresholds of the two analysis checks, from the Platform Intent.
GateMigration	new	Migration identity and what its proof records.
ResolvedMigration	added identity, image user, deadline, memory, CPU, scratch space, database, credential, egress	Task 1 named identity, owner role and deadline in prose. A migration job also needs database address, owner credential that only it holds, and network policy.
MigratedDatabase	new	Database host, port and name.
ResolvedProcess	added lifecycle, api, assets, sidecars	Whether the `Process` serves, runs once or prepares (which the revision element names); its API access, configuration files and `Sidecar`s.
ResolvedApiAccess, ResolvedApiRule, AdmittedRange	new	API rules a `Process` holds; address range a policy admits: API server for API access, backup off-cluster destination.
ResolvedAsset, ResolvedSidecar	new	Configuration file with content-derived name; `Sidecar` with locked image and resources.
ResolvedGrant	path and access optional; added engine, paths, destination, mountAt, fileMode	Transit or database `Secret` has no single path; recorded as Vault paths its policy covers. Synced `Secret` needs Kubernetes `Secret` copied to its mount.
PolicyPath	new	One path of a Secret policy and operations allowed.
ResolvedVolume	added mountAt	Workload template needs the mount path.
BackupPlan	added user, group, identity, claim, egress, peer, credential, destinations	A backup runs as its own identity with its own claim and network policy; it connects to the `Process` it dumps and copies off-cluster with a credential.
BackupPeer	new	Where a backup connects, and the credential it logs in with.
EnvEntry	value optional; added secret	A secret placeholder becomes a reference, so the value never appears in a file.
SecretReference	new	The secret path and key a variable reads.
StartupProbe	added timeout	Specification gives the startup probe the Platform Intent probe timeout.
ResolvedExposure	added listener, certificates, proxyApplication, proxyNamespace	Entry point protocol and certificate source; proxy whose middleware the routes name.

Class	Change	Reason
PolicyPeer	added rule; process optional	Which rule admitted the peer, so two rules admitting one peer stay two entries, as in production; peer such as cluster DNS is namespace without Process.

Table 9: Changes to the Decision Classes of the Target Metamodel

Generated Files. Figure 5 shows every subclass of Deliverable. Task 1 had nine. There are now 21. Three kinds of change were made.

One file per Application: workload, Canary and identity files, which Task 1 tied to one Process, now list processes because the specification writes one file per Application holding all its Process resources. Task 1's worked example had one Process, so this difference did not show. For the same reason, the network policy file holds one ProcessPolicy per Process, and the Secret file refers to its Application and holds one SecretHolder per identity, since a Backup identity holds Secrets too.

Monitors: MonitorFile gained timeout and kind. A blue/green Process is scraped through its Pods; any other through its Service.

Twelve new file kinds: Services, volume claims, configuration maps, backups, disruption budgets, migrations, RBAC, the secret operator connection, Vault policies and roles, the policy job and the events route.




Figure 5: The Generated-File Classes of the Target Metamodel, Task 1 Against Task 2

The hand-written model of minimal from Task 1 was updated with these changes: its files refer to the Process through processes, it gained the configuration map that carries the ReleaseGate inputs, and its revision was set to the production implementation's (Section 4.1.3).

A.3 Changes to the Source Metamodel

The source metamodel kept every class. Table 10 lists what was added or changed.

Most additions are declarations in the Platform Intent that a derivation needs and Task 1 left implicit. A rule needing a value the Platform Intent does not declare would otherwise contain it as a constant.

Class	Change	Reason
Process	added api (ApiAccess, ApiRule, ApiVerb)	The `Process` declares the Kubernetes API access it needs, with a reason; platform intent delivery tools need it.
Platform	added apiAccess (ApiAccessPolicy)	Which `Applications` may hold API access, and the API server address range.
Platform	added secretStore, telemetry (TelemetryPolicy), policyJob (VaultPolicyJob)	References to the secret store, the telemetry collector and the metrics stack, whose addresses the resolution finds in their `Projects`; Vault policy job image, role and resources.
DeliveryPolicy	added gate, reporter	References to the `Release Gate` and the events receiver `Applications`.
AnalysisPolicy	added errorRate, latency	The thresholds the `Release Gate` checks.
Substrate	added clusterDns	The namespace every egress policy admits for DNS.
EnginePolicy	added surface	The port a database engine backup connects to.
OffClusterCopy	added egress (DestinationRange)	The address ranges a backup copy goes to.
HandoverLedger	added serving (ServingLocation)	Where a `Project` not yet moved still runs, so an edge to it resolves.
RenderedArtifacts	added pullSecret	Used by delivery, not by the resolution.
Placeholder	added suffix	Text after a placeholder, as in ${exposure:auth.public#url}/login.
Grant	rotation required	Every Grant states how it tolerates rotation, which decides its restart targets.
Volume	size required	A claim cannot be generated without a size.
EffectiveProject	removed apiVersion, kind, schemaVersion	Lowered model is written by the lowering, not by an author, so it has no document header.

Table 10: Changes to the Source Metamodel

A.4 Grammars for the Pinned Inputs

The pinned inputs use grammars rather than a Java YAML reader or hand-written XMI, so both implementations read the same YAML files and their results can be compared.

Four grammars were added beside the Project and Platform grammars: NodeContract, ImagesLock, ClusterState and MigrationProof. Each inherits the Project grammar, reusing its terminals, indentation tokens and scalar rule, and adds only the rules for its own document. As with the `Platform Intent`, the file name selects the grammar: `node-contract.yml`, `images.lock.yml`, `cluster-state.yml` and `migration-proof.yml`.

One input file changed: the Project grammar scalar terminal cannot contain a colon, so the snapshot's capture time is now quoted, as digests and URLs already were. The production implementation reads the same value either way.

Example 4 shows the smallest grammar.

```
grammar dev.jorisjonkers.deploykit.emf.syntax.ClusterState
        with dev.jorisjonkers.deploykit.emf.syntax.ProjectIntent
import "https://jorisjonkers.dev/deploy-kit/pinned-inputs/1"

ClusterState returns ClusterState:
        (('apiVersion' ':' apiVersion=Text)
        & ('kind' ':' kind=Text)
        & ('schemaVersion' ':' schemaVersion=Text)
        & ('cluster' ':' cluster=Text)
        & ('capturedAt' ':' capturedAt=Text)
        & ('bindings' ':' BEGIN (DASH BEGIN bindings+=Binding END)* END)
        & ('placements' ':' BEGIN (DASH BEGIN placements+=CurrentPlacement END)* END)
        & ('backups' ':' BEGIN (DASH BEGIN backups+=RollbackBackup END)* END)?);

Binding returns Binding:
        (('claim' ':' claim=Text)
        & ('node' ':' node=Text));
```

Example 4: The Grammar of the Cluster-State Snapshot, Abridged

B The Hand-in Archive

The archive holds `report.pdf`, a `README.md` with the steps from Appendix B.1, and two folders.

`task-2-transformations/` is an Eclipse project for reading the models (Table 11), imported via File > Import > Existing Projects into Workspace. It contains no Java, so the transformations do not run from it: the resolution and estate pass call the `Hashing` library, which the implementation plug-in registers.

`implementation/` holds the EMF implementation and the examples the tests read.

Path	Contents
`model/`	The source, pinned-inputs and target metamodels.
`transforms/`	`lower.qvto`, `resolution.qvto` and `estate.qvto`.
`examples/platform/`	The `Platform Intent` and the pinned inputs every example reads.
`examples/<example>/authored/`	The `Project Intent` with its env and configuration files.
`examples/<example>/resolution.intent.xmi`	The intent extent: authored and lowered `Projects`, plus `Platform Intent`.
`examples/<example>/resolution.pinned.xmi`	The pinned extent.
`examples/<example>/<project>.resolveddeployment`	The `Resolved Deployment` the transformation wrote.
`examples/<example>/dependencies.json`	The edges exported from it, beside `expected-dependencies.json`, a copy of the oracle `expected/dependencies.json`.
`examples/minimal/minimal.hand-written.resolveddeployment`	The hand-written target model from Task 1, updated in Appendix A.2.
`examples/secrets/secrets.expected.resolveddeployment`	The complete expected model of `secrets` (Section 4.1.3).

Table 11: The Models Project of the Archive, One Folder per Example of Table 7

Every XMI declares its metamodel in `xsi:schemaLocation`, so Eclipse opens it in the Sample Reflective Ecore Model Editor without a registered package.

B.1 Running the Transformations

In `implementation/emf`, run `./mvnwcleanverify` with JDK 21. It builds the implementation, runs every test, and writes each example's models and edges under `bundles/cli/target/parity/<example>/`. It takes about four minutes.

In Eclipse Modeling Tools with the QVT-Operational SDK, import `implementation/emf` as existing Maven projects.

Run `resolution.launch` in `dev.jorisjonkers.deploykit.emf.resolve`. It resolves `minimal` from the extents Step 1 wrote.

References

[1] P. Merle and F. Petrillo. Visualizing Cloud-native Applications with KubeDiagrams. In *Proc. VISSOFT 2025*, pp. 106–116, 2025. Tool: https://github.com/philippemerle/KubeDiagrams.

[2] KubeOrch, visual Kubernetes workflow orchestrator. https://github.com/KubeOrch (repositories `core` and `ui`), visited 15 October 2026.

[3] kubert, a kubectx and kubens alternative. https://github.com/idebeijer/kubert, visited 15 October 2026.

[4] L. Burgueño, J. Cabot and S. Gérard. The Future of Model Transformation Languages: An Open Community Discussion. *Journal of Object Technology* 18(3), 7:1–11, 2019.

[5] M. van Amstel, S. Bosems, I. Kurtev and L. Ferreira Pires. Performance in Model Transformations: Experiments with ATL and QVT. In *Proc. ICMT 2011*, LNCS 6707, pp. 198–212, 2011.

[6] Object Management Group. *Meta Object Facility Query/View/Transformation Specification*, version 1.3, 2016.