lab05.md 5/10/2022

Lab 5 - Create bank helper functions

Preparations

If you couldn't finish the previous exercise, you can copy and paste the pervious solution from the *labsSolutions* folder.

Work in the main. ts file.

Exercise 1 - Format customer names

In our bank we will need to format customer names.

1. Create that function. The shape looks like this:

```
function formatName(firstName: string, lastName: string, insertion:
    string): string {
        // TODO: Implement
}
```

- 2. Test that it works: formatName('Pascalle', 'Vries', 'de') should result in 'Pascalle de Vries'.
- 3. Change preposition to make sure it is optional. formatName('Foo', 'Bar') should result in 'Foo Bar'.

Exercise 2 - Generate IBAN account numbers

In the main.ts file, create a generateIban function. It should generate a new random IBAN account number. It does *not* have to be a valid IBAN, just one that looks like it.

1. Implement the following function:

```
function generateIban(bankCode: string, countryCode: string) {
    // TODO: implement
    return {
        countryCode: /* TODO */,
        bankCode: /* TODO */,
        accountNumber: /* TODO */,
        controlNumber: '00'
    };
}
```

As control number, you can use '00' for now.

Note: you can use Math.floor(Math.random() * 10000000000).toString() to generate random account number

lab05.md 5/10/2022

2. Make the bankCode and countryCode optional, the default values are DEFAULT_BANK_CODE and DEFAULT_COUNTRY_CODE respectively.

3. Can you guess what the return type of this function is? Verify this by hovering over the function name in your code editor.

Exercise 3 - Format IBAN account numbers

1. Create and implement the formatIban(iban: any) function. It should format the IBAN in groups of 4:

```
NL50 TYPE 3532 0409 92
NL97 INGB 9589 7465 22
DE09 DEUT 6102 3797 98
```

Verify that your method works using these examples:

```
const ibanTypedBank = generateIban();
const ibanIng = generateIban('INGB', 'NL');
const ibanDeutscheBank = generateIban('DEUT', 'DE');
console.log(formatIban(ibanTypedBank));
console.log(formatIban(ibanIng));
console.log(formatIban(ibanDeutscheBank));
```

2. Improve the function by using *Object matching* in the parameter names

Exercise 4 - Valid IBAN accounts - If time permits

Make sure that the <code>generateIban</code> function only generate <code>valid</code> IBAN account numbers by calculating the control number (https://nl.wikipedia.org/wiki/International_Bank_Account_Number).

Hint: you might need to use BigInt for this.