

# infer: An R package for tidyverse-friendly statistical inference

Simon P. Couch<sup>1, 2</sup>, Andrew P. Bray<sup>3</sup>, Chester Ismay<sup>4</sup>, Evgeni Chasnovski<sup>5</sup>, Benjamin S. Baumer<sup>6</sup>, and Mine Çetinkaya-Rundel<sup>2, 7</sup>

**1** Johns Hopkins, Department of Biostatistics **2** RStudio **3** UC Berkeley, Department of Statistics and Reed College Mathematics Department (on leave) **4** Flatiron School **5** No Affiliation **6** Smith College, Program in Statistical & Data Sciences **7** Duke University, Department of Statistical Science

DOI:

Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Submitted:

Published:

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC-BY](#)).

## Summary

`infer` implements an expressive grammar to perform statistical inference that adheres to the `tidyverse` design framework (Wickham et al., 2019). Rather than providing methods for specific statistical tests, this package consolidates the principles that are shared among common hypothesis tests into a set of four main verbs (functions), supplemented with many utilities to visualize and extract value from their outputs.

## Statement of Need

Packages implementing methods for basic statistical inference in R are highly variable in their interfaces. The structure of inputted data, argument names, expected argument types, argument orders, output types, and spelling cases varies widely both within and among packages. This diversity in approaches obscures the intuition shared among common inferential procedures, makes details of usage difficult to remember, and prevents an expressive and idiomatic coding style.

`infer` is an R package for randomization-based hypothesis testing, naturalizing an intuitive understanding of statistical inference via a unified and expressive grammar. Four functions provide functionality encompassing a large swath of basic frequentist statistical inference, abstracting away details of specific tests and shifting the focus of the analyst to the observed data and the processes that generated it. Such a grammar lends itself to applications in teaching, data pedagogy research, applied scientific research, and advanced predictive modeling. For one, the principled approach of the package has made it an especially good fit for teaching introductory statistics (Baumer, Bray, Çetinkaya-Rundel, & Hardin, 2020; Ismay & Kim, 2019) and research in data pedagogy (Çetinkaya-Rundel & Ellison, 2021; Fergusson & Pfannkuch, 2021; Loy, 2021). Further, the package has already seen usage in a number of published scientific applications (Ask et al., 2021; Fallon & Hinds, 2021; McLean et al., 2021). Finally, the package integrates with the greater `tidymodels` collection of packages, a burgeoning software ecosystem for tidyverse-aligned predictive modeling used across many modern research and industrial applications (Kuhn & Wickham, 2020). To date, the package has been downloaded more than 400,000 times.

## Underlying Principles

Regardless of the hypothesis test in question, an analyst asks the same kind of question when conducting statistical inference: is the effect/difference in the observed data real, or due to random chance? To answer this question, the analyst begins by assuming that the effect in the observed data was simply due to random chance, and calls this assumption the *null hypothesis*. (In reality, they might not believe in the null hypothesis at all—the null hypothesis is in opposition to the *alternate hypothesis*, which supposes that the effect present in the observed data is actually due to the fact that “something is going on.”) The analyst then calculates a *test statistic* from the data that describes the observed effect. They can use this test statistic to calculate a *p-value* via juxtaposition with a *null distribution*, giving the probability that the observed data could come about if the null hypothesis were true. If this probability is below some pre-defined *significance level*  $\alpha$ , then the analyst can reject the null hypothesis.

The workflow of this package is designed around this idea. Starting out with some dataset,

- `specify()` allows the analyst to specify the variable, or relationship between variables, that they are interested in.
- `hypothesize()` allows the analyst to declare the null hypothesis.
- `generate()` allows the analyst to generate data reflecting the null hypothesis.
- `calculate()` allows the analyst to calculate summary statistics, either from
  - the observed data, to form the observed test statistic.
  - data `generate()`d to reflect the null hypothesis, to form the randomization-based null distribution of test statistics.

As such, the ultimate output of an infer pipeline using these four functions is generally an *observed statistic* or *null distribution* of test statistics. These four functions are thus supplemented with many utilities to visualize and extract value from their outputs.

- `visualize()` plots the null distribution of test statistics.
  - `shade_p_value()` situates the observed statistic in the null distribution, shading the region as or more extreme.
  - `shade_confidence_interval()` situates the confidence interval region in the null distribution, shading the region within the bounds.
- `get_p_value()` calculates a p-value via the juxtaposition of the test statistic and null distribution.
- `get_confidence_interval()` calculates a confidence interval via the juxtaposition of the test statistic and null distribution.

Beyond this, the package offers:

- methods for inference using theory-based distributions
- shorthand wrappers for common statistical tests using tidy data
- model-fitting workflows to accommodate multiple explanatory variables

## Comparison to Other Packages

`broom` and `parameters` convert model objects to unified output formats, though do not provide methods for fitting models, describing null distributions, or calculating summary statistics from tabular data. `statsexpressions`, and adjacent packages in the `easystats` ecosystem, implement wrappers with consistent interfaces for theory-based hypothesis tests. At a higher level, the structure of each of these packages is defined by model types, where each model type has its own associated function and/or model object. In contrast, `infer` is structured around four functions, situating statistics and model types within

a more abstracted grammar. `infer`'s initial release on the Comprehensive R Archive Network predated that of each of the packages mentioned above, with the exception of `broom`, a package situated in the same `tidymodels` ecosystem (R Core Team, 2021).

## Acknowledgements

We acknowledge contributions from Albert Y. Kim, Jo Hardin, Jay Lee, Amelia McNamara, Nick Solomon, and Richie Cotton.

## References

- Ask, A. V., Jenssen, B. M., Tartu, S., Angelier, F., Chastel, O., & Gabrielsen, G. W. (2021). Per-and polyfluoroalkyl substances are positively associated with thyroid hormones in an arctic seabird. *Environmental Toxicology and Chemistry*, 40(3), 820–831. doi:[10.1002/etc.4978](https://doi.org/10.1002/etc.4978)
- Baumer, B. S., Bray, A. P., Çetinkaya-Rundel, M., & Hardin, J. S. (2020). Teaching introductory statistics with DataCamp. *Journal of Statistics Education*, 28(1), 89–97. doi:[10.1080/10691898.2020.1730734](https://doi.org/10.1080/10691898.2020.1730734)
- Çetinkaya-Rundel, M., & Ellison, V. (2021). A fresh look at introductory data science. *Journal of Statistics and Data Science Education*, 29(sup1), S16–S26. doi:[10.1080/10691898.2020.1804497](https://doi.org/10.1080/10691898.2020.1804497)
- Fallon, M. E., & Hinds, M. T. (2021). Single cell morphological metrics and cytoskeletal alignment regulate VCAM-1 protein expression. *Biochemical and Biophysical Research Communications*, 555, 160–167. doi:[10.1016/j.bbrc.2021.03.129](https://doi.org/10.1016/j.bbrc.2021.03.129)
- Fergusson, A., & Pfannkuch, M. (2021). Introducing teachers who use GUI-driven tools for the randomization test to code-driven tools. *Mathematical Thinking and Learning*, 1–21. doi:[10.1080/10986065.2021.1922856](https://doi.org/10.1080/10986065.2021.1922856)
- Ismay, C., & Kim, A. Y. (2019). *Statistical inference via data science: A Modern Dive into R and the tidyverse*. CRC Press. doi:[10.1080/00224065.2020.1848366](https://doi.org/10.1080/00224065.2020.1848366)
- Kuhn, M., & Wickham, H. (2020). Tidymodels: A collection of packages for modeling and machine learning using tidyverse principles. *Boston, MA, USA*. Retrieved from <https://tidymodels.org>
- Loy, A. (2021). Bringing visual inference to the classroom. *Journal of Statistics and Data Science Education*, 1–12. doi:[10.1080/26939169.2021.1920866](https://doi.org/10.1080/26939169.2021.1920866)
- McLean, Z. L., Appleby, S. J., Fermin, L. M., Henderson, H. V., Wei, J., Wells, D. N., & Oback, B. (2021). Controlled cytoplasm arrest and morula aggregation enhance development, cryoresilience, and in vivo survival of cloned sheep embryos. *Cellular Reprogramming*, 23(1), 14–25. doi:[10.1089/cell.2020.0078](https://doi.org/10.1089/cell.2020.0078)
- R Core Team. (2021). *R: A language and environment for statistical computing*. Vienna, Austria: R Foundation for Statistical Computing. Retrieved from <https://www.R-project.org/>
- Wickham, H., Averick, M., Bryan, J., Chang, W., McGowan, L. D., François, R., Grolemond, G., et al. (2019). Welcome to the tidyverse. *Journal of Open Source Software*, 4(43), 1686. doi:[10.21105/joss.01686](https://doi.org/10.21105/joss.01686)