



13 The recursive procedure `Delete()` is defined as follows:

```

PROCEDURE Delete(Index, Target)
  IF Numbers[Index] > 0 THEN
    IF Numbers[Index] >= Target THEN
      Numbers[Index] ← Numbers[Index + 1]
    ENDIF
    Index ← Index + 1
    CALL Delete(Index, Target)
  ENDIF
ENDPROCEDURE

```

An array `Numbers` is used to store a sorted data set of non-zero positive integers. Unused cells contain zero.

The contents of the array at the start of the algorithm are:

Numbers									
[1]	[2]	[3]	[4]	[5]	[6]	[7]	[8]	[9]	[10]
2	3	7	11	15	17	19	23	0	0

Complete the trace table for the algorithm for the procedure call:

`CALL Delete(1, 15)`

Index	Target	Numbers									
		[1]	[2]	[3]	[4]	[5]	[6]	[7]	[8]	[9]	[10]
		2	3	7	11	15	17	19	23	0	0

[4]

Permission to reproduce items where third-party owned material protected by copyright is included has been sought and cleared where possible. Every reasonable effort has been made by the publisher (UCLES) to trace copyright holders, but if any items requiring clearance have unwittingly been included, the publisher will be pleased to make amends at the earliest possible opportunity.

To avoid the issue of disclosure of answer-related information to candidates, all copyright acknowledgements are reproduced online in the Cambridge Assessment International Education Copyright Acknowledgements Booklet. This is produced for each series of examinations and is freely available to download at www.cambridgeinternational.org after the live examination series.

Cambridge Assessment International Education is part of Cambridge Assessment. Cambridge Assessment is the brand name of the University of Cambridge Local Examinations Syndicate (UCLES), which is a department of the University of Cambridge.

