

(c) The procedure `StoreData()`:

- takes **two** parameters: a 1D array `DataToStore` and a filename
- opens the text file with the filename that is passed as a parameter
- appends each item of data from `DataToStore` to a new line in the text file
- uses exception handling when opening and writing data to the text file.

Write program code for `StoreData()`

Save your program.

Copy and paste the program code into part **2(c)** in the evidence document.

[5]

(d) Each of the six colours has a blank text file where the numbers will be stored. The names of these six text files are:

- `Blue.txt`
- `Green.txt`
- `Orange.txt`
- `Pink.txt`
- `Red.txt`
- `Yellow.txt`

The procedure `SplitData()` needs amending to call `StoreData()` **six** times, with each of the **six** colour arrays and the name of the text file that corresponds to that colour.

For example, `StoreData()` will be called with the red array and the file name `"Red.txt"`

Write program code to amend `SplitData()`

Save your program.

Copy and paste the program code into part **2(d)** in the evidence document.

[2]

(e) The main program calls `ReadData()` and then `SplitData()`

(i) Write program code for the main program.

Save your program.

Copy and paste the program code into part **2(e)(i)** in the evidence document.

[3]

(ii) Test your program. Input the text `"TheData.txt"` when prompted.

Take a screenshot of the output(s) and a screenshot showing the content of the file that stores the red numbers.

Save your program.

Copy and paste the screenshot(s) into part **2(e)(ii)** in the evidence document.

[2]