

You have been supplied with the following source files:

QueueData.txt

Open the evidence document, **evidence.doc**

Make sure that your name, centre number and candidate number will appear on every page of this document. This document must contain your answers to each question.

Save this evidence document in your work area as:

evidence_ followed by your centre number_candidate number, for example: **evidence_zz999_9999**

A class declaration can be used to declare a record. If the programming language used does not support arrays, a list can be used instead.

One source file is used to answer **Question 1**. The file is called **QueueData.txt**

1 A program reads data from a text file and stores it in a queue. The linear queue `Queue` is stored as a 1D array of up to 50 elements. The queue has the following pointers:

- `HeadPointer` – this stores the index of the first element in the queue, initialised to `-1`
- `TailPointer` – this stores the index of the last element in the queue, initialised to `-1`

(a) `Queue` is a global array of 50 integers with all elements initialised to `-1` in the main program.

The **two** pointers are declared as global variables and initialised to `-1`

Write program code to declare and initialise `Queue`, `HeadPointer` and `TailPointer`

Save your program as **Question1_J25**.

Copy and paste the program code into part **1(a)** in the evidence document.

[3]

(b) The function `Enqueue()`:

- takes an integer parameter to store in the next position in the queue
- returns `FALSE` if the queue is full and the parameter cannot be stored in the queue
- returns `TRUE` if the parameter is stored in the queue
- updates the pointers where appropriate.

Write program code for `Enqueue()`

Save your program.

Copy and paste the program code into part **1(b)** in the evidence document.

[6]