

- 3 A program stores data in a linked list that is designed using Object-Oriented Programming (OOP).

The class `Node` stores data about the nodes.

Node	
<code>TheData : Integer</code>	stores the integer data
<code>NextNode : Node</code>	stores the next node in the linked list
<code>Constructor()</code>	initialises <code>TheData</code> to its parameter value, initialises <code>NextNode</code> to a null value
<code>GetData()</code>	returns <code>TheData</code>
<code>GetNextNode()</code>	returns <code>NextNode</code>
<code>SetNextNode()</code>	takes an object of type <code>Node</code> as a parameter and stores it in <code>NextNode</code>

- (a) (i) Write program code to declare the class `Node` and its constructor.

Do **not** declare the other methods.

Use your programming language appropriate constructor.

If you are writing in Python, include attribute declarations using comments.

Save your program as **Question3_J25**.

Copy and paste the program code into part **3(a)(i)** in the evidence document.

[4]

- (ii) Write program code for the **two** get methods.

Save your program.

Copy and paste the program code into part **3(a)(ii)** in the evidence document.

[3]

- (iii) The method `SetNextNode()` takes an object of type `Node` as a parameter. The method stores the parameter in the attribute `NextNode`

Write program code for `SetNextNode()`

Save your program.

Copy and paste the program code into part **3(a)(iii)** in the evidence document.

[2]