



- 8 An exam paper has a maximum of 75 marks. One of five pass grades (A to E) is assigned, depending on the mark obtained. The lowest mark for a given grade is known as the grade boundary. For example, if the grade boundary for an A grade is 65 marks, then any candidate who achieves a mark of 65 or above will be awarded an A. A grade of U is awarded for marks below the E grade boundary.

The five grade boundaries are stored in a global 1D array `GradeBoundary` of type integer.

For example:

Element	Value	Comment
<code>GradeBoundary[1]</code>	65	The minimum mark for an A grade.
<code>GradeBoundary[2]</code>	57	The minimum mark for a B grade.
<code>GradeBoundary[3]</code>	43	The minimum mark for a C grade.
<code>GradeBoundary[4]</code>	35	The minimum mark for a D grade.
<code>GradeBoundary[5]</code>	27	The minimum mark for an E grade.

A global 2D array `Result` of type integer contains candidate marks for the exam. Each row relates to one candidate. Column 1 contains the candidate mark and column 2 contains the unique candidate ID.

For example, for the fourth and fifth candidates:

Element	Mark	Element	ID
<code>Result[4, 1]</code>	56	<code>Result[4, 2]</code>	1074832
<code>Result[5, 1]</code>	54	<code>Result[5, 2]</code>	2573839

There are more rows in the array than candidates who sit the exam. Any unused rows will be at the end of the array.

Candidate papers that are given a mark within two marks of any grade boundary must be checked.

For example, given the values in the example grade boundaries above, any paper that was awarded between 41 and 45 marks (inclusive) would need to be checked.

A program is being written to identify papers that need to be checked.

The programmer has defined the first program module as follows:

Module	Description
<code>CheckMark()</code>	- called with a parameter of type integer representing a candidate mark - returns <code>TRUE</code> if the mark is within 2 of any of the five grade boundaries, otherwise returns <code>FALSE</code>

