



- 6 A shop sells sandwiches and snacks. The owner chooses a 'daily special' sandwich which is displayed on a board outside the shop. Each 'daily special' has two different fillings and is made with one type of bread.

The owner wants a program to randomly choose the 'daily special' sandwich.

The program designer decides to store the possible sandwich fillings in a 1D array of type string.

The array is declared in pseudocode as follows:

```
DECLARE Filling : ARRAY [1:35] OF STRING
```

Each element contains the name of one filling.

An example of the first five elements is as follows:

Index	Element value
1	"Cheese"
2	"Onion"
3	"Salmon"
4	"Anchovies"
5	"Peanut Butter"

A second 1D array stores the possible bread used:

```
DECLARE Bread : ARRAY [1:10] OF STRING
```

Each element contains the name of one type of bread.

An example of the first three elements is as follows:

Index	Element value
1	"White"
2	"Brown"
3	"Pitta"

Both arrays may contain unused elements. The value of these will be an empty string and they may occur anywhere in each array.

A procedure `Special()` will output a message giving the 'daily special' sandwich made from **two** randomly selected different fillings and **one** randomly selected bread.

Unused array elements must **not** be used when creating the 'daily special' sandwich.

Using the above examples, the output could be:

```
"The daily special is Cheese and Onion on Brown bread."
```

