

(b) The board objects are placed on a board that is represented by a 0-indexed 2D array:

- the board is a 10 x 10 grid
- each position on the board is identified by a row and column number
- rows are numbered 0 to 9
- columns are numbered 0 to 9
- board objects can be placed at a row and column position
- each board position is initialised with an empty `BoardObject`, an empty `BoardObject` has `Code = "-"` and `Value = 0`

For example, the element highlighted in the given board is in row 1 and column 3.

Row	Column									
	0	1	2	3	4	5	6	7	8	9
0										
1										
2										
3										
4										
5										
6										
7										
8										
9										

The class `Board` stores the data about the board and where the board objects are placed.

Board	
<code>TheBoard : ARRAY[0:9, 0:9] of BoardObject</code>	stores the board contents as a 2D array of 10 x 10 elements of type <code>BoardObject</code>
<code>Constructor()</code>	initialises each of <code>TheBoard</code> elements to an empty <code>BoardObject</code> with <code>Code = "-"</code> and <code>Value = 0</code>
<code>GetObject()</code>	takes a row and column number as parameters and returns the <code>BoardObject</code> at the row, column position
<code>SetObject()</code>	takes a <code>BoardObject</code> , row number and column number as parameters. Stores the <code>BoardObject</code> in <code>TheBoard</code> at the given row, column position
<code>DisplayBoard()</code>	outputs the code of each <code>BoardObject</code> stored in <code>TheBoard</code> , one row at a time