

- 11 Students in a class are recording the amount of time in minutes spent in front of a screen for each day of the week.

The one-dimensional (1D) array `StudentName[]` contains the names of the students in the class.

The two-dimensional (2D) array `ScreenTime[]` is used to input the number of minutes on each day spent in front of a screen.

The position of each student's data in the two arrays is the same. For example, the student stored at index 10 in `StudentName[]` and `ScreenTime[]` is the same.

The variable `ClassSize` contains the number of students in the class.

Write a program that meets these requirements:

- allows all the students to enter their daily minutes of screen times for the past week
- calculates the total number of minutes of screen time for each student in the week
- counts, for each student, the number of days with more than 300 minutes of screen time
- calculates the average weekly minutes of screen time for the whole class
- finds the student with the lowest weekly minutes of screen time
- outputs for each student:
 - name
 - total week's screen time in hours and minutes
 - number of days with more than 300 minutes of screen time
- outputs the average weekly minutes of screen time for the whole class
- outputs the name of the student with the lowest weekly screen time.

You must use pseudocode or program code **and** add comments to explain how your code works. All inputs and outputs must contain suitable messages.

Assume that the array `StudentName[]` and the variable `ClassSize` already contain the required data.

You do **not** need to declare any arrays or variables; you may assume that this has already been done.

This image shows a full page of white paper with ten horizontal dashed lines, typical of primary school handwriting practice paper. The lines are evenly spaced and extend across the entire width of the page. There is no text or other markings on the paper.