

- 10** The one-dimensional (1D) array `Clubs[]` is used to store the names of 12 cricket clubs in a local sports league.

The two-dimensional (2D) array `Statistics[]` is used to store, for each cricket club, the number of:

- matches won
- matches drawn
- matches lost.

The 1D array `Points[]` is used to store the total number of points each cricket club has been awarded.

The position of any cricket club's data is the same in all three arrays. For example, the data in index 2 of `Statistics[]` and index 2 of `Points[]` belongs to the cricket club in index 2 of `Clubs[]`

The variable `Matches` stores the number of matches played by each team. Each team plays the same number of matches.

Points are awarded for:

- a win – 12 points
- a draw – 5 points
- a loss – 0 points.

Write a program that meets the following requirements:

- allows the number of matches played to be input and stored, with a maximum of 22 matches
- validates the number of matches played
- allows the names of the cricket clubs to be input and stored
- allows the number of matches won, drawn and lost to be input and stored for each team
- validates the number of matches won, drawn or lost against the number of matches played
- asks the user to re-enter the number of matches won, drawn or lost if the total does not match the number of matches played
- calculates and stores the total number of points for each club
- finds the cricket club or clubs with the highest number of points
- outputs the name or names of the winning club or clubs, the number of wins and the total number of points awarded.

You must use pseudocode or program code **and** add comments to explain how your code works.

You do **not** need to declare any arrays or variables; you may assume that this has already been done.

All inputs and outputs must contain suitable messages.

.....

.....

.....

.....

.....

.....