



- 4 This pseudocode algorithm is intended to sort a pre-populated one-dimensional (1D) array named `ItemList` into alphabetical order using a bubble sort.

```

01 DECLARE ItemList : ARRAY[1:100] OF STRING
02 DECLARE Counter : STRING
03 DECLARE Limit : INTEGER
04 DECLARE Pass : INTEGER
05 DECLARE Swapped : BOOLEAN
06 DECLARE Temp : STRING
07 Limit ← 100
08 Pass ← 1
09 Temp ← TRUE
10 WHILE Swapped = TRUE OR Pass <= Limit - 1 DO
11     Swapped ← FALSE
12     FOR Counter ← 1 TO Limit - Pass
13         IF ItemList[Counter] > ItemList[Counter + 1]
14             THEN
15                 Temp ← ItemList[Counter]
16                 ItemList[Counter] ← ItemList[Counter + 1]
17                 ItemList[Counter + 1] ← Temp
18                 Swapped ← TRUE
19             ENDCASE
20         Pass ← Pass + 1
21     NEXT Counter
22 ENDWHILE

```

- (a) Identify the line numbers of **five** errors in the pseudocode and suggest a correction for each error.

Error 1 line number

Correction

.....

Error 2 line number

Correction

.....

Error 3 line number

Correction

.....

Error 4 line number

Correction

.....

