

# Iris strips recognition and generation of iris strips patterns using Gang

1<sup>st</sup> Jose Corona

*dept. Robotics and Computer Vision*

*Innopolis University*

Kazan, Russia

j.coronaboch@innopolis.university

**Abstract**—This paper focus in getting and detect different iris strips and using GAN based methods generate iris strips to allow better training of models.

**Index Terms**—component, formatting, style, styling, insert

## I. INTRODUCTION

Biometric authentication now a days is more common on devices like smartphones, is based on physiological characteristics of the person such as fingerprints, face and iris patterns. Biometric security systems refer to an recognition algorithm to get access to a system or devices. Security systems based on Iris recognition has been developed because iris images has unique patterns, they are complex, it can easily be sampled and it is protected from the environment. [1]

Some problems to deal with while acquiring high quality iris image are: reflected light in the eyes, the irradiation near infrared light and external noise. Filtering techniques like smoothing and sharpening are very efficient to remove noise in the iris image. The iris image after the filtering process may vary in some information on thickness of the iris strips and some patterns may disappear. [2]

To increase iris recognition rates after noise reduction filtering super-resolution techniques are applied. A super resolution image could be archive using Generative adversarial networks (GANs) to generate the image. GAN is a class of machine learning framework, use two neural network models, one of them is a generator of data with the same distribution as the training set, and the other one is a discriminator that learns to classify between the original data and the fake one generated. GANs could learn to generate new data, given a training set, with the same characteristics and distribution as the original. [3]

The objective of this study was to evaluate the accuracy of the iris recognition technique using GAN based methods to generate new iris patterns, to allow training the model with more data.

## II. RELATED WORK

The idea of using GANs for generating more data from a given set, to train models with a bigger number of samples, is not new, and since the invention of GANs there have been several works trying to improve them. Some works are try to

improve GANs by changing the Loss function, other ones try to change the architecture of the neural networks.

Leding present a generative adversarial network (GAN) for image super-resolution (SR), know as SRGAN. The basic idea is to increase the resolution of a image, the super-resolution image looks very similar to the original. The framework generate photo-realistic natural images with a up-scaling factors of 4x. They focus on the use of a perceptual loss function, which is a combination of an adversarial loss and a content loss. [3]

To get many other works about GAN frameworks and models refer to [5] for a detailed list.

A related work on biometrics Iris recognition algorithm using Iris images and GAN networks was develop by Shervin Minaee. They develop a machine learning framework using GANs. The framework is able to generate iris images sampled from two databases, CASIA-1000 and IIT-Delhi. The images generated where very similar to the images in this databases. The model of convolution network they use for the generator and the discriminator contain 5 layers, each layer was followed by a batch normalization non-linearity layer. To measure the diversity of the generated iris image, they use the Frechet Inception distance (FID), and they get a high FID score, showing they have good diversity. [2]

Other work related to iris recognition using deep convolutional neural networks (DCNNs) and SRGANs was developed by Koji Kashiara. He focused in the effects of SRGANs using iris images with low signal-to-noise ratio and other types of external noise and some prefiltering process. Because biometrics systems get the images by camera, and some cameras and photographic environment could cause a low signal-to-noise ratio. He use iris images from the UBIRIS.v1 database. He develop a SRGANs framework that was able to restore the images, and a DCNNs that could accurately predict the individual iris patterns. He use a pixel-based differences for the classifier for biometrics. [4]

## III. IMPLEMENTATION

Git Hub link of the Proyect. Proyect was developed in Google Colabs.

[https://github.com/Jose-R-Corona/Iris-GAN\\_ProyectCV](https://github.com/Jose-R-Corona/Iris-GAN_ProyectCV)

#### ACKNOWLEDGMENT

I would like to thank Ian Goodfellow for his work on GANs. Also I would like to thank Center for Biometrics and Security Research (CASIA) and IIT Delhi for the provided Iris image database.

#### REFERENCES

- [1] R. Saini "Comparison of various biometric methods," International Journal of Advances in Science and Technology, vol. 2, no. 1, 2, 2014.
- [2] S. Minaee, A. Abdolrashidi, Iris-GAN: Learning to Generate Realistic Iris Images Using Convolutional GAN, CoRR, abs/1812.04822, 2018.
- [3] C. Ledig, L. Theis, "Photo-realistic single image super-resolution using a generative adversarial network," Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, pp. 4681–4690, 2017.
- [4] K. Kashiwara, "Iris Recognition for Biometrics Based on CNN with Super-resolution GAN," 2020 IEEE Conference on Evolving and Adaptive Intelligent Systems (EAIS), Bari, Italy, 2020, pp. 1-6.
- [5] <https://github.com/hindupuravinash/the-gan-zoo>