clashcallerbot-reddit Documentation

Release 2.6.8

Jose A. Lerma III

GETTING STARTED

1	Usage Information				
	1.1	Quickstart	4		
		1.1.1 Prerequisites	4		
		1.1.2 Python Installation	4		
		1.1.3 Running Scripts Directly	5		
	1.2	Installation	6		
		1.2.1 Deployment Options	6		
		1.2.2 Building Documentation	15		
		1.2.3 Disclaimer	16		
	1.3	clashcallerbotreddit	16		
		1.3.1 clashcallerbotreddit package	16		
	1.4	FAQs	24		
		1.4.1 What is the point of ClashCallerBot?	24		
		1.4.2 Is it ready yet?	24		
		1.4.3 How do you call ClashCallerBot?	24		
		1.4.4 Do PMs work?	24		
		1.4.5 What options does it have?	25		
		1.4.6 Hey, why didn't it notice me?	26		
		1.4.7 Why was the message off by a few minutes?	26		
			26		
		1.4.9 Can I delete my comment?	26		
	1.5		26		
		1.5.1 Python	26		
		1.5.2 PRAW	27		
		1.5.3 Database	27		
		1.5.4 Documentation	27		
		1.5.5 Miscellaneous	27		
	1.6	Index	28		
Рy	thon I	Module Index	29		
•			21		
ш	dex	•	31		

ClashCallerBot was made to help /r/ClashOfClans clans coordinate attacks during Clan Wars (or Clan War Leagues) from within reddit.

For example, someone wants to attack base 1 and 7, but they haven't posted an update in over an hour and those two bases still haven't been attacked. Is it okay to attack those bases? Did your fellow clan member die? Who knows?

Well, if they (or someone on their behalf) had called those bases for a set period of time, you would know for certain.

Think of ClashCallerBot as an independent time keeper that runs entirely within reddit.

If not obvious enough, it's a fork of SIlver-'s RemindMeBot. It's a sweet (as in awesome) little program.

I plan to make a few more tweaks to make it even more useful.

Check us out on /r/ClashCallerBot.

GETTING STARTED 1

2 GETTING STARTED

USAGE INFORMATION

Usage can be inferred from the regular expressions used to process each comment in clashcallerbotreddit. search:

```
# Regular expressions
   clashcaller_re = re.compile(r'''
41
42
                                                      # prefix ! or space (optional)
                                 [C|c]lash[C|c]aller # lower or camelcase ClashCaller.
43
   → (required)
                                                      # suffix ! or space (required)
                                 [!|\sl
44
                                 ''', re.VERBOSE)
45
   expiration_re = re.compile(r'''
                                (?P < exp_digit > (\d) \{1, 2\})
                                                             # single or double digit.
47
   → (required)
                                                             # space (optional)
48
                                (?P<exp_unit>minute(s)?\s| # minute(s) (space after...
49
   →required)
                                                             # minute abbr. (space after_
                               min(s)?\s|
   →required)
                               hour(s)?\s|
                                                             # hour(s) (space after_
51
   →required)
                                                             # hour abbr. (space after
                               hr(s)?\s
52
   →required)
                               )+''', re.VERBOSE | re.IGNORECASE) # case-insensitive
   message_re = re.compile(r'''
                                         # space (optional)
55
                                         # opening double quote (required)
56
                                        # string: base(s) (required)
                            base(s)?
57
                                        # non-word character or space (optional)
                            [\W|\s]*
58
                             (\d){1,2} # single or double digit (required)
59
                                         # any character after (optional)
60
                                         # closing double quote (required)
61
                            ''', re.VERBOSE | re.IGNORECASE) # case-insensitive
62
63
```

To sum:

- The clashcaller string must be present in either lower or CamelCase with an exclamation point! either before or after.
- The expiration time in minutes or hours may follow either abbreviated or with full spelling with an optional space between the number and word, but mandatory space after the word: 4min. Case is ignored. If not given, defaults to 1 hour. The expiration time is limited to within 24 hours.
- The message within quotes must follow with the singular or plural form of base and a required single or double digit number. Case is ignored. Maximum message length is 100 characters to save database space.

1.1 Quickstart

This is what you'll need to run **clashcallerbot-reddit** ASAP (As Soon As Possible). **clashcallerbot-reddit** is developed on various Linux distros, so *Installation* is assumed to be on Linux.

We'll cover running installing into Python and running the scripts directly.

1.1.1 Prerequisites

Python clashcallerbot-reddit is a massive *python* script, so at least Python 3.6 is needed.

Pip Configuring *python* is easiest using pip. Once pip is installed, the requirements can be installed by running pip install -r requirements.txt from within the source code directory.

MySQL clashcallerbot-reddit uses a MySQL-compatible database to store calls and to keep track of comments that were replied to. Either MySQL or MariaDB can be used.

With these prerequisites met, **clashcallerbot-reddit** can be setup and run.

1.1.2 Python Installation

You're a brave one. This method is arguably faster; however, including a setup.py file is merely convention. This method will install the internal modules into the Python environment so that they can be called directly as programs.

Setup

First, add the bot's reddit metadata to *praw-example.ini* and rename to *praw.ini*, then add the database's root and desired bot user credentials to *database-example.ini* and rename to *database.ini*. Then, create a logs directory by entering mkdir ./logs in a terminal window.

Next, change the following line in clashcallerbotreddit.database

```
# Create the clashcaller database
database = ClashCallerDatabase(config_file=config, root_user=False)
457
```

to database = ClashCallerDatabase(config_file=config, root_user=True). This may get updated to be default later.

Starting

Once the database script is setup, **clashcallerbot-reddit** can be installed by entering:

```
python3 setup.py install
```

from within the source code directory. Now that **clashcallerbot-reddit** is installed, scripts can be run from terminal directly. First, we configure the the MySQL-compatible database by running <code>clashcallerbotreddit.database</code> in terminal:

```
database
```

Now, the bot can be started by calling clashcallerbotreddit.search and clashcallerbotreddit.reply:

```
nohup reply > /dev/null 2>&1 & nohup search > /dev/null 2>&1 &
```

Warning: This will **not** check for already running instances! Any running instances would have to be terminated manually. Instances will appear with process names search and reply.

1.1.3 Running Scripts Directly

Not gonna lie, I'm a run scripts directly kind of guy. IMO (In My Opinion), it's less hassle and more secure to do so, but YMMV (Your Mileage May Vary).

Setup

First, add the bot's reddit metadata to *praw-example.ini* and rename to *praw.ini*, then add the database's root and desired bot user credentials to *database-example.ini* and rename to *database.ini*. Then, create a logs directory by entering mkdir ./logs in a terminal window.

Next, change the following line in clashcallerbotreddit.database

```
# Create the clashcaller database
database = ClashCallerDatabase(config_file=config, root_user=False)
457
```

to database = ClashCallerDatabase(config_file=config, root_user=True). This may get updated to be default later.

Now, the MySQL-compatible database can be setup by running clashcallerbotreddit.database directly from within terminal:

```
python3 -m clashcallerbotreddit.database
```

Starting

Once the database is setup, the bot can be run by calling clashcallerbotreddit.search and clashcallerbotreddit.reply directly from within terminal:

```
python3 -m clashcallerbotreddit.search && python3 -m clashcallerbotreddit.reply
```

Alternatively, by running the provided bash script from within terminal:

```
./clashcallerbot.sh
```

Note:

- Remember to set executable mode with ${\tt chmod} + {\tt x}$./clashcallerbot.sh.
- Script assumes files are in the *clashcallerbotreddit* directory and is run as crontab in *Amazon Linux AMI Setup*.
- How often to run as a crontab depends on how long you want the bot to be down/broken.
- If you have access to root, check *Installation* for info on setting up systemd instead.
- Logfile can be removed if not necessary (remove variable and >> \$logfile).

1.1. Quickstart 5

- python3 can be replaced with relevant python version.
- The function in kill returns all script PIDs, so it must be restarted.
- If you have access to pidof, you can avoid killing all script instances.

Restarting

A bash script is provided to restart both scripts and can be run from within terminal:

```
./restart.sh
```

Note:

- Remember to set executable mode with chmod +x ./restart.sh
- Script assumes files are in the *clashcallerbotreddit* directory.
- If you have access to root, check *Installation* for info on setting up systemd instead.
- Logfile can be removed if not necessary (remove variable and >> \$logfile).
- python3 can be replaced with relevant python version.
- The function in kill returns all script PIDs, so it must be restarted.
- If you have access to pidof, you can avoid killing all script instances.

Updating

A bash script is also provided for updating both scripts and can be run directly from within terminal:

```
./update.sh
```

Note:

- Don't forget to set executable mode with chmod +x ./update.sh.
- The -f and -q switch silence outputs to certain degrees.

1.2 Installation

This thing has to run 24/7. As a proof of concept, I set it up in an Ubuntu VM for the open alpha and a CentOS VM for the open beta. Production version was running on CloudLinux OS in a shared host at one point, but has since moved to AWS. If you are using a different OS, your mileage may vary.

1.2.1 Deployment Options

Believe me, the list of where I have not deployed it is shorter. I mostly went with virtual machines for the development, and had the production version on a shared host for a bit. It has been migrated to an Amazon EC2 instance in hopes of minimizing costs.

Ubuntu 14.04 LTS Setup

For the open alpha, I went with an OS that is convenient (need something? There's a package for that) as a proof of concept and debugging environment.

Ubuntu Desktop is a good choice because most IDEs need a GUI, but other versions are available (like Server). The following instructions are a combination of setting up the Ubuntu OS to run the bot (build packages and setting up MySQL tables) as well as adding all the needed dependencies into python. Everything here is run in a terminal.

First, enable compiling from source. There will be a lot of compiling from source in the future...

```
sudo apt-get install build-essential python-dev libffi-dev libssl-dev
```

Next, set up pip:

```
sudo apt-get install python-pip && sudo pip install pip
```

Then, set up the needed environment. From within the virtual environment, run:

```
sudo pip install praw
```

Now, setup MySQL/MariaDB.

```
sudo apt-get install mysql-server # For MariaDB: sudo apt-get install mariadb-server_
→mariadb

# Set MySQL `root` pw when prompted (recommended)

mysql_secure_installation # say yes to everything after first prompt

sudo apt-get install libmysqlclient-dev # For MariaDB: sudo apt-get install

→libmariadbclient-dev
```

From within the MySQL/MariaDB prompt, set up the database itself.

```
mysql -uroot -p"password" # login as root

CREATE DATABASE db_name;

USE db_name;

CREATE TABLE message_table (id INT UNSIGNED NOT NULL AUTO_INCREMENT, permalink_

VARCHAR(100), message VARCHAR(100),

new_date DATETIME, userID VARCHAR(20), PRIMARY KEY(id));

ALTER TABLE message_table AUTO_INCREMENT=1;

CREATE TABLE comment_table (id MEDIUMINT NOT NULL, list VARCHAR(35), PRIMARY KEY(id));

INSERT INTO comment_table VALUES (1, "'0'");

GRANT SELECT, INSERT, UPDATE, DELETE, CREATE, DROP, INDEX, ALTER, CREATE TEMPORARY_

TABLES, LOCK TABLES ON db_name.*

TO 'botname'@localhost IDENTIFIED BY 'password';
```

Now that MySQL/MariaDB is set up, install more dependencies.

```
source clashcallerbot-reddit/bin/activate # set virtual environment, if needed
sudo pip install mysql-connector
```

Start, redirect output, and background process.

```
source clashcallerbot-reddit/bin/activate # set virtual environment, if needed nohup python3 -m clashcallerbotreddit.reply > /dev/null 2>&1 & nohup python3 -m clashcallerbotreddit.search > /dev/null 2>&1 &
```

1.2. Installation 7

CentOS 7.0 Setup

For the open beta, I went with an OS that is often available for production environments.

How you want CentOS installed is your choice. I went with the xxx-Minimal.iso so that it would be as lean as possible (since I planned for it to be in the cloud) and would only be as large as necessary to run the bot. Installation settings are also up to you (security, networking, user accounts, etc.). Since it is a minimal install, there is no GUI (Graphical User Interface) and everything is run from TTY1 (TeleTYpewriter number 1).

First, install EPEL (Extra Packages for Enterprise Linux). Pip isn't even available, so we start here:

```
yum install epel-release
```

Enable compiling from source. The list of what won't be compiled from source is shorter.

```
yum install gcc python-devel openssl-devel libffi-devel
```

Install and upgrade pip and wheel,:

```
yum install python-pip python-wheel && pip install -U pip wheel
```

Then, set up the needed environment. From within the virtual environment, run:

```
pip install praw
```

Now, setup MySQL/MariaDB.

```
yum install mariadb-server mariadb mariadb-devel
systemctl start mariadb # start mariadb
systemctl enable mariadb # start at boot
systemctl status mariadb # confirm installation
mysql_secure_installation # Say yes to everything!
mysql -uroot -p"password" # login to mysql
```

From within the MySQL prompt, setup the database itself.

```
CREATE DATABASE db_name;

USE db_name;

CREATE TABLE message_table (id INT UNSIGNED NOT NULL AUTO_INCREMENT, permalink_

VARCHAR(100), message VARCHAR(100),

new_date DATETIME, userID VARCHAR(20), PRIMARY KEY(id));

ALTER TABLE message_table AUTO_INCREMENT=1;

CREATE TABLE comment_table (id MEDIUMINT NOT NULL, list VARCHAR(35), PRIMARY KEY(id));

INSERT INTO comment_table VALUES (1, "'0'");

GRANT SELECT, INSERT, UPDATE, DELETE, CREATE, DROP, INDEX, ALTER, CREATE TEMPORARY_

TABLES, LOCK TABLES ON db_name.*

TO 'botname'@localhost IDENTIFIED BY 'password';
```

Now that MySQL is setup, install more dependencies.

```
source clashcallerbot-reddit/bin/activate # set virtual environment, if needed
pip install mysql-connector
```

Start, redirect output, and background process.

```
source clashcallerbot-reddit/bin/activate # set virtual environment, if needed nohup python -m clashcallerbotreddit.reply > /dev/null 2>&1 & nohup python -m clashcallerbotreddit.search > /dev/null 2>&1 &
```

Tip: Alternatively, use systemd service.

No Root Setup

For my first attempt at a production version, I got a shared host running CloudLinux OS that does not provide root access, but has both Python and MySQL pre-installed.

What system you install to is your choice, but this setup assumes a CloudLinux OS without root access and with both Python and MySQL installed. Everything is run from terminal (ssh compatible).

Note: If you have multiple Python versions, replace python and pip with your version, e.g., python2.7 get-pip.py --user, pip2.7 install --user -U pip wheel.

Since root is not available, pip needs to be installed locally.

```
wget https://bootstrap.pypa.io/get-pip.py && python get-pip.py --user
```

To ~/.bashrc, add PATH=\$PATH:~/.local/bin and PYTHONPATH=\$PYTHONPATH:~/.local/lib/python/site-packages/, then run source ~./bashrc to apply changes.

Next, update pip and wheel,:

```
pip install --user -U pip wheel
```

Then, set up the needed environment. From within the virtual environment, run:

```
pip install --user praw
```

From within the MySQL prompt, setup the database itself.

```
CREATE DATABASE db_name;

USE db_name;

CREATE TABLE message_table (id INT UNSIGNED NOT NULL AUTO_INCREMENT, permalink_

VARCHAR (100), message VARCHAR (100),

new_date DATETIME, userID VARCHAR (20), PRIMARY KEY(id));

ALTER TABLE message_table AUTO_INCREMENT=1;

CREATE TABLE comment_table (id MEDIUMINT NOT NULL, list VARCHAR (35), PRIMARY KEY(id));

INSERT INTO comment_table VALUES (1, "'0'");

GRANT SELECT, INSERT, UPDATE, DELETE, CREATE, DROP, INDEX, ALTER, CREATE TEMPORARY_

TO 'botname'@localhost IDENTIFIED BY 'password';
```

Now that MySQL is setup, install more dependencies.

```
source clashcallerbot-reddit/bin/activate # set virtual environment, if needed pip install --user mysql-connector
```

Start, redirect output, and background process.

```
source clashcallerbot-reddit/bin/activate # set virtual environment, if needed nohup python -m clashcallerbotreddit.reply > /dev/null 2>&1 & nohup python -m clashcallerbotreddit.search > /dev/null 2>&1 &
```

1.2. Installation 9

Tip: Alternatively, use systemd service.

Amazon Linux AMI Setup

For what I hope is the final production version, I set up an Amazon EC2 instance running Amazon Linux AMI. I particularly like that it has pip and python pre-installed.

Setup Amazon Linux

Amazon Linux AMI is a fork of RHEL6 (Red Hat Enterprise Linux version 6) made to run on the EC2 (Amazon Elastic Compute Cloud) of AWS (Amazon Web Services). It is a good choice for having an operating system that is fully up to date and supported by the "host." I particularly like that it is already setup with most of what is needed. If preferred, use Ubuntu, OpenSUSE, Red Hat, et al., but your mileage will vary using this guide.

Tip: Check out the *CentOS Setup Guide* or the *Ubuntu Setup Guide* if using those distros.

Get an AWS account set up/prep for using EC2, then set up the EC2 instance itself. It is a bit of an orchestration, but worth it.

Note:

- Opted for a t2.micro instance since the free tier lasts 12 months, though that may change to a t1.micro. Also used Security Groups to limit access to My IP and used a key pair.
- It is a good idea to enable billing alerts.

Configure an EBS (Elastic Block Store) to store the database. Went with 22 GB since it is free, but I may change that to around 10 GB later. Also went with magnetic storage because it costs less than SSD storage and the I/O speed is not needed right now.

Note:

- The root volume is deleted on termination of the instance, so I turned on termination protection. Alternatively, the root volume can be changed to persist.
- When connecting from Windows operating systems, I prefer PuTTY/KiTTY, but there is a doc detailing setup.

Next, secure the EC2 instance. It is an old guide, so the only thing that needs to be done is adding a new user (with limited access, by default) to run the bot. At this point, a root volume snapshot can be made to save progress, if persistence was not enabled previously.

Tip:

• Install and enable yum-cron to keep the EC2 instance updated automatically.

Setup pip and python

Install some dependencies as the **default user**, not the new one.

```
sudo yum install gcc python36-devel.x86_64 openssl-devel libffi-devel sudo pip install --upgrade pip
```

As the **new user**, set up the needed environment and select it from within the package directory:

```
python3 -m venv clashcallerbot-reddit/env
source clashcallerbot-reddit/env/bin/activate # selects venv
```

From within the virtual environment, run:

```
pip install -U wheel
pip install --upgrade pip
pip install praw
pip install mysql-connector
```

Setup MySQL

Set up a MySQL database within an EBS volume as the **default user**. The guide is for Ubuntu, but setup for Amazon Linux is very similar (replace apt-get with yum and use sudo service mysqld [start|stop] to start or stop MySQL). Once the EBS volume is created and attached, the **default user** needs to run the following from within the Amazon Linux EC2 instance to create an XFS filesystem at /vol:

```
# Create XFS filesystem
sudo yum install xfsprogs mysql-server mysql-devel
grep -q xfs /proc/filesystems || sudo modprobe xfs
sudo mkfs.xfs /dev/sdb # change to wherever volume is mounted

# Mount XFS filesystem
echo "/dev/sdb /vol xfs noatime 0 0" | sudo tee -a /etc/fstab
sudo mkdir -m 000 /vol
sudo mount /vol
```

Now that MySQL is installed, it must be configured.

```
sudo service mysqld start
sudo service mysqld status # Confirm it is running
sudo mysql_secure_installation # Say 'y' to everything!
sudo mysql -uroot -p"password"
```

From within the MySQL prompt, mysql>, the database can be set up.

(continues on next page)

1.2. Installation 11

(continued from previous page)

```
'password';
QUIT
```

Make sure that MySQL is stopped with sudo service mysqld stop && sudo service mysqld status, then move MySQL into the EBS volume.

```
sudo mkdir /vol/etc /vol/lib /vol/log
sudo mv /etc/my.cnf /vol/etc/
sudo mv /var/lib/mysql /vol/lib/
sudo mv /var/log/mysqld.log /vol/log

sudo ln -s /vol/etc/my.cnf /etc/my.cnf
sudo ln -s /vol/log/mysqld.log /var/log/mysqld.log

sudo mkdir /var/lib/mysql
echo "/vol/lib/mysql /var/lib/mysql none bind" | sudo tee -a /etc/fstab
sudo mount /var/lib/mysql

sudo service mysqld start && sudo service mysqld status
sudo chkconfig --level 3 mysqld on # set to start at boot
```

Setup ClashCallerBot

Now that python, pip, and MySQL have been set up, the **new user** can download and setup the bot:

```
source clashcallerbot-reddit/env/bin/activate # set virtual environment, if needed
wget https://github.com/JoseALermaIII/clashcallerbot-reddit/raw/master/update.sh
chmod +x ./update.sh
./update.sh
```

Next, add the bot's reddit metadata to *praw-example.ini* and rename to *praw.ini*, then add the database's root and desired bot user credentials to *database-example.ini* and rename to *database.ini*.

Then, all requirements can be installed via pip:

```
pip install -r requirements.txt
```

Once all relevant files have been downloaded and configured, the bot can be started:

```
chmod +x ./clashcallerbot.sh
./clashcallerbot.sh
```

Tip:

• The bot has to login to reddit at least once to refresh the oauth token. Amazon Linux does not have a web browser installed by default, so run sudo yum install lynx as the **default user** before running the script.

Amazon Linux 2 Setup

For what is intended to be the final production version, an Amazon EC2 instance is running Amazon Linux 2. Amazon Linux 2 includes such conveniences as pip and python pre-installed.

Setup Amazon Linux 2

Amazon Linux 2 is Amazon's latest version of Amazon Linux. According to OS (Operating System) metadata, Amazon Linux 2 *may be* a fork of RHEL7 (Red Hat Enterprise Linux version 7) or the equivalent Fedora version, but built to run on the EC2 of AWS. It is a good choice for having an operating system that is fully up to date and supported by the "host." I particularly like that it is already setup with most of what is needed. If preferred, use Ubuntu, OpenSUSE, Red Hat, et al., but your mileage will vary using this guide.

Tip: Check out the *CentOS Setup Guide* or the *Ubuntu Setup Guide* if using those distros.

Get an AWS account set up/prep for using EC2, then set up the EC2 instance itself. It is a bit of an orchestration, but worth it.

Note:

- Opted for a t3.micro instance since that's what's 'in' right now. Also used Security Groups to limit access to My IP and used a key pair.
- It is a good idea to enable billing alerts.
- The root volume is deleted on termination of the instance, so I enabled termination protection. Alternatively, the root volume can be changed to persist.

Configure an EBS to store the database. Went with 20 GB since that should be more than enough. Also went with magnetic storage because it costs less than SSD storage and the I/O speed is not needed.

Tip:

- Adding tags helps keep instances organized, like Name: ClashCallerBot, Category: EC2 t3. micro, Stack: Production, etc
- When connecting from Windows operating systems, I prefer PuTTY/KiTTY, but there is a doc detailing setup.

Next, secure the EC2 instance. It is an old guide, so the only thing that needs to be done is adding a new user (with limited access, by default) to run the bot. At this point, a root volume snapshot can be made to save progress, if persistence was not enabled previously.

Tip:

• Install and enable yum-cron to keep the EC2 instance updated automatically.

Setup pip and python

Install some dependencies as the **default user**, not the new one.

```
sudo yum install gcc python3-devel.x86_64 openssl-devel libffi-devel pip3 install --upgrade pip
```

As the **new user**, set up the needed environment and select it from within the package directory:

1.2. Installation 13

```
python3 -m venv clashcallerbot-reddit/env
source clashcallerbot-reddit/env/bin/activate # selects venv
```

From within the virtual environment, run:

```
pip install -U wheel
pip install --upgrade pip
pip install praw==6.0.0 # Still on praw6.0.0, for now
pip install mysql-connector
```

Setup MariaDB

Set up a MySQL database within an EBS volume as the **default user**. The guide is for MySQL and Ubuntu, but setup for MariaDB and Amazon Linux 2 is very similar (replace apt-get with yum, mysql with mariadb, and use sudo systemctl [start|stop] mariadb to start or stop MariaDB). Mainly follow the steps for creating and attaching an EBS volume. Fear not, the remaining steps will be summarized in this guide.

First, once the EBS volume has been created and attached, the **default user** needs to run the following from within the EC2 instance to create an XFS filesystem at /vol:

```
# Create XFS filesystem
sudo yum install xfsprogs mariadb-server mariadb-devel
grep -q xfs /proc/filesystems || sudo modprobe xfs
sudo mkfs.xfs /dev/sdf # change to wherever volume is mounted

# Mount XFS filesystem
echo "/dev/sdf /vol xfs noatime 0 0" | sudo tee -a /etc/fstab
sudo mkdir -m 000 /vol
sudo mount /vol
```

Now that MariaDB is installed, it must be configured.

```
sudo systemctl start mariadb
sudo systemctl status mariadb  # Confirm it is running
sudo mysql_secure_installation  # Say 'y' to everything!
sudo mysql -uroot -p"password"
```

From within the MariaDB prompt, MariaDB [(none)]>, the database can be set up.

Tip: Alternatively, run the database.py script with the settings specified in *Quickstart*.

Make sure that MariaDB is stopped with sudo systematl stop mariadb && sudo systematl status mariadb, then move MariaDB into the EBS volume.

```
sudo mkdir /vol/etc /vol/lib /vol/log
sudo mv /etc/my.cnf.d /vol/etc/
sudo mv /var/lib/mysql /vol/lib/
sudo mv /var/log/mariadb /vol/log/

sudo ln -s /vol/etc/my.cnf.d /etc/my.cnf.d
sudo ln -s /vol/log/mariadb /var/log/mariadb

sudo mkdir /var/lib/mysql
echo "/vol/lib/mysql /var/lib/mysql none bind" | sudo tee -a /etc/fstab
sudo mount /var/lib/mysql

sudo systemctl start mariadb && sudo systemctl status mariadb
sudo systemctl enable mariadb # set to start at boot
```

Setup ClashCallerBot

Now that python, pip, and MariaDB have been set up, the **new user** can download and setup the bot:

```
source clashcallerbot-reddit/env/bin/activate # set virtual environment, if needed
cd clashcallerbot-reddit # go to desired source directory
wget https://github.com/JoseALermaIII/clashcallerbot-reddit/raw/master/update.sh
chmod +x ./update.sh
./update.sh
```

Next, add the bot's reddit metadata to *praw-example.ini* and rename to *praw.ini*, then add the database's root and desired bot user credentials to *database-example.ini* and rename to *database.ini*.

Then, all requirements can be installed via pip:

```
pip install -r requirements.txt
```

Once all relevant files have been downloaded and configured, the bot can be started:

```
chmod +x ./clashcallerbot.sh
./clashcallerbot.sh
```

Tip:

• The bot has to login to reddit at least once to refresh the oauth token. Amazon Linux 2 does not have a web browser installed by default, so run sudo yum install lynx as the **default user** before running the script.

1.2.2 Building Documentation

Note: Building the documentation is **not needed or recommended** unless contributing to the documentation. The latest version of the documentation is available at josealermaiii@github.io/clashcallerbot-reddit or as a PDF in the source code. You have been warned.

Building the docs requires a few more pip packages:

Sphinx

1.2. Installation 15

- sphinxcontrib-napoleon
- sphinx-rtd-theme

If that wasn't bad enough, a symbolic link to praw.ini must be made from within ~/.config.:

```
cd ~/.config
ln -s absolute_path_here/clashcallerbot-reddit/praw.ini praw.ini
```

This has to do with how *praw* finds the *praw.ini* file. This may get fixed later much like the *database.ini* fix in __init__.py.

Now, we can build the docs in HTML format:

```
cd absolute_path_here/clashcallerbot-reddit/docs make html
```

This will save the docs website in ../../clashcallerbot-reddit-docs/.

Building the PDF is even more involved. First, LaTeX must be installed on the OS. For example, in Ubuntu 18.04:

Installing these dependencies is not recommended, if not needed, because they require > 300 MB of disk space.

Now, we can build the docs in PDF format:

```
cd absolute_path_here/clashcallerbot-reddit/docs
make latexpdf
```

This will save the doc's PDF in .../clashcallerbot-reddit.pdf.

1.2.3 Disclaimer

Though covered by the MIT License, I reiterate: executing code from the Internet in terminal can end up doing bad things.

Read and understand all code you copy and paste before running it.

1.3 clashcallerbotreddit

1.3.1 clashcallerbotreddit package

Submodules

clashcallerbotreddit.database module

Setup the MySQL-compatible database.

If run directly, this module will setup the ClashCallerBot database with tables and display their format and contents. Additionally, this module provides a class with various methods for managing the MySQL-compatible database:

- · Create database and tables.
- View table data and properties.

- Lock tables for reading and writing.
- Grant user permissions (if logged into database as root).
- · Add rows to tables.
- Delete tables and rows.
- Convert python datetime to MySQL datetime.

Bases: object

Implements a class for a ClashCaller Database.

Acts as an object-relational mapper for mysql.connector specific to ClashCallerBot.

config_file

A configparser object with database.ini file pre-read.

Type configparser.ConfigParser

section

Section heading containing bot information. Defaults to 'bot'.

Type str

root_user

Specifies whether the database will be setup as root user.

Type bool

mysql_connection

A mysql.connector.connect object.

Type mysql.connector.connect

cursor

A mysql.connector.connect.cursor object.

Type mysql.connector.connect.cursor

$\textbf{close_connections} \, (\,) \, \to None$

Close database connections.

Method closes database cursor and connection.

static convert_datetime (dt: <module 'datetime' from '/usr/lib/python3.6/datetime.py'>) \rightarrow str Converts python datetime to MySQL datetime.

Method converts given python datetime object to MySQL datetime format.

Parameters dt – Datetime object in default format.

Returns Datetime string in MySQL format.

$\texttt{create_database} \, (\,) \, \to None$

Create database.

Method creates database with database name.

$create_table(tbl_name: str, cols: str) \rightarrow None$

Create table in database.

Method creates table in database with given name and specifications.

Parameters

- tbl_name Name to give table.
- cols Columns to put in table.

Example

```
delete\_row(tid: str) \rightarrow None
```

Deletes row from message table.

Method deletes given table id (row) from message table.

Parameters tid – Table id from id column of message table.

```
describe\_table(tbl\_name: str) \rightarrow list
```

Gets description of table.

Method returns a list describing the structure of the given table.

```
Parameters tbl_name - Name of table to describe
```

Returns List with table description, empty list otherwise.

```
drop\_table(tbl\_name: str) \rightarrow None
```

Drop table from database.

Function drops given table from given database.

```
Parameters tbl_name - Table to drop.
```

```
\texttt{get\_expired\_messages} (time\_now: datetime.datetime) \rightarrow list
```

Retrieves list of messages that have expired.

Method returns list of messages whose expiration times are before current datetime.

```
Parameters time_now - Current datetime.
```

Returns List containing results of query.

```
\texttt{get\_removable\_messages} (usr_name: str, link: str) \rightarrow list
```

Retrieves list of messages that match the username and permalink.

Checks the message table for rows containing the given user name and given link.

Parameters

- usr name Reddit username wanting to delete saved calls.
- link Comment permalink of saved call (without domain prefix)

Returns List of messages matching query. Empty list if none found.

get_rows ($tbl_name: str$) \rightarrow tuple

Fetch table rows.

Method gets rows of given table by order of id in a tuple.

Parameters tbl_name – Name of table to get rows from.

Returns Tuple containing each row's data, empty tuple otherwise.

 $\texttt{get_tables}() \rightarrow list$

Return table list of database.

Method returns a list with the names of the tables.

Returns List of table names.

 $get_user_messages(usr_name: str) \rightarrow list$

Retrieves list of messages that match the username.

Checks the message table for rows containing the given user name.

Parameters usr_name – Reddit username wanting to list saved calls.

Returns List of messages matching query. Empty list if none found.

 ${\tt grant_permissions}\,(\,)\,\to None$

Grants bot user permissions to database.

Method grants bot user permissions to database.

Notes

Only database root user can grant database permissions.

 $lock_read(tbl_name: str) \rightarrow None$

Locks table for reading.

Method locks a given table for read access.

Parameters tbl_name - Name of table to lock.

Returns True if successful, False otherwise.

Notes

- · Any previous locks are implicitly released.
- Read locks have lower priority than write locks.

 $lock_write(tbl_name: str) \rightarrow None$

Locks table for writing.

Method locks a given table for write access.

Parameters tbl_name - Name of table to lock.

Notes

- Any previous locks are implicitly released.
- Write locks have higher priority than read locks.

$open_connections() \rightarrow None$

Open database connections.

Method makes database connection and cursor.

save_message (link: str, msg: str, exp: < module 'datetime' from '/usr/lib/python3.6/datetime.py'>, usr name: str) \rightarrow None

Saves given comment data into message_data table.

Method saves given inputs in message_date table as a row.

Parameters

- link Comment permalink.
- msg Comment message.
- **exp** Expiration datetime object.
- usr_name Comment author username.

```
select\_database() \rightarrow None
```

Select database for command execution.

Method selects database within MySQL for command execution.

```
{\tt unlock\_tables}\,(\,)\,\to None
```

Unlocks tables to allow access.

Method unlocks tables to allow read/write access.

```
clashcallerbotreddit.database.main()
```

clashcallerbotreddit.reply module

Performs cleanup operations.

This module implements functions designed to clean up various data sets:

- Sends and deletes stored messages in the MySQL-compatible database.
- Checks bot's comments and removes comments below a certain threshold.
- Checks bot's messages for keywords and deletes them after:
 - Adding message author to call reminder.
 - PMing list of message author's calls.
 - Deleting message author from call.

```
clashcallerbotreddit.reply.check_comments (usr: str, limit: int = -5) \rightarrow None Checks comments and deletes if at or below threshold.
```

Checks given user's last 100 comments and deletes each one at or below the given threshold.

Parameters

- usr User to check comments of.
- limit Threshold at or below which comment will be deleted. Defaults to –5.

Returns None. Comments at or below threshold are deleted.

Note: Skips archived comments (> 6 months from start time).

clashcallerbotreddit.reply.check_database() \rightarrow None

Checks messages in database and sends PM if expiration time passed.

Checks messages saved in a MySQL-compatible database and sends a reminder via PM if the expiration time has passed. If so, the message is removed from the database.

Returns None. Message is removed from database if expiration time has passed.

clashcallerbotreddit.reply.check_messages() $\rightarrow None$

Checks inbox messages.

Checks authorized user's inbox messages for commands, processes them, then deletes the message.

Returns None. Messages are processed then deleted.

Notes

- Does not process mentions or comment replies.
- Skips old messages (> 6 months from start time).

```
clashcallerbotreddit.reply.get_parent(link: str) \rightarrow str
```

Fetch parent comment or submission.

Function gets parent comment of given permalink or submission if top level comment.

Parameters link – Permalink to get parent of.

Returns Parent comment link or default string.

```
clashcallerbotreddit.reply.main()
```

```
clashcallerbotreddit.reply.process_add_me (msg_obj: praw.models.reddit.message.Message)

Process an AddMe! command from a message.
```

Processes an AddMe! command from a given message that invoked it. The message author is added to the MySQL-compatible database with the permalink, message, and expiration time from the message body.

Parameters msq_obj - Instance of Message class that invoked the AddMe! command.

Returns Error message string if unsuccessful, None otherwise.

clashcallerbotreddit.reply.**process_delete_me** (*msg_obj: praw.models.reddit.message.Message*) Process a DeleteMe! command from a message.

Processes a DeleteMe! command from a given message that invoked it. If calls from the message author for the permalink from the message body are found in the MySQL-compatible database, they are removed from the database.

Parameters msg_obj – Instance of Message class that invoked the DeleteMe! command.

Returns Error message string if unsuccessful, None otherwise.

clashcallerbotreddit.reply.process_my_calls (msg_obj: praw.models.reddit.message.Message)
Process a MyCalls! command from a message.

Processes a MyCalls! command from a given message that invoked it. If calls from the message author are found in the MySQL-compatible database, they are sent in a table format via PM.

Parameters msg_obj – Instance of Message class that invoked the MyCalls! command.

Returns Error message string if unsuccessful, None otherwise.

```
clashcallerbotreddit.reply.send_reminder(link: str, msg: str, usr: str) \rightarrow None Sends reminder PM to username.
```

Function sends given permalink and message to given username.

Parameters

- link Permalink to comment.
- msq Message in comment that was saved.
- usr User to send reminder to.

clashcallerbotreddit.search module

Searches recent reddit comments for ClashCaller! string and saves to database.

This module uses the Python Reddit API Wrapper (PRAW) to search recent reddit comments for the ClashCaller! string.

If found, the userID, permalink, comment time, message, and expiration time (if any) are parsed. The default, or provided, expiration time is applied, then all the comment data is saved to a MySQL-compatible database.

The comment is replied to, then the userID is PM'ed confirmation.

```
clashcallerbotreddit.search.have_replied(cmnt_obj: praw.reddit.Reddit.comment, usr\_name: str) \rightarrow bool
```

Check if user has replied to a comment.

Function checks reply authors of given comment for given user.

Parameters

- cmnt_obj Comment object to get replies of.
- usr_name Name of bot to check for.

Returns True if successful, False otherwise.

```
clashcallerbotreddit.search.is_recent (cmnt_time: float, time_arg: datetime.datetime) \rightarrow bool
```

Checks if comment is a recent comment.

Function compares given comment Unix timestamp with given time.

Parameters

- cmnt_time Comment's created Unix timestamp in UTC.
- time_arg Time to compare with comment timestamp.

Returns True if comment's created time is after given time, False otherwise.

```
clashcallerbotreddit.search.main() clashcallerbotreddit.search.send_confirmation(usr_name: str, link: str, exp: date-time.datetime) \rightarrow None Send confirmation to reddit user.
```

Function sends given user confirmation of given expiration time with given link.

Parameters

- usr name username of user.
- link Permalink of comment.
- **exp** Expiration datetime of call.

Returns None.

Replies to a comment.

Function replies to a given comment object with a given message.

Parameters

- **cmnt_obj** Comment object to reply to.
- exp Expiration datetime of call.
- message_arg Original call message.

Returns id of new comment if successful, None otherwise

clashcallerbotreddit.search.send_error_message ($usr_name: str, link: str, error: str) \rightarrow None$ Send error message to reddit user.

Function sends given error to given user.

Parameters

- usr_name username of user.
- link Permalink of comment.
- **error** Error to send to user.

Returns None.

```
clashcallerbotreddit.search.send_message(usr_name: str, subject_arg: str, message_arg: str) \rightarrow None
```

Send message to reddit user.

Sends a message to a reddit user with given subject line.

Parameters

- usr_name username of user.
- **subject_arg** Subject line of message.
- message_arg Message to send.

Returns None.

Module contents

clashcallerbot-reddit constants

Contains constant variables used in source files.

```
clashcallerbotreddit.__version__
```

String with version number using the Semantic Versioning Scheme

Type str

```
\verb|clashcaller| bot reddit.config|
```

A configparser object containing the sections inside database.ini

Type configparser.ConfigParser

```
clashcallerbotreddit.module dir
```

String with the absolute path of the module's directory.

```
Type str
```

clashcallerbotreddit.locations

List containing all possible paths of database.ini

```
Type list
```

clashcallerbotreddit.LOGGING

Dictionary containing definitions for the loggers, handlers, and formatters.

Type dict

1.4 FAQs

No one really asked them, but these are the anticipated FAQs (Frequently Asked Questions).

1.4.1 What is the point of ClashCallerBot?

ClashCallerBot was made to help /r/ClashOfClans clans coordinate attacks during Clan Wars (or Clan War Leagues) from within reddit.

For example, someone wants to attack base 1 and 7, but they haven't posted an update in over an hour and those two bases still haven't been attacked. Is it okay to attack those bases? Did your fellow clan member die? Who knows?

Well, if they (or someone on their behalf) had called those bases for a set period of time, you would know for certain.

Think of ClashCallerBot as an independent time keeper that runs entirely within reddit.

If not obvious enough, it's a fork of SIlver-'s RemindMeBot. It's a sweet (as in awesome) little program.

I plan to make a few more tweaks to make it even more useful.

1.4.2 Is it ready yet?

What I thought I'd do was keep it in permanent **Open Beta**, like Google. Let me know in /r/ClashCallerBot or via PM when something breaks.

1.4.3 How do you call ClashCallerBot?

```
ClashCaller! OPTIONAL TIME "REQUIRED MESSAGE" (with quotes)
```

Time is optional (defaults to an hour); however, a message is required. Meaning if you do a simple ClashCaller! the bot won't do anything, but you will contribute to spam. Ideally, the message will be something like "Base #3" or something to indicate the base being called. Everything before ClashCaller! is not caught and everything after is. So feel free to use it in long winded posts but make sure it's after to avoid problems.

The PM will give you the permalink to your original comment.

1.4.4 Do PMs work?

Kind of. Everyone needs to see what you called so they know not to attack it, so you cannot directly set a call via PM. However, **ClashCallerBot** can execute certain commands from the comment replies.

1.4.5 What options does it have?

Usage can be inferred from the regular expressions used to process each comment in clashcallerbotreddit. search:

```
# Regular expressions
40
   clashcaller_re = re.compile(r'''
41
                                 [!|\s]?
                                                      # prefix ! or space (optional)
42
                                 [C|c]lash[C|c]aller # lower or camelcase ClashCaller..
43
   44
                                 [!|\sl_s]
                                                      # suffix ! or space (required)
                                ''', re.VERBOSE)
45
   expiration_re = re.compile(r'''
46
                                (?P < exp_digit > (\d) \{1, 2\})
                                                          # single or double digit.
47
   → (required)
                                (\slashs)?
                                                             # space (optional)
                                (?P<exp_unit>minute(s)?\s| # minute(s) (space after_
   →required)
                                                             # minute abbr. (space after...
                               min(s)?\s|
50
   ⇒required)
                               hour(s)?\s|
                                                             # hour(s) (space after
51
   →required)
                               hr(s)?\s
                                                             # hour abbr. (space after
   →required)
                               )+''', re.VERBOSE | re.IGNORECASE) # case-insensitive
53
   message_re = re.compile(r'''
54
                                         # space (optional)
55
                            (\slashs) *
                                         # opening double quote (required)
56
                            base(s)? # string: base(s) (required)
57
                                       # non-word character or space (optional)
                            [\W|\s]*
                            (\d){1,2} # single or double digit (required)
59
                                       # any character after (optional)
60
                                         # closing double guote (required)
61
                            ''', re.VERBOSE | re.IGNORECASE) # case-insensitive
62
```

To sum:

- The clashcaller string must be present in either lower or CamelCase with an exclamation point! either before or after.
- The expiration time in minutes or hours may follow either abbreviated or with full spelling with an optional space between the number and word, but mandatory space after the word: 4min. Case is ignored. If not given, defaults to 1 hour. The expiration time is limited to within 24 hours.
- The message within quotes must follow with the singular or plural form of base and a required single or double digit number. Case is ignored. Maximum message length is 100 characters to save database space.

ClashCallerBot will then make this comment and will message you at the given time:

```
I will be messaging you on Jan. 21, 2019 at 06:17:09 PM UTC to remind you of this ⇒call.

Others can tap REMIND ME, TOO to send me a PM to be added to the call reminder and ⇒reduce spam.

You can also tap REMOVE ME to remove yourself from the call reminder or MY CALLS to ⇒list your current calls.
```

(continues on next page)

1.4. FAQs 25

(continued from previous page)

```
Thank you for entrusting us with your warring needs!

[^(More info)](https://www.reddit.com/r/ClashCallerBot/comments/4e9vo7/clashcallerbot_
info/)
```

1.4.6 Hey, why didn't it notice me?

Whoops! You should delete your comment (cut down on spam) and try again. Sometimes the bot misses a comment because there are too many comments happening at once on reddit, connection issues, my PC restarted, my Internet is down/too slow, or I'm watching Crunchyroll. Do not worry about the reminder though, as long you got the confirmation PM/comment, the reminder PM will come. Worst case scenario is that it will come late if there are connection issues.

Also, make sure you are calling the bot correctly. Like so:

```
ClashCaller! OPTIONAL TIME (default is an hour without it) "REQUIRED MESSAGE".
```

You must do it as ClashCaller! exactly because it is case sensitive.

1.4.7 Why was the message off by a few minutes?

The bot currently goes to sleep every 2 minutes to save on resources. Meaning your message can be as late as 2 minutes + any connection issues it is having with reddit.

1.4.8 What happens if it gets banned?

As long as it doesn't receive a global ban on reddit, it will get your message. For example, the bot is currently banned on /r/AskReddit (all bots are). Although it won't send the message to your comment, it will PM you to confirm.

If you see others doing ClashCaller! and no response from the bot, no worries! PMs are private.

1.4.9 Can I delete my comment?

Yes. The bot sends a PM to the username that called it. As long as you don't delete your account you'll get your message. Note that if you delete your message – unless it's a top level comment – it won't be able to return the original parent comment.

1.5 References

clashcallerbot-reddit wasn't built with inherent knowledge. These are all the reference materials used to help make the bot run properly. Truth be told, these are all the bookmarks in my clashcallerbot folder.

1.5.1 Python

- logging.config Logging configuration
- datetime Basic date and time types
 - strftime() and strptime() Behavior

- re Regular expression operations
- configuration file parser
- · Python Packages and You
- Building and Distributing Packages with Setuptools
- os.path Common pathname manipulations
- · Robust exception handling

1.5.2 PRAW

- Submission Stream Reply Bot
- · Comment Extraction and Parsing
- SubredditStream
- Comment
- Redditor
- praw/config.py at v6.0.0

1.5.3 Database

- MySQL 8.0 Reference Manual
 - Internal Locking Methods
- How to connect Python programs to MariaDB
- MySQL Connector/Python Developer Guide Connector/Python Coding Examples
- MySQL Connector/Python Developer Guide Guidelines for Python Developers

1.5.4 Documentation

- Setting up Sphinx for generating documentation from DocStrings, leveraging the Napoleon extension
 - Sphinx for Python documentation Giselle Zeno
 - * Publishing sphinx-generated docs on github sphinxdoc-test v0.1 documentation
 - Example Google Style Python Docstrings napoleon 0.7 documentation
 - reStructuredText Primer Sphinx 2.0.0+ documentation
- Semantic Versioning 2.0.0
- LaTeX error attempting to build PDF on Ubuntu 11.04

1.5.5 Miscellaneous

- JoseALermaIII/clashcallerbot-reddit
- Regex Tester
- Testing Thread Trois: ClashCallerBot

1.5. References 27

- commenting reddit.com
- Logging module is causing Sphinx to crash. Google Groups

1.6 Index

PYTHON MODULE INDEX

С

clashcallerbotreddit.database, 16
clashcallerbotreddit.reply, 20
clashcallerbotreddit.search, 22

30 Python Module Index

INDEX

Symbols	18
version (in module clashcallerbotreddit), 23	drop_table() (clashcallerbotred-dit.database.ClashCallerDatabase method),
С	18
check_comments() (in module clashcallerbotred-dit.reply), 20	G
check_database() (in module clashcallerbotred-dit.reply), 20	<pre>get_expired_messages() (clashcallerbotred-</pre>
check_messages() (in module clashcallerbotred-dit.reply), 21	<pre>get_parent() (in module clashcallerbotreddit.reply), 21</pre>
clashcallerbotreddit (module), 23 clashcallerbotreddit.database (module), 16 clashcallerbotreddit.reply (module), 20 clashcallerbotreddit.search (module), 22 ClashCallerDatabase (class in clashcallerbotreddit.database), 17	get_removable_messages() (clashcallerbotred-dit.database.ClashCallerDatabase method), 18 get_rows() (clashcallerbotred-dit.database.ClashCallerDatabase method), 18
close_connections() (clashcallerbotred-dit.database.ClashCallerDatabase method), 17	get_tables() (clashcallerbotred- dit.database.ClashCallerDatabase method),
config (in module clashcallerbotreddit), 23 config_file (clashcallerbotreddit.database.ClashCallerDatabase attribute), 17	get_user_messages() (clashcallerbotred- dit.database.ClashCallerDatabase method), 19
convert_datetime() (clashcallerbotred-dit.database.ClashCallerDatabase static method), 17	grant_permissions() (clashcallerbotred- dit.database.ClashCallerDatabase method), 19
create_database() (clashcallerbotred-dit.database.ClashCallerDatabase method), 17	H have_replied() (in module clashcallerbotred- dit.search), 22
create_table() (clashcallerbotred- dit.database.ClashCallerDatabase method), 17	is reasont () (in module clash call substraddit sequel)
cursor (clashcallerbotred- dit.database.ClashCallerDatabase attribute), 17	is_recent() (in module clashcallerbotreddit.search), 22 L
D delete_row() (clashcallerbotred- dit.database.ClashCallerDatabase method), 18	<pre>locations (in module clashcallerbotreddit), 24 lock_read()</pre>
describe_table() (clashcallerbotred- dit.database.ClashCallerDatabase method),	dit.database.ClashCallerDatabase method),

LOGGING (in module clashcallerbotreddit), 24 M main() (in module clashcallerbotreddit.database), 20 main() (in module clashcallerbotreddit.reply), 21 main() (in module clashcallerbotreddit.search), 22 module_dir (in module clashcallerbotreddit), 23 mysql_connection (clashcallerbotreddit.database.ClashCallerDatabase attribute), 0 open_connections() (clashcallerbotreddit.database.ClashCallerDatabase method), Р process_add_me() (in module clashcallerbotreddit.reply), 21 process_delete_me() (in module clashcallerbotreddit.reply), 21 process_my_calls() (in module clashcallerbotreddit.reply), 21 R (clashcallerbotredroot_user dit.database.ClashCallerDatabase attribute), S (clashcallerbotredsave_message() dit.database.ClashCallerDatabase method), (clashcallerbotredsection dit.database.ClashCallerDatabase attribute), select_database() (clashcallerbotreddit.database.ClashCallerDatabase method), send_confirmation() (in module clashcallerbotreddit.search), 22 send_confirmation_reply() (in module clashcallerbotreddit.search), 23 send_error_message() (in module clashcallerbotreddit.search), 23 send_message() (in module clashcallerbotreddit.search), 23 send_reminder() (in module clashcallerbotreddit.reply), 21 U unlock_tables() (clashcallerbotreddit.database.ClashCallerDatabase method), 20

32 Index