

Linux Kernel Rollback Guide

Rolling back the Linux kernel means booting into or reinstalling a previous kernel version because the latest one caused issues.

1. Boot into an Older Kernel (GRUB method)

- Reboot and open GRUB menu (Shift/Esc).
- Select "Advanced options".
- Choose previous kernel version.
- Boot and confirm stability.

2. Set a Previous Kernel as Default

Debian/Ubuntu:

```
sudo grub-set-default "Advanced options for Ubuntu>Ubuntu, with Linux <version>"
sudo update-grub
```

RHEL/CentOS/Fedora:

```
sudo grubby --set-default /boot/vmlinuz-<kernel-version>
```

3. Remove the Faulty Kernel (optional)

Debian/Ubuntu:

```
sudo apt remove linux-image-<version> && sudo update-grub
```

RHEL/CentOS/Fedora:

```
sudo dnf remove kernel-<version>
```

4. Reinstall a Known-Good Kernel

Debian/Ubuntu:

```
sudo apt install linux-image-<version>
```

RHEL/CentOS:

```
sudo dnf install kernel-<version>
```

5. Prevent Future Auto-Upgrade of Kernel

Debian/Ubuntu:

```
sudo apt-mark hold linux-image-generic
```

RHEL/Fedora:

```
sudo dnf versionlock kernel
```