MDPI

Article

Sensitivity of Fuzzy-PSO Inertia Control to Linguistic Granularity and Rule-Base Structure

José Barrera-García [1,2,3,*], Broderick Crawford [1,*], José Gómez-Pulido [2,4,5], Felipe Cisternas-Caneo [4,6], Yoslandy Lazo [1], Alex Paz [7], Álvaro Peña Fritz [7], and Ricardo Soto [1]

[1] Escuela de Ingeniería Informática, Pontificia Universidad Católica de Valparaíso, Avenida Brasil 2241, Valparaíso 2362807, Chile; jose.barrera@pucv.cl (J.B.-G.); broderick.crawford@pucv.cl (B.C.); yoslandy.lazo@pucv.cl (Y.L.); ricardo.soto@pucv.cl (R.S.)
[2] Department of Computer Science, Universidad de Alcalá, 28805 Alcalá de Henares, Spain; jose.gomez@uah.es (J.G.-P.)
[3] Escuela de Negocios y Economía, Pontificia Universidad Católica de Valparaíso, Amunátegui 1838, Viña del Mar 2580129, Chile
[4] Health Computing and Intelligent Systems Research Group (HCIS), Universidad de Alcalá, 28805 Alcalá de Henares, Madrid, Spain
[5] Ramón y Cajal Institute for Health Research (IRYCIS), Madrid, Spain
[6] Departamento de Ingeniería Industrial, Facultad de Ingeniería, Universidad del Bío-Bío, Avda. Collao 1202, Casilla 5-C, Concepción 4051381, Región del Biobío, Chile; fcisternas@ubiobio.cl (F.C.-C.)
[7] Escuela de Ingeniería en Construcción y Transporte, Pontificia Universidad Católica de Valparaíso, Avenida Brasil 2147, Valparaíso 2362804, Chile; alex.paz@pucv.cl (A.P.); alvaro.pena@ucv.cl (Á.P.F.)
* Correspondence: Broderick Crawford (broderick.crawford@pucv.cl); José Barrera-García (jose.barrera@pucv.cl)

Abstract: The performance of fuzzy-controlled particle swarm optimization (PSO_FCS) depends on the structure of its inference system, yet the influence of linguistic granularity and rule-base design remains insufficiently characterized. This study investigates the sensitivity of inertia-weight control to these structural choices using a static Mamdani fuzzy controller. A factorial comparison considers four linguistic granularities and eight systematically generated rule-base patterns, yielding 32 fuzzy configurations evaluated against classical PSO. Experiments comprise 63,426 independent runs across 62 function–dimension instances from the classical F1–F23 benchmark suite. The results reveal substantial differences among rule-base patterns, whereas increasing linguistic granularity does not consistently improve performance or reduce the dispersion between patterns. The best-ranked configuration, FCS-3-R1, achieves a mean Friedman rank of 4.77, compared with 6.36 for classical PSO, although both belong to the same Nemenyi critical-difference group. Performance rankings also differ between scalable and fixed-dimensional benchmark subsets, indicating that the preferred configuration depends on the evaluated problem set. A formal characterization establishes that four pairs of rule bases generate complementary inertia-control surfaces under the specified Mamdani inference architecture, without implying equivalent optimization performance. These findings demonstrate the importance of rule-base structure in fuzzy inertia control and provide a mathematical and empirical basis for examining structural configuration choices in PSO.

Keywords: fuzzy control; swarm intelligence; particle swarm optimization; linguistic granularity; rule-base structure; Mamdani inference

Citation: Barrera-García, J.; Crawford, B.; Gómez-Pulido, J.; Cisternas-Caneo, F.; Lazo, Y.; Paz, A.; Peña Fritz, Á.; Soto, R. Sensitivity of Fuzzy-PSO Inertia Control to Linguistic Granularity and Rule-Base Structure. *Mathematics* **2026**, *1*, 0. https://doi.org/

Received:
Revised:
Accepted:
Published:

Copyright: © 2026 by the authors. Submitted to *Mathematics* for possible open access publication under the terms and conditions of the Creative Commons Attribution (CC BY) license (https://creativecommons.org/licenses/by/4.0/).

1. Introduction

Particle swarm optimization (PSO) is a bio-inspired, population-based stochastic optimizer rooted in swarm intelligence, in which particles update their positions using individual and collective search experience [1]. The inertia weight scales the previous velocity and helps regulate the balance between exploration and exploitation [2]. A fuzzy control system (FCS) can adjust this weight during the search using measures of optimization progress [3]. Research on evolved fuzzy feedback policies further illustrates the scope for

state-dependent parameter control [4]. Within this swarm-intelligence framework, fuzzy partitions and the rule base determine how observations of the search process are translated into a control action.

In a Mamdani fuzzy inference system (FIS), the antecedents and consequents of linguistic rules are represented by fuzzy sets [5]. Linguistic granularity is a substantive design choice in fuzzy modeling, with implications for partition resolution, rule-base complexity, and interpretability [5,6]. For the controller studied here, the number n of linguistic labels determines the resolution of both input and output partitions, while the rule base maps combinations of diversity and iteration progress to an inertia weight. These are distinct but coupled structural choices: for a complete two-input table with equal granularity, increasing n from 3 to 9 raises the rule count from 9 to 81. Whether finer partitions improve PSO performance therefore requires empirical assessment, rather than being inferred from representational resolution alone.

The specific question addressed here is how the performance of a static Mamdani inertia controller varies with linguistic granularity and rule-base pattern when the inference architecture and optimization budget are held fixed. This complements research on fuzzy parameter control and partition design by comparing complete controller configurations under common experimental conditions. The study evaluates 32 PSO_FCS configurations formed by four granularities and eight rule-base patterns across the Classical Benchmark Suite F1–F23, using classical PSO as a baseline. It characterizes ranking and dynamic variation across functions and benchmark groups, rather than introducing a new optimizer or an adaptive selector. Because changing granularity also changes the rule-table size, the comparison does not isolate granularity and rule structure as independent causal effects.

The contributions of this work are:

1. an explicit parametric specification of a static Mamdani FCS, including its generated linguistic partitions and rule-base pattern families;
2. a mathematical characterization of the mirror symmetry satisfied by designated rule-pattern pairs under the specified inference architecture;
3. a controlled factorial comparison of four granularities and eight consequent patterns under a common PSO implementation and experimental budget, supported by supplementary run-level data and machine-readable statistical summaries; and
4. empirical evidence of ranking and dynamic heterogeneity among the evaluated configurations across functions and benchmark groups.

The remainder of the paper is organized as follows. Section 2 reviews prior work; Section 3 introduces the parametric controller and formalizes its rule-base families; Section 4 describes the experimental protocol; Section 5 reports global, function- and problem-class rankings, rule-base and granularity comparisons, robustness and dimensional scaling, and controller dynamics; and Sections 6 and 7 interpret the findings and summarize the conclusions and future work.

2. Related Work

2.1. Inertia-Weight Control in Particle Swarm Optimization

PSO is a population-based stochastic optimizer in which each particle combines inertia with cognitive and social attraction terms [1]. The inertia weight w directly scales the previous velocity; it is therefore a principal mechanism for controlling the exploration–exploitation balance. The original and early variants used a constant coefficient, whereas the widely used linearly decreasing inertia-weight schedule explicitly changes search behavior over the optimization horizon [2]. Subsequent work has investigated nonlinear schedules [7], feedback from swarm success [8], stability-aware adaptation [9], and joint adaptation of inertia and acceleration coefficients [10,11].

This body of work establishes an important distinction. A time-indexed schedule changes w but does not observe the current search state. State-dependent controllers instead use quantities such as diversity, improvement, distance, or stagnation to react to the population trajectory [8,9]. Such feedback is particularly relevant because benchmark

landscapes differ substantially in modality and conditioning; a search policy suitable for rapid local refinement need not be suitable for maintaining diversity in a multimodal landscape. The question addressed here is more specific: once a fuzzy state-feedback controller has been selected, how sensitive is its behavior to the semantic resolution of its partitions and to its rule-base structure?

2.2. Fuzzy State-Feedback Control of PSO Parameters

A fuzzy inference system (FIS) provides an interpretable way to map numerical state descriptors into a control action. In a Mamdani FIS, linguistic antecedents and consequents are combined through a rule base and a defuzzification operator; this architecture remains a canonical model-free fuzzy-control paradigm [12–14]. When used in PSO, the inputs commonly represent population diversity, iteration progress, or an improvement signal, and the output is an adapted value of w or of several PSO coefficients [3,15,16].

Fuzzy-PSO studies address different control targets and design questions. Valdez et al. compared fuzzy-logic augmentation across PSO variants for mathematical functions using co-evolution [16]. Xia et al. designed a multiple-input multiple-output fuzzy controller to tune adaptive learning weights [17], while Roy et al. developed benchmark-trained fuzzy feedback policies and reported 127 PSO algorithm variants with up to seven controlled parameters [4]; the latter article was published in 2025. Salimi et al. applied fuzzy-adaptive PSO to reachability analysis in systems specified through graph transformations [18], a distinct application domain. These contributions demonstrate the breadth of fuzzy parameter control, but they do not change the question addressed here: sensitivity of a fixed static Mamdani inertia architecture to granularity and consequent-pattern choices.

2.3. Fuzzy Partitions, Linguistic Granularity, and Interpretability

Linguistic granularity is the number of labels used to discretize a fuzzy universe. It is not merely an implementation detail: it determines which distinctions the controller can express and, for a multi-input rule base, determines the number of candidate rules. A well-formed fuzzy partition is expected to provide coverage, normality, distinguishability, and a semantically ordered set of labels [19,20]. Uniform triangular Ruspini partitions are a common construction because adjacent sets overlap smoothly while their membership grades sum to one over the normalized domain.

The accuracy–interpretability trade-off associated with granularity has long been recognized in fuzzy modeling. Fine partitions can represent smaller input distinctions, but expand the potential rule base; coarser partitions reduce complexity at the cost of local resolution. Gacto et al. review measures for interpretability in linguistic fuzzy rule-based systems [5], while Castiello et al. study variable-granularity interpretable partitions for classified data [6]. These works motivate treating granularity as a structural design choice, but they do not make optimization performance a direct measure of interpretability. For the present controller, the number of labels and consequent mapping are separate, coupled choices.

Rule-base design is a second, distinct source of semantic variation. Fuzzy-system design methods can tune membership parameters, induce or prune rules, or modify the partition itself [21,22]. Evolving systems may split rules in response to drift [23] or derive interpretable partitions from observed data [24]. Such adaptive approaches are valuable, but they do not identify whether a particular static combination of granularity and rule logic generalizes over qualitatively different optimization landscapes. Establishing that baseline is necessary before attributing an advantage to more elaborate structural adaptation.

2.4. From Structural Adaptation to Configuration Selection

The broader fuzzy-systems literature distinguishes parameter adaptation from structural adaptation. The former changes membership-function parameters or rule weights; the latter may add, split, merge, or remove rules and partition elements [22,25]. Recent research further investigates interpretable evolving partitions [23], semantic constraints during evo-

lutionary controller design [26], and variable-granularity knowledge representations [27]. These strands demonstrate that fuzzy semantics need not be treated as immutable.

Nevertheless, the flexibility of an adaptive mechanism can make interpretation difficult when multiple semantic choices change together. A controlled comparison of static configurations provides complementary descriptive evidence about how rankings vary when granularity and rule patterns are changed under a common architecture. Such comparisons do not by themselves identify independent causal effects or confirm a factorial interaction.

2.5. Research Gap and Positioning of This Study

Prior fuzzy-PSO studies demonstrate feedback controllers, multi-parameter adaptation, and optimized fuzzy policies, while fuzzy-modeling research treats partition granularity and interpretability as substantive design concerns. The present study is positioned as a controlled structural sensitivity analysis of a static Mamdani fuzzy inertia controller, not as a claim that no earlier factorial study exists. It evaluates four granularities, $n \in \{3,5,7,9\}$, and eight generated consequent patterns, $R_1, \ldots, R_8$, under common inputs, membership-function family, inference method, PSO implementation, and experimental budget. Because granularity changes both partition resolution and rule-table size, the results compare complete configurations rather than identify independent causal effects. The analysis also examines whether performance dispersion among rule-base patterns changes consistently across linguistic granularities, providing descriptive evidence on the sensitivity of complete controller configurations. The study does not validate an adaptive selector.

3. Parametric Fuzzy Inertia Controller

This section defines the static fuzzy-control component used by all PSO_FCS variants. The controller receives normalized diversity and iteration progress and returns an inertia weight bounded by $[w_{\min}, w_{\max}]$.

3.1. Mamdani FIS design

The two inputs are the diversity ratio $d_t \in [0,1]$ and normalized progress $p_t \in [0,1]$. The output universe is normalized to $[0,1]$ and is linearly rescaled to $[w_{\min}, w_{\max}]$ after defuzzification. For each evaluated granularity $n \in \{3,5,7,9\}$, let $\mathcal{L}_n = \{0, \ldots, n-1\}$ index the labels. Each input and output partition is uniform triangular with overlap one and shoulders at the boundaries, satisfying $\sum_{i \in \mathcal{L}_n} \mu_i(x) = 1$ on $[0,1]$. The indices $i, j, k \in \mathcal{L}_n$ denote diversity, progress, and output labels; μ_i^D, μ_j^P, and μ_k^W are their membership functions. For selected pattern $R \in \{R1, \ldots, R8\}$, $k_R(i,j) \in \mathcal{L}_n$ is the consequent index assigned to antecedent pair (i,j).

Figure 1 shows the two I1 input partitions and Figure 2 shows the O1 output partition for all four granularities. Increasing n narrows the support of each label and refines the controller's resolution; the Ruspini property and boundary shoulders are preserved.




Figure 1. I1 input membership functions for $n \in \{3,5,7,9\}$. Top: normalized swarm diversity; bottom: iteration progress. Each panel shows all four granularities.




Figure 2. O1 output membership functions for $n \in \{3,5,7,9\}$ on the normalized universe $[0,1]$. The defuzzified centroid is rescaled to $[w_{\min}, w_{\max}] = [0.1, 0.9]$.

For antecedent pair (i,j), the firing strength is

$$\alpha_{ij} = \min\{\mu_i^D(d_t), \mu_j^P(p_t)\}. \tag{1}$$

Mamdani implication clips each consequent membership function and max aggregation gives

$$\mu_{\text{agg}}(z) = \max_{i,j} \min\{\alpha_{ij}, \mu^W_{k_R(i,j)}(z)\}. \tag{2}$$

The aggregated membership function is defined over $z \in [0,1]$, and the raw output is its centroid. In the implementation, the integral is approximated by trapezoidal quadrature

on a 501-point grid; the raw centroid is normalized using the minimum and maximum centroids of the output sets before affine rescaling:

$$\begin{aligned} \bar{z}_t &= \frac{\int_0^1 z\,\mu_{\mathrm{agg}}(z)\,dz}{\int_0^1 \mu_{\mathrm{agg}}(z)\,dz}, \\ \widetilde{z}_t &= \mathrm{clip}\left(\frac{\bar{z}_t - z^c_{\min}}{z^c_{\max} - z^c_{\min}}, 0, 1\right), \\ w_t &= w_{\min} + \widetilde{z}_t(w_{\max} - w_{\min}). \end{aligned} \tag{3}$$

Here $z^c_{\min}$ and $z^c_{\max}$ are the smallest and largest centroids of the output membership functions. If the aggregated area is at most 10^{-12}, the implementation uses raw centroid fallback $\bar{z}_t = 0.5$ before applying the same centroid-bound normalization. For this experiment, $w_{\min} = 0.1$ and $w_{\max} = 0.9$.

3.2. Rule bank R1–R8

The rule bank contains eight fixed patterns representing the admissible directional relationships between diversity, progress, and the output inertia weight. Each pattern is generated algorithmically for arbitrary n; no rule matrix is manually rewritten for a particular granularity. A configuration is therefore identified by the pair (n, R), with $n \in \{3, 5, 7, 9\}$ and $R \in \{R1, \ldots, R8\}$.

The rule generator produces n^2 consequents for every pattern. The resulting matrices are validated for cardinality, deterministic generation, and bounded output. Figure 3 shows all eight patterns at $n = 3$; the complete matrices for $n = 5, 7, 9$ are provided in Appendix C. Each cell reports the consequent label assigned to an antecedent pair.




Figure 3. Rule bases R1–R8 at $n = 3$. Rows index diversity and columns index progress; each cell gives the consequent inertia-weight label.

3.3. Formal characterization of the rule-base families

3.3.1. Granularity and rule cardinality

For an odd granularity n, the central label index is $c = (n-1)/2$. Index 0 denotes the lowest label, index $n-1$ the highest, and index c the central label. Only odd values are admitted in this study so that a symmetric central label exists; the evaluated set is $n \in \{3,5,7,9\}$, whose labels are declared in the configuration file and range from *low, medium, high* at $n = 3$ to *very_very_low*, ..., *very_very_high* at $n = 9$. Here c is a label-center index, distinct from the PSO acceleration coefficients c_1 and c_2.

Because the controller has two inputs, a rule base assigns one consequent to every antecedent pair, so its cardinality is

$$|\mathcal{R}_n| = |\mathcal{L}_n|^2 = n^2, \tag{4}$$

which grows from 9 rules at $n = 3$ to 81 at $n = 9$. Raising n therefore increases the resolution with which the controller can distinguish swarm states, and increases at the same quadratic rate the number of decisions that a reader must inspect to understand the controller. Granularity is in this sense a resolution–interpretability trade-off, not a free parameter.

3.3.2. Rule generator

Let $i \in \mathcal{L}_n$ index the diversity label and $j \in \mathcal{L}_n$ the progress label of an antecedent pair; the selected pattern assigns consequent index $k_R(i,j) \in \mathcal{L}_n$. This consequent index is distinct from coordinate index k in Equation (12). Each pattern is determined by two ordinal effects, one per input:

$$e_{\text{prog}}(j) = \begin{cases} c-j, & \text{decreasing} \\ 0, & \text{neutral} \\ j-c, & \text{increasing} \end{cases} \qquad e_{\text{div}}(i) = \begin{cases} i-c, & \text{following} \\ 0, & \text{neutral} \\ c-i, & \text{compensating.} \end{cases} \tag{5}$$

The consequent is obtained from their sum under two regimes. When exactly one axis is non-neutral, the effect is transferred directly. When both are active, let $s = e_{\text{prog}}(j) + e_{\text{div}}(i)$ denote their combined ordinal effect; the sum is compressed into bands of two adjacent indices:

$$k_R(i,j) = \begin{cases} c + e_{\text{prog}}(j) + e_{\text{div}}(i), & \text{one axis active} \\ \Phi_n\big(e_{\text{prog}}(j) + e_{\text{div}}(i)\big), & \text{both axes active,} \end{cases} \tag{6}$$

where the band map Φ_n compresses the aggregate effect onto the label set,

$$\Phi_n(s) = \min\Big(\max\big(c + \operatorname{sgn}(s)\,\lceil |s|/2 \rceil,\ 0\big),\ n-1 \Big). \tag{7}$$

In the one-axis regime the active effect satisfies $|e| \le c$, so $c+e$ always lies in $\mathcal{L}_n$ and no clipping occurs. In the two-axis regime the sum ranges over $[-2c, 2c]$, and Φ_n maps it onto $\mathcal{L}_n$ through bands of width two around a central band of width one, saturating at the extremes. Both regimes are deterministic and defined for every n, so the eight matrices are generated from the pair of semantic axes, including at granularities for which no rule base has been published.

3.3.3. Semantic axes

The two axes describe ordinal effects in the consequent table. A *decreasing* progress direction assigns lower consequents as the progress label increases, while an *increasing* direction assigns higher consequents; a neutral axis contributes zero to this mapping. A *following* diversity reaction assigns higher consequents to higher diversity labels, whereas a *compensating* reaction assigns lower consequents; a neutral diversity axis repeats the

same consequent across diversity labels. This rule-table neutrality does not, by itself, make the effective output independent of that input, because every rule still includes both antecedents in its firing strength.

For R1, the generator gives $k_{R1}(i,j) = n-1-j$ for every diversity index i. However, with the implemented minimum conjunction and maximum aggregation, the strongest firing strength associated with progress label j is

$$\max_i \min\{\mu_i^d(d), \mu_j^p(p)\} = \min\{q_n(d), \mu_j^p(p)\}, \qquad q_n(d) = \max_i \mu_i^d(d), \tag{8}$$

where μ_i^d and μ_j^p are the diversity and progress membership functions. Since $q_n(d)$ varies with diversity, the effective R1 control surface need not reduce to a function of progress alone. Table 1 therefore describes the nominal consequent axes, not guaranteed independence of the effective inputs. The combination with both axes neutral is excluded because its consequent table is constant.

Table 1. Eight patterns classified by their nominal consequent axes. A neutral axis contributes zero to the consequent mapping; it does not remove that input from the common Mamdani inference. The doubly-neutral combination is excluded because its consequent table is constant.

Pattern	Progress direction	Diversity reaction
R1	decreasing	neutral
R2	increasing	neutral
R3	neutral	following
R4	neutral	compensating
R5	decreasing	following
R6	decreasing	compensating
R7	increasing	following
R8	increasing	compensating

3.3.4. Mirror symmetry of the rule bank

The generator makes the bank closed under semantic reversal. Call two patterns a *mirror pair* when every non-neutral axis of one is the inverse of the corresponding axis of the other and the neutral axes coincide; this covers both the reversal of a single active axis, as in R1 against R2 or R3 against R4, and the simultaneous reversal of two active axes, as in R5 against R8 or R6 against R7.

Proposition 1. *Let R_a and R_b be a mirror pair evaluated on the same partition family, with the same defuzzifier and the same bounds $[w_{\min}, w_{\max}]$. Then for every admissible n and every antecedent pair,*

$$k_b(i,j) = (n-1) - k_a(i,j), \tag{9}$$

and the induced control surfaces satisfy

$$w_{R_a}(d,p) + w_{R_b}(d,p) = w_{\min} + w_{\max} \qquad \forall (d,p) \in [0,1]^2. \tag{10}$$

The argument is constructive. Inverting an active axis changes the sign of its effect in Equation (5), and a neutral axis contributes zero and is unaffected, so the aggregate effect of a mirror pair satisfies $e_b = -e_a$. Both branches of Equation (6) are odd around the centre, since $c + (-e) = 2c - (c+e)$ and $\Phi_n(-s) = 2c - \Phi_n(s)$, with $2c = n-1$; the saturation of Φ_n is symmetric and therefore preserves the relation. The output partition is a uniform Ruspini family with shoulders, so the membership function of label k is the reflection about the midpoint of the output universe of the membership function of label $(n-1)-k$. Reflecting every activated consequent reflects the aggregated membership function, the centroid of a reflected set is the reflection of its centroid, and the affine rescaling onto $[w_{\min}, w_{\max}]$ preserves reflections, which yields Equation (10).

The property is verified numerically as part of the controller test suite, over the 28 unordered pairs of R1–R8 and the four granularities: exactly four pairs satisfy the index reflection, namely those identified above, and the surface identity holds to machine precision. Proposition 1 motivates the mirror-pattern contrasts in Section 5.4: a mirror pair differs by a complete reversal of the control law rather than an arbitrary perturbation, and the same relation appears in the trajectories of Section 5.7.

3.4. Integration with PSO

The FCS–PSO workflow is shown in Appendix C. At each iteration, both inputs determine one inertia weight shared by all particles.

Let $f : \mathbb{R}^d \to \mathbb{R}$ be the objective to be minimized, N the population size, and d the problem dimension. Particle index $i \in \{1, \dots, N\}$ and iteration index $t \in \{0, \dots, T_{\max}\}$ identify each state; $\mathbf{x}_{i,t}$, $\mathbf{v}_{i,t}$, $\mathbf{p}_{i,t}$, and $\mathbf{g}_t$ belong to $\mathbb{R}^d$, and $\mathbf{L}, \mathbf{U} \in \mathbb{R}^d$ are the coordinatewise search bounds. Initial positions are sampled coordinatewise uniformly within these bounds and initial velocities are zero. At each update iteration t, the controller is evaluated from the current population state and its output is used in the standard PSO velocity update:

$$\begin{aligned} \mathbf{v}_{i,t+1} &= \mathrm{clip}\Big(w_t \mathbf{v}_{i,t} + c_1 \mathbf{r}_{1,i,t} \odot (\mathbf{p}_{i,t} - \mathbf{x}_{i,t}) \\ &\qquad + c_2 \mathbf{r}_{2,i,t} \odot (\mathbf{g}_t - \mathbf{x}_{i,t}), -V_{\max}, V_{\max} \Big), \\ \mathbf{x}_{i,t+1} &= \mathrm{clip}(\mathbf{x}_{i,t} + \mathbf{v}_{i,t+1}, \mathbf{L}, \mathbf{U}). \end{aligned} \tag{11}$$

Here $\odot$ denotes elementwise multiplication; components of $\mathbf{r}_{1,i,t}$ and $\mathbf{r}_{2,i,t}$ are generated separately as uniform draws from $[0, 1)$. The acceleration coefficients are $c_1 = c_2 = 2$. The operator clip acts componentwise: for coordinate ℓ, it returns $\min(b_\ell, \max(a_\ell, z_\ell))$ for input z_ℓ and bounds a_ℓ, b_ℓ. The velocity bound is the scalar $V_{\max} = 0.1 U_1$, where U_1 is the upper bound of the first coordinate; this same bound applies to every velocity component. For position clipping, $\mathbf{L}, \mathbf{U}$ supply coordinatewise bounds. The solver clips updated positions before objective evaluation. Progress scalar p_t is distinct from personal-best vector $\mathbf{p}_{i,t}$.

For the FCS input, swarm diversity is measured with the Hussain mean-absolute-deviation statistic. Let $\bar{x}_k(t) = N^{-1} \sum_{i=1}^{N} x_{i,k}(t)$ denote the mean position in coordinate k. Its value is the mean absolute deviation over all particles and coordinates, rounded to three decimal places:

$$\begin{aligned} D_t &= \mathrm{round}\left(\frac{1}{Nd} \sum_{k=1}^{d} \sum_{i=1}^{N} |x_{i,k}(t) - \bar{x}_k(t)|, 3 \right), \\ D_t^{\max} &= \max_{0 \le s \le t} D_s, \\ d_t &= \begin{cases} D_t / D_t^{\max}, & D_t^{\max} > 10^{-12}, \\ 0, & \text{otherwise}, \end{cases} \qquad p_t = \frac{t}{T_{\max}}. \end{aligned} \tag{12}$$

The running maximum $D_t^{\max}$ includes the initial population; s in its definition is a dummy iteration index. The controller clips d_t and p_t to $[10^{-12}, 1 - 10^{-12}]$ before fuzzification. The same scalar w_t is shared by all particles. The baseline records $w_0 = 0.9$ at initialization, but velocity updates use $t = 1, \dots, T_{\max}$ in $w_t = 0.9 - 0.8t/T_{\max}$. Thus, for $T_{\max} = 1000$, the first applied value is 0.8992 and the final applied value is 0.1. Under FCS mode, w_t is returned by the Mamdani controller defined above.

The combined effect of the partitions and rule base is the control surface $(d_t, p_t) \mapsto w_t$. Figure 4 shows all eight effective surfaces at $n = 5$; surfaces at $n = 3, 7, 9$ are in Appendix C. These displays show the actual Mamdani outputs, including diversity sensitivity induced by antecedent firing even when a consequent axis is nominally neutral.

The remaining effective surfaces are provided in Appendix C. Algorithm 1 gives the iteration procedure using the diversity and PSO update equations defined above; the baseline schedule is specified separately.




Figure 4. Effective Mamdani inertia-weight surfaces for R1–R8 at $n = 5$, over diversity and progress; $w \in [0.1, 0.9]$.

Algorithm 1 Fuzzy-controlled PSO iteration

Require: Objective f, population size N, bounds $\mathbf{L}, \mathbf{U}$, iteration limit $T_{\max}$, granularity n, rule pattern $R \in \{R1, \ldots, R8\}$
Ensure: Best-so-far position $\mathbf{g}$ and its objective value $f(\mathbf{g})$ are recorded
Sample initial positions within $[\mathbf{L}, \mathbf{U}]$, set velocities to zero, evaluate the swarm, and set personal/global bests; initialize $D^{\max}$
for $t = 1, \ldots, T_{\max}$ **do**
  Compute (d_t, p_t) from the current swarm using Equation (12)
  $w_t \leftarrow \mathrm{FIS}_{n,R}(d_t, p_t)$ ▷ one weight shared by all particles
  for $i = 1, \ldots, N$ **do**
    Update velocity and position using Equation (11)
    Evaluate $f(\mathbf{x}_i)$ and update the personal best if improved
  end for
  Update the global best from the personal bests
end for
Record $(\mathbf{g}, f(\mathbf{g}))$ as the result

4. Experimental Design

The experimental design follows a controlled factorial protocol. The benchmark contains the 23 classical functions F1–F23 [28,29]. Functions F1–F13 are evaluated at dimensions $d \in \{10, 30, 50, 100\}$, whereas F14–F23 retain the dimensions imposed by their definitions. Each configuration is evaluated for 1000 iterations, with a population of 20 and 31 independent runs. Every run uses a distinct pseudorandom seed, defined as 42 plus its unique experiment identifier; seeds are not shared across configurations. Run identifiers therefore do not define cross-configuration pairing blocks. The resulting batch contains 62 benchmark instances and 63,426 completed runs.

4.1. Benchmark suite and dimensions

The functions are grouped for analysis into unimodal functions, scalable multimodal functions, and fixed-dimensional multimodal or composite functions. Table 2 reports the scalable functions F1–F13, and Table 3 reports the fixed-dimension functions F14–F23; both list the analytical definition, the search domain, and the reference optimum used by the solver. No shifted or rotated competition suite is included; all reported results use the experimental domains specified in these tables.

The optimum associated with each function is used to compute normalized performance measures. Special care is required for functions whose documented optimum is expressed per dimension: the reference value of F8 is $-418.9829\,d$, and it is scaled accordingly at every dimension before the gap is computed. Function F7 contains an additive uniform noise term and is therefore stochastic even for a fixed candidate solution; its dispersion across runs is not attributable to the optimizer alone.

Table 2. Scalable benchmark functions F1–F13. Formulations follow the classical suite [28,29]. Bounds and reference optima are the values used by the solver. All functions are evaluated at $d \in \{10, 30, 50, 100\}$.

Function	Name	Definition	Range	f^*
F1	Sphere	$\sum_{i=1}^{d} x_i^2$	$[-100, 100]$	0
F2	Schwefel 2.22	$\sum_{i=1}^{d} \lvert x_i \rvert + \prod_{i=1}^{d} \lvert x_i \rvert$	$[-10, 10]$	0
F3	Schwefel 1.2	$\sum_{i=1}^{d} \left(\sum_{j=1}^{i} x_j \right)^2$	$[-100, 100]$	0
F4	Schwefel 2.21	$\max_i \{ \lvert x_i \rvert, 1 \le i \le d \}$	$[-100, 100]$	0
F5	Rosenbrock	$\sum_{i=1}^{d-1} \left[100 \left(x_{i+1} - x_i^2 \right)^2 + (x_i - 1)^2 \right]$	$[-30, 30]$	0
F6	Step	$\sum_{i=1}^{d} (\lfloor x_i + 0.5 \rfloor)^2$	$[-100, 100]$	0
F7	Quartic with noise	$\sum_{i=1}^{d} i\, x_i^4 + \text{random}[0, 1)$	$[-1.28, 1.28]$	0
F8	Schwefel 2.26	$\sum_{i=1}^{d} \left(-x_i \sin \sqrt{\lvert x_i \rvert} \right)$	$[-500, 500]$	$-418.9829\, d$
F9	Rastrigin	$\sum_{i=1}^{d} \left[x_i^2 - 10 \cos(2\pi x_i) + 10 \right]$	$[-5.12, 5.12]$	0
F10	Ackley	$-20 \exp\left(-0.2 \sqrt{\frac{1}{d} \sum_{i=1}^{d} x_i^2} \right) - \exp\left(\frac{1}{d} \sum_{i=1}^{d} \cos(2\pi x_i) \right) + 20 + e$	$[-32, 32]$	0
F11	Griewank	$\frac{1}{4000} \sum_{i=1}^{d} x_i^2 - \prod_{i=1}^{d} \cos\left(\frac{x_i}{\sqrt{i}} \right) + 1$	$[-600, 600]$	0
F12	Penalized 1	$\frac{\pi}{d} \Big\{ 10 \sin(\pi y_1) + \sum_{i=1}^{d-1} (y_i - 1)^2 \times \left[1 + 10 \sin^2(\pi y_{i+1}) \right] + (y_d - 1)^2 \Big\} + \sum_{i=1}^{d} u(x_i, 10, 100, 4)$	$[-50, 50]$	0
F13	Penalized 2	$0.1 \Big\{ \sin^2(3\pi x_1) + \sum_{i=1}^{d-1} (x_i - 1)^2 \times \left[1 + \sin^2(3\pi x_{i+1}) \right] + (x_d - 1)^2 \left[1 + \sin^2(2\pi x_d) \right] \Big\} + \sum_{i=1}^{d} u(x_i, 5, 100, 4)$	$[-50, 50]$	0

For both benchmark tables, $\mathbf{x} = (x_1, \ldots, x_d) \in \mathbb{R}^d$ is a candidate point and the displayed range applies coordinatewise. F1–F7 are unimodal; F8–F13 are multimodal. In F12, $y_i = 1 + \frac{x_i + 1}{4}$. In F12–F13, the penalty term is $u(x_i, a, k, m) = k(x_i - a)^m$ if $x_i > a$, $k(-x_i - a)^m$ if $x_i < -a$, and 0 otherwise. F7 is stochastic: its solver reference $f^* = 0$ is the lower support bound of the additive $U[0, 1)$ noise, used when computing normalized gaps. The landscape visualizations instead plot the expected objective, whose noise contribution is 0.5. The reference optimum of F8 is dimension-dependent and is scaled by d when the normalized gap is computed.

Table 3. Fixed-dimension multimodal benchmark functions F14–F23. The dimension is imposed by the definition of each function; the reference optima are the values used by the solver when computing the normalized gap.

Function	Name	Definition	d	Range	f^*
F14	Shekel's Foxholes	$\left(\frac{1}{500}+\sum_{j=1}^{25}\frac{1}{j+\sum_{i=1}^{2}(x_i-a_{ij})^6}\right)^{-1}$	2	$[-65.536, 65.536]$	1
F15	Kowalik	$\sum_{i=1}^{11}\left[a_i-\frac{x_1(b_i^2+b_ix_2)}{b_i^2+b_ix_3+x_4}\right]^2$	4	$[-5,5]$	0.00030
F16	Six-Hump Camel-Back	$4x_1^2-2.1x_1^4+\frac{1}{3}x_1^6+x_1x_2-4x_2^2+4x_2^4$	2	$[-5,5]$	-1.0316
F17	Branin RCOS	$\left(x_2-\frac{5.1}{4\pi^2}x_1^2+\frac{5}{\pi}x_1-6\right)^2+10\left(1-\frac{1}{8\pi}\right)\cos x_1+10$	2	$[-5,5]$	0.398
F18	Goldstein–Price	$[1+(x_1+x_2+1)^2\times(19-14x_1+3x_1^2-14x_2+6x_1x_2+3x_2^2)]\times[30+(2x_1-3x_2)^2\times(18-32x_1+12x_1^2+48x_2-36x_1x_2+27x_2^2)]$	2	$[-2,2]$	3
F19	Hartmann 3-D	$-\sum_{i=1}^{4}c_i\exp\left(-\sum_{j=1}^{3}a_{ij}(x_j-p_{ij})^2\right)$	3	$[0,1]$	-3.86
F20	Hartmann 6-D	$-\sum_{i=1}^{4}c_i\exp\left(-\sum_{j=1}^{6}a_{ij}(x_j-p_{ij})^2\right)$	6	$[0,1]$	-3.32
F21	Shekel-5	$-\sum_{i=1}^{5}\left[\|\mathbf{x}-\mathbf{a}_i\|_2^2+c_i\right]^{-1}$	4	$[0,10]$	-10.1532
F22	Shekel-7	$-\sum_{i=1}^{7}\left[\|\mathbf{x}-\mathbf{a}_i\|_2^2+c_i\right]^{-1}$	4	$[0,10]$	-10.4029
F23	Shekel-10	$-\sum_{i=1}^{10}\left[\|\mathbf{x}-\mathbf{a}_i\|_2^2+c_i\right]^{-1}$	4	$[0,10]$	-10.5364

The fixed coefficients use their classical benchmark values [28]: F14 uses Foxholes centers a_{ij} ($i=1,2$, $j=1,\ldots,25$); F15 uses Kowalik coefficients a_i, b_i ($i=1,\ldots,11$), where the implemented b_i are the reciprocals of $(0.25, 0.5, 1, 2, 4, 6, 8, 10, 12, 14, 16)$; F19–F20 use Hartmann constants a_{ij}, p_{ij}, c_i ($i=1,\ldots,4$, $j=1,\ldots,d$); and F21–F23 use Shekel centers $\mathbf{a}_i \in \mathbb{R}^4$ and scalar offsets c_i ($i=1,\ldots,m$, $m=5,7,10$). The Shekel product $(\mathbf{x}-\mathbf{a}_i)(\mathbf{x}-\mathbf{a}_i)^\top$ is the squared Euclidean distance. Branin (F17) was evaluated over $[-5,5]^2$, rather than the conventional domain $[-5,10]\times[0,15]$; this experimental domain retains one of the three conventional global minimizers. Reference optima are rounded for presentation; normalized gaps use the reference values stored in the experimental configuration, with negative gaps clipped to zero.

Illustrative landscape plots are provided in Appendix D. For functions with $d > 2$, these are two-coordinate slices with remaining coordinates fixed at the bounds midpoint; they provide visual context and are not quantitative landscape characterizations. Function definitions, dimensions, domains, and solver reference optima are reported in Tables 2–3.

4.2. Factorial configuration

The principal factorial design contains four levels of granularity and eight rule patterns, producing $4 \times 8 = 32$ fuzzy configurations, denoted FCS-n-Rk. The output and input partition families are fixed to O1 and I1, respectively; both use uniform triangular partitions with overlap one and shoulders. The single PSO baseline uses a linear inertia schedule from 0.9 to 0.1, as implemented in the solver.

The resulting comparison has 33 algorithmic configurations per benchmark instance: 32 fuzzy configurations and the classical PSO baseline.

Table 4. Summary of the executed factorial design and computational budget.

Design element	Specification
Benchmark	Classical F1–F23 suite; 62 function–dimension instances. F1–F13 use $d \in \{10, 30, 50, 100\}$; F14–F23 use their fixed dimensions (Tables 2 and 3).
Factorial factors	Granularity $n \in \{3, 5, 7, 9\}$ and rule-base pattern $R \in \{R1, \ldots, R8\}$, giving $4 \times 8 = 32$ FCS configurations.
Algorithms	32 FCS configurations plus classical PSO with a linear inertia schedule from 0.9 to 0.1; 33 configurations per instance.
Controller controls	Input/output partitions I1/O1; uniform triangular Ruspini partitions with shoulders; effective inertia range $[0.1, 0.9]$.
Run budget	1000 iterations with population size 20: 20,000 update evaluations plus 20 initial-population evaluations (20,020 total per run).
Replication	31 independently seeded runs per algorithm–instance pair; no seed is reused across configurations.
Completed batch	$62 \times 33 \times 31 = 63{,}426$ runs; all planned records are present.

4.3. Metrics and statistical tests

The primary outcomes are final best fitness and normalized gap; execution time and number of function evaluations are also recorded. The analyses address the five research questions (RQ1–RQ5), not confirmatory hypotheses. All 63,426 planned run records are present; no completed run was excluded.

For RQ1, each instance contributes the median normalized gap over 31 runs for each of the 33 configurations. A Friedman test uses the 62 instances as blocks; Nemenyi post-hoc comparisons use $\alpha = 0.05$ and are summarized by the critical-difference diagram. RQ2 describes transfer across landscape classes and between the scalable and fixed-dimensional subsets using Kendall's τ between configuration rankings; the S_1–S_2 association is reported with its p-value. RQ3 asks descriptively whether observed performance differences among R1–R8 decrease consistently as n increases. For ranks, the existing per-instance Friedman ranks are averaged over dimensions within each function and configuration before computing the sample standard deviation across the eight patterns at each function and n. For normalized gaps, the median over 31 runs is log-transformed as $\log_{10}(\max(\text{gap}_{\text{median}}, 10^{-12}) + 10^{-12})$, averaged over dimensions within each function and configuration, and summarized by the same within-function standard deviation across patterns. We report the median of these function-level spreads across all 23 functions and separately for S_1 (F1–F13) and S_2 (F14–F23), giving each function equal weight. RQ3 therefore evaluates observed dispersion, not a formal factorial interaction. The run-level data are nested within function–dimension instances, and dimensions are nested within functions.

For RQ4, each of the 32 FCS configurations is compared with PSO separately on each instance using a two-sided Mann–Whitney U test on independent samples of 31 final-fitness values per configuration. The asymptotic test uses a continuity correction. Let $X = (x_1, \ldots, x_{31})$ and $Y = (y_1, \ldots, y_{31})$ denote the FCS and PSO samples. Vargha–Delaney A_{12} is estimated as $\left[\#(x_r < y_s) + \frac{1}{2}\#(x_r = y_s)\right]/31^2$; because lower fitness is better, $A_{12} > 0.5$ favours FCS. Bonferroni correction covers all $32 \times 62 = 1984$ configuration–instance tests ($\alpha_{\text{Bonferroni}} = 0.05/1984$). Comparisons with adjusted $p < 0.05$ are classified as wins or losses according to the direction of A_{12}; the remainder are non-significant, not evidence of equivalence.

Table 11 compares the eight predefined rule-pattern pairs at each of four granularities and 62 instances, giving a separate family of $8 \times 4 \times 62 = 1984$ tests. Each contrast uses independent samples and a two-sided asymptotic Mann–Whitney U test with continuity correction. Holm's step-down procedure is applied once across this complete family. The same A_{12} convention identifies the direction of a significant difference; non-significant comparisons are not interpreted as ties or equivalence. RQ5 reports subgroup rank concordance and the best-ranked configuration for S_1 and S_2; Kendall's τ is interpreted descriptively

without treating a fixed cutoff as a confirmatory decision rule. Statistical significance and effect magnitude are discussed separately.

5. Results

All experiments were executed for 31 independent runs per (configuration, instance) pair. Statistical summaries report mean, median, standard deviation, interquartile range, and coefficient of variation of the final best fitness. Normalized gap was computed as $(\text{fitness}_{\text{best}} - \text{optimum})/\max(|\text{optimum}|, 1)$, clipped to zero when the optimum was reached. Configuration rankings were compared with a Friedman omnibus test and Nemenyi post-hoc procedure. Run-level RQ4 and rule-pattern comparisons use two-sided independent-sample Mann–Whitney U tests; multiplicity is controlled separately with Bonferroni and Holm correction, respectively. Effect size is summarized with Vargha–Delaney A_{12}.

5.1. Global ranking of fuzzy-control configurations

Table 5 ranks the top 10 PSO_FCS configurations by mean Friedman rank across all F1–F23 instances and dimensions. The best-performing configuration, `FCS-3-R1` (3 labels, rule pattern R1), achieved a mean rank of 4.77 across the 62 instances, while the classical PSO baseline obtained a mean rank of 6.36 and placed second overall.

Table 5. Top 10 of the 33 configurations by mean Friedman rank over 62 benchmark instances (lower is better).

Configuration	Mean rank
FCS-3-R1	4.774
PSO	6.363
FCS-5-R1	6.968
FCS-7-R1	8.202
FCS-9-R1	8.427
FCS-9-R5	9.016
FCS-3-R5	9.250
FCS-7-R5	10.129
FCS-3-R6	10.694
FCS-5-R5	11.565

Table 6 summarizes RQ1–RQ5 and their principal evidence, findings, and scope. The Results sections report the global Friedman/Nemenyi comparison, class and subset rank transfer, descriptive dispersion across granularity and rule patterns, independent-sample outcomes against PSO, and subset specialists.

The Critical Difference diagram in Figure 5 visualizes the outcome of the Nemenyi post-hoc test. Configurations are sorted by mean rank and the shaded band spans one critical difference from the leader. Nine configurations fall within that band: the four R1 variants, four of the R5 and R6 variants, and the baseline itself. All configurations built on R2, R3, R4, R7, and R8 lie outside it, and the last position is occupied by `FCS-9-R2` with a mean rank of 26.54. The rule-base pattern therefore separates the configurations far more sharply than the number of labels: the four R1 variants span mean ranks 4.77 to 8.43, whereas a single granularity such as $n = 9$ spans 8.43 to 26.54 depending on the rule pattern.

5.2. Function-level performance

The aggregated ranking of Section 5.1 hides where each configuration actually wins. Table 7 therefore reports, for every benchmark function, the fuzzy configuration that wins the largest number of its instances, the per-instance rank of that configuration and of the baseline, and the Bonferroni-significant outcomes for the selected configuration. Ranks are computed within each instance over the 33 algorithmic configurations using the median




Figure 5. Critical-difference diagram of 33 configurations over 62 instances (Friedman/Nemenyi, $\alpha = 0.05$). Lower mean rank is better; shading marks configurations within CD = 6.59 of the leader. PSO is bold.

Table 6. Research questions RQ1–RQ5, principal evidence, observed findings, and scope. RQ3 is descriptive; non-significance is not interpreted as equivalence or independence.

Research question	Main evidence	Observed finding	Interpretation and scope
RQ1. Does higher granularity improve configuration ranks?	Friedman $p = 1.56 \times 10^{-200}$; Nemenyi CD = 6.59. Best mean rank at $n = 3/5/7/9$: 4.77/6.97/8.20/8.43.	Configuration ranks differ overall; the best mean rank worsens as n increases. FCS-3-R1 and PSO share a Nemenyi group.	The omnibus test compares complete configurations and does not isolate an independent granularity effect.
RQ2. How do rankings vary across classes and dimensional regimes?	Class-level Kendall τ: 0.867 (unimodal/scalable), 0.083 (unimodal/fixed), and 0.080 (scalable/fixed).	Concordance is high between the two scalable classes and weak between either and the fixed-dimensional group.	These comparisons describe the evaluated benchmark groups; they do not establish causal class effects or general transferability.
RQ3. Does granularity consistently reduce differences among rule patterns?	Function-level median SD across R1–R8 at $n = 3/5/7/9$: ranks 8.884/8.366/8.715/9.374; log-gap 0.912/1.170/1.173/0.901.	Neither dispersion measure decreases consistently with granularity.	Descriptive evidence only; no factorial interaction test is reported.
RQ4. How does each fixed FCS configuration compare with PSO?	FCS-3-R1: 30/30/2 nominal wins/non-significant/losses; 16/46/0 after Bonferroni correction over 1,984 tests.	Across all configurations, 22 wins, 906 non-significant comparisons, and 1,056 losses remain after correction.	Non-significance does not establish equivalence. Choosing the best FCS separately for each instance is an oracle comparison.
RQ5. Do the best-ranked configurations transfer between S_1 and S_2?	$\tau(S_1, S_2) = 0.095$, $p = 0.451$; mean-gap leaders: S_1 FCS-3-R5, S_2 FCS-5-R6.	The subset leaders differ and observed rank concordance is weak.	The non-significant association is not evidence of independence and applies only to this evaluated split.

normalized gap, so rank 1 denotes the best configuration on that instance. Configurations are named `FCS-`n`-R`k, where n is the number of linguistic labels and k the rule-base pattern; the input and output partition families are I1 and O1 for every configuration and are therefore omitted from the label.

Three observations follow from the disaggregated view. First, the best fuzzy configuration outranks the baseline on 50 of the 62 instances. Of these rank wins, 32 have nominal independent-sample $p < 0.05$ and 17 remain significant after Bonferroni correction across the RQ4 family. The baseline ranks ahead on 6 instances, and the best FCS and PSO share the minimum rank on the remaining 6. Second, the winning configuration is not unique: 15 distinct FCS configurations record at least one rank-based win over PSO. `FCS-3-R1` accounts for 30 of the 50 wins, including 28 of the 46 wins in the scalable subset S_1; the other wins span all four granularities and six additional rule patterns. The function-level table identifies the best fuzzy candidate even when it does not outrank PSO. Third, the effect size is heterogeneous: the median A_{12} reaches 0.95–0.98 on F1, F2, and F6, but remains near 0.54 on F7 and F8 and on most fixed-dimensional functions.

The fixed-dimensional subset behaves differently from the scalable one. On F16 and F17, normalized gap is zero in all 31 runs for all 33 configurations. On F19, 990 of 1023 run-level gaps are zero; although 33 runs have a nonzero gap, every configuration has a zero median gap. The 33 configurations therefore share mean rank 17 on these functions, and no unique median-gap winner is identified. For F16, the independent-sample test on raw final fitness is nominally significant ($p = 0.0419$), but its Bonferroni-adjusted p is 1.000; $A_{12} = 0.56$ and all normalized gaps are zero, so the test does not establish a normalized-gap advantage. On F14, F15, F21, and F22 the baseline falls to ranks 11–27 while a fuzzy configuration takes the first position. On F23, the ordering reverses: PSO takes the first position and the best fuzzy configuration, `FCS-5-R6`, ranks second with $A_{12} = 0.34$, favouring PSO. The independent-sample $p = 0.0234$ is nominally significant but does not survive Bonferroni correction. This subset therefore includes both large rank

Table 7. Function-level summary of the FCS configuration with the most per-instance rank wins, its ranks, Bonferroni-significant outcomes, effect size, and unpaired runtime overhead.

Function	Landscape	Dimensions	Best FCS	PSO rank	FCS rank	Rank wins	Bonferroni wins	A_{12}	Overhead (%)
F1	Unimodal	10, 30, 50, 100	`FCS-3-R1`	3.0	1.0	4/4	3/4	0.96	31.8
F2	Unimodal	10, 30, 50, 100	`FCS-3-R1`	2.0	1.0	4/4	4/4	0.98	34.1
F3	Unimodal	10, 30, 50, 100	`FCS-5-R5`	11.0	1.0	4/4	1/4	0.74	14.6
F4	Unimodal	10, 30, 50, 100	`FCS-9-R5`	4.0	1.0	3/4	1/4	0.56	26.2
F5	Unimodal	10, 30, 50, 100	`FCS-3-R1`	3.0	1.0	4/4	0/4	0.64	29.6
F6	Unimodal	10, 30, 50, 100	`FCS-3-R1`	2.0	1.0	4/4	4/4	0.95	33.9
F7	Unimodal	10, 30, 50, 100	`FCS-5-R1`	3.0	1.0	3/4	0/4	0.54	28.7
F8	Scalable multimodal	10, 30, 50, 100	`FCS-9-R8`	3.5	1.5	2/4	0/4	0.54	27.1
F9	Scalable multimodal	10, 30, 50, 100	`FCS-5-R2`	9.0	1.0	4/4	0/4	0.60	25.4
F10	Scalable multimodal	10, 30, 50, 100	`FCS-3-R1`	3.5	1.0	3/4	1/4	0.77	26.9
F11	Scalable multimodal	10, 30, 50, 100	`FCS-3-R1`	4.0	1.0	4/4	2/4	0.75	30.7
F12	Scalable multimodal	10, 30, 50, 100	`FCS-3-R1`	2.0	1.0	3/4	0/4	0.72	25.4
F13	Scalable multimodal	10, 30, 50, 100	`FCS-3-R1`	3.0	1.0	4/4	0/4	0.74	28.7
F14	Fixed-dimensional	2	`FCS-3-R1`	27.0	3.0	1/1	0/1	0.58	-5.0
F15	Fixed-dimensional	4	`FCS-3-R1`	11.0	1.0	1/1	0/1	0.75	86.9
F16	Fixed-dimensional	2	–	17.0	17.0	0/1	0/1	0.56	–
F17	Fixed-dimensional	2	–	17.0	17.0	0/1	0/1	0.50	–
F18	Fixed-dimensional	2	`FCS-3-R1`	15.0	15.0	0/1	0/1	0.45	161.5
F19	Fixed-dimensional	3	–	17.0	17.0	0/1	0/1	0.56	–
F20	Fixed-dimensional	6	`FCS-3-R1`	14.0	14.0	0/1	0/1	0.55	53.2
F21	Fixed-dimensional	4	`FCS-7-R1`	24.0	1.0	1/1	0/1	0.61	17.8
F22	Fixed-dimensional	4	`FCS-3-R6`	20.0	1.0	1/1	0/1	0.57	14.6
F23	Fixed-dimensional	4	`FCS-5-R6`	1.0	2.0	0/1	0/1	0.34	8.2

Ranks are medians of per-instance ranks on median normalized gap (lower is better). Rank wins count instances where the selected FCS has a lower rank than PSO. Bonferroni wins use independent-sample Mann–Whitney tests adjusted over all 1,984 RQ4 comparisons. A_{12} is the median effect size; $A_{12} > 0.5$ favours FCS. Overhead is $100(\text{median}(t_{\text{FCS}})/\text{median}(t_{\text{PSO}}) - 1)$ using independent run samples. A dash marks functions where all FCS configurations share the best median-gap rank.

differences favouring fuzzy control and a function on which PSO ranks first; it does not support a universally dominant configuration.

Figure A1 in Appendix A shows the complete rank matrix: columns are ordered by mean rank, PSO is bracketed, and the S1/S2 boundary is marked. It shows predominantly better FCS ranks across the scalable subset and more varied outcomes across fixed-dimensional instances, complementing Table 7.

5.3. Problem-class dependence

The performance ranking depends strongly on the rule-base pattern (R1 through R8) and weakly on linguistic granularity ($n \in \{3,5,7,9\}$). Figure 6 presents, for each configuration and landscape class, the mean across instances of the instance-level median normalized gap (smaller is better). The classes are unimodal functions (F1–F7), scalable multimodal functions (F8–F13), and fixed-dimensional multimodal functions (F14–F23); each configuration appears once as a row.




Figure 6. Mean instance-level median normalized gap for the 32 FCS configurations by landscape class. Colour shows $\log_{10}$ mean gap with a 10^{-12} display floor; lower values indicate better performance.

Two complementary partitions of the benchmark are used. For landscape effects, functions are grouped as unimodal (F1–F7), scalable multimodal (F8–F13), and fixed-dimensional multimodal (F14–F23). For the transferability analysis, the benchmark is

split into the scalable subset S_1 (F1–F13, evaluated at four dimensions each) and the fixed-dimensional subset S_2 (F14–F23); this split is by dimensional regime, not by modality.

Table 8 summarizes the class-level rankings. The leading configuration differs across the evaluated groups: `FCS-3-R5` leads on unimodal functions, `FCS-3-R1` on scalable multimodal functions, and `FCS-5-R6` on fixed-dimensional functions. `FCS-3-R1` remains relatively competitive, ranking 2nd, 1st, and 3rd, respectively. These descriptive results do not isolate causal effects of modality or dimensionality, nor establish a universally optimal configuration for any group.

Table 8. Positions of the 33 configurations by mean instance-level median normalized gap within each benchmark group (lower is better). For each configuration–instance pair, the median normalized gap over 31 runs was first computed; these medians were then averaged within the group. Positions use minimum ranks for ties and are not Friedman mean ranks.

Benchmark group	Functions	Instances	Leading configuration	PSO position	FCS-3-R1 position
Unimodal (F1–F7)	7	28	FCS-3-R5	8/33	2/33
Scalable multimodal (F8–F13)	6	24	FCS-3-R1	2/33	1/33
Fixed-dimensional (F14–F23)	10	10	FCS-5-R6	25/33	3/33

As a descriptive sensitivity check, configurations were also ranked by median normalized gap within each instance and these ranks were averaged by benchmark group. Under mean within-instance ranks, FCS-3-R1 leads the unimodal group (with PSO 2nd and FCS-3-R1 1st), remains the scalable multimodal leader (PSO 2nd and FCS-3-R1 1st), and FCS-5-R6 remains the fixed-dimensional leader (PSO 17th and FCS-3-R1 2nd). The unimodal leader therefore changes from FCS-3-R5 under mean instance-level median gap to FCS-3-R1 under mean within-instance rank. The gap mean preserves magnitude differences among instances, whereas the rank mean summarizes relative ordering with equal instance weight; neither aggregation is universally superior.

Table 9 reports Kendall τ between the configuration rankings induced by each pair of landscape classes. The two scalable classes show strong observed rank concordance ($\tau = 0.867$ between unimodal and scalable multimodal); the fixed-dimensional class shows weak observed concordance with them ($\tau = 0.080$ and $\tau = 0.083$). These coefficients describe the evaluated classes and do not establish independence or a general transferability result.

Table 9. Kendall's τ between configuration rankings induced by each landscape class. The two scalable classes show strong observed concordance; concordance with the fixed-dimensional class is weak.

Class	Unimodal	Scalable multimodal	Fixed-dimensional
Unimodal	1.000	0.867	0.083
Scalable multimodal	0.867	1.000	0.080
Fixed-dimensional	0.083	0.080	1.000

Rank concordance between S_1 and S_2 is weak ($\tau = 0.095$, $p = 0.451$); this non-significant result does not establish independence. `FCS-3-R5` has the lowest mean normalized gap on S_1 and ranks 11th on S_2, whereas `FCS-5-R6` leads on S_2 and ranks 13th on S_1. These rankings describe only the evaluated subsets.

Figure 7 plots the rank matrix in the (S_1, S_2) space and highlights the non-dominated frontier. No configuration occupies the lower-left corner: the frontier is formed by the two subset specialists and by `FCS-3-R1`, which ranks 2nd on S_1 and 3rd on S_2 and is the closest

available compromise. This dispersion is the aggregated counterpart of the per-instance heterogeneity reported in Section 5.2.




Figure 7. Configuration ranks on S1 versus S2, computed from per-instance median normalized gap; better ranks lie toward the upper right. The red line marks the non-dominated frontier and the star denotes PSO.

5.4. Effect of rule-base structure

Sections 5.1–5.3 establish that rule-table patterns separate the configurations more sharply than the number of labels, but do not by themselves attribute this ranking to independent input effects. As defined in Section 3.3, R1–R8 combine two nominal consequent axes: progress direction (decreasing, neutral, or increasing) and diversity reaction (following, neutral, or compensating). Table 10 places the patterns on those axes with their mean Friedman rank across the four granularities. A neutral consequent axis does not guarantee that the corresponding input is absent from the effective Mamdani surface.

Table 10. Mean Friedman ranks by nominal progress direction and diversity consequent, averaged over four granularities. A neutral consequent does not remove an antecedent from Mamdani inference.

	Diversity-following	**Diversity-neutral**	**Diversity-compensating**
Progress decreasing	R5 (10.0)	R1 (7.1)	R6 (12.1)
Progress neutral	R3 (21.9)	–	R4 (22.0)
Progress increasing	R7 (24.1)	R2 (24.3)	R8 (17.2)

The grid is ordered almost entirely by rows. The three patterns with a decreasing progress effect occupy the best mean ranks (R1 = 7.1, R5 = 10.0, R6 = 12.1), the two progress-neutral patterns sit in the lower half (R3 = 21.9, R4 = 22.0), and two of the three patterns with an increasing progress effect close the ranking (R7 = 24.1, R2 = 24.3). Column position accounts for a much smaller spread: within the decreasing row the three patterns differ by 5.0 ranks, whereas the difference between the best and the worst row exceeds 17 ranks.

To compare rule-pattern contrasts, the 31 run-level outcomes for each pattern are treated as independent samples at equal granularity and on the same instance. The two-sided Mann–Whitney tests are adjusted with Holm's procedure across all 1,984 contrasts. Mirror pairs invert every non-neutral consequent axis and, by Proposition 1, reflect the control surface about the midpoint of $[w_{\min}, w_{\max}]$. Single-axis pairs change one nominal consequent axis while holding the other fixed. These are descriptive comparisons of rule tables; they do not imply orthogonal effective-input effects under min–max inference. Table 11 reports both pair families.

Table 11. Independent-sample comparisons of rule-pattern pairs at equal granularity and instance (248 tests per pair). Holm adjustment is applied once across the complete family of 1,984 comparisons.

Pair	Axis changed	Nominal W/NS/L	Holm W/NS/L	Dominant	A_{12}	Strongest in
Mirror pairs						
R1 vs R2	progress direction	192/56/0	175/73/0	**R1**	0.99	Unimodal
R3 vs R4	diversity reaction	118/59/71	104/98/46	**R4**	0.41	Scalable multimodal
R5 vs R8	progress direction + diversity reaction	173/73/2	142/106/0	**R5**	0.91	Unimodal
R6 vs R7	progress direction + diversity reaction	173/57/18	152/91/5	**R6**	0.95	Scalable multimodal
Single-axis pairs						
R5 vs R7	progress direction	172/75/1	152/96/0	**R5**	0.96	Scalable multimodal
R6 vs R8	progress direction	176/65/7	156/92/0	**R6**	0.92	Unimodal
R5 vs R6	diversity reaction	132/81/35	99/130/19	**R5**	0.66	Unimodal
R7 vs R8	diversity reaction	154/68/26	137/98/13	**R8**	0.09	Scalable multimodal

W/NS/L denotes significant wins for the dominant pattern, non-significant comparisons, and significant losses. Nominal counts use $p < 0.05$; Holm counts use adjusted $p < 0.05$ across all 1,984 tests. A_{12} is the median effect for the first pattern; values above 0.5 favour it. These contrasts compare implemented rule tables and do not isolate causal input effects.

After Holm correction across the full Table 11 family, the decreasing-progress pattern has more significant wins than losses in each matched contrast with its increasing-progress counterpart: R1 over R2, 175/73/0 (wins/non-significant/losses); R5 over R7, 152/96/0; and R6 over R8, 156/92/0. Their median A_{12} values are 0.99, 0.96, and 0.92, respectively. These are empirical differences among the tested rule tables, not evidence that the effective controller responds only to progress.

Among patterns with different diversity consequents, the Holm-adjusted independent-sample comparisons also vary with the nominal progress direction. For decreasing progress, R5 has 99 significant wins and 19 losses against R6, with 130 non-significant comparisons ($A_{12} = 0.66$). For increasing progress, R8 has 137 wins and 13 losses against R7, with 98 non-significant comparisons ($A_{12} = 0.09$ in favour of R8). For the nominally progress-neutral pattern, R4 has 104 wins and 46 losses against R3, with 98 non-significant comparisons; their aggregate mean ranks remain close (22.0 and 21.9). These comparisons describe the tested rule tables and do not establish a general benefit of diversity feedback.

Both effects are also visible in the mirror pairs, which reverse the pattern as a whole. R1 dominates R2 and R5 dominates R8 most clearly on the unimodal class, whereas R6 dominates R7 most clearly on the scalable multimodal class, which is consistent with the landscape dependence reported in Section 5.3.

These results explain the composition of the leading group of Section 5.1. Every configuration inside the critical-difference band uses a decreasing-progress consequent pattern: the four R1 variants, three R5 variants, and one R6 variant. No pattern with a nominally neutral or increasing progress consequent enters the band, and R2, R3, R4, R7, and R8 remain outside it at every granularity. The single exception to the row ordering, R8 at rank 17.2 ahead of the nominally progress-neutral R3 and R4, combines an increasing-progress consequent with the compensating diversity consequent favoured by the Holm-adjusted R7–R8 contrast. Overall, rankings align most strongly with nominal progress-consequent direction, while independent-sample differences across diversity-consequent

patterns depend on that direction. Since a neutral consequent axis does not remove the input from min–max firing, these comparisons are not independent causal effects of the two inputs.

5.5. Effect of linguistic granularity

Granularity cannot be read in isolation from the rule-base pattern, because n fixes the resolution at which a pattern is expressed and simultaneously raises the number of consequents from $n^2 = 9$ at $n = 3$ to $n^2 = 81$ at $n = 9$. Table 12 therefore reports the mean Friedman rank of every pattern at each granularity, together with the granularity that minimizes it and the spread between its best and worst rank.

Table 12. Mean Friedman rank of each rule-base pattern at each granularity (lower is better). Spread is the maximum minus minimum across n; the 2.5-rank stability threshold is descriptive, not an equivalence test.

Pattern	Progress	$n = 3$	$n = 5$	$n = 7$	$n = 9$	Best n	Spread	Trend
R1	dec.	4.8	7.0	8.2	8.4	3	3.7	degradation
R2	incr.	21.2	25.0	24.3	26.5	3	5.3	degrad. (non-monot.)
R3	neutral	20.1	22.0	22.4	23.1	3	2.9	degradation
R4	neutral	20.0	20.8	23.0	24.5	3	4.5	degradation
R5	dec.	9.2	11.6	10.1	9.0	9	2.5	non-monotonic
R6	dec.	10.7	13.1	12.9	11.7	3	2.4	stable
R7	incr.	23.9	23.2	24.9	24.3	5	1.6	stable
R8	incr.	16.0	18.2	18.1	16.2	3	2.2	stable

Six of the eight patterns attain their best rank at $n = 3$; the exceptions are R5, which is marginally better at $n = 9$ (9.02 against 9.25), and R7, which is marginally better at $n = 5$ within a spread of 1.6 ranks. The response to n is pattern-dependent. R1's mean rank worsens monotonically from 4.77 at $n = 3$ to 8.43 at $n = 9$, an increase of 3.65 positions, but this is not the largest change across patterns: R2 increases by 5.33 positions (spread 5.3) and R4 by 4.53 (spread 4.5). Here, spread is the maximum minus minimum mean rank over the four granularities. R6, R7, and R8 show comparatively small observed spreads of 2.4, 1.6, and 2.2 positions, respectively. The table's 2.5-rank stability threshold is descriptive; it does not establish equivalence or absence of a granularity effect.

The aggregate view agrees. Averaged over the eight patterns, the mean rank worsens from 15.74 at $n = 3$ to 17.62 at $n = 5$ and then remains near 17.99 and 17.97 for $n = 7$ and $n = 9$; the best rank achievable at each granularity degrades monotonically from 4.77 to 6.97, 8.20, and 8.43. The distribution of the normalized gap, shown in Figure 8, follows the same shape: the median of $\log_{10}$ gap rises from 0.02 at $n = 3$ to 0.22 at $n = 5$ and then settles at 0.21 and 0.19, while the interquartile range contracts from 3.50 to 3.19 and remains at 3.24 and 3.27. The observed gap worsens from three to five labels and then changes little through $n = 9$.

Figure 9 descriptively traces each pattern across granularities. The three curves of the progress-decreasing family never cross those of the other two families: R1, R5, and R6 occupy the first three positions at $n = 3, 5, 7$, and 9. Kendall τ between the orderings of the eight patterns at different granularities ranges from 0.79 to 0.93, the minimum occurring between the most distant pair, $n = 3$ and $n = 9$. Granularity shifts the patterns vertically without reordering their leading family; the only exchanges of position occur inside the group outside the critical-difference band, where R2, R3, R4, and R7 swap places. These global profiles describe relative ranks and are distinct from performance-gap dispersion or a formal interaction.

In the benchmark-wide summary, the standard deviation across the eight mean Friedman ranks is 6.778, 6.397, 6.707, and 7.524 for $n = 3, 5, 7, 9$. The standard deviation across the eight pooled median normalized gaps is 3.994, 4.460, 4.470, and 4.635; these gap medians pool 1,922 run-level observations per pattern and granularity. The median of the




Figure 8. Boxplots of run-level final normalized gap, transformed as $\log_{10}(\max(\text{gap}, 10^{-12}) + 10^{-12})$ and pooled over 62 instances and eight FCS patterns at each granularity. Outliers are omitted.




Figure 9. Benchmark-wide summaries over 62 instances. Left: mean Friedman rank by pattern and granularity (lower ranks appear upward); colour and line style identify nominal progress-consequent direction. Right: standard deviation across the eight pattern-specific mean ranks.

function-level rank spreads across the 23 functions is 8.884, 8.366, 8.715, and 9.374; the corresponding log-gap spreads are 0.912, 1.170, 1.173, and 0.901. For ranks, the S_1 medians are 8.884, 8.789, 9.128, and 10.194, while the S_2 medians are 7.255, 6.556, 6.834, and 5.456. For log-gaps, the S_1 medians are 1.359, 1.468, 1.374, and 1.396, and the S_2 medians are 0.075, 0.308, 0.263, and 0.070. From $n = 3$ to $n = 9$, rank spread is lower in $6/23$ functions and log-gap spread in $11/23$; each measure is non-increasing across all four granularities in $3/23$ functions. The observed dispersion therefore does not decrease consistently with granularity; these summaries are not evidence of equivalence or a formal interaction.

5.6. Robustness, dimensional scaling, and computational overhead

Section 5.2 measured the best fuzzy configuration available on each instance, which is an oracle selection: the winner is allowed to change from one instance to the next. The complementary and stricter question is whether a *single fixed* configuration, chosen once and applied everywhere, beats the baseline across the benchmark. Table 13 reports the ten configurations with the largest number of Bonferroni-significant wins, ordered by corrected wins, nominal wins, and then mean A_{12}. Each configuration is compared with PSO on all 62 instances using independent samples and a two-sided Mann–Whitney U test. Because the objective is minimized, the Vargha–Delaney effect size is defined so that $A_{12} > 0.5$ favours the fuzzy configuration and $A_{12} < 0.5$ favours the baseline.

Table 13. Ten configurations with the most Bonferroni-significant wins against PSO, based on independent-sample Mann–Whitney tests over 62 instances.

Configuration	Nominal W/NS/L	Bonferroni W/NS/L	A_{12} mean	n
FCS-3-R1	30/30/2	16/46/0	0.669	3
FCS-9-R5	6/30/26	2/44/16	0.383	9
FCS-5-R5	5/24/33	2/36/24	0.304	5
FCS-7-R5	5/28/29	1/43/18	0.363	7
FCS-9-R7	1/13/48	1/22/39	0.176	9
FCS-3-R5	4/28/30	0/48/14	0.358	3
FCS-5-R7	2/15/45	0/24/38	0.177	5
FCS-7-R7	2/13/47	0/22/40	0.173	7
FCS-5-R1	1/54/7	0/62/0	0.463	5
FCS-3-R2	1/15/46	0/23/39	0.183	3

W/NS/L denotes FCS wins, non-significant comparisons, and FCS losses. Bonferroni adjustment covers all $32 \times 62 = 1,984$ tests ($\alpha = 2.52 \times 10^{-5}$). Non-significance does not establish equivalence. Lower fitness favours FCS when $A_{12} > 0.5$.

The leading fixed configuration, `FCS-3-R1`, records nominal W/NS/L = 30/30/2 and mean $A_{12} = 0.67$; Bonferroni adjustment leaves 16/46/0. The other R1 granularities have 62 non-significant results each after correction, despite nominal non-significant counts of 54, 56, and 53. This is not an equivalence result. Several R5 and R7 variants have more adjusted losses than wins, with mean A_{12} favouring PSO. The 50/62 instance-specific rank wins remain an oracle summary, not a deployable policy.

Figure A2 shows nominal outcomes; Table 13 gives Bonferroni-adjusted counts.

Table 13 summarizes corrected outcomes and effect sizes. The four-instance dispersion map uses lower-left for lower mean gap and variability; FCS performs favourably on F1 and F14, whereas PSO has lower mean gap on F23.

Dimensional robustness was assessed on the scalable subset S_1 (F1–F13) at dimensions 10, 30, 50, and 100. For each configuration and function, the median normalized gap at dimension d was transformed as $y = \log_{10}(\max(\text{gap}_{\text{median}}, 10^{-12}) + 10^{-12})$, and the log–log slope b in $y = a + b \log_{10}(d)$ was averaged over the thirteen functions. Table 14 lists the five configurations with the gentlest and the five with the steepest slopes.

The four R4 variants occupy the five gentlest slopes, with mean values between 2.24 and 2.56 and R^2 above 0.97, while the steepest slopes belong to the R1 and R5 variants, with mean values near 8.3–8.8 and median values above 12.1. A gentle slope, however, is not evidence of better behaviour at large dimension, because the fit measures relative degradation from each configuration's own starting point. `FCS-5-R4` begins at a median gap of 6.7×10^{-1} at $d = 10$, twelve orders of magnitude above the 4.5×10^{-13} of `FCS-3-R1`, and it remains worse at $d = 100$ (2.8×10^{1} against 7.3). Its flat slope reflects a configuration that is already poor at low dimension and therefore has little room left to degrade. Slope should accordingly be read as a descriptor of the degradation profile, not as a criterion for selecting a configuration for large-scale problems.

Table 14. Log-log slope of the median normalized gap against dimension over the scalable subset S1 (F1-F13). The table lists the five configurations with the lowest and highest median fitted slopes; a lower slope describes less relative degradation but does not necessarily indicate better absolute performance.

Status	Config.	n	R	Mean slope	Median slope	Mean R^2
lowest-median-slope	FCS-5-R4	5	R4	2.390	2.328	0.977
lowest-median-slope	FCS-9-R4	9	R4	2.238	2.385	0.985
lowest-median-slope	FCS-3-R4	3	R4	2.565	2.432	0.977
lowest-median-slope	FCS-7-R4	7	R4	2.348	2.435	0.982
lowest-median-slope	FCS-9-R7	9	R7	3.237	2.590	0.867
highest-median-slope	FCS-5-R1	5	R1	8.321	12.447	0.894
highest-median-slope	FCS-7-R5	7	R5	8.738	12.488	0.865
highest-median-slope	FCS-5-R5	5	R5	8.815	12.511	0.853
highest-median-slope	FCS-3-R5	3	R5	8.527	12.651	0.881
highest-median-slope	FCS-9-R5	9	R5	8.789	12.723	0.873

Figure 10 makes the distinction explicit. It does not show the configurations of Table 14, but the five entries with the best mean rank, namely `FCS-3-R1`, the baseline, and the R1 variants at $n = 5, 7$, and 9. Their curves are almost superimposed, with `FCS-3-R1` separating at $d = 10$ and $d = 50$ and converging with the rest at $d = 100$. Within the group of best-ranked configurations, therefore, dimensional behaviour is essentially indistinguishable, and the differences reported in Table 14 arise between the leading and the trailing rule families rather than inside the leading one.




Figure 10. Median normalized gap versus dimension for the five highest mean-rank configurations on S1, including PSO. Both axes are logarithmic.

Runtime overhead is estimated as the ratio of independent sample medians for each configuration–instance group, without matching run identifiers. Across the 1,984 FCS–PSO group ratios, median overhead is 27.75% (interquartile range: 19.81–50.94%); the 32 configuration-level median ratios range from 25.79% to 30.90%. Function-level values in Table 7 refer to the selected best-ranked FCS for that function; the large relative values on some inexpensive fixed-dimensional functions should not be interpreted as hardware-

independent computational complexity. All execution times were measured in the same six-worker experiment environment.

5.7. Dynamic behavior of the controller

The preceding subsections characterize what each configuration achieves; this one characterizes what it does while achieving it. Every run logs inertia weight and exploration percentage at each iteration. Exploration percentage (XPL) is $100 D_t / D_t^{\max}$, rounded to two decimals; the controller input is the corresponding normalized ratio d_t. Figure 11 shows mean inertia weight and XPL over instances and runs. The XPL series is aligned to the pre-update swarm state used to compute each w_t.

The R1 mean trajectories decline over the run, but they are not the classical linear schedule. The baseline has mean inertia 0.500000 over iterations 0–1000; the existing run summaries give 0.499481, 0.499555, 0.499566, and 0.499835 for FCS-n-R1 at $n = 3, 5, 7, 9$, respectively. Despite these close overall means, the maximum absolute difference between each R1 mean trajectory and the observed PSO mean trajectory is 0.13480, 0.04194, 0.03315, and 0.02731, respectively. A direct 21-by-21 (d, p) grid evaluation with the implemented controller ($n_{\text{grid}} = 501$) found maximum fixed-progress variation across diversity of 0.05325, 0.01160, 0.00973, and 0.00416 for those granularities. A convergence check on an 11-by-11 grid found that increasing the defuzzification grid from 501 to 1001 changed w by less than 10^{-5}; the observed diversity effects are therefore not numerical integration noise. R1 has diversity-invariant consequents but a weakly diversity-dependent, nonlinear effective schedule. Its leading rank does not establish a benefit of diversity feedback or equivalence to linear PSO. R2, its mirror, inverts the trajectory, while R5 and R6 produce other decreasing schedules and R7 and R8 increase inertia.

The aggregate profiles show a descriptive association between the early-to-late drop in w and mean Friedman rank across the eight patterns (Spearman $\rho = -0.786$, $p = 0.021$): patterns with larger declines tend to have better ranks. The end-of-run exploration percentage alone is not associated with rank ($\rho = 0.21$, $p = 0.61$). R4 and R8, the two patterns that retain the most exploration in the final hundred iterations (5.2% and 3.6%, respectively, versus roughly 0.6% for R1, R3, R5, and R7), also do not converge. These summaries do not identify a causal mechanism; in particular, a nominally neutral consequent axis does not guarantee input independence under min–max inference.

Figure 12 traces this into the convergence profile on four representative instances. On the unimodal F1 at $d = 30$, `FCS-3-R1` remains below the baseline throughout and ends three orders of magnitude lower (1.7×10^{-9} against 7.7×10^{-6}), while `FCS-9-R2` stalls at 1.1×10^{3} within the first two hundred iterations and never recovers: its weight is still rising when the budget ends. The same contrast appears on F14, where `FCS-3-R1` settles at a median of 1.99 against 3.97 for the baseline.




Figure 11. Mean inertia weight w_t (top) and normalized diversity XPL (bottom) by pattern and granularity, averaged over 62 instances and 31 runs. XPL is aligned to the pre-update state used for w_t. Colour and line style denote progress-consequent direction; PSO is shown as a linear-schedule reference.




Figure 12. Median best fitness by iteration with interquartile bands over 31 runs for four representative instances. Panels compare PSO, `FCS-3-R1`, the function's best FCS when different, and `FCS-9-R2`; the vertical axis is symmetric-logarithmic.

These trajectories connect the leading ranks to the decreasing-progress consequent family, but do not show that R1 reproduces linear PSO or that its policy is driven solely by iteration progress. Its mean trajectory is nonlinear, and the effective R1 surface varies with diversity through the antecedent firing strengths. The results therefore concern the implemented Mamdani controllers, not an isolated comparison of time-only scheduling against diversity-state feedback.

The mechanism, however, does not imply universal dominance, for two reasons that the same figure makes explicit. On the scalable multimodal F9 at $d = 30$, the configuration that wins most instances of that function, `FCS-5-R2`, descends faster than every alternative during the first two hundred iterations and reaches a median of 38.5, but it then stops improving entirely and finishes behind the baseline, which continues from 87.9 at iteration 200 down to 35.8. An aggressive early transition pays on functions where the budget is the binding constraint and costs on functions where it is not. On F23 the ordering reverses altogether: the baseline and `FCS-5-R6` both reach the optimum at -10.54, while `FCS-3-R1` stalls at -3.84, the same value as the last configuration of the study. A trajectory that is optimal on average is therefore not optimal everywhere, which is the dynamic counterpart of the per-instance heterogeneity of Section 5.2: the 15 configurations that win at least one instance correspond to different ways of scheduling the transition, and none of them fits every landscape.

6. Discussion

6.1. Rule-Base Structure and Linguistic Granularity

Within the evaluated configurations, patterns with decreasing-progress consequent maps occupy the leading ranks, whereas no progress-neutral or progress-increasing pattern enters the critical-difference group. The Holm-adjusted independent-sample comparisons retain the same dominant direction in the matched contrasts that hold nominal diversity-consequent patterns fixed. This is an association with the encoded rule tables, not evidence

that the effective inertia policy is independent of diversity or that progress direction alone causes the ranking.

Increasing granularity from $n = 3$ to $n = 9$ raises the size of a complete two-input rule table from 9 to 81 rules. The finer partition offers more representational distinctions, but those distinctions do not guarantee a better optimization response: the observed rankings and dispersion do not improve consistently with n. This separates representational capacity from demonstrated optimization utility. It is consistent with the broader concern for complexity and granularity in interpretable fuzzy modeling [5,6], although this experiment measures optimization outcomes, not interpretability scores.

FCS-3-R1 has the best overall mean rank among the evaluated configurations, but its interpretation requires care. Its rule table assigns the same consequent across diversity labels at each progress level; under the implemented min–max Mamdani inference, however, diversity still changes rule firing strengths and therefore the effective output. Its near-0.5 mean inertia is not evidence of a trajectory identical to the 0.9-to-0.1 linear PSO schedule, nor does its ranking isolate a benefit of diversity feedback. The result is specific to this implementation and benchmark; it neither establishes that diversity feedback improves PSO nor shows that diversity feedback is unnecessary in general.

Proposition 1 establishes that designated mirror patterns induce control surfaces complementary about the midpoint of the inertia interval under the stated partition and inference conditions. The Holm-adjusted independent-sample comparisons nevertheless show performance differences between mirror patterns. This contrast shows that symmetry of the controller mapping does not imply equivalent search trajectories or performance: the reflected inertia responses interact with the evolving stochastic swarm. For fuzzy-controller design in bio-inspired optimization, the proposition and empirical comparisons address complementary questions: which relations hold between control surfaces, and how the controlled swarm performs. This supports assessing linguistic granularity and rule-base structure through both mathematical properties and benchmark behavior within the evaluated PSO architecture.

6.2. Landscape dependence of the best configuration

The preferred configuration differs between the evaluated benchmark subsets. The scalable classes show strong observed rank concordance, while the fixed-dimensional class has weak observed concordance with them. Between S_1 and S_2, observed concordance is weak ($\tau = 0.095$, $p = 0.451$); the applied test provides insufficient evidence of a positive association but does not establish independence. The leading configurations also differ within these subsets: FCS-3-R5 leads on S_1, whereas FCS-5-R6 leads on S_2. These findings describe the evaluated benchmark and do not establish or rule out transferability to other problems. The subset specialists both use decreasing-progress consequents but differ in their nominal diversity consequent. At the instance level, the best-performing fuzzy configuration outranks PSO on 50 of 62 cases; 32 of these comparisons are nominally significant and 17 remain significant after Bonferroni correction. Across the 62 instance-specific selections, 34 comparisons are nominally significant. F23 favours PSO in effect size ($A_{12} = 0.34$), although its nominal independent-sample $p = 0.0234$ does not survive the familywise correction. The instance-wise winners are an oracle comparison: the selected configuration changes after the instance is known.

The class-level results establish heterogeneity within this benchmark, but do not identify a single landscape property that causes each rule pattern to succeed. The trajectories offer a plausible interpretation: a decreasing progress policy supports an exploration-to-exploitation transition, while the diversity axis modifies that transition conditionally. The direction of the preferred diversity response changes with the progress direction, so neither "more exploration" nor "more exploitation" is a sufficient class-independent prescription. This is consistent with the weak transfer of rankings to fixed-dimensional functions, but should not be read as a causal taxonomy of landscapes.

6.3. Implications for adaptive fuzzy control

Roy et al. describe a distinct policy-design approach in which fuzzy feedback policies are optimized on a training benchmark [4]. The present study instead characterizes performance heterogeneity among predefined static configurations. This heterogeneity motivates future work on online selection, but an instance-wise oracle is not an implementable selector: a deployable method would need to use information available during optimization and be evaluated without selecting configurations retrospectively from test results. No adaptive selector is tested here.

The present ranking also does not isolate the value of diversity feedback. R1 is nominally diversity-agnostic in its consequent table, yet its effective output is diversity-sensitive because both antecedents participate in min–max firing and aggregation. Future comparisons should distinguish consequent-table semantics from the measured sensitivity of the resulting control surface before attributing performance to feedback from a particular input.

6.4. Study Limitations

The findings should be interpreted within the experimental conditions considered. All configurations use uniform triangular Ruspini partitions with shoulder functions, a common two-input Mamdani inference architecture, eight predefined consequent patterns, and centroid defuzzification. Other membership-function shapes, overlap levels, and partition structures were not examined. Moreover, the controller regulates only the inertia weight, while the acceleration coefficients, velocity bounds, population size, and computational budget remain fixed. The comparison is restricted to classical PSO with a linear inertia schedule and the unshifted, unrotated F1–F23 benchmark suite. Consequently, the observed configuration rankings should not be assumed to extend to other PSO implementations, fuzzy-controller architectures, or benchmark families.

The analysis also has limitations arising from the benchmark structure and the aggregation of experimental outcomes. Functions evaluated at multiple dimensions are not independent problem families, and the fixed-dimensional subset differs from the scalable subset in more than dimensionality alone. Accordingly, differences between these groups cannot be attributed to individual landscape characteristics. The granularity-by-rule analysis describes the observed dispersion among consequent patterns rather than estimating a general interaction effect. These considerations delimit the interpretation and generalizability of the findings without affecting the descriptive comparisons within the evaluated configurations.

7. Conclusions and Future Work

This paper establishes a reproducible framework for studying static Mamdani fuzzy-control configurations in PSO. The study varies linguistic granularity and rule-base structure under a common partition family and evaluates their effects over the Classical F1–F23 benchmark suite.

The global ranking places FCS-3-R1 first (mean Friedman rank 4.77) and classical PSO second (6.36); both fall within the same critical-difference group. At the instance level, the best FCS configuration ranks ahead of PSO on 50 of 62 cases, but this is an oracle comparison because the selected configuration changes after the instance is known. The fixed-subset leaders differ: FCS-3-R5 on scalable S_1 and FCS-5-R6 on fixed-dimensional S_2. Observed rank concordance is weak ($\tau = 0.095$, $p = 0.451$); the applied test does not establish a positive association, and its non-significant result does not establish independence. These results describe heterogeneity within this benchmark but do not establish or rule out transferability to other problem sets.

FCS-3-R1 is nominally diversity-agnostic in its consequent table, but the implemented min–max Mamdani inference leaves its effective output weakly diversity-dependent. Its leading rank and near-0.5 mean inertia therefore do not demonstrate that diversity feedback improves PSO, nor do they imply a trajectory identical to the classical linear schedule.

Within the evaluated configurations, adding explicit diversity trends does not invariably improve ranking; this is not evidence that diversity feedback is unnecessary in general. Proposition 1 characterizes complementary mirror-pair surfaces; the Holm-adjusted independent-sample comparisons show that this structural symmetry does not ensure equivalent optimization performance.

For the tested FCS configurations and F1–F23 benchmark functions, observed performance differences among rule-base patterns did not decrease consistently as linguistic granularity increased. This descriptive finding is limited to the evaluated configurations and benchmark; it does not establish equivalence or estimate a formal factorial interaction. The result should not be generalized to other fuzzy controllers, PSO implementations, or optimization landscapes. Practically, the findings caution against assuming that finer partitions alone improve a fuzzy inertia controller or that an instance-wise oracle winner can be used as a deployable policy.

Future work can evaluate rule-semantic or configuration selection using information available during optimization, with selection separated from the test instances. A confirmatory study of the granularity-by-rule interaction should predefine its estimand, experimental unit, and repeated-measures procedure, calibrate that procedure under realistic dependence structures, and validate it on independent benchmark data. The present conclusions are limited to the tested membership functions, rule patterns, PSO settings, and classical F1–F23 benchmark suite.

Appendix A. Complete Experimental Results and Ranking Diagnostics

The table lists the best-ranked FCS and its comparison with PSO for each of the 62 function–dimension instances. It complements the function-level summary and aggregate RQ4 results in Section 5.

Table A1. Per-instance FCS–PSO results (part 1 of 3). Ranks use median normalized gap across 33 configurations.

Instance	Best FCS	n	R	PSO rk.	FCS rk.	PSO gap	FCS gap	p_{Bonf}	A_{12}
F1_D10	`FCS-3-R1`	3	R1	5	1	6.3×10^{-37}	1.4×10^{-44}	$<10^{-3}$	0.96
F1_D30	`FCS-3-R1`	3	R1	3	1	7.7×10^{-6}	1.7×10^{-9}	$<10^{-3}$	0.97
F1_D50	`FCS-3-R1`	3	R1	3	1	0.059	1.1×10^{-3}	$<10^{-3}$	0.99
F1_D100	`FCS-3-R1`	3	R1	2	1	16.744	10.263	1.000	0.72
F2_D10	`FCS-3-R1`	3	R1	6	1	3.5×10^{-18}	7.7×10^{-25}	$<10^{-3}$	0.98
F2_D30	`FCS-3-R1`	3	R1	2	1	4.5×10^{-4}	5.2×10^{-6}	$<10^{-3}$	0.98
F2_D50	`FCS-3-R1`	3	R1	2	1	0.099	8×10^{-3}	$<10^{-3}$	0.98
F2_D100	`FCS-3-R1`	3	R1	2	1	2.357	1.375	$<10^{-3}$	0.94
F3_D10	`FCS-5-R5`	5	R5	9	1	8.3×10^{-11}	2.8×10^{-15}	$<10^{-3}$	0.93
F3_D30	`FCS-7-R5`	7	R5	3	1	41.57	37.246	1.000	0.58
F3_D50	`FCS-5-R7`	5	R7	13	1	1692.014	1247.305	1.000	0.65
F3_D100	`FCS-9-R7`	9	R7	18	1	2×10^{4}	1.4×10^{4}	0.027	0.82
F4_D10	`FCS-9-R5`	9	R5	5	1	1.4×10^{-8}	3.2×10^{-11}	$<10^{-3}$	0.90
F4_D30	`FCS-9-R1`	9	R1	6	1	1.379	1.281	1.000	0.56
F4_D50	`FCS-5-R1`	5	R1	3	1	4.347	4.234	1.000	0.56
F4_D100	`FCS-5-R5`	5	R5	1	2	14.314	14.356	1.000	0.50
F5_D10	`FCS-3-R1`	3	R1	5	1	4.768	4.197	0.215	0.79
F5_D30	`FCS-3-R1`	3	R1	4	1	29.198	27.947	1.000	0.50
F5_D50	`FCS-3-R1`	3	R1	2	1	150.43	116.51	1.000	0.61
F5_D100	`FCS-3-R1`	3	R1	2	1	955.011	814.72	1.000	0.67
F6_D10	`FCS-3-R1`	3	R1	4	1	2.8×10^{-32}	0	0.006	0.82

p_{Bonf} is the Bonferroni-adjusted two-sided independent-sample Mann–Whitney U p-value across 1,984 RQ4 tests. $A_{12} > 0.5$ favours the listed FCS because lower fitness is better. Parentheses report configurations sharing the best median-gap rank.

Table A2. Per-instance FCS–PSO results (part 2 of 3). Ranks use median normalized gap across 33 configurations.

Instance	Best FCS	n	R	PSO rk.	FCS rk.	PSO gap	FCS gap	p_{Bonf}	A_{12}
F6_D30	FCS-3-R1	3	R1	2	1	2.4×10^{-6}	1.9×10^{-9}	$<10^{-3}$	0.99
F6_D50	FCS-3-R1	3	R1	2	1	0.046	1.1×10^{-3}	$<10^{-3}$	0.97
F6_D100	FCS-3-R1	3	R1	2	1	22.053	7.284	$<10^{-3}$	0.93
F7_D10	FCS-7-R6	7	R6	8	1	1.3×10^{-3}	1×10^{-3}	1.000	0.56
F7_D30	FCS-5-R1	5	R1	1	2	9×10^{-3}	9.1×10^{-3}	1.000	0.52
F7_D50	FCS-3-R1	3	R1	2	1	0.028	0.027	1.000	0.53
F7_D100	FCS-5-R1	5	R1	4	1	0.142	0.132	1.000	0.55
F8_D10	FCS-9-R8	9	R8	6	1	0.415	0.396	1.000	0.56
F8_D30	FCS-7-R3	7	R3	12	1	0.495	0.465	1.000	0.55
F8_D50	FCS-3-R1	3	R1	1	2	0.483	0.491	1.000	0.43
F8_D100	FCS-5-R6	5	R6	1	2	0.502	0.503	1.000	0.54
F9_D10	FCS-5-R2	5	R2	11	1	10.945	8.955	1.000	0.59
F9_D30	FCS-5-R5	5	R5	7	1	35.818	31.853	1.000	0.56
F9_D50	FCS-3-R5	3	R5	14	1	67.66	55.771	1.000	0.68
F9_D100	FCS-7-R5	7	R5	4	1	132.303	122.623	1.000	0.61
F10_D10	FCS-3-R1 (6 tied)	3	R1	4	4	4×10^{-15}	4×10^{-15}	1.000	0.45
F10_D30	FCS-3-R1	3	R1	2	1	6.6×10^{-4}	1.5×10^{-5}	$<10^{-3}$	0.93
F10_D50	FCS-3-R1	3	R1	4	1	0.522	0.019	0.094	0.80
F10_D100	FCS-3-R1	3	R1	3	1	2.192	1.966	1.000	0.74
F11_D10	FCS-9-R1	9	R1	10	1	0.091	0.069	1.000	0.64
F11_D30	FCS-7-R1	7	R1	5	1	7.5×10^{-3}	1.4×10^{-3}	1.000	0.54

p_{Bonf} is the Bonferroni-adjusted two-sided independent-sample Mann–Whitney U p-value across 1,984 RQ4 tests. $A_{12} > 0.5$ favours the listed FCS because lower fitness is better. Parentheses report configurations sharing the best median-gap rank.

Table A3. Per-instance FCS–PSO results (part 3 of 3). Ranks use median normalized gap across 33 configurations.

Instance	Best FCS	n	R	PSO rk.	FCS rk.	PSO gap	FCS gap	p_{Bonf}	A_{12}
F11_D50	FCS-3-R1	3	R1	3	1	0.064	0.012	$<10^{-3}$	0.91
F11_D100	FCS-3-R1	3	R1	2	1	1.168	1.042	0.004	0.85
F12_D10	FCS-3-R1	3	R1	2	1	4.8×10^{-32}	4.7×10^{-32}	0.284	0.77
F12_D30	FCS-3-R1	3	R1	2	1	1.2×10^{-8}	2.1×10^{-11}	0.065	0.81
F12_D50	FCS-7-R1	7	R1	1	2	4.1×10^{-4}	4.9×10^{-4}	1.000	0.49
F12_D100	FCS-5-R1	5	R1	3	1	2.769	2.313	1.000	0.67
F13_D10	FCS-3-R1	3	R1	3	1	1.8×10^{-32}	1.3×10^{-32}	0.126	0.76
F13_D30	FCS-3-R1	3	R1	2	1	2.4×10^{-6}	9.4×10^{-9}	1.000	0.65
F13_D50	FCS-3-R1	3	R1	3	1	0.025	8.9×10^{-3}	0.112	0.80
F13_D100	FCS-3-R1	3	R1	3	1	16.942	9.312	1.000	0.73
F14_D2	FCS-3-R1 (6 tied)	3	R1	27	3	2.968	0.992	1.000	0.58
F15_D4	FCS-3-R1	3	R1	11	1	7.5×10^{-6}	7.5×10^{-6}	1.000	0.75
F16_D2	FCS-3-R1 (32 tied)	3	R1	17	17	0	0	1.000	0.56
F17_D2	FCS-3-R1 (32 tied)	3	R1	17	17	0	0	1.000	0.50
F18_D2	FCS-3-R1 (28 tied)	3	R1	15	15	0	0	1.000	0.45
F19_D3	FCS-3-R1 (32 tied)	3	R1	17	17	0	0	1.000	0.56
F20_D6	FCS-3-R1 (27 tied)	3	R1	14	14	0	0	1.000	0.55
F21_D4	FCS-7-R1	7	R1	24	1	0.736	0	1.000	0.61
F22_D4	FCS-3-R6 (2 tied)	3	R6	20	1	0.642	0	1.000	0.57
F23_D4	FCS-5-R6	5	R6	1	2	0	1.7×10^{-16}	1.000	0.34

p_{Bonf} is the Bonferroni-adjusted two-sided independent-sample Mann–Whitney U p-value across 1,984 RQ4 tests. $A_{12} > 0.5$ favours the listed FCS because lower fitness is better. Parentheses report configurations sharing the best median-gap rank.




Figure A1. Per-instance Friedman ranks of 33 configurations across 62 instances, computed on median normalized gap (rank 1 = best). Columns are ordered by mean rank; vertical rules bracket PSO and the horizontal rule separates S1 and S2. Green denotes better ranks.




Figure A2. Nominal independent-sample Mann–Whitney outcomes against PSO for the ten configurations ranked by Bonferroni-significant wins. Bars cover 62 instances; green, grey, and red denote wins, non-significant comparisons, and losses at $p < 0.05$.

Appendix B. Extended Performance and Dispersion Diagnostics

Figure A3 shows four representative instances; the atlas that follows covers all 62 function–dimension instances. Each point is one fixed configuration, lower-left indicates lower mean gap and variability, both axes are logarithmic, and zero gaps use a 10^{-12} floor. The scalable functions share axis limits across their four dimensions. The representative cases are interpreted in Section 5.6.




Figure A3. Mean normalized gap versus run-to-run standard deviation over 31 runs for four instances. Both axes are logarithmic; zero gaps use a 10^{-12} display floor. Colour denotes pattern, marker shape granularity, the star PSO, and the open circle the function's best FCS.




Figure A4. Mean-versus-dispersion panels for the function–dimension instances identified in each subplot.




Figure A5. Mean-versus-dispersion panels for the function–dimension instances identified in each subplot.




Figure A6. Mean-versus-dispersion panels for the function–dimension instances identified in each subplot.




Figure A7. Mean-versus-dispersion panels for the function–dimension instances identified in each subplot.




Figure A8. Mean-versus-dispersion panels for the function–dimension instances identified in each subplot.




Figure A9. Mean-versus-dispersion panels for the function–dimension instances identified in each subplot.




Figure A10. Mean-versus-dispersion panels for the function–dimension instances identified in each subplot.

Appendix C. Fuzzy Controller Configurations and Control Surfaces

This appendix provides the remaining rule-consequent matrices, effective Mamdani control surfaces, and workflow diagram referenced in Section 3. All configurations use the common two-input architecture and inference procedure defined in the main text.




Figure A11. Rule-base consequents R1–R8 at $n = 5$. Rows denote diversity labels and columns denote progress labels.




Figure A12. Rule-base consequents R1–R8 at $n = 7$. Rows denote diversity labels and columns denote progress labels.




Figure A13. Rule-base consequents R1–R8 at $n = 9$. Rows denote diversity labels and columns denote progress labels.




Figure A14. Effective Mamdani inertia-weight surfaces for R1–R8 at $n = 3$, over diversity and progress; $w \in [0.1, 0.9]$.




Figure A15. Effective Mamdani inertia-weight surfaces for R1–R8 at $n = 7$, over diversity and progress; $w \in [0.1, 0.9]$.




Figure A16. Effective Mamdani inertia-weight surfaces for R1–R8 at $n = 9$, over diversity and progress; $w \in [0.1, 0.9]$.




Figure A17. PSO–FCS workflow: the common two-input fuzzy controller returns one inertia weight shared by all particles.

Appendix D. Benchmark Landscape Visualizations

The panels below are illustrative objective landscapes and two-coordinate slices; the benchmark functions, dimensions, domains, and solver reference optima are defined in Tables 2–3 in Section 4.1. They do not constitute quantitative landscape characterization.




Figure A18. Benchmark objective landscapes and two-dimensional slices: (a) F1 (Sphere, $d = 10$); (b) F2 (Schwefel 2.22, $d = 10$); (c) F3 (Schwefel 1.2, $d = 10$). Contours are shown at left and 3-D surfaces at right; colour shows log-compressed objective excess on function-specific scales. For $d > 2$, other coordinates are fixed at the midpoint of the solver bounds. Bounds and reference optima are listed in Tables 2–3.




Figure A19. Benchmark objective landscapes and two-dimensional slices: (a) F4 (Schwefel 2.21, $d = 10$); (b) F5 (Rosenbrock, $d = 10$); (c) F6 (Shifted step, $d = 10$). Contours are shown at left and 3-D surfaces at right; colour shows log-compressed objective excess on function-specific scales. For $d > 2$, other coordinates are fixed at the midpoint of the solver bounds. Bounds and reference optima are listed in Tables 2–3.




Figure A20. Benchmark objective landscapes and two-dimensional slices: (a) F7 (Quartic with noise, $d = 10$); (b) F8 (Schwefel 2.26, $d = 10$); (c) F9 (Rastrigin, $d = 10$). Contours are shown at left and 3-D surfaces at right; colour shows log-compressed objective excess on function-specific scales. For $d > 2$, other coordinates are fixed at the midpoint of the solver bounds. Bounds and reference optima are listed in Tables 2–3. The F7 panel uses the expected objective, including its 0.5 uniform-noise offset.




Figure A21. Benchmark objective landscapes and two-dimensional slices: (a) F10 (Ackley, $d = 10$); (b) F11 (Griewank, $d = 10$); (c) F12 (Penalized 1, $d = 10$). Contours are shown at left and 3-D surfaces at right; colour shows log-compressed objective excess on function-specific scales. For $d > 2$, other coordinates are fixed at the midpoint of the solver bounds. Bounds and reference optima are listed in Tables 2–3.




Figure A22. Benchmark objective landscapes and two-dimensional slices: (a) F13 (Penalized 2, $d = 10$); (b) F14 (Shekel foxholes, $d = 2$); (c) F15 (Kowalik, $d = 4$). Contours are shown at left and 3-D surfaces at right; colour shows log-compressed objective excess on function-specific scales. For $d > 2$, other coordinates are fixed at the midpoint of the solver bounds. Bounds and reference optima are listed in Tables 2–3.




Figure A23. Benchmark objective landscapes and two-dimensional slices: (a) F16 (Six-hump camel, $d = 2$); (b) F17 (Branin, $d = 2$); (c) F18 (Goldstein-Price, $d = 2$). Contours are shown at left and 3-D surfaces at right; colour shows log-compressed objective excess on function-specific scales. For $d > 2$, other coordinates are fixed at the midpoint of the solver bounds. Bounds and reference optima are listed in Tables 2–3.




Figure A24. Benchmark objective landscapes and two-dimensional slices: (a) F19 (Hartmann 3-D, $d = 3$); (b) F20 (Hartmann 6-D, $d = 6$); (c) F21 (Shekel-5, $d = 4$). Contours are shown at left and 3-D surfaces at right; colour shows log-compressed objective excess on function-specific scales. For $d > 2$, other coordinates are fixed at the midpoint of the solver bounds. Bounds and reference optima are listed in Tables 2–3.




Figure A25. Benchmark objective landscapes and two-dimensional slices: (a) F22 (Shekel-7, $d = 4$); (b) F23 (Shekel-10, $d = 4$). Contours are shown at left and 3-D surfaces at right; colour shows log-compressed objective excess on function-specific scales. For $d > 2$, other coordinates are fixed at the midpoint of the solver bounds. Bounds and reference optima are listed in Tables 2–3.

Funding: This research received no external funding.

Data Availability Statement: The consolidated run-level dataset, including the verified run seeds, and the machine-readable statistical summaries supporting the findings are provided in the Supplementary Materials.

Acknowledgments: José Barrera-García is supported by the National Agency for Research and Development (ANID)/Scholarship Program/DOCTORADO NACIONAL/2024-21242516. Broderick Crawford is supported by Grant ANID/FONDECYT/REGULAR/1262511.

Conflicts of Interest: The authors declare no conflicts of interest.

References

1. Kennedy, J.; Eberhart, R. Particle swarm optimization. In Proceedings of the International Conference on Neural Networks, 1995, Vol. 4, pp. 1942–1948. https://doi.org/10.1109/ICNN.1995.488968.
2. Shi, Y.; Eberhart, R. A modified particle swarm optimizer. In Proceedings of the IEEE International Conference on Evolutionary Computation, 1998, pp. 69–73. https://doi.org/10.1109/ICEC.1998.699146.
3. Shi, Y.; Eberhart, R. Fuzzy adaptive particle swarm optimization. In Proceedings of the 2001 Congress on Evolutionary Computation, 2001, Vol. 1, pp. 101–106. https://doi.org/10.1109/CEC.2001.934377.
4. Roy, N.; Beauthier, C.; Mayer, A. Hyperparameter control using fuzzy logic: Evolving policies for adaptive fuzzy particle swarm optimization algorithm. *Evolutionary Computation* **2025**, *33*, 279–308. https://doi.org/10.1162/evco_a_00353.
5. Gacto, M.J.; Alcalá, R.; Herrera, F. Interpretability of linguistic fuzzy rule-based systems: An overview of interpretability measures. *Information Sciences* **2011**, *181*, 4340–4360. https://doi.org/10.1016/j.ins.2011.02.021.
6. Castiello, C.; Fanelli, A.M.; Lucarelli, M.; Mencar, C. Interpretable fuzzy partitioning of classified data with variable granularity. *Applied Soft Computing* **2019**, *74*, 567–582. https://doi.org/10.1016/j.asoc.2018.10.040.
7. Chatterjee, A.; Siarry, P. Nonlinear inertia weight variation for dynamic adaptation in particle swarm optimization. *Computers and Operations Research* **2006**, *33*, 859–871. https://doi.org/10.1016/j.cor.2004.08.012.
8. Nickabadi, A.; Ebadzadeh, M.S.; Safabakhsh, R. A novel particle swarm optimization algorithm with adaptive inertia weight. *Applied Soft Computing* **2011**, *11*, 3658–3670. https://doi.org/10.1016/j.asoc.2011.01.037.
9. Taherkhani, M.; Safabakhsh, R. A novel stability-based adaptive inertia weight for particle swarm optimization. *Applied Soft Computing* **2015**, *38*, 281–295. https://doi.org/10.1016/j.asoc.2015.10.004.
10. Duan, Y.; Chen, N.; Chang, L.; Ni, Y.; Kumar, S.; Zhang, P. CAPSO: Chaos adaptive particle swarm optimization algorithm. *IEEE Access* **2022**, *10*, 33857–33878. https://doi.org/10.1109/access.2022.3158666.
11. Han, Y.; Lin, M.; Li, N.; Qi, Q.; Li, J.; Liu, Q. DCWPSO: Particle swarm optimization with dynamic inertia weight updating and enhanced learning strategies. *PeerJ Computer Science* **2024**, *10*, e2253. https://doi.org/10.7717/peerj-cs.2253.
12. Mamdani, E.H. Application of fuzzy algorithms for control of simple dynamic plant. *Proceedings of the Institution of Electrical Engineers* **1974**, *121*, 1585–1588. https://doi.org/10.1049/piee.1974.0328.
13. Lee, C.C. Fuzzy logic in control systems: Fuzzy logic controller—Part I. *IEEE Transactions on Systems, Man, and Cybernetics* **1990**, *20*, 404–418. https://doi.org/10.1109/21.52551.
14. Nguyen, A.T.; Taniguchi, T.; Eciolaza, L.; Campos, V.; Palhares, R.M.; Sugeno, M. Fuzzy control systems: Past, present and future. *IEEE Computational Intelligence Magazine* **2019**, *14*, 56–68. https://doi.org/10.1109/MCI.2018.2881644.
15. Nobile, M.S.; Cazzaniga, P.; Besozzi, D.; Colombo, R.; Mauri, G.; Pasi, G. Fuzzy self-tuning PSO: A settings-free algorithm for global optimization. *Swarm and Evolutionary Computation* **2018**, *39*, 70–85. https://doi.org/10.1016/j.swevo.2017.09.001.
16. Valdez, F.; Vázquez, J.; Melin, P.; Castillo, O. Comparative study of the use of fuzzy logic in improving particle swarm optimization variants for mathematical functions using co-evolution. *Applied Soft Computing* **2017**, *52*, 1070–1083. https://doi.org/10.1016/j.asoc.2016.09.024.
17. Xia, X.; Song, H.; Zhang, Y.; Gui, L.; Xu, X.; Li, K.; Li, Y. A particle swarm optimization with adaptive learning weights tuned by a multiple-input multiple-output fuzzy logic controller. *IEEE Transactions on Fuzzy Systems* **2023**, *31*, 2464–2478. https://doi.org/10.1109/TFUZZ.2022.3227464.
18. Salimi, N.; Soleimani, S.; Rafe, V.; Khodadad, D. A Hybrid Approach for Reachability Analysis of Complex Software Systems Using Fuzzy Adaptive Particle Swarm Optimization Algorithm and Rule Composition. *Mathematical and Computational Applications* **2025**, *30*, 65. https://doi.org/10.3390/mca30030065.
19. Klir, G.J.; Yuan, B. *Fuzzy sets and fuzzy logic: Theory and applications*, 2nd ed.; Prentice Hall, 2005.
20. Dubois, D.; Prade, H. *Fundamentals of Fuzzy Sets*; Springer, 2000. https://doi.org/10.1007/978-1-4615-4429-6.
21. Ojha, V.; Abraham, A.; Snášel, V. Heuristic design of fuzzy inference systems: A review of three decades of research. *Engineering Applications of Artificial Intelligence* **2019**, *85*, 845–864. https://doi.org/10.1016/j.engappai.2019.08.010.
22. Gu, X.; Han, J.; Shen, Q.; Angelov, P. Autonomous learning for fuzzy systems: A review. *Artificial Intelligence Review* **2022**, *56*, 4199–4229. https://doi.org/10.1007/s10462-022-10355-6.
23. Lughofer, E.; Pratama, M.; Škrjanc, I. Incremental rule splitting in generalized evolving fuzzy systems for autonomous drift compensation. *IEEE Transactions on Fuzzy Systems* **2018**, *26*, 1854–1868. https://doi.org/10.1109/TFUZZ.2017.2753727.

24. Guillaume, S.; Charnomordic, B. Generating an interpretable family of fuzzy partitions from data. *IEEE Transactions on Fuzzy Systems* **2004**, *12*, 324–335. https://doi.org/10.1109/TFUZZ.2004.825979.
25. Sa'ad, H.H.; Isa, N.A.M.; Ahmed, M.F. A structural evolving approach for fuzzy systems. *IEEE Transactions on Fuzzy Systems* **2020**, *28*, 273–286. https://doi.org/10.1109/TFUZZ.2019.2904928.
26. Megherbi, H.; Megherbi, A.; Benmahammed, K. On accommodating the semantic-based interpretability in evolutionary linguistic fuzzy controller. *Journal of Intelligent & Fuzzy Systems* **2019**, *36*, 1625–1638. https://doi.org/10.3233/JIFS-18637.
27. Ahmed, M.T.; Isa, N.A.M. Knowledge base to fuzzy information granule: A review from the interpretability–accuracy perspective. *Applied Soft Computing* **2017**, *54*, 121–140. https://doi.org/10.1016/j.asoc.2016.12.055.
28. Yao, X.; Liu, Y.; Lin, G. Evolutionary programming made faster. *IEEE Transactions on Evolutionary Computation* **1999**, *3*, 82–102. https://doi.org/10.1109/4235.771163.
29. Abualigah, L.; Diabat, A.; Mirjalili, S.; Abd Elaziz, M.; Gandomi, A.H. The Arithmetic Optimization Algorithm. *Computer Methods in Applied Mechanics and Engineering* **2021**, *376*, 113609. https://doi.org/10.1016/j.cma.2020.113609.