Multi-objective Optimization

Features:

- Distributed Data Flow
- Fog nodes mobility
- IoT devices mobility
- Migration support
- Partitioning techniques
- Data placement optimization
- Migration Optimization

Variables:

- QoS
  - latency
- Cost
  - CPU
  - RAM
  - MEM
  - BW
- Energy
  - busyPower
  - idlePower
- Bandwidth

Notations:

- N − fog nodes $S = \{s_1, ..., s_n\}$

- M − modules $U = \{u_1, ..., u_m\}$

- fP^{Mips} − matrix $1 \times N$ representing the MIPS price of each fog node per unit

- fP^{Ram} − matrix $1 \times N$ representing the memory price of each fog node per unit

- fP^{Strg} − matrix $1 \times N$ representing the storage price of each fog node per unit

- fP^{Bw} − matrix $1 \times N$ representing the bandwidth price of each fog node per unit

- f^{Mips} − matrix $N \times 1$ representing the MIPS capacity of each fog node

- f^{Ram} − matrix $N \times 1$ representing the memory capacity of each fog node

- f^{Strg} − matrix $N \times 1$ representing the storage capacity of each fog node

- f^{bPw} = matrix $N \times 1$ representing the busy power consumption of each fog node per unit

- f^{iPw} − matrix $N \times 1$ representing the idle power consumption of each fog node per unit

- m^{Mips} − matrix $M \times 1$ representing the MIPS needed for each application's module

- m^{Ram} − matrix $M \times 1$ representing the memory needed for each application's module

- m^{Strg} − matrix $M \times 1$ representing the storage needed for each application's module

- K − total number of dependencies/edges

- e^{Cpu} − matrix $1 \times K$ representing the tuple CPU size (MI) needed to be processed

- e^{Nw} − matrix $1 \times K$ representing the tuple network size (MB) needed to be sent

- e^{Prob} − matrix $1 \times K$ representing the probability of sending the tuple

- e^{Pe} − matrix $1 \times K$ representing the periodicity of the producer (i.e., periodic sources)

- e^{S} − matrix $1 \times K$ representing the edge source

- e^{D} − matrix $1 \times K$ representing the edge destination

- Z − total number of dependencies/edges between different pairs of nodes

- l^{S} − matrix $N \times 1$ representing the starting nodes of each pair of nodes

- l^{D} − matrix $N \times 1$ representing the ending nodes of each pair of nodes

- mD − matrix $M \times M$ representing the dependencies between modules

- mB − matrix $M \times M$ representing the bandwidth needed between modules

- fL − matrix $N \times N$ representing the latency between each two direct nodes

- fB − matrix $N \times N$ representing the bandwidth between each two direct nodes

- D − matrix $N \times M$ representing the nodes where each module can be deployed

- P − matrix $N \times M$ representing the placement mapping between modules and nodes

- R − matrix $Z \times N \times N$ representing the routing map between modules

- e − matrix 1xN, with all entries to 1

- h − matrix NxN, with all entries to 1 except for diagonal which is filled with zeros

- α − operational weight

- β − energetic weight

- γ − processing weight

- δ − transmission weight

- ζ − bandwidth weight

Preliminary computations:

$$m_i^{Mips} = \sum_{k \in K} \left(\frac{e_k^{Prob} e_k^{Cpu}}{e_k^{Pe}} \right), e_k^D = i$$

$$mB_{i,j} = \sum_{k \in K} \left(\frac{e_k^{Prob} e_k^{Nw}}{e_k^{Pe}} \right), e_k^S = i, \ e_k^D = j$$

$$mD_{i,j} = \sum_{k \in K} \left(\frac{e_k^{Prob}}{e_k^{Pe}} \right), e_k^S = i, \ e_k^D = j$$

Problem formulation:

The cost function is mainly characterized by two components: Operational Cost and Service Quality Cost.

Operational Cost (C_O) is characterized by the resources allocated in each fog node to support all users' computations, namely: CPU, memory, storage, and bandwidth.

$$C_O = fP^{Mips} \times P \times m^{Mips} + fP^{Ram} \times P \times m^{Ram} + fP^{Strg} \times P \times m^{Strg} + \left(fP^{Bw} \times h. * \sum_{z \in Z} mB_{l_z^S, l_z^D} \times R_z \right) e'$$

Power Cost (C_{Pw}) is characterized by the busy/idle power in each fog node to support all users' computations as well as the willing to wast energy to prevent clients to process the whole application.

$$C_{Pw} = \sum_{n \in N} \left(f_n^{iPw} + (f_n^{bPw} - f_n^{iPw}) \times \frac{P_n \times m^{Mips}}{f_n^{Mips}} \right)$$

Processing Cost (C_P) is characterized by the percentage of unused MIPS using the Jain's fairness index.

$$C_P = \frac{\left(\sum_{n \in N} \frac{P_n \times m^{Mips}}{f_n^{Mips}} \right)^2}{N \times \sum_{n \in N} \left(\frac{P_n \times m^{Mips}}{f_n^{Mips}} \right)^2} \quad - OR - \quad C_P = \sum_{n \in N} \frac{P_n \times m^{Mips}}{f_n^{Mips}}$$

Transmission Cost (C_T) is characterized by the total latency on the tuple transmission ($Total_{lat} = lat + \frac{tuple\_size}{Bw}$).

$$C_T = e \left(fL. * \sum_{z \in Z} \left(mD_{l_z^S, l_z^D} \times R_z \right) + 1./(fB + \epsilon) \ . * \sum_{z \in Z} \left(mB_{l_z^S, l_z^D} \times R_z \right) \right) e' \ , \epsilon = 1^{-9}$$

Bandwidth Cost (C_B) is characterized by the percentage of unused MIPS using the Jain's fairness index.

$$C_B = \sum_{i \in N} \sum_{j \in N} \frac{\sum_{z \in Z} \left(mB_{l_z^S, l_z^D} \times R_{z,i,j} \right)}{fB_{i,j}}$$

Final problem:

$$
\begin{aligned}
\underset{P,R}{\text{minimize}} \quad & C = \alpha C_O + \beta C_{Pw} + \gamma C_P + \delta C_T + \zeta C_B \\
\text{subject to} \quad & P \times m^{Mips} \leq f^{Mips}, \\
& P \times m^{Ram} \leq f^{Ram}, \\
& P \times m^{Strg} \leq f^{Strg}, \\
& P \leq D \\
& P_{i,j} \in \{0,1\}, \forall i \in [0,N], \forall j \in [0,M] \\
& \sum_{i \in N} P_{i,j} = 1, \forall j \in [0,M] \\
& R_{z,i,j} \in \{0,1\}, \forall z \in [0,Z], \forall i \in [0,N], \forall j \in [0,N] \\
& \sum_{j \in N} R_{z,i,j} - \sum_{j \in N} R'_{z,i,j} = P_{i,l_z^S} - P_{i,l_z^D} \ , \forall z \in [0,Z], \forall i \in [0,N] \\
& \sum_{z \in Z} mB_{l_z^S, l_z^D} \times R_{z,i,j} \leq fB_{i,j} \ , \forall i \in [0,N], \forall j \in [0,N]
\end{aligned}
$$