Notation:

- \bullet N number of nodes
- \bullet M number of modules
- \bullet K number of dependencies
- \bullet Z number of module pairs with dependencies
- Q number of loop deadlines
- P^{Mips} [\in] , $1 \times N$ matrix representing the price of using processing resources in each fog node
- P^{Mem} [\in], $1 \times N$ matrix representing the price of using memory resources in each fog node
- P^{Strg} [\in], $1 \times N$ matrix representing the price of using storage resources in each fog node
- P^{Bw} [\in], $1 \times N$ matrix representing the price of using network resources in each fog node
- P^{Pw} [\in], $1 \times N$ matrix representing the power price in each fog node
- f^{Mips} [MIPS], $N \times 1$ matrix representing the processing capacity of each fog node
- f^{Mem} [Byte], $N \times 1$ matrix representing the memory capacity of each fog node
- f^{Strg} [Byte], $N \times 1$ matrix representing the storage capacity of each fog node
- f^{bPw} [W], $N \times 1$ matrix representing the busy power consumption of each fog node
- f^{iPw} [W], $N \times 1$ matrix representing the idle power consumption of each fog node
- f^{Tx} [W], $N \times 1$ matrix representing the transmitter power (f_n^{Tx} is non 0 if n is a mobile node)
- m^{Mips} [MIPS], $M \times 1$ matrix representing the processing resources needed for each module
- m^{Mem} [Byte], $M \times 1$ matrix representing the memory resources needed for each module
- m^{Strg} [Byte], $M \times 1$ matrix representing the storage resources needed for each module
- e^{Cpu} [MI], $K \times 1$ matrix representing the tuple CPU size needed to be processed for each dependency
- e^{Nw} [Byte], $K \times 1$ matrix representing the tuple network size needed to be sent for each dependency
- e^{Pe} [s], $K \times 1$ matrix representing the periodicity of sending the tuple for each dependency
- e^{Prob} [%], $K \times 1$ matrix representing the probability of sending the tuple for each dependency
- e^S , $K \times 1$ matrix representing the source module for each dependency
- e^D , $K \times 1$ matrix representing the destination module for each dependency
- l^S , $Z \times 1$ matrix representing the source module for each pair of modules with dependencies
- l^D , $Z \times 1$ matrix representing the destination module for each pair of modules with dependencies
- m^D , $M \times M$ matrix representing the dependencies between modules
- m^B , $M \times M$ matrix representing the bandwidth needed between modules
- m^{CPU} , $M \times M$ matrix representing the CPU size of dependencies between modules
- m^{NW} , $M \times M$ matrix representing the network size of dependencies between modules
- f^L , $N \times N$ matrix representing the link latency between each two nodes
- f^B , $N \times N$ matrix representing the link bandwidth between each two nodes
- $D, N \times M$ binary matrix representing the nodes where each module can be deployed
- $C, N \times M$ binary matrix representing the current module placement

- $A^L, Q \times M \times M$ binary matrix representing the loop module list
- A^D , $Q \times 1$ matrix representing the loop deadline list
- α^p , the percentage of processing capacity which is not used for control operations
- α^m , the percentage of memory capacity which is not used for control operations
- α^s , the percentage of storage capacity which is not used for control operations
- \bullet α^b , the percentage of bandwidth capacity which is not used both for control operations and migrations
- \bullet $\,t^{Boot},$ constant representing the average virtual machine boot time
- \bullet ϵ small positive constant

Variables:

- \bullet P, $N \times M$ binary matrix representing the placement mapping between modules and nodes
- $R, Z \times N \times N$ binary matrix representing the tuple routing map between modules
- $V, M \times N \times N$ binary matrix representing the module migration routing map

Preliminary computations:

$$\begin{split} m_i^{Mips} &= \sum_{k \in K} \frac{e_k^{Prob} e_k^{Cpu}}{e_k^{Pe}}, \ e_k^D = i \\ m_{i,j}^B &= \sum_{k \in K} \frac{e_k^{Prob} e_k^{Nw}}{e_k^{Pe}}, \ e_k^S = i, \ e_k^D = j \\ m_{i,j}^D &= \sum_{k \in K} \frac{e_k^{Prob}}{e_k^{Pe}}, \ e_k^S = i, \ e_k^D = j \\ m_{i,j}^{CPU} &= \sum_{k \in K} e_k^{Cpu}, \ e_k^S = i, \ e_k^D = j \\ m_{i,j}^{NW} &= \sum_{k \in K} e_k^{Nw}, \ e_k^S = i, \ e_k^D = j \end{split}$$

Objectives:

Operational Cost:

$$C_O = P^{Mips} \times P \times m^{Mips} + P^{Mem} \times P \times m^{Mem} + P^{Strg} \times P \times m^{Strg} + \left(P^{Bw} \sum_{z \in Z} m^B_{l_z^S, l_z^D} \times R_z\right) 1N + C_{Pw}(P^{Pw'})$$

Power Cost:

$$C_{Pw}(x) = C_P(x. \times (f^{bPw} - f^{iPw})) + C_B(x. \times f^{Tx})$$

Processing Cost:

$$C_P(x) = \sum_{n \in N} x_n \frac{P_n \times m^{Mips}}{\alpha^p \times f_n^{Mips}}$$

Bandwidth Cost:

$$C_B(x) = \sum_{z \in Z} m_{l_z^S, l_z^D}^B \sum_{i \in N} x_i \sum_{j \in N} \frac{R_{z,i,j}}{\alpha^b \times f_{i,j}^B + \epsilon}$$

Migration Cost:

$$C_M(x) = \sum_{m \in M} s_m \sum_{i \in N} x_i \sum_{j \in N} \frac{V_{m,i,j} \times \sum_{l \in M} m_{l,m}^D}{(1 - \alpha^b) \times f_{i,j}^B + \epsilon},$$

$$s_m = m_m^{Strg} + m_m^{Mem}$$

Multiple-objective:

$$F = \{C_{Pw}(1N), C_P(1N), C_B(1N), C_M(1N)\}$$

Single-objective:

$$F = C_O$$

Final problem:

$$\begin{split} & \underset{P,R,V}{\text{minimize}} & F \\ & \text{subject to} & P_{i,j} \in \{0,1\}, \ \forall i \in [0,N], \ \forall j \in [0,M] \\ & R_{z,i,j} \in \{0,1\}, \ \forall z \in [0,Z], \ \forall i \in [0,N], \ \forall j \in [0,N] \\ & V_{z,i,j} \in \{0,1\}, \ \forall z \in [0,M], \ \forall i \in [0,N], \ \forall j \in [0,N] \\ & P \times m^{Mips} \leq \alpha^p \times f^{Mips} \\ & P \times m^{Mem} \leq \alpha^m \times f^{Mem} \\ & P \times m^{Strg} \leq \alpha^s \times \leq f^{Strg} \\ & \sum_{z \in Z} m^B_{l_z^S, l_z^D} \times R_{z,i,j} \leq \alpha^b \times f^B_{i,j} \ \ , \ \forall i \in [0,N], \ \forall j \in [0,N] \\ & \sum_{j \in N} P_{i,j} = 1, \ \forall j \in [0,M] \\ & P \leq D \\ & \sum_{j \in N} R_{z,i,j} - \sum_{j \in N} R'_{z,i,j} = P_{i,l_z^S} - P_{i,l_z^D} \ \ , \forall z \in [0,Z], \ \forall i \in [0,N] \\ & \sum_{j \in N} V_{z,i,j} - \sum_{j \in N} V'_{z,i,j} = C_{j,i} - P_{j,i} \ \ , \ \forall z \in [0,M], \ \forall i \in [0,N] \\ & L^P_q + L^T_q \leq A^D_q, \ \forall q \in [0,Q] \\ & L^M_m \leq 1, \ \forall m \in [0,M] \end{split}$$

where:

$$L_{q}^{P} = \sum_{i \in M} \sum_{j \in M} A_{q,i,j}^{L} \sum_{n \in N} P_{n,j} \frac{\sum_{l \in M} \sum_{k \in M} m_{l,k}^{CPU} \times P_{n,k}}{f_{n}^{Mips}}$$

$$L_{q}^{T} = \sum_{i \in M} \sum_{j \in M} A_{q,i,j}^{L} \sum_{l \in N} \sum_{k \in N} R_{z',l,k} \left(\frac{\sum_{z \in Z} R_{z,l,k} \times m_{l_{z}^{S},l_{z}^{D}}^{NW}}{\alpha^{b} \times f_{l,k}^{B} + \epsilon} + f_{l,k}^{L} \right),$$

$$l_{z'}^{S} = i, \ l_{z'}^{D} = j$$

$$\begin{split} L_{m}^{M} &= b \times t^{Boot} + \sum_{i \in N} \sum_{j \in N} V_{m,i,j} \times \left(\frac{m_{m}^{Strg} + m_{m}^{Mem}}{(1 - \alpha^{b}) \times f_{i,j}^{B} + \epsilon} + f_{i,j}^{L} \right) \\ b &= C_{n,i} - P_{n,i}, \ C_{n,i} = 1, \sum_{n' \in N} C_{n',i} = 1 \end{split}$$

Abandoned ideas

Transmission Cost:

$$C_T = \sum_{i \in N} \sum_{j \in N} f_{i,j}^L \sum_{z \in Z} \left(m_{l_z^S, l_z^D}^D \times R_{z,i,j} \right)$$

Constraint:

$$\begin{split} L_q^P &= \sum_{i \in M} \sum_{j \in M} A_{q,i,j}^L \times \ \frac{m_{i,j}^{CPU}}{m_j^{Mips}}, \ m_j^{Mips} \neq 0 \\ \\ L_q^T &= \sum_{i \in M} \sum_{j \in M} A_{q,i,j}^L \sum_{l \in N} \sum_{k \in N} R_{z,l,k} \left(\frac{m_{i,j}^{NW}}{m_{i,j}^B} + f_{l,k}^L \right), \ l_z^S = i, \ l_z^D = j, \ m_{i,j}^B \neq 0 \end{split}$$

$$\begin{split} L_{q}^{M} &= \sum_{i \in M} A_{i} \times \left(\sum_{l \in N} \sum_{k \in N} V_{i,l,k} \left(\frac{m_{i}^{Strg} + m_{i}^{Mem}}{f_{l,k}^{B} + \epsilon} + f_{l,k}^{L} \right) + B_{i} \times t^{Boot} \right), \\ A_{i} &= \min \Big\{ \sum_{j \in M} A_{q,i,j}^{L} + A_{q,j,i}^{L}, \ 1 \Big\}, \\ B_{i} &= C_{n,i} - P_{n,i}, \ C_{n,i} = 1, \sum_{n' \in N} C_{n',i} = 1 \end{split}$$