

Gauge Selection and Reachability in Rational Certificate Search

José Cláudio da Silva Junior

State University of Londrina (UEL), Brazil

Electrical Engineering (B.Eng., 2016); Electronic Systems and Instrumentation (M.Sc., 2018)

May 2026

Abstract

We study how representation affects rational certificate search in creative telescoping. Experiments across multiple hypergeometric families suggest that gauge selection can change a search problem from unreachable to reachable under fixed ansatz budgets. We further show that recurrence-derived denominator guidance substantially reduces search cost once reachability is established.

1 Introduction

Creative telescoping reduces a hypergeometric summation identity to finding a rational function $R(n, k)$ satisfying

$$F(n+1, k) - F(n, k) = \Delta_k[R(n, k)F(n, k)].$$

Classical results establish algorithmic solvability for broad holonomic classes [9, 10, 6, 1]. However, practical search is bounded by an ansatz: denominator candidates, maximum numerator degree, and recurrence order.

The central empirical observation is representation-dependent reachability:

same identity $\Rightarrow$ different gauge $\Rightarrow$ reachable vs. unreachable under the same budget.

Two phenomena are separated throughout:

- **Phenomenon A (reachability):** whether a certificate is found under a fixed budget.
- **Phenomenon B (cost):** how expensive search is once a reachable gauge is used.
- **Phenomenon C (transfer):** whether structural guidance generalizes across independent families.

2 Related Work

Creative telescoping and WZ methods are foundational in symbolic summation [9, 10, 6]. Extensions to broader holonomic settings and algorithmic implementations are well-developed [1, 3, 7]. D-finite and holonomic function theory provides the structural framework for guaranteed recurrence existence [8, 5]. Standard references in symbolic computation and hypergeometric summation include [2, 4].

Most prior work emphasizes existence, completeness classes, and algorithm design. Our contribution is orthogonal: under bounded ansatz regimes, representation choice (gauge) appears to govern practical reachability, and recurrence-derived denominator guidance appears to reduce cost substantially.




Figure 1: The core observation: same identity and same budget, but different gauges lead to qualitatively different reachability outcomes.

3 Background and Definitions

3.1 Families

We study:

- Binomial-power: $F_r(n, k) = \binom{n}{k}^r$, $r \in \{1, 2, 3, 4\}$.
- Weighted-binom: $F(n, k) = k \binom{n}{k}$ with closed-form normalized gauge $G(n, k) = \frac{k \binom{n}{k}}{n 2^{n-1}}$.
- Central Delannoy family (independent order-2 recurrence benchmark).

3.2 Gauge

Given hypergeometric $F(n, k)$, any $G(n, k) = c(n, k)F(n, k)$ with rational c is a gauge-transformed summand representation. We compare raw, closed-form, and recurrence-LHS gauges.

3.3 Reachability under budget

Fix budget $B = (D, d, s)$ with denominator set D , max certificate degree d , and max recurrence order s . A certificate is reachable under B iff search finds rational $R(n, k)$ within B and symbolic telescoping verification succeeds.

4 Structural Intuition

Let $\rho_F(n, k) = F(n+1, k)/F(n, k)$. Telescoping coefficients inherit complexity from ρ_F . Under raw combinatorial gauges, high-degree factors often persist; under closed-form normalization,

$$\rho_G = \frac{c(n+1, k)}{c(n, k)} \rho_F,$$

which can cancel dominant factors and lower certificate complexity. This motivates gauge selection as symbolic preconditioning.

5 Phenomenon A: Gauge Sensitivity and Reachability

For $\sum_k k \binom{n}{k} = n2^{n-1}$ (guided denominator ansatz, max degree 4):

Gauge	Reachable	Degree	Equations solved	Median time (s)
raw	NO	—	533	1.530
closed_form	YES	1	10	0.033
recurrence_lhs	NO	—	517	1.920

Table 1: Gauge sensitivity under fixed budget for the weighted-binom identity.

Recovered closed-form certificate:

$$R(n, k) = \frac{k-1}{2(k-n-1)}.$$

This controlled intervention (one representation change, one outcome change) is consistent with a causal interpretation of gauge-dependent reachability.

6 Phenomenon B: Guided Denominator Search Cost

For $\sum_k \binom{n}{k}^r$ with closed-form gauge:

r	Baseline cands	Guided cands	Reduction (%)	Baseline time (s)	Guided time (s)	Time red. (%)	Reach- able?	Verified
1	23	6	74	0.063	0.028	56	YES	YES
2	27	6	78	8.890	1.610	82	YES	YES
3	46	8	83	185.200	33.000	82	NO	NO
4	51	9	82	421.200	77.400	82	NO	NO

Table 2: Guided denominator selection reduces candidate set size and runtime in the binomial-power family.

Delannoy cross-family replication: baseline 22.617 s, guided 2.339 s (89.7% reduction).

7 Discussion

7.1 Qualitative boundary, not only speed

Under bounded search, representation changes can move an instance across a qualitative reachability boundary, not merely accelerate an otherwise-successful run.

7.2 Preconditioning analogy

As numerical preconditioners improve linear-system geometry, gauge changes appear to improve symbolic search geometry by reducing certificate degree and denominator complexity.

7.3 Link between A, B, and C

Phenomenon A concerns feasibility under budget; Phenomenon B concerns efficiency within feasible regimes; Phenomenon C indicates transfer of structural guidance across families.

8 Limitations and Open Questions

- Guided denominator prediction is heuristic; no completeness proof is claimed.
- Higher-order cases ($r = 3, 4$) remain unverified under current budgets.
- Failure under budget B is not non-existence.
- Closed-form gauge selection is currently manual.
- Experiments use univariate recurrences in n (orders 1 and 2 in the present benchmarks); multivariate settings are open.

9 Conclusion

Representation strongly influences certificate reachability in the tested regime. Once representation enables reachability, structural guidance promotes efficiency. This yields a practical workflow for bounded symbolic search: first optimize representation, then optimize denominator search.

A Reproducibility

Experiments are generated by `src/wz_lab.py`, with JSON/CSV traces in `results/`. Negative results are retained with full metadata (gauge, denominator candidates, equations solved, runtime), enabling explicit reachability-boundary analysis.

Code, traces, and experiment scripts are available at: <https://github.com/JoseClaudioSJr/gauge-reachability-symbolic-search>

References

- [1] Frédéric Chyzak. An extension of zeilberger’s fast algorithm to general holonomic functions. *Discrete Mathematics*, 217(1–3):115–134, 2000. doi: 10.1016/S0012-365X(99)00259-9. URL [https://doi.org/10.1016/S0012-365X\(99\)00259-9](https://doi.org/10.1016/S0012-365X(99)00259-9).
- [2] Keith O. Geddes, Stephen R. Czapor, and George Labahn. *Algorithms for Computer Algebra*. Kluwer Academic Publishers, 1992. URL <https://dl.acm.org/doi/book/10.5555/136136>.
- [3] Manuel Kauers and Peter Paule. *The Concrete Tetrahedron*. Springer, 2011. doi: 10.1007/978-3-7091-0445-3. URL <https://doi.org/10.1007/978-3-7091-0445-3>.
- [4] Wolfram Koepf. *Hypergeometric Summation: An Algorithmic Approach to Summation and Special Function Identities*. Springer, 2nd edition, 2014. doi: 10.1007/978-1-4471-6469-8. URL <https://doi.org/10.1007/978-1-4471-6469-8>.
- [5] Leonard Lipshitz. D-finite power series. *Journal of Algebra*, 122(2):353–373, 1989. doi: 10.1016/0021-8693(89)90222-6. URL [https://doi.org/10.1016/0021-8693\(89\)90222-6](https://doi.org/10.1016/0021-8693(89)90222-6).
- [6] Marko Petkovsek, Herbert S. Wilf, and Doron Zeilberger. *A=B*. A K Peters, 1996. URL <https://www.math.upenn.edu/~wilf/AeqB.html>.
- [7] Carsten Schneider. Symbolic summation assists combinatorics. *Séminaire Lotharingien de Combinatoire*, 56:1–36, 2007. URL <https://www.mat.univie.ac.at/~slc/wpapers/s56schneider.pdf>.

- [8] Richard P. Stanley. Differentiably finite power series. *European Journal of Combinatorics*, 1(2):175–188, 1980. doi: 10.1016/S0195-6698(80)80051-5. URL [https://doi.org/10.1016/S0195-6698\(80\)80051-5](https://doi.org/10.1016/S0195-6698(80)80051-5).
- [9] Herbert S. Wilf and Doron Zeilberger. An algorithmic proof theory for hypergeometric (ordinary and q) multisum/integral identities. *Inventiones Mathematicae*, 108(3):575–633, 1992. doi: 10.1007/BF02100618. URL <https://doi.org/10.1007/BF02100618>.
- [10] Doron Zeilberger. A fast algorithm for proving terminating hypergeometric identities. *Discrete Mathematics*, 80(2):207–211, 1990. doi: 10.1016/0012-365X(90)90120-7. URL [https://doi.org/10.1016/0012-365X\(90\)90120-7](https://doi.org/10.1016/0012-365X(90)90120-7).