

Yet Another Monad Tutorial

Parallel Functional Programming (DAT280)

John Hughes

Recall Input/Output in Haskell...

```
writeFile "baz" s :: IO ()
```

Write `s :: String` to file `baz`

```
readFile "foo" :: IO String
```

"An IO action
returning a String"

Read file `foo` and return its contents



"How do I get the String out of an IO String?"

```
writeFile "baz" (readFile "foo")
```

Couldn't match type 'IO String' with '[Char]'

Expected type: String

Actual type: IO String

In the second argument of 'writeFile', namely '(readFile "foo")'

Recall Input/Output in Haskell...

```
writeFile "baz" s :: IO ()
```

Write `s :: String` to file `baz`

```
readFile "foo" s :: IO String
```

"An IO action
returning a String"

Read file `foo` and return its contents

String

IO String

```
do s <- readFile "foo"  
   writeFile "baz" s } :: IO ()
```

Well typed

*Everything that
does I/O has an
IO type*

With great power...

Mutable variable
containing an a

```
import Data.IORef
```

```
newIORef    :: a -> IO (IORef a)
readIORef   :: IORef a -> IO a
writeIORef  :: IORef a -> a -> IO ()
```

```
increment :: IORef Integer -> IO Integer
```

```
increment r = do n <- readIORef r
                writeIORef r (n+1)
                return n
```

••• r++

...comes great responsibility

```
newIORef    :: a -> IO (IORef a)
readIORef   :: IORef a -> IO a
writeIORef  :: IORef a -> a -> IO ()
```

```
bad = do r <- newIORef 0
      return (increment r - increment r)
```

**+1 or
-1?**

No instance for (Num (IO Integer)) arising from a use of ‘-’
In the first argument of ‘return’, namely
‘(increment r - increment r)’

...comes great responsibility

```
newIORef    :: a -> IO (IORef a)
readIORef   :: IORef a -> IO a
writeIORef  :: IORef a -> a -> IO ()
```

```
bad = do r <- newIORef 0
        a <- increment r
        b <- increment r
        return (a - b)           -1  +1
```

Haskell forces you to *sequence* all input/output

Compare...

```
twice io = do a <- io
              b <- io
              return (a,b)
```

```
twoOf io = do a <- io
              return (a,a)
```

$\text{IO } a \rightarrow \text{IO } (a,a)$

```
*Ex> r <- newIORef 0
```

```
*Ex> twoOf (increment r)
(0,0)
```

```
*Ex> twice (increment r)  ?
(1,2)
```




WAIT!

WHAT IS GOING ON?!

Overloading in Haskell

```
*Ex> 1 + 2 :: Integer
```

```
3
```

```
*Ex> 1.0 + 2.0 :: Double
```

```
3.0
```

```
*Ex> :t (+)
```

```
(+) :: a -> a -> a
```

```
*Ex> :i Num
```

```
class Num a where
```

```
    (+) :: a -> a -> a
```

```
    (-) :: a -> a -> a
```

```
    (*) :: a -> a -> a
```

```
...
```

```
instance Num Integer -- Defined in 'GHC.Num'
```

```
instance Num Double -- Defined in 'GHC.Float'
```

```
...
```

Writing your own instances

```
data Complex a = a :+: a
```

e.g. Complex Float,
Complex Double...



```
instance Num a => Num (Complex a) where
```

```
  (x:+y) + (x':+y') = (x+x') :+: (y+y')
```

```
  (x:+y) - (x':+y') = (x-x') :+: (y-y')
```

```
  (x:+y) * (x':+y') = (x*x'-y*y') :+: (x*y'+y*x')
```

```
  ...
```

A different implementation of
(+) etc. for each type



```
sumsq x y = x*x + y*y
```

```
sumsq :: Num a => a -> a -> a
```

Handling failure in Haskell

```
*Ex> 5 `div` 2
```

```
2
```

```
*Ex> 5 `div` 0
```

```
*** Exception: divide by zero
```

```
data Maybe a =  
    Nothing  
  | Just a
```

```
safeDiv m n =  
    if n==0 then                else        m `div` n
```

```
*Ex> 5 `safeDiv` 2
```

```
Just 2
```

```
*Ex> 5 `safeDiv` 0
```

```
Nothing
```

```
1 + (a `safeDiv` b)
```

Couldn't match expected type 'Integer'
with actual type 'Maybe Integer'
In the expression: 1 + (a `safeDiv` b)



"How do I get the Integer out of a Maybe Integer?"

```
import Data.Maybe  
fromJust (Just a) = a
```

```
1 + fromJust (a `safeDiv` b) :: Maybe Integer
```

```
*Ex> 1 + fromJust (5 `safeDiv` 0)
```

```
*** Exception: Maybe.fromJust: Nothing
```

fmap () 1 + (a `safeDiv` b) Maybe Integer

Integer
->
Integer

Maybe
Integer

```
fmap :: (a->b) -> Maybe a -> Maybe b
fmap f (Just n) = Just (f n)
fmap f Nothing  = Nothing
```

```
map :: (a->b) -> [a] -> [b]
```

```
fmap :: (a->b) -> IO a -> IO b
fmap f ioA = do a <- ioA
               return (f a)
```

Overloaded fmap

```
*Ex> fmap (+1) (Just 3)  
Just 4
```

```
*Ex> fmap (+1) [1,2,3]  
[2,3,4]
```

```
*Ex> fmap (length . lines) (readFile "Ex.hs")  
37
```

```
class Functor f where  
    fmap :: (a -> b) -> f a -> f b
```

```
instance Functor Maybe ...
```

```
instance Functor [] ...
```

```
instance Functor IO ...
```

fmap () (a `safeDiv` b) **<*>**(c `safeDiv` d)

Integer

->

Integer

->

Integer

Maybe

Integer

Maybe

Integer

└──┘

Maybe

(Integer

->

Integer)

(**<*>**) :: Maybe (a -> b) -> Maybe a -> Maybe b

$(\langle * \rangle) :: \text{Maybe } (a \rightarrow b) \rightarrow \text{Maybe } a \rightarrow \text{Maybe } b$

Just **f** $\langle * \rangle$ **Just** **a** = **Just** (**f** **a**)
— $\langle * \rangle$ — = **Nothing**

We don't need **fmap** any more!

fmap **f** **maybeA** = **pure** **f** $\langle * \rangle$ **maybeA**

pure **(+)** $\langle * \rangle$ (**a** **`safeDiv`** **b**)
 $\langle * \rangle$ (**c** **`safeDiv`** **d**)

pure = **Just**

We can do the same for lists and IO!

```
(<*>) :: [a -> b] -> [a] -> [b]
```

```
fs <*> as = [f a | f <- fs, a <- as]  
pure a = [a]
```

```
(<*>) :: IO (a -> b) -> IO a -> IO b
```

```
ioF <*> ioA = do f <- ioF  
                 a <- ioA  
                 return (f a)  
pure a = return a
```

Applicative Functors

```
class Functor f => Applicative f where  
  pure    :: a -> f a  
  (<*>)   :: f (a -> b) -> f a -> f b
```

```
instance Applicative Maybe ...  
instance Applicative [] ...  
instance Applicative IO ...
```

`(a `safeDiv` b) `safeDiv` c)`

Maybe
Integer

Integer
->
Maybe
Integer

fmap

Maybe
(Maybe
Integer)

`(>>=) :: Maybe Integer ->
 (Integer -> Maybe Integer) -> Maybe Integer`

>>=

$(\gg=) :: \text{Maybe } a \rightarrow (a \rightarrow \text{Maybe } b) \rightarrow \text{Maybe } b$

Just a $\gg=$ f = f a

Nothing $\gg=$ _ = Nothing

$(\gg=) :: [a] \rightarrow (a \rightarrow [b]) \rightarrow [b]$

as $\gg=$ f = [b | a <- as, b <- f a]

$(\gg=) :: \text{IO } a \rightarrow (a \rightarrow \text{IO } b) \rightarrow \text{IO } b$

**ioA $\gg=$ f = do a <- ioA
 f a**

Monads

```
class Applicative m => Monad m where
  (>>=)  :: m a -> (a -> m b) -> m b
  return :: a -> m a
```

"bind"

```
instance Monad Maybe ...
instance Monad [] ...
instance Monad IO ...
```

We don't need (`<*>`) any more!

$$mf \text{ <*> } ma = mf \text{ >>= } (\backslash f \text{ -> } ma \text{ >>= } (\backslash a \text{ -> } \text{return } (f \text{ } a)))$$

$$\begin{array}{ccccccccccc} \uparrow & \uparrow & \uparrow & \uparrow & \uparrow & \uparrow & \uparrow & \uparrow & \uparrow \\ m \text{ (a->b)} & m \text{ a} & m \text{ (a->b)} & a\text{->b} & m \text{ a} & a & m \text{ b} & b \end{array}$$

The Meaning of `do`

```
do a <- ma  
    body...
```

```
ma >>= (\a -> do body...)
```

```
do ma  
    body...
```

```
do _ <- ma  
    body...
```

```
do ma
```

```
ma
```

```
do s <- readFile "foo"  
    writeFile "baz" s
```

```
readFile "foo" >>= (\s ->  
    do writeFile "baz" s)
```

```
readFile "foo" >>= (\s ->  
    writeFile "baz" s)
```

What have we seen so far?

Maybe a, [a], IO a — all "ways of producing" **a**s

```
class Functor f where  
  fmap :: (a -> b) -> f a -> f b
```

```
class Functor f => Applicative f where  
  pure  :: a -> f a  
  (<*>) :: f (a -> b) -> f a -> f b
```

```
class Applicative m => Monad m where  
  (>>=) :: m a -> (a -> m b) -> m b  
  return :: a -> m a
```

do-notation

Libraries that work with any **Monad/Applicative/Functor**



Designing a parsing library

What should the type of a parser be?

```
type Parser a = String -> a
```

Suppose we have **number :: Parser Integer**

```
*Ex> number "123"
```

```
123
```

```
*Ex> number "123,456"
```

```
*** Exception: Ex.hs:79:1-53: Non-exhaustive patterns  
in function number
```

Designing a parsing library

What should the type of a parser be?

```
type Parser a = String -> Maybe
```

Suppose we have `number :: Parser Integer`

```
*Ex> number "123"
```


```
Just 123
```

```
*Ex> number "123,456"
```

```
Nothing
```

```
Just 123
```

```
Just (123, ",456")
```



How can I *reuse*
number to parse a
sequence of numbers?

Designing a parsing library

What should the type of a parser be?


```
type Parser a = String -> Maybe (a, String)
```

Suppose we have `number :: Parser Integer`

```
*Ex> number "123"  
Just (123, "")
```

```
*Ex> number "123,456"  
Just (123, ",456")
```

```
*Ex> number "-123"  
Nothing
```



The type defines a
calling convention
for parsing functions

Designing a parsing library


What should the type of a parser be?

```
type Parser a = String -> Maybe (a, String)
```

Suppose we have `number :: Parser Integer`

```
*Ex> number "123"  
Just (123, "")
```

```
*Ex> number "123,456"  
Just (123, ",456")
```



The type defines a
calling convention
for parsing functions

```
*Ex> number "-123"  
Nothing  
newtype = Parser (
```

Example: a basic parser

```
newtype Parser a = Parser (String -> Maybe (a,String))
```

```
literal :: Char -> Parser Char
```

```
literal c = Parser $  
  case s of  
    x:xs | x==c -> Just (x,xs)  
    _          -> Nothing
```

```
unParser (Parser p) = p
```

```
*Ex> unParser (literal 'a') "abc"  
Just ('a',"bc")
```

```
*Ex> unParser (literal 'a') "bc"  
Nothing
```

The Parser Monad

```
instance Monad Parser where
```

```
  return a = Parser $ \s -> Just (a,s)
```

```
  Parser a    a -> Parser b
```

```
  Parser p >>= f = Parser $ \s ->
```

```
    p s >>= \(a,s') -> let Parser p' = f a in p' s'
```

Maybe

(a,String)

(b,String)

Parser b

```
instance Applicative Parser where
```

```
  pure = return
```

```
  (<*>) = ap
```

```
import Control.Monad
```

```
instance Functor Parser where
```

```
  fmap f x = pure f <*> x
```

"123,456"

```
twoNumbers = do m <- number
               literal ','
               n <- number
               return (m,n)
```

***Ex>** unParser twoNumbers "123,456"
Just ((123,456), "")

twoNumbers = (,) <\$> number <* literal ',' <*> number

$(\langle * \rangle) :: f\ a \rightarrow f\ b \rightarrow f\ a$

$(\langle \$ \rangle) :: (a \rightarrow b) \rightarrow f\ a \rightarrow f\ b$

Parsing a digit

```
satisfies :: (Char->Bool) -> Parser Char
```

```
satisfies p = Parser $ \s ->  
  case s of  
    x:xs | p x -> Just (x,xs)  
    _      -> Nothing
```

```
*Ex> unParser (satisfies isDigit) "123"  
Just ('1',"23")
```

```
*Ex> unParser (satisfies isDigit) "456"  
Just ('4',"56")
```

```
import Data.Char
```


Choosing between alternatives

```
class Applicative f => Alternative f where
  empty :: f a
  (<|>) :: f a -> f a -> f a
```

```
instance Alternative Maybe where
  empty = Nothing
```

```
Just a <|> _ = Just a
Nothing <|> b = b
```

```
instance Alternative [] where
  empty = []
  xs <|> ys = xs ++ ys
```

```
instance Alternative IO ???
```

Choosing between parsers

```
instance Alternative Parser where
  empty = Parser $ \s -> empty
  Parser f <|> Parser g = Parser $ \s -> f s <|> g s
```

```
many, some :: Alternative f => f a -> f [a]
```

```
many p = some p <|> pure []
```

```
some p = (:) <$> p <*> many p
```

Parsing numbers

```
*Ex> unParser (satisfies isDigit) "123,456"  
Just ('1',"23,456")
```

```
*Ex> unParser (some (satisfies isDigit)) "123,456"  
Just ("123",",456")
```

```
*Ex> unParser (read <$> some (satisfies isDigit) :: Parser Integer)  
"123,456"  
Just (123,",456")
```

```
number :: Parser Integer  
number = read <$> some (satisfies isDigit)
```

Parsing a list of numbers

```
listOfNumbers :: Parser [Integer]
```

```
listOfNumbers = (*>) :: f a -> f b -> f b  
  (:) <$> number <*> many (literal ',' *> number)
```

```
*Ex> unParser listOfNumbers "12,34,5"  
Just ([12,34,5], "")
```

```
listOfNumbers = commaSeparated number
```

```
commaSeparated p =  
  (:) <$> p <*> many (literal ',' *> p)  
  <|> pure []
```

Monad transformers: libraries to build monads

```
newtype Parser a = Parser (StateT String Maybe a)
```

```
newtype StateT s m a = StateT (s -> m (a, s))  
                        Control.Monad.State
```

```
class Monad m => MonadState s m | m -> s where  
  get  :: m s  
  put  :: s -> m ()
```

```
{-# LANGUAGE GeneralizedNewtypeDeriving,  
      FlexibleContexts #-}
```

```
module PL where
```

```
import Control.Applicative  
import Control.Monad.State
```

```
newtype Parser a = Parser (StateT String Maybe a)  
  deriving (Functor, Applicative, Alternative, Monad,  
           MonadState String)
```

```
runParser (Parser p) = runStateT p
```

```
satisfies p = do  
  s <- get  
  case s of  
    x:xs | p x -> do put xs  
                  return x  
    _      -> empty
```

```
literal c = satisfies (==c)
```

A Simple Calculator

***Calc>** runParser expr "1+2+3"
Just (6.0, "")

1 (- 2) (- 3)

***Calc>** runParser expr "1-2-3"
Just (-4.0, "")

***Calc>** runParser expr "1+2*3+4*5"
Just (27.0, "")

()

***Calc>** runParser expr "(1+2)/(3+4)"
Just (0.42857142857142855, "")

```
module Calc where
```

```
import Data.Char
import Control.Applicative
```

```
import PL
```

```
expr :: Parser Double
```

```
expr = leftAssoc term (plusMinus <*> term)
```

```
term = leftAssoc factor (timesDiv <*> factor)
```

```
factor = number
```

```
    <|> literal '(' *> expr <*> literal ')'
```

```
number = read <$> some (satisfies isDigit)
```

```
plusMinus = flip <$> ((+) <$ literal '+' <|> (-) <$ literal '-')
```


```
timesDiv = flip <$> ((*> <$ literal '*' <|> (/) <$ literal '/')
```

```
leftAssoc pa pb = do
```

```
  a <- pa
```

```
  bs <- many pb
```

```
  return (foldl (flip id) a bs)
```



expr ::= term ((+|-) term)*
term ::= factor ((*|/) factor)*
factor ::= digit+ | '(' expr ')'

Not a complete parsing library...

- White space
- Separate lexical analysis
- Error messages and locations
- Layout-sensitive parsing
- Operator precedences
- ...

Comprehending Monads

Philip Wadler
University of Glasgow*

1 *monads* in the 1960's to
pects of universal algebra.
vented *list comprehensions*
express certain programs in-

ture by straightforward th
stance, a counter can be sin
evant functions to accept a
counter
(the c

Lisp & FP'90

1340



Imperative functional programming

Simon L Peyton Jones

Philip Wadler

Dept of Computing Science, University of Glasgow
Email: {simonpj,wadler}@dcs.glasgow.ac.uk

' model, based on monads, for perform-
in a non-strict, purely functional lan-
osable. extensible. efficient. requires no

grams that do so (Section 2). Comb
order fir
highly
perform

POPL'93

783



FUNCTIONAL PEARL

Applicative programming with effects

CONOR MCBRIDE¹

University of Nottingham

ROSS PATERSON


City University, London

Abstract

In this article, we introduce **Applicative** functors – an abstract characterisation of an applicative style of effectful programming, weaker than Monads and **Comonads**. Indeed, it is the ubiquity of this programming pattern that drives

JFP'08

565



FUNCTIONAL PEARL

Monadic parsing in Haskell

GRAHAM HUTTON

University of Nottingham, Nottingham, UK

ERIK MEIJER

University of Utrecht, Utrecht, The Netherlands

1 Introduction

This paper is a tutorial on defining recursive descent parsers in Haskell. In the spirit of *one-stop shopping*, the paper combines material from three areas into a single source. The three areas are functional parsers (Burge, 1987),

JFP'98

247

