

Zurich ServiceNow AI Platform Capabilities

Last updated: January 16, 2026

Some examples and graphics depicted herein are provided for illustration only. No real association or connection to ServiceNow products or services is intended or should be inferred.

This PDF was created from content on docs.servicenow.com. The web site is updated frequently. For the most current ServiceNow product documentation, go to docs.servicenow.com.

Company Headquarters

2225 Lawson Lane
Santa Clara, CA 95054
United States
(408)501-8550

API Service Graph Connectors

You can use an API Service Graph Connector to import and integrate third-party API data into CMDB tables.

Important: Visit the [ServiceNow Store](#) website to view the latest list of all API Service Graph Connectors.

Select a technology to learn about the API Service Graph Connector available for ingesting data from an application using the technology into your CMDB.



AWS API Gateway



Azure API Management



Kong Gateway



Kong Connect

API Service Graph Connector for Apigee X

Use the ServiceNow® API Service Graph Connector for Apigee X to import API proxy details from an Apigee X application into the Configuration Management Database (CMDB).

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Key features

Import data into a normalized data model for consistency across other technologies.

The API Insights workspace provides a centralized interface where you can analyze and interact with API data, without needing direct access to Apigee X, enhancing visibility, governance, and collaboration across the API estate. To learn more, see [API Insights](#).

Supported ServiceNow versions

- Xanadu
- Yokohama
- Zurich

Use cases

You can use the API Service Graph Connector for Apigee X to:

- Maintain an end-to-end inventory of exposed and backend APIs, identifying what APIs are published, used, and by whom.
- Track APIs from customer-facing endpoints to the underlying services, identifying impacted endpoints when services change or fail and creating incidents for reported issues.
- Address vulnerabilities and security incidents related to API endpoints, and create compliance requirements to measure against.

Important information for upgrading API Service Graph Connector for Apigee X

If you're an existing customer using production instances, reach out to Now Support before upgrading to API Service Graph Connector for Apigee X v2.3.0. This upgrade alters source native keys that can impact Source [sys_object_source] table records. Coordinating with Now Support helps to prevent duplicate record creation.

Configuring a connection for the connector

You can configure a connection for the connector by using the SGC Central view in the CMDB Workspace. The view enables you to discover

and install connectors, and then effectively manage the full life cycle of creating, editing, monitoring, and debugging connections. To configure the connector using SGC Central, see [Configure API Service Graph Connector for Apigee X using SGC Central](#).

Data mapping

Data from the Apigee X data sources is mapped and transformed into the CMDB Configuration Item (CI) class definitions using the Robust Transform Engine (RTE). Data is inserted into the CMDB using the Identification and Reconciliation Engine (IRE).

When you complete setting up the connection, you can configure the integration to periodically pull data from an Apigee X application.

The following table lists the data sources in the order that they run, the staging tables, and the target tables as CMDB CI and non-CMDB classes for an Apigee X application.

Data mapping for Apigee X

Data source	Staging table	Target tables
Apigee Organization	SGA Apigee X Apigee Organization [sn_apigee_x_apigee_organization]	Google Organization Project Apigee API Gateway
Managed API	SGA Apigee X Managed API [sn_apigee_x_sga_apigee_x_managed_api]	Managed API API Deployment Apigee API Gateway
API Consumer	SGA Apigee X API Consumer [sn_apigee_x_sga_apigee_x_api_consumer]	API Consumer
API Frontend Backend	SGA Apigee X Frontend Backend [sn_apigee_x_sga_apigee_x_frontend_backend]	API Frontend API Backend

Data source	Staging table	Target tables
	gee_x_frontend_backend]	
API Product	SGA Apigee X API Product [sn_apigee_x_sga_api gee_x_api_product]	API Product Bundle Key Value
API Consumer Subscription	SGA Apigee X API Consumer Subscription [sn_apigee_x_sga_api gee_x_api_consumer_subscription]	API Consumer Subscription Key Value
API Consumer Access	SGA Apigee X API Consumer Access [sn_apigee_x_sga_api gee_x_api_consumer_access]	API Consumer Access
GCP Organization	SGA Apigee X Organization [sn_apigee_x_sga_api gee_x_organization]	Cloud Organizations
GCP Folder	SGA Apigee X Folder [sn_apigee_x_sga_api gee_x_folder]	Google Organization Folder
GCP Project	SGA Apigee X Project [sn_apigee_x_sga_api gee_x_project]	Google Organization Project

For more information on where data is saved when pulling data from an Apigee X application, see [Target tables for storing API Service Graph Connector for Apigee X data](#).

You can use the IntegrationHub ETL app to view the data maps. See [IntegrationHub ETL](#) for more information.

Record removal process

The connector supports soft deletion for CMDB CI classes only, meaning records aren't permanently removed from the system. Instead, any CMDB CI records not discovered during the last scheduled job run are marked as **Non-Operational**.

Configure API Service Graph Connector for Apigee X using SGC Central

Set up scheduled import jobs to pull in Apigee X data into your CMDB.

Before you begin

Install API Service Graph Connector for Apigee X version 1.0.0 or later from the ServiceNow Store. For ServiceNow Store installation steps, see [Install a ServiceNow Store application](#).

Role required: The following table shows the roles required for each stage of the playbook.

Role required for each playbook stage

Stage	Role
Prerequisites	admin
Setup	cmdb_inst_admin or admin

About this task

The playbook experience for onboarding connectors is activated with SGC Central in the CMDB Workspace. To configure the SGC Central application, see [Configuring SGC Central](#) and for more information on how to interact with a playbook, see [Interact with Playbook](#).

Note: Alternatively, you can configure a default connection already available from the installed or draft connections in SGC Central. Go to **All > Service Graph Connectors**, then select **Setup** for the connector from the menu. To learn about installed and draft connections, see [Managing connections added for Service Graph Connectors in SGC Central](#).

Procedure

1. Navigate to **Workspaces > CMDB Workspace**.
2. In the CMDB Workspace, select **SGC Central**.
3. On the Overview page, select **Create connection**.

Tip: Alternatively, you can select **Create connection** on the All connections page.
4. On the Create connection window, select the Apigee X connector type, and then select **Create connection**.
5. Complete the initial prerequisites when setting up a connection for the first time using a connector.

Note: This step is required only during the first-time setup. See [Perform initial setup tasks when creating a connection in SGC Central](#).
6. Complete the prerequisites for setting up the Apigee X environment.
 - a. Set up the Apigee X environment and create a Java KeyStore (JKS) certificate to encrypt the security certificates obtained from an Apigee X application.
 - a. In the **Prerequisites** stage of the playbook, select the **Review setup instructions** activity.
 - b. Review and complete the setup instructions on the [API Service Graph connector for Apigee X - Setup Instructions \[KBB0010364\]](#) article in the Now Support Knowledge Base.

You must create a service account, assign roles, bind roles to the service account, enable APIs, create a P12 file, and register it in your ServiceNow instance.

Make a note of the destination keystore password. You need to specify this password while importing the JKS certificate into the API Service Graph Connector for Apigee X application.

- c. Select the **I have read the setup instructions** check box to confirm that you have set up the Apigee X environment according to the instructions.
- d. Select **Continue**.
- b. Create an X.509 certificate to associate the Java KeyStore (JKS) certificate for the Apigee X application with the connector.

Note: You can skip this step if you're reusing a previously created certificate.

- a. In the **Prerequisites** stage of the playbook, select the **Create X.509 certificate** activity.
- b. On the form, fill in the fields.

X.509 Certificate form

Field	Description
Name	Name of the X.509 certificate. For example, ApigeeX-509Certificate.
Key store password	Password to access the JKS certificate as noted down in the previous step .
Short description	Description of the X.509 certificate.

- c. In the Attachments section, select **Add File**.

- d. Browse and select the P12 file for the JKS certificate you created in the [previous step](#).
 - e. On the Upload a file dialog box, select **Upload**.
 - f. Select **Continue**.
7. Enter connection details and test the API connection for importing Apigee X data.
 - a. In the **Setup** stage of the playbook, select the **Create and test connection** activity.
 - b. On the form, fill in the fields.

Configure and test connection form

Field	Description
Connection name	Name to identify the Apigee X connection record.
Service account email	Email address associated with the ServiceNow service account used for authentication with Apigee X as noted in the previous step .
X.509 certificate	Name of the X.509 certificate as noted in the previous step .
Keystore password	Password associated with the keystore as noted in the previous step .

- c. Select **Create and test connection**.
 - d. Once the connection test is complete, select **Continue**.
8. Set the configuration properties for the connection.
 - a. In the **Setup** stage of the playbook, select the **Set configuration properties** activity.
 - b. Enter the properties.

Service Graph Connection Properties

Property	Description
Apigee identification	
Apigee organization name/GCP project id	Apigee X organization names or GCP project IDs from which data should be fetched. If left blank, data is retrieved from all permitted Apigee X organizations. For multiple values, separate them with commas.
Data retrieval configuration	
Include environments	Apigee X environments to include in the connection. For multiple environments, separate them with commas. Only API proxies in the environments listed in the Include environments property are imported. If you leave this field empty, the data sources within the connector import API proxies from all environments.
Collection period (in days)	Duration in days for collecting API usage data.
Collect usage data	Option to enable usage data collection to retrieve API usage data over a specified duration.

Property	Description
Apigee identification	
Expand HTTP method types	HTTP methods including GET, POST, PUT, PATCH, DELETE, OPTIONS, HEAD, CONNECT, and TRACE, to consider for routes. For multiple methods, separate them with commas. If left blank, results in a single API Frontend being created with the ALL method, indicating support for all standard HTTP methods.
GCP identification	
GCP Organization id	GCP organization ID for retrieving data from GCP Organization, GCP Folder, and GCP Project data sources.

c. Select **Continue**.

9. Configure the import schedule to import data at regular intervals.

- a. In the **Setup** stage of the playbook, select the **Configure import schedule** activity.
- b. Expand the Parent scheduled data import within the Import schedules list to select the **Apigee Organization** import schedule associated with your connection.

Note: The connection name is prefixed to the schedule name.

- c. In the Configure import schedule dialog box, select the **Active** check box, and then fill in the run schedule and time details.

For more information, see [Schedule a data import](#).

d. Select **Save**.
Alternatively, select **Execute Now** to execute the import schedule immediately.

e. Select **Continue**.

10. In the **Setup** stage of the playbook, select the **Confirm connection creation** activity to verify whether the connection was created.

What to do next

Select **View all connections** to review the connection details. The configured connection appears in the Installed connections list.

You can then manage connections from the SGC Central view of the CMDB Workspace. For more information, see [Managing connections added for Service Graph Connectors in SGC Central](#).

Related concepts

- [API Service Graph Connector for Apigee X](#)

Related reference

- [Target tables for storing API Service Graph Connector for Apigee X data](#)

Target tables for storing API Service Graph Connector for Apigee X data

When you complete setting up the connection, you can configure the integration to periodically pull data from an Apigee X application. The data is saved in tables that extend from the Configuration item [cmdb_ci] classes and other non-CMDB tables.

Google Organization Project [cmdb_ci_gcp_project]

The following attributes in the Google Organization Project [cmdb_ci_gcp_project] table are populated by collected data:

Attribute label	Attribute name
Parent	parent_ci
Name	name
Object ID	object_id
Install Status	install_status
Operational status	operational_status
Parent Id	parent_id
Parent Type	parent_type
Project Id	project_id
Time	time

Relationships created for Google Organization Project

Parent class	Relationship type	Child class
Google Organization Project [cmdb_ci_gcp_project]	Reference	Cloud Organizations [cmdb_ci_cloud_org]
Google Organization Project [cmdb_ci_gcp_project]	Reference	Google Organization Folder [cmdb_ci_gcp_folder]
Google Organization Project [cmdb_ci_gcp_project]	Contains::Contained by	Apigee API Gateway [cmdb_ci_apigee_api_gateway]

Apigee API Gateway [cmdb_ci_apigee_api_gateway]

The following attributes in the Apigee API Gateway [cmdb_ci_apigee_api_gateway] table are populated by collected data:

Attribute label	Attribute name
ID	id
Name	name
Install Status	install_status
Operational status	operational_status

Relationships created for Apigee API Gateway

Parent class	Relationship type	Child class
Apigee API Gateway [cmdb_ci_apigee_api_gateway]	Provides::Provided by	Managed API [cmdb_ci_managed_api]
Apigee API Gateway [cmdb_ci_apigee_api_gateway]	Reference	API Consumer [api_consumer]
Apigee API Gateway [cmdb_ci_apigee_api_gateway]	Provides::Provided by	API Consumer Subscription [cmdb_ci_api_consumer_subscription]
Apigee API Gateway [cmdb_ci_apigee_api_gateway]	Provides::Provided by	API Product Bundle [cmdb_ci_api_product_bundle]

Managed API [cmdb_ci_managed_api]

The following attributes in the Managed API [cmdb_ci_managed_api] table are populated by collected data:

Attribute label	Attribute name
Description	short_description
Life Cycle Stage	life_cycle_stage
ID	id
Name	name
Version	version
Base URL	base_url
Model ID	model_id
Correlation ID	correlation_id
Life Cycle Stage Status	life_cycle_stage_status
Operational status	operational_status

Relationships created for Managed API

Parent class	Relationship type	Child class
Managed API [cmdb_ci_managed_api]	Uses::Used by	API Frontend [cmdb_ci_api_frontend]
Managed API [cmdb_ci_managed_api]	Uses::Used by	API Backend [cmdb_ci_api_backend]
Managed API [cmdb_ci_managed_api]	Reference	API Deployment [api_deployment]
Managed API [cmdb_ci_managed_api]	Uses::Used by	DNS Alias [cmdb_ci_dns_alias]

API Deployment [api_deployment]

The following attributes in the API Deployment [api_deployment] table are populated by collected data:

Attribute label	Attribute name
API	api
Name	name

API Consumer [api_consumer]

The following attributes in the API Consumer [api_consumer] table are populated by collected data:

Attribute label	Attribute name
ID	id
API Gateway	api_gateway
Custom ID	custom_id
Email	email
Registration Date	registration_date
Username	username

API Frontend [cmdb_ci_api_frontend]

The following attributes in the API Frontend [cmdb_ci_api_frontend] table are populated by collected data:

Attribute label	Attribute name
API Version	api_version
Host	host
Method	method

Attribute label	Attribute name
Path	path
URL	url
Description	short_description
Name	name
Operational status	operational_status
Protocol	protocol

Relationship created for API Frontend

Parent class	Relationship type	Child class
API Frontend [cmdb_ci_api_frontend]	Use End Point To::Use End Point From	API Backend [cmdb_ci_api_backend]

API Backend [cmdb_ci_api_backend]

The following attributes in the API Backend [cmdb_ci_api_backend] table are populated by collected data:

Attribute label	Attribute name
URL	url
Name	name
Operational status	operational_status
Type	type

API Product Bundle [cmdb_ci_api_product_bundle]

The following attributes in the API Product Bundle [cmdb_ci_api_product_bundle] table are populated by collected data:

Attribute label	Attribute name
ID	id
Creation Date	creation_date
Description	short_description
Discovered Access Type	discovered_access_type
Discovered Approval Type	discovered_approval_type
Last Modified Date	last_modified_date
Name	name
Operational status	operational_status

Relationships created for API Product Bundle

Parent class	Relationship type	Child class
API Product Bundle [cmdb_ci_api_product_bundle]	Contains::Contained by	API [cmdb_ci_api]
API Product Bundle [cmdb_ci_api_product_bundle]	Used by::Uses	API Consumer Subscription [cmdb_ci_api_consumer_subscription]
API Product Bundle [cmdb_ci_api_product_bundle]	Reference	Key Value [cmdb_key_value]

Key Value [cmdb_key_value]

The following attributes in the Key Value [cmdb_key_value] table are populated by collected data:

Attribute label	Attribute name
Tag	tag
Configuration item	configuration_item
Key	key
Value	value

API Consumer Subscription [cmdb_ci_api_consumer_subscription]

The following attributes in the API Consumer Subscription [cmdb_ci_api_consumer_subscription] table are populated by collected data:

Attribute label	Attribute name
ID	id
Creation Date	creation_date
API Consumer	api_consumer
Discovered State	discovered_state
Last Modified Date	last_modified_date
Name	name
Operational status	operational_status

Relationship created for API Consumer Subscription

Parent class	Relationship type	Child class
API Consumer Subscription [cmdb_ci_api_consumer_subscription]	Reference	Key Value [cmdb_key_value]

API Consumer Access [api_consumer_access]

The following attributes in the API Consumer Access [api_consumer_access] table are populated by collected data:

Attribute label	Attribute name
Auth Method	access_type
State	state
Valid to	valid_to
API Product Bundle	api_product_bundle
API Consumer Subscription	api_consumer_subscription
API	api
API Consumer	api_consumer

Cloud Organizations [cmdb_ci_cloud_org]

The following attributes in the Cloud Organizations [cmdb_ci_cloud_org] table are populated by collected data:

Attribute label	Attribute name
Object ID	object_id
Install Status	install_status
Name	name
Operational status	operational_status
Time	time

Relationship created for Cloud Organizations

Parent class	Relationship type	Child class
Cloud Organizations [cmdb_ci_cloud_org]	Contains::Contained by	Google Organization Folder [cmdb_ci_gcp_folder]

Google Organization Folder [cmdb_ci_gcp_folder]

The following attributes in the Google Organization Folder [cmdb_ci_gcp_folder] table are populated by collected data:

Attribute label	Attribute name
Parent	parent_ci
Object ID	object_id
Install Status	install_status
Name	name
Operational status	operational_status
Parent Id	parent_id
Parent Type	parent_type
Time	time

Relationships created for Google Organization Folder

Parent class	Relationship type	Child class
Google Organization Folder [cmdb_ci_gcp_folder]	Reference	Google Organization Folder [cmdb_ci_gcp_folder]
Google Organization Folder [cmdb_ci_gcp_folder]	Reference	Cloud Organizations [cmdb_ci_cloud_org]

DNS Alias [cmdb_ci_dns_alias]

The following attributes in the DNS Alias [cmdb_ci_dns_alias] table are populated by collected data:

Attribute label	Attribute name
Name	name
Operational status	operational_status

Accessing the connection details of API Service Graph Connector for Apigee X

You can access the connection details of the API Service Graph Connector for Apigee X in a single view using the common connection framework (CCF) included within the Integration Commons for CMDB (sn_cmdb_int_util) store app.

With the CCF, you can access all the connections used by the API Service Graph Connector for Apigee X. The connection details include the connection alias, connection properties, data sources, and scheduled data imports associated with a connection. You can also test the connection. For more information, see [Accessing the connection details of Service Graph Connectors](#).

Access the details of an Apigee X connection

Access the details of an Apigee X connection configured for the API Service Graph Connector for Apigee X.

Before you begin

Role required: admin

Procedure

1. Navigate to **All > Service Graph Connectors > Apigee X > Connections**.
2. From the **Name** column of the Service Graph Connections list, select a connection.

3. On the Service Graph Connections page, view the connection details such as the connection name and alias.
4. Select a related list to view further details of the connection.
5. (Optional) Select the **Test Connection** related link to test the connection.

API Service Graph Connector for AWS API Gateway

Use the ServiceNow® API Service Graph Connector for AWS API Gateway to import API details from an AWS API Gateway service into the Configuration Management Database (CMDB).

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Key features

Import data into a normalized data model for consistency across other technologies.

The API Insights workspace provides a centralized interface where you can analyze and interact with API data, without needing direct access to AWS API Gateway, enhancing visibility, governance, and collaboration across the API estate. To learn more, see [API Insights](#).

Supported ServiceNow versions

- Washington DC
- Xanadu
- Yokohama
- Zurich

Use cases

You can use the API Service Graph Connector for AWS API Gateway to:

- Maintain an end-to-end inventory of defined APIs, identifying what APIs are published, used, and by whom.
- Track APIs from customer-facing endpoints to the underlying services, identifying impacted endpoints when services change or fail and creating incidents for reported issues.
- Address vulnerabilities and security incidents related to API endpoints, and create compliance requirements to measure against.

Configuring a connection for the connector

You can configure a connection for the connector by using the SGC Central view in the CMDB Workspace. The view enables you to discover and install connectors, and then effectively manage the full life cycle of creating, editing, monitoring, and debugging connections. To configure the connector using SGC Central, see [Configure API Service Graph Connector for AWS API Gateway using SGC Central](#).

Data mapping

Data from the AWS API Gateway data sources is mapped and transformed into the CMDB Configuration Item (CI) class definitions using the Robust Transform Engine (RTE). Data is inserted into the CMDB using the Identification and Reconciliation Engine (IRE).

When you complete setting up the connection, you can configure the integration to periodically pull data from an AWS API Gateway service.

The following table lists the data sources in the order they run, the staging tables, and the target tables as CMDB CI and non-CMDB classes for an AWS API Gateway service.

Data mapping for AWS API Gateway

Data source	Staging table	Target tables
Managed API Rest	SGA-AWS Managed API Rest [sn_aws_api_gw_int_api_gateway_managed_api_import_set]	AWS API Gateway DNS Alias Managed API

Data source	Staging table	Target tables
		Key Value
Managed API V2	SGA-AWS Managed API V2 [sn_aws_api_gw_int_sga_aws_managed_api_v2]	Managed API AWS API Gateway DNS Alias Key Value
Frontend Backend REST	SGA-AWS Frontend-Backend REST [sn_aws_api_gw_int_sga_aws_frontend_backend_rest]	API Backend API Frontend
Backend V2	SGA-AWS Backend V2 [sn_aws_api_gw_int_sga_aws_backend_v2]	API Backend
Frontend V2	SGA-AWS Frontend V2 [sn_aws_api_gw_int_sga_aws_frontend_v2]	API Frontend
Deployment Rest	SGA-AWS API Gateway Deployment Rest [sn_aws_api_gw_int_sga_aws_api_gateway_deployment_rest]	API Deployment
Deployment V2	SGA-AWS API Gateway Deployment V2 [sn_aws_api_gw_int_sga_aws_api_gateway_deployment_v2]	API Deployment

Data source	Staging table	Target tables
Consumer	SGA-AWS Consumers [sn_aws_api_gw_int_sg a_aws_consumers]	API Consumer
Policies	SGA-AWS API Gateway Policies [sn_aws_api_gw_int_sg a_aws_api_gateway_ policies]	API Policy
API Consumer Access	SGA-AWS-API- Consumer-Access [sn_aws_api_gw_int_sg a_aws_api_consumer_ access]	API Consumer Access

For more information on where data is saved when pulling data from an AWS API Gateway service, see [Target tables for storing API Service Graph Connector for AWS API Gateway data](#).

You can use the IntegrationHub ETL app to view the data maps. See [IntegrationHub ETL](#) for more information.

Record removal process

The connector supports soft deletion for CMDB CI classes only, meaning records are not permanently removed from the system. Instead, any CMDB CI records not discovered during the last scheduled job run are marked as **Non-Operational**.

Configure API Service Graph Connector for AWS API Gateway using SGC Central

Set up scheduled import jobs to pull in AWS API Gateway data into your CMDB.

Before you begin

Install API Service Graph Connector for AWS API Gateway version 1.0.0 or later from the ServiceNow Store. For ServiceNow Store installation steps, see [Install a ServiceNow Store application](#).

The authentication mechanism used by the connector is AWS Signature Type (HMAC Authentication Technique) with AWS Security Token Service (STS) token. For information about permissions, see the [API Service Graph Connector for AWS API Gateway - Setup Instructions \[KB1962734\]](#) article in the Now Support Knowledge Base.

Role required: The following table shows the roles required for each stage of the playbook.

Role required for each playbook stage

Stage	Role
Prerequisites	admin
Setup	cmdb_inst_admin or admin

About this task

The playbook experience for onboarding connectors is activated with SGC Central in the CMDB Workspace. To configure the SGC Central application, see [Configuring SGC Central](#) and for more information on how to interact with a playbook, see [Interact with Playbook](#).

Note: Alternatively, you can configure a default connection already available from the installed or draft connections in SGC Central. Go to **All > Service Graph Connectors**, then select **Setup** for the connector from the menu. To learn about installed and draft connections, see [Managing connections added for Service Graph Connectors in SGC Central](#).

Procedure

1. Navigate to **Workspaces > CMDB Workspace**.

2. In the CMDB Workspace, select **SGC Central**.
3. On the Overview page, select **Create connection**.

Tip: Alternatively, you can select **Create connection** on the All connections page.
4. On the Create connection window, select the AWS API Gateway connector type, and then select **Create connection**.
5. Complete the initial prerequisites when setting up a connection for the first time using a connector.

Note: This step is required only during the first-time setup. See [Perform initial setup tasks when creating a connection in SGC Central](#).
6. Enter connection details and test the API connection for importing AWS API Gateway data.
 - a. In the **Setup** stage of the playbook, select the **Create and test connection** activity.
 - b. On the form, fill in the fields.

Create and test connection form

Field	Description
AWS API Gateway Connection Name	Name to identify the AWS API Gateway connection record. For example, SG-AWS-API-Gateway connection.
Access Key	Access key ID of the IAM user that has permissions to interact with the AWS resources.
Secret Key	Secret access key that corresponds to the Access key ID required for authenticating the connection securely.

- c. Select **Create and test connection**.
 - d. Once the connection test is complete, select **Continue**.
7. (Optional) Copy configuration properties from an existing AWS connection.

Note: The Copy configuration properties activity is displayed only when an AWS connection is already set up on your instance.

 - a. In the **Setup** stage of the playbook, select the **Copy configuration properties** activity.
 - b. In the **AWS Connection** field, select the connection.

The values of the following properties are copied from the selected AWS connection:

 - Standalone account ID
 - Management account ID
 - Gov cloud
 - STS assume role
 - AWS regions
 - Config aggregator name
 - Config aggregator account
 - Config aggregator region
 - c. Select **Continue**.
 - d. Once the connection test is complete, select **Continue**.
8. Set the configuration properties for the connection.
 - a. In the **Setup** stage of the playbook, select the **Set configuration properties** activity.
 - b. Fill in the property details.

Note: If you select to copy the configuration properties from an existing AWS connection, the properties listed in the step 7.b are copied from the existing connection automatically.

AWS API Gateway configuration properties

Property	Description
Management account ID or standalone account ID	
Management account ID	Management account ID associated with the AWS API Gateway account.
Standalone account ID	ID of a member account associated with the AWS API Gateway account.
STS assume role name and AWS regions	
STS assume role name	STS Assume Role name of the AWS account that is used for querying the STS Assume Role API to obtain the API credentials.
AWS regions	List of comma-separated regions where the AWS API Gateway resides.
Config aggregator setup	
Config aggregator account ID	AWS account ID where the aggregator resource type in the AWS Config service has been configured.
Config aggregator name	Name of the aggregator resource type in the AWS Config service.

Property	Description
Management account ID or standalone account ID	
Config aggregator region	Region where the aggregator resource type resides.
API usage data	
CollectUsageData	Option to enable usage data collection to retrieve API usage data over a specified duration.
Collection period in days	Duration in days for collecting API usage data.
Gov cloud setup	
Is gov cloud	Option to indicate that the connection setup is for the AWS GovCloud.

c. Select **Continue**.

9. Configure the import schedule to import data at regular intervals.

a. In the **Setup** stage of the playbook, select the **Configure import schedule** activity.

b. Expand the Parent scheduled data import within the Import schedules list to select the **Managed API Rest** import schedule associated with your connection.

Note: The connection name is prefixed to the schedule name.

c. In the Configure import schedule dialog box, select the **Active** check box, and then fill in the run schedule and time details.

For more information, see [Schedule a data import](#).

d. Select **Save**.

Alternatively, select **Execute Now** to execute the import schedule immediately.

e. Select **Continue**.

10. In the **Setup** stage of the playbook, select the **Confirm connection creation** activity to verify whether the connection was configured.

What to do next

Select **View all connections** to review the connection details. The configured connection appears in the Installed connections list.

You can then manage connections from the SGC Central view of the CMDB Workspace. For more information, see [Managing connections added for Service Graph Connectors in SGC Central](#).

Related concepts

- [API Service Graph Connector for AWS API Gateway](#)

Related reference

- [Target tables for storing API Service Graph Connector for AWS API Gateway data](#)

Target tables for storing API Service Graph Connector for AWS API Gateway data

When you complete setting up the connection, you can configure the integration to periodically pull data from an AWS API Gateway service. The data is saved in tables that extend from the Configuration item [cmdb_ci] classes and other non-CMDB classes.

AWS API Gateway [cmdb_ci_aws_api_gateway]

The following attributes in the AWS API Gateway [cmdb_ci_aws_api_gateway] table are populated by collected data:

Attribute label	Attribute name
ID	id
Name	name
Operational status	operational_status

Relationships created for AWS API Gateway

Parent class	Relationship type	Child class
AWS API Gateway [cmdb_ci_aws_api_gateway]	Provides::Provided by	Managed API [cmdb_ci_managed_api]
AWS API Gateway [cmdb_ci_aws_api_gateway]	Reference	API Policy [api_policy]
AWS API Gateway [cmdb_ci_aws_api_gateway]	Reference	API Consumer [api_consumer]
AWS API Gateway [cmdb_ci_aws_api_gateway]	Uses::Used by	DNS Alias [cmdb_ci_dns_alias]

DNS Alias [cmdb_ci_dns_alias]

The following attributes in the DNS Alias [cmdb_ci_dns_alias] table are populated by collected data:

Attribute label	Attribute name
Name	name
Operational status	operational_status

Managed API [cmdb_ci_managed_api]

The following attributes in the Managed API [cmdb_ci_managed_api] table are populated by collected data:

Attribute label	Attribute name
Life Cycle Stage Status	life_cycle_stage_status
ID	id
Name	name
Base URL	base_url
Operational status	operational_status
Life Cycle Stage	life_cycle_stage
Model ID	model_id
Type	type

Relationships created for Managed API

Parent class	Relationship type	Child class
Managed API [cmdb_ci_managed_api]	Uses::Used by	API Frontend [cmdb_ci_api_frontend]
Managed API [cmdb_ci_managed_api]	Uses::Used by	API Backend [cmdb_ci_api_backend]
Managed API [cmdb_ci_managed_api]	Reference	API Deployment [api_deployment]
Managed API [cmdb_ci_managed_api]	Reference	Key Value [cmdb_key_value]

API Frontend [cmdb_ci_api_frontend]

The following attributes in the API Frontend [cmdb_ci_api_frontend] table are populated by collected data:

Attribute label	Attribute name
Host	host
Method	method
Path	path
URL	url
Authorization	authorization
Name	name
Operational status	operational_status
Protocol	protocol

Relationship created for API Frontend

Parent class	Relationship type	Child class
API Frontend [cmdb_ci_api_frontend]	Use End Point To::Use End Point From	API Backend [cmdb_ci_api_backend]

API Backend [cmdb_ci_api_backend]

The following attributes in the API Backend [cmdb_ci_api_backend] table are populated by collected data:

Attribute label	Attribute name
ID	id
URL	url

Attribute label	Attribute name
Name	name
Operational status	operational_status
Type	type

API Consumer [api_consumer]

The following attributes in the API Consumer [api_consumer] table are populated by collected data:

Attribute label	Attribute name
ID	id
Username	username
API Gateway	api_gateway

API Consumer Access [api_consumer_access]

The following attributes in the API Consumer Access [api_consumer_access] table are populated by collected data:

Attribute label	Attribute name
API	api
API Consumer	api_consumer
State	state

API Deployment [api_deployment]

The following attributes in the API Deployment [api_deployment] table are populated by collected data:

Attribute label	Attribute name
Name	name
API	api

API Policy [api_policy]

The following attributes in the API Policy [api_policy] table are populated by collected data:

Attribute label	Attribute name
Name	name
Consumer	consumer
ID	id
Managed API	managed_api

Relationship created for API Policy

Parent class	Relationship type	Child class
API Policy [api_policy]	Reference	Managed API [cmdb_ci_managed_api]

Key Value [cmdb_key_value]

The following attributes in the Key Value [cmdb_key_value] table are populated by collected data:

Attribute label	Attribute name
Key	key
Value	value

Accessing the connection details of API Service Graph Connector for AWS API Gateway

You can access the connection details of the API Service Graph Connector for AWS API Gateway in a single view using the common connection framework (CCF) included within the Integration Commons for CMDB (sn_cmdb_int_util) store app.

With the CCF, you can access all the connections used by the API Service Graph Connector for AWS API Gateway. The connection details include the connection alias, connection properties, data sources, and scheduled data imports associated with a connection. You can also test the connection. For more information, see [Accessing the connection details of Service Graph Connectors](#).

Access the details of an AWS API Gateway connection

Access the details of an AWS API Gateway connection configured for the API Service Graph Connector for AWS API Gateway.

Before you begin

Role required: admin

Procedure

1. Navigate to **All > Service Graph Connectors > AWS API Gateway > Connections**.
2. From the **Name** column of the Service Graph Connections list, select a connection.
3. On the Service Graph Connections page, view the connection details such as the connection name and alias.
4. Select a related list to view further details of the connection.
5. (Optional) Select the **Test Connection** related link to test the connection.

API Service Graph Connector for Azure API Management

Use the ServiceNow® API Service Graph Connector for Azure API Management to import API details from an Azure API Management application into the Configuration Management Database (CMDB).

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Key features

Import data into a normalized data model for consistency across other technologies.

The API Insights workspace provides a centralized interface where you can analyze and interact with API data, without needing direct access to Azure API Management, enhancing visibility, governance, and collaboration across the API estate. To learn more, see [API Insights](#).

Supported ServiceNow versions

- Xanadu
- Yokohama
- Zurich

Use cases

You can use the API Service Graph Connector for Azure API Management to:

- Maintain an end-to-end inventory of exposed and backend APIs, identifying what APIs are published, used, and by whom.
- Track APIs from customer-facing endpoints to the underlying services, identifying impacted endpoints when services change or fail and creating incidents for reported issues.

- Address vulnerabilities and security incidents related to API endpoints, and create compliance requirements to measure against.

Configuring a connection for the connector

You can configure a connection for the connector by using the SGC Central view in the CMDB Workspace. The view enables you to discover and install connectors, and then effectively manage the full life cycle of creating, editing, monitoring, and debugging connections. To configure the connector using SGC Central, see [Configure API Service Graph Connector for Azure API Management using SGC Central](#).

Important: Unless there are configuration issues, use the SGC Central view in the CMDB Workspace to configure the connection for the connector, as the guided setup method is being deprecated.

Data mapping

Data from the Azure API Management data sources is mapped and transformed into the CMDB Configuration Item (CI) class definitions using the Robust Transform Engine (RTE). Data is inserted into the CMDB using the Identification and Reconciliation Engine (IRE).

When you complete setting up the connection, you can configure the integration to periodically pull data from an Azure API Management application.

The following table lists the data sources in the order they run, the staging tables, and the target tables as CMDB CI and non-CMDB classes for an Azure API Management application.

Data mapping for Azure API Management

Data source	Staging table	Target tables
API Management Services	SGA Azure API Management [sn_azure_api_gw_sga_azure_api_management]	Azure API Management Azure Subscription Cloud Service Account

Data source	Staging table	Target tables
		Resource Group DNS Alias
Managed API	SGA Azure Managed API [sn_azure_api_gw_sga_azure_managed_api]	Managed API
API Frontend Backend	SGA Azure API Frontend Backend [sn_azure_api_gw_sga_azure_api_frontend_backend_import]	API Frontend API Backend
API GraphQL Frontend Backend	SGA Azure API GraphQL Frontend Backend [sn_azure_api_gw_sga_azure_api_graphql_frontend_backend]	API Frontend API Backend
API Consumer	SGA Azure API Consumer [sn_azure_api_gw_sga_azure_api_consumer]	API Consumer
API Product	SGA Azure API Product [sn_azure_api_gw_sga_azure_api_product]	API Product Bundle
API Consumer Subscription	SGA Azure API Consumer Subscription [sn_azure_api_gw_sga_azure_api_subscription]	API Consumer Subscription
API Tag	API Tag [sn_azure_api_gw_api_tag]	Key Value

Data source	Staging table	Target tables
API Consumer Access	SGA Azure API Consumer Access [sn_azure_api_gw_sga_azure_managed_api]	API Consumer Access

For more information on where data is saved when pulling data from an Azure API Management application, see [Target tables for storing API Service Graph Connector for Azure API Management data](#).

You can use the IntegrationHub ETL app to view the data maps. See [IntegrationHub ETL](#) for more information.

Record removal process

The connector supports soft deletion for CMDB CI classes only, meaning records are not permanently removed from the system. Instead, any CMDB CI records not discovered during the last scheduled job run are marked as **Non-Operational**.

Configure API Service Graph Connector for Azure API Management using SGC Central

Set up scheduled import jobs to pull in Azure API Management data into your CMDB.

Before you begin

Install API Service Graph Connector for Azure API Management version 1.0.0 or later from the ServiceNow Store. For ServiceNow Store installation steps, see [Install a ServiceNow Store application](#). Obtain the OAuth credentials from your Azure administrator. Make a note of the following details:

- Application (client) ID
- Client Secret
- Directory (tenant) ID
- Connection URL

Role required: The following table shows the roles required for each stage of the playbook.

Role required for each playbook stage

Stage	Role
Prerequisites	admin
Setup	cmdb_inst_admin or admin

About this task

The playbook experience for onboarding connectors is activated with SGC Central in the CMDB Workspace. To configure the SGC Central application, see [Configuring SGC Central](#) and for more information on how to interact with a playbook, see [Interact with Playbook](#).

Note: Alternatively, you can configure a default connection already available from the installed or draft connections in SGC Central. Go to **All > Service Graph Connectors**, then select **Setup** for the connector from the menu. To learn about installed and draft connections, see [Managing connections added for Service Graph Connectors in SGC Central](#).

Procedure

1. Navigate to **Workspaces > CMDB Workspace**.
2. In the CMDB Workspace, select **SGC Central**.
3. On the Overview page, select **Create connection**.

Tip: Alternatively, you can select **Create connection** on the All connections page.
4. On the Create connection window, select the Azure API Management connector type, and then select **Create connection**.
5. Complete the initial prerequisites when setting up a connection for the first time using a connector.

Note: This step is required only during the first-time setup. See [Perform initial setup tasks when creating a connection in SGC Central](#).

6. Enter connection details and test the API connection for importing Azure API Management data.
 - a. In the **Setup** stage of the playbook, select the **Create and test connection** activity.
 - b. On the form, fill in the fields.

Create and test connection form

Field	Description
Azure API Management Connection Name	Name to identify the Azure API Management connection record. For example, <code>Azure API Management Connection</code> .
Connection URL	Base URL to connect to the Azure API Management service. Note: This field is automatically set to the URL to connect to the application. Leave the field value as is.
OAuth Client ID	Application (client) ID of your Azure client application as noted in the Before you begin section.
OAuth Client Secret	Client Secret of your Azure client application as noted in the Before you begin section.

Field	Description
OAuth Token URL	Token URL of your Azure client application. Based on the region of your Azure client application, enter the token URL in one of the following formats: - Global https://login.microsoftonline.com/<tenantid>/oauth2/v2.0/token - US Government https://login.microsoftonline.us/<tenantid>/oauth2/v2.0/token - China https://login.partner.microsoftonline.cn/<tenantid>/oauth2/v2.0/token - Germany https://login.microsoftonline.de/<tenantid>/oauth2/v2.0/token Where <tenantid> is the tenant ID of your Azure client application as noted in the Before you begin section.

c. Select **Create and test connection**.

d. Once the connection test is complete, select **Continue**.

7. (Optional) Set the configuration properties for the connection.

Note: To skip this step, select **Continue** for the **Set configuration properties** activity.

a. In the **Setup** stage of the playbook, select the **Set configuration properties** activity.

b. Fill in the property details.

Azure API Management configuration properties

Property	Description
Azure API Management connection	
Discovery Scope	Discovery scope of the Azure client application. The available options are: Management Group Select Management Group when the ServiceNow service account has access to data within the Azure management group. Subscription Select Subscription when the ServiceNow service account has access to data within the Azure subscription only.
Subscription	
Subscription Id(s)	Subscription IDs of Azure API Management services. For multiple subscription IDs, separate them with commas.

Property	Description
Azure API Management connection	
	If the discovery scope is set to Subscription and this field is left blank, all subscriptions for the specified tenant in the credentials are discovered.
Management Group	
Management Group Id(s)	Management group IDs of Azure API Management services. For multiple management groups, separate them with commas.
Get Nested Group Subscriptions	Option to enable retrieving data from all nested child subscriptions when Management Group is set as the discovery scope. Disable the property to exclude nested child subscriptions.
Optional Exclusive Configuration	
ExcludeServices	Azure API Management services that should be excluded from the connection. For multiple services, separate them with commas. All gateways except those listed

Property	Description
Azure API Management connection	
	in the ExcludeServices property are fetched.
ResourceGroups	Resource group name of Azure API Management services. For multiple resource groups, separate their names with commas. If you leave this field empty, the data sources within the connector import data from all the available resource groups.
Usage Data Configuration	
CollectUsageData	option to enable usage data collection to retrieve API usage data over a specified duration.

- c. Select **Continue**.
8. Configure the import schedule to import data at regular intervals.
 - a. In the **Setup** stage of the playbook, select the **Configure import schedule** activity.
 - b. Expand the Parent scheduled data import within the Import schedules list to select the **API Management Services** import schedule associated with your connection.

Note: The connection name is prefixed to the schedule name.
 - c. In the Configure import schedule dialog box, select the **Active** check box, and then fill in the run schedule and time details.

For more information, see [Schedule a data import](#).

d. Select **Save**.
Alternatively, select **Execute Now** to execute the import schedule immediately.

e. Select **Continue**.

9. In the **Setup** stage of the playbook, select the **Confirm connection creation** activity to verify whether the connection was created.

What to do next

Select **View all connections** to review the connection details. The created connection appears in the Installed connections list.

You can then manage connections from the SGC Central view of the CMDB Workspace. For more information, see [Managing connections added for Service Graph Connectors in SGC Central](#).

Related concepts

- [API Service Graph Connector for Azure API Management](#)

Related reference

- [Target tables for storing API Service Graph Connector for Azure API Management data](#)

Target tables for storing API Service Graph Connector for Azure API Management data

When you complete setting up the connection, you can configure the integration to periodically pull data from an Azure API Management application. The data is saved in tables that extend from the Configuration item [cmdb_ci] classes and other non-CMDB classes.

Cloud Service Account [cmdb_ci_cloud_service_account]

The following attributes in the Cloud Service Account [cmdb_ci_cloud_service_account] table are populated by collected data:

Attribute label	Attribute name
Account Id	account_id
Name	name
Object ID	object_id
Datacenter Type	datacenter_type
Operational status	operational_status

Relationship created for Cloud Service Account

Parent class	Relationship type	Child class
Cloud Service Account [cmdb_ci_cloud_service_account]	Contains::Contained by	Resource Group [cmdb_ci_resource_group]

Azure Subscription [cmdb_ci_azure_subscription]

The following attributes in the Azure Subscription [cmdb_ci_azure_subscription] table are populated by collected data:

Attribute label	Attribute name
Name	name
Object ID	object_id
Operational status	operational_status

Azure API Management [cmdb_ci_azure_api_mgmt]

The following attributes in the Azure API Management [cmdb_ci_azure_api_mgmt] table are populated by collected data:

Attribute label	Attribute name
ID	id
Name	name
Fully qualified domain name	fqdn
Gateway URL	gateway_url
Operational status	operational_status
Version	version

Relationships created for Azure API Management

Parent class	Relationship type	Child class
Azure API Management [cmdb_ci_azure_api_mgmt]	Provides::Provided by	API Product Bundle [cmdb_ci_api_product_bundle]
Azure API Management [cmdb_ci_azure_api_mgmt]	Provides::Provided by	API Consumer Subscription [cmdb_ci_api_consumer_subscription]
Azure API Management [cmdb_ci_azure_api_mgmt]	Uses::Used by	DNS Alias [cmdb_ci_dns_alias]
Azure API Management [cmdb_ci_azure_api_mgmt]	Provides::Provided by	Managed API [cmdb_ci_managed_api]
Azure API Management	Reference	API Consumer [api_consumer]

Parent class	Relationship type	Child class
[cmdb_ci_azure_api_mgmt]		

Resource Group [cmdb_ci_resource_group]

The following attributes in the Resource Group [cmdb_ci_resource_group] table are populated by collected data:

Attribute label	Attribute name
Name	name
Object ID	object_id
Operational status	operational_status

DNS Alias [cmdb_ci_dns_alias]

The following attributes in the DNS Alias [cmdb_ci_dns_alias] table are populated by collected data:

Attribute label	Attribute name
Name	name

Managed API [cmdb_ci_managed_api]

The following attributes in the Managed API [cmdb_ci_managed_api] table are populated by collected data:

Attribute label	Attribute name
ID	id
Minor Version	minor_version
Name	name
Version	version

Attribute label	Attribute name
Base URL	base_url
Correlation ID	correlation_id
Description	short_description
Fully qualified domain name	fqdn
Operational status	operational_status
Type	type
Life Cycle Stage Status	life_cycle_stage_status
Life Cycle Stage	life_cycle_stage
Model ID	model_id

Relationships created for Managed API

Parent class	Relationship type	Child class
Managed API [cmdb_ci_managed_api]	Uses::Used by	API Frontend [cmdb_ci_api_frontend]
Managed API [cmdb_ci_managed_api]	Uses::Used by	API Backend [cmdb_ci_api_backend]
Managed API [cmdb_ci_managed_api]	Uses::Used by	API Consumer Subscription [cmdb_ci_api_consumer_subscription]

Parent class	Relationship type	Child class
		Note: Applies only when the Discovered Scope [discovered_scope] attribute value is set to <code>api</code> .

API Frontend [cmdb_ci_api_frontend]

The following attributes in the API Frontend [cmdb_ci_api_frontend] table are populated by collected data:

Attribute label	Attribute name
API Minor Version	api_minor_version
API Version	api_version
Host	host
Method	method
Path	path
URL	url
Description	short_description
Name	name
Operational status	operational_status

Relationship created for API Frontend

Parent class	Relationship type	Child class
API Frontend [cmdb_ci_api_frontend]	Use End Point To::Use End Point From	API Backend [cmdb_ci_api_backend]

API Backend [cmdb_ci_api_backend]

The following attributes in the API Backend [cmdb_ci_api_backend] table are populated by collected data:

Attribute label	Attribute name
Host	host
ID	id Note: Applicable to GraphQL APIs only.
Method	method Note: Applicable to GraphQL APIs only.
Path	path
URL	url
Name	name
Operational status	operational_status

API Consumer [api_consumer]

The following attributes in the API Consumer [api_consumer] table are populated by collected data:

Attribute label	Attribute name
ID	id
Discovered State	discovered_state
Email	email
Provider	provider

Attribute label	Attribute name
Registration Date	registration_date
Username	username

API Product Bundle [cmdb_ci_api_product_bundle]

The following attributes in the API Product Bundle [cmdb_ci_api_product_bundle] table are populated by collected data:

Attribute label	Attribute name
ID	id
Discovered Access Type	discovered_access_type
Discovered Approval Type	discovered_approval_type
Discovered State	discovered_state
Name	name
Operational status	operational_status

Relationships created for API Product Bundle

Parent class	Relationship type	Child class
API Product Bundle [cmdb_ci_api_product_bundle]	Contains::Contained by	Managed API [cmdb_ci_managed_api]
API Product Bundle [cmdb_ci_api_product_bundle]	Used by::Uses	API Consumer Subscription [cmdb_ci_api_consumer_subscription]

API Consumer Subscription [cmdb_ci_api_consumer_subscription]

The following attributes in the API Consumer Subscription [cmdb_ci_api_consumer_subscription] table are populated by collected data:

Attribute label	Attribute name
ID	id
Creation Date	creation_date
Discovered Scope	discovered_scope
Name	name
Sys ID	sys_id
API Consumer	api_consumer
Operational status	operational_status

Relationship created for API Consumer Subscription

Parent class	Relationship type	Child class
API Consumer Subscription [cmdb_ci_api_consumer_subscription]	Reference	API Consumer Access [api_consumer_access]

Key Value [cmdb_key_value]

The following attributes in the Key Value [cmdb_key_value] table are populated by collected data:

Attribute label	Attribute name
Key	key
Value	value

API Consumer Access [api_consumer_access]

The following attributes in the API Consumer Access [api_consumer_access] table are populated by collected data:

Attribute label	Attribute name
API Consumer	api_consumer
Access type	access_type
API Product Bundle	api_product_bundle
State	state
API Consumer Subscription	api_consumer_subscription
API	api
Valid to	valid_to

Accessing the connection details of API Service Graph Connector for Azure API Management

You can access the connection details of the API Service Graph Connector for Azure API Management in a single view using the common connection framework (CCF) included within the Integration Commons for CMDB (sn_cmdb_int_util) store app.

With the CCF, you can access all the connections used by the API Service Graph Connector for Azure API Management. The connection details include the connection alias, connection properties, data sources, and scheduled data imports associated with a connection. You can also test the connection. For more information, see [Accessing the connection details of Service Graph Connectors](#).

Access the details of an Azure API Management connection

Access the details of an Azure API Management connection configured for the API Service Graph Connector for Azure API Management.

Before you begin

Role required: admin

Procedure

1. Navigate to **All > Service Graph Connectors > Azure API Management > Connections**.
2. From the **Name** column of the Service Graph Connections list, select a connection.
3. On the Service Graph Connections page, view the connection details such as the connection name and alias.
4. Select a related list to view further details of the connection.
5. (Optional) Select the **Test Connection** related link to test the connection.

API Service Graph Connector for Kong Gateway

Use the ServiceNow® API Service Graph Connector for Kong Gateway to import API details from a Kong Gateway application into the Configuration Management Database (CMDB).

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Key features

Import data into a normalized data model for consistency across other technologies.

The API Insights workspace provides a centralized interface where you can analyze and interact with API data, without needing direct access to Kong Gateway, enhancing visibility, governance, and collaboration across the API estate. To learn more, see [API Insights](#).

Supported ServiceNow versions

- Washington DC
- Xanadu
- Yokohama

Use cases

You can use the API Service Graph Connector for Kong Gateway to:

- Maintain an end-to-end inventory of exposed and backend APIs, identifying what APIs are published, used, and by whom.
- Track APIs from customer-facing endpoints to the underlying services, identifying impacted endpoints when services change or fail and creating incidents for reported issues.
- Address vulnerabilities and security incidents related to API endpoints, and create compliance requirements.

Configuring a connection for the connector

You can configure a connection for the connector by using the SGC Central view in the CMDB Workspace. The SGC Central view enables you to discover and install connectors, and then effectively manage the full life cycle of creating, editing, monitoring, and debugging connections. To configure the connector using SGC Central, see [Configure API Service Graph Connector for Kong Gateway using SGC Central](#).

Note: You can also include a Prometheus connection and map it to the Kong Gateway connection during setup for importing Kong Gateway metrics data using the Prometheus plugin. To learn more about the Prometheus plugin, see [Prometheus](#) on the Kong Developer documentation site.

Data mapping

Data from the Kong Gateway data sources is mapped and transformed into the CMDB Configuration Item (CI) class definitions using the Robust Transform Engine (RTE). Data is inserted into the CMDB using the Identification and Reconciliation Engine (IRE).

When you complete setting up the connection, you can configure the integration to periodically pull data from a Kong Gateway application.

The following table lists the data sources in the order they run, the staging tables, and the target tables as CMDB CI and non-CMDB classes for a Kong Gateway application.

Data mapping for Kong Gateway

Data source	Staging table	Target tables
SG-Kong Gateway	SG-Kong Gateway [sn_kong_integ_sg_kong_gateway]	Kong Gateway
SG-Kong Workspaces	SG-Kong Workspaces [sn_kong_integ_sg_kong_workspaces]	Kong Workspace
SG-Kong Load Balancers	SG-Kong Load Balancers [sn_kong_integ_sg_kong_lbs]	Kong Load Balancer
SG-Kong Targets	SG-Kong Targets [sn_kong_integ_sg_kong_targets]	Kong Target Key Value
SG-Kong Services	SG-Kong Services [sn_kong_integ_sg_kong_services]	Managed API API Backend Key Value
SG-Kong Routes	SG-Kong Routes [sn_kong_integ_sg_kong_routes]	API Frontend
SG-Kong Consumers	SG-Kong Consumers [sn_kong_integ_sg_kong_consumers]	API Consumer

Data source	Staging table	Target tables
SG-Kong Plugins	SG-Kong Plugins [sn_kong_integ_sg_kong_plugins]	API Policy

For more information on where data is saved when pulling data from a Kong Gateway application, see [Target tables for storing API Service Graph Connector for Kong Gateway data](#).

You can use the IntegrationHub ETL app to view the data maps. See [IntegrationHub ETL](#) for more information.

Configure API Service Graph Connector for Kong Gateway using SGC Central

Set up scheduled import jobs to pull in Kong Gateway data into your Configuration Management Database (CMDB).

Before you begin

Install API Service Graph Connector for Kong Gateway version 2.0.0 or later from the ServiceNow Store. For ServiceNow Store installation steps, see [Install a ServiceNow Store application](#).

If setting up the Prometheus connection, enable the Prometheus plugin on Kong Gateway and verify that any required credentials are available. To learn more about the Prometheus plugin, see [Prometheus](#) on the Kong Developer documentation site.

Role required: The following table shows the roles required for each stage of the playbook.

Role required for each playbook stage

Stage	Role
Prerequisites	admin
Setup	cmdb_inst_admin or admin

About this task

The playbook experience for onboarding connectors is activated with SGC Central in the CMDB Workspace. To configure the SGC Central application, see [Configuring SGC Central](#) and for more information on how to interact with a playbook, see [Interact with Playbook](#).

Note: Alternatively, you can configure a default connection already available from the installed or draft connections in SGC Central. Go to **All > Service Graph Connectors**, then select **Setup** for the connector from the menu. To learn about installed and draft connections, see [Managing connections added for Service Graph Connectors in SGC Central](#).

Procedure

1. Navigate to **Workspaces > CMDB Workspace**.
2. In the CMDB Workspace, select **SGC Central**.
3. On the Overview page, select **Create connection**.

Tip: Alternatively, you can select **Create connection** on the All connections page.
4. On the Create connection window, select the Kong connector type, and then select **Create connection**.
5. Complete the initial prerequisites when setting up a connection for the first time using a connector.

Note: This step is required only during the first-time setup. See [Perform initial setup tasks when creating a connection in SGC Central](#).
6. Select a template for the authentication type to create a connection.
 - a. In the **Setup** stage of the playbook, select the **Select alias template** activity.
 - b. Select a template type.

- **Kong RBAC Authentication:** Select when using token-based authentication.
 - **Kong Basic Authentication:** Select when using basic authentication.
7. Enter connection details and test the API connection for importing Kong Gateway data.
- a. In the **Setup** stage of the playbook, select the **Create and test connection** activity.
 - b. On the form, fill in the fields.

Create and test connection form

Field	Description
Connection Name	Name to identify the Kong Gateway connection record.
Host Name	Admin URL address of the Kong Admin API server.
Protocol	Protocol used for the connection ensuring secured communication between the client and the Kong server.
Override default port	Port used by the Kong Admin API.
API Key	Authentication secret to connect to the Kong Gateway service. This field appears only when Kong RBAC Authentication is selected in the Select alias template activity.
User Name	User name required for authenticating requests to the Kong Gateway Admin API. This field appears only when

Field	Description
	Kong Basic Authentication is selected in the Select alias template activity.
Password	Password associated with the user name required for authenticating requests. This field appears only when Kong Basic Authentication is selected in the Select alias template activity.

- c. Select **Create and test connection**.
 - d. Once the connection test is complete, select **Continue**.
8. (Optional) Set the configuration properties for the connection.
- a. In the **Setup** stage of the playbook, select the **Set configuration properties** activity.
 - b. In the Expand HTTP Method Types field available in the Data retrieval configuration section, enter the HTTP methods including GET, POST, PUT, PATCH, DELETE, OPTIONS, HEAD, CONNECT, and TRACE, to consider for routes.
For multiple methods, separate them with commas. If left blank, results in a single API Frontend being created with the ALL method, indicating support for all standard HTTP methods.
 - c. In the Exclude workspaces field available in the Property settings section, enter the workspace that must be excluded from import.

For multiple workspaces, separate them with commas. For example: `workspace1,workspace2`. If you leave this field empty, the data sources within the connector import data from all the workspaces.
 - d. Select the **Import tags** check box available in the tag settings section, to ingest tags from the Kong Gateway service.
When selected, specify the key-value pair separator for tags in the **Tags value separator** field. If not selected, tags won't be fetched.

- e. In the **Tags value separator** field available in the tag settings section, enter the separator for key and value in tags. For example, if the tag value separator is set to =, the tag env=prod is saved with env as the key and prod as the value.

If left empty, no tags will be ingested.
 - f. Select the **Collect Usage Data** check box available in the Metric Settings section to enable usage data collection to retrieve API usage data over a specified duration.
 - g. In the **Collection period (in days)** field available in the Metric Settings section, enter the duration in days for collecting API usage data.
 - h. Select **Continue**.
9. (Optional) Enter Prometheus connection details and test the API connection for importing Kong Gateway metrics data using the Prometheus plugin.
- Note:** You can skip this step if API usage monitoring with Prometheus isn't required or if you're using an existing Prometheus instance. To skip this step, select **Skip** for the **Create and Test Prometheus Connection** activity.
- a. In the **Setup** stage of the playbook, select the **Create and Test Prometheus Connection** activity.
 - b. On the form, fill in the fields.

Create and Test Prometheus Connection form

Field	Description
Connection Name	Name to identify the Prometheus connection record.
Connection URL	Base URL of the Prometheus HTTP API, used for fetching metrics.

Field	Description
User Name	User name required for authenticating requests to the Prometheus server.
Password	Password associated with the user name required for authenticating requests to the Prometheus server.

- c. Select **Create and test connection**.
 - d. Once the connection test is complete, select **Continue**.
10. (Optional) Associate the Prometheus connection with a Kong Gateway connection.

Note: You can skip this step if API usage monitoring with Prometheus isn't required. To skip this step, select **Skip** for the **Kong Prometheus Mapping** activity.

 - a. In the **Setup** stage of the playbook, select the **Kong Prometheus Mapping** activity.
 - b. In the **Prometheus Connections** field, search for and select a Prometheus connection to associate.
You can select the Prometheus connection created in step 9 or select any existing Prometheus connection during this step. If you skip step 9, select any existing Prometheus connection.
 - c. Select **Submit**.
A Prometheus connection can be associated with multiple Kong Gateway connections. You can update the Prometheus mapping in the Kong Gateway connection from the SGC Central view at any time. See [Update a connection for a Service Graph Connector in SGC Central](#).
11. Configure the import schedule to import data at regular intervals.
 - a. In the **Setup** stage of the playbook, select the **Configure import schedule** activity.
 - b. Select **Configure import schedule**.

- c. Expand the Parent scheduled data import within the Import schedules list to select the **SG-Kong Gateway** import schedule associated with your connection.

Note: The connection name is prefixed to the schedule name.

- d. In the Configure import schedule dialog box, select the **Active** check box, and then fill in the run schedule and time details.

For more information, see [Schedule a data import](#).

- e. Select **Save**.
Alternatively, select **Execute Now** to execute the import schedule immediately.
- f. Select **Continue**.

12. In the **Setup** stage of the playbook, select the **Confirm connection creation** activity to check whether the connection was configured.

What to do next

Select **View all connections** to review the connection details. The configured connections, including the Kong Gateway connection and the Prometheus connection, if created, appear in the Installed connections list.

You can then manage connections from the SGC Central view of the CMDB Workspace. For more information, see [Managing connections added for Service Graph Connectors in SGC Central](#).

Related concepts

- [API Service Graph Connector for Kong Gateway](#)

Related reference

- [Target tables for storing API Service Graph Connector for Kong Gateway data](#)

Target tables for storing API Service Graph Connector for Kong Gateway data

When you complete setting up the connection, you can configure the integration to periodically pull data from a Kong Gateway application. The data is saved in tables that extend from the Configuration item [cmdb_ci] classes and other non-CMDB tables.

Kong Gateway [cmdb_ci_kong_gateway]

The following attributes in the Kong Gateway [cmdb_ci_kong_gateway] table are populated by collected data:

Attribute label	Attribute name
ID	id
Name	name
Admin URL	admin_url
Database	database
Description	short_description
Operational status	operational_status
Version	version

Relationships created for Kong Gateway

Parent class	Relationship type	Child class
Kong Gateway [cmdb_ci_kong_gateway]	Provides::Provided by	Kong Load Balancer [cmdb_ci_kong_lb]
Kong Gateway [cmdb_ci_kong_gateway]	Provides::Provided by	Managed API [cmdb_ci_managed_api]

Parent class	Relationship type	Child class
Kong Gateway [cmdb_ci_kong_gateway]	Reference	Kong Workspace [kong_workspace]
Kong Gateway [cmdb_ci_kong_gateway]	Reference	API Policy [api_policy]
Kong Gateway [cmdb_ci_kong_gateway]	Reference	API Consumer [api_consumer]

Kong Workspace [kong_workspace]

The following attributes in the Kong Workspace [kong_workspace] table are populated by collected data:

Attribute label	Attribute name
ID	id
Name	name
API Gateway	api_gateway

Relationship created for Kong Workspace

Parent class	Relationship type	Child class
Kong Workspace [kong_workspace]	Reference	Kong Gateway [cmdb_ci_kong_gateway]

Kong Load Balancer [cmdb_ci_kong_lb]

The following attributes in the Kong Load Balancer [cmdb_ci_kong_lb] table are populated by collected data:

Attribute label	Attribute name
ID	id
Name	name
Algorithm	algorithm
Operational status	operational_status

Relationships created for Kong Load Balancer

Parent class	Relationship type	Child class
Kong Load Balancer [cmdb_ci_kong_lb]	Contains::Contained by	Kong Target [cmdb_ci_kong_target]
Kong Load Balancer [cmdb_ci_kong_lb]	Reference	Key Value [cmdb_key_value]

Kong Target [cmdb_ci_kong_target]

The following attributes in the Kong Target [cmdb_ci_kong_target] table are populated by collected data:

Attribute label	Attribute name
ID	id
Name	name
Target	target
Operational status	operational_status

Relationship created for Kong Target

Parent class	Relationship type	Child class
Kong Target [cmdb_ci_kong_target]	Reference	Key Value [cmdb_key_value]

Managed API [cmdb_ci_managed_api]

The following attributes in the Managed API [cmdb_ci_managed_api] table are populated by collected data:

Attribute label	Attribute name
Life Cycle Stage	life_cycle_stage
Life Cycle Stage Status	life_cycle_stage_status
ID	id
Name	name
Base URL	base_url
Type	type
Model ID	model_id
Operational status	operational_status

Relationships created for Managed API

Parent class	Relationship type	Child class
Managed API [cmdb_ci_managed_api]	Uses::Used by	API Frontend [cmdb_ci_api_frontend]
Managed API [cmdb_ci_managed_api]	Uses::Used by	API Backend [cmdb_ci_api_backend]

API Backend [cmdb_ci_api_backend]

The following attributes in the API Backend [cmdb_ci_api_backend] table are populated by collected data:

Attribute label	Attribute name
Host	host
ID	id
Path	path
URL	url
Name	name
Port	port
Protocol	protocol
Operational status	operational_status

Relationship created for API Backend

Parent class	Relationship type	Child class
API Backend [cmdb_ci_api_backend]	Uses::Used by	Kong Load Balancer [cmdb_ci_kong_lb]

API Frontend [cmdb_ci_api_frontend]

The following attributes in the API Frontend [cmdb_ci_api_frontend] table are populated by collected data:

Attribute label	Attribute name
Host	host
ID	id

Attribute label	Attribute name
Method	method
Path	path
URL	url
Name	name
Protocol	protocol
Operational status	operational_status

Relationship created for API Frontend

Parent class	Relationship type	Child class
API Frontend [cmdb_ci_api_frontend]	Use End Point To::Use End Point From	API Backend [cmdb_ci_api_backend]

API Consumer [api_consumer]

The following attributes in the API Consumer [api_consumer] table are populated by collected data:

Attribute label	Attribute name
ID	id
API Gateway	api_gateway
Custom ID	custom_id
Username	username

Relationship created for API Consumer

Parent class	Relationship type	Child class
API Consumer [api_consumer]	Reference	Kong Gateway [cmdb_ci_kong_gateway]

API Policy [api_policy]

The following attributes in the API Policy [api_policy] table are populated by collected data:

Attribute label	Attribute name
Frontend	frontend
ID	id
Active	active
Name	name
Protocols	protocols
Managed API	managed_api
Consumer	consumer
API Gateway	api_gateway

Relationship created for API Policy

Parent class	Relationship type	Child class
API Policy [api_policy]	Reference	Kong Gateway [cmdb_ci_kong_gateway]

Key Value [cmdb_key_value]

The following attributes in the Key Value [cmdb_key_value] table are populated by collected data:

Attribute label	Attribute name
Configuration item	configuration_item
Key	key
Value	value

Accessing the connection details of API Service Graph Connector for Kong Gateway

You can access the connection details of the API Service Graph Connector for Kong Gateway in a single view using the common connection framework (CCF) included within the Integration Commons for CMDB (sn_cmdb_int_util) store app.

With the CCF, you can access all the connections used by the API Service Graph Connector for Kong Gateway. The connection details include the connection alias, connection properties, data sources, and scheduled data imports associated with a connection. You can also test the connection. For more information, see [Accessing the connection details of Service Graph Connectors](#).

Access the details of a Kong Gateway connection

Access the details of a Kong Gateway connection configured for the API Service Graph Connector for Kong Gateway.

Before you begin

Role required: admin

Procedure

1. Navigate to **All > Service Graph Connectors > Kong Gateway > Connections**.

2. From the **Name** column of the Service Graph Connections list, select a connection.
3. On the Service Graph Connections page, view the connection details such as the connection name and alias.
4. Select a related list to view further details of the connection.
5. (Optional) Select the **Test Connection** related link to test the connection.

API Service Graph Connector for Kong Konnect

Use the ServiceNow® API Service Graph Connector for Kong Konnect to import API details from a Kong Konnect service into the Configuration Management Database (CMDB).

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Key features

Import data into a normalized data model for consistency across other technologies.

The API Insights workspace provides a centralized interface where you can analyze and interact with API data, without needing direct access to Kong Konnect, enhancing visibility, governance, and collaboration across the API estate. To learn more, see [API Insights](#).

Supported ServiceNow versions

- Xanadu
- Yokohama
- Zurich

Use cases

You can use the API Service Graph Connector for Kong Connect to:

- Maintain an end-to-end inventory of defined APIs, identifying what APIs are published, used, and by whom.
- Track APIs from customer-facing endpoints to the underlying services, identifying impacted endpoints when services change or fail and creating incidents for reported issues.
- Address vulnerabilities and security incidents related to API endpoints and create compliance requirements to measure against.

Configuring a connection for the connector

You can configure a connection for the connector by using the SGC Central view in the CMDB Workspace. The view enables you to discover and install connectors, and then effectively manage the full life cycle of creating, editing, monitoring, and debugging connections. To configure the connector using SGC Central, see [Configure API Service Graph Connector for Kong Connect using SGC Central](#).

Data mapping

Data from the Kong Connect data sources is mapped and transformed into the CMDB Configuration Item (CI) class definitions using the Robust Transform Engine (RTE). Data is inserted into the CMDB using the Identification and Reconciliation Engine (IRE).

When you complete setting up the connection, you can configure the integration to periodically pull data from a Kong Connect service.

The following table lists the data sources in the order they run, the staging tables, and the target tables as CMDB CI classes and non-CMDB tables for a Kong Connect service.

Data mapping for Kong Connect

Data source	Staging table	Target tables
Gateway	Gateway [sn_kong_connect_gateway]	Kong Gateway DNS Alias

Data source	Staging table	Target tables
		Logical Datacenter Cloud Service Account Key Value
Load Balancer	Load Balancer [sn_kong_konnect_load_balancer]	Kong Load Balancer
Target	Target [sn_kong_konnect_target]	Kong Target
Services	Services [sn_kong_konnect_services]	Managed API API Backend Key Value
Routes	Routes [sn_kong_konnect_routes]	API Frontend
Consumer	Consumer [sn_kong_konnect_consumer]	API Consumer
Policy	Policy [sn_kong_konnect_policy]	API Policy
Developers	Developers [sn_kong_konnect_developers]	API Consumer

Data source	Staging table	Target tables
Applications	Applications [sn_kong_konnect_ap plications]	API Consumer Subscription
API Consumer Access	API Consumer Access [sn_kong_konnect_api _consumer_access]	API Consumer Access

For more information on where data is saved when pulling data from a Kong Konnect service, see [Target tables for storing API Service Graph Connector for Kong Konnect data](#).

You can use the IntegrationHub ETL app to view the data maps. See [IntegrationHub ETL](#) for more information.

Record removal process

The connector supports soft deletion for CMDB CI classes only, meaning records are not permanently removed from the system. Instead, any CMDB CI records not discovered during the last scheduled job run are marked as **Non-Operational**.

Configure API Service Graph Connector for Kong Konnect using SGC Central

Set up scheduled import jobs to pull in Kong Konnect data into your CMDB.

Before you begin

Install API Service Graph Connector for Kong Konnect version 1.0.0 or later from the ServiceNow Store. For ServiceNow Store installation steps, see [Install a ServiceNow Store application](#).

Role required: The following table shows the roles required for each stage of the playbook.

Role required for each playbook stage

Stage	Role
Prerequisites	admin
Setup	cmdb_inst_admin or admin

About this task

The playbook experience for onboarding connectors is activated with SGC Central in the CMDB Workspace. To configure the SGC Central application, see [Configuring SGC Central](#) and for more information on how to interact with a playbook, see [Interact with Playbook](#).

Note: Alternatively, you can configure a default connection already available from the installed or draft connections in SGC Central. Go to **All > Service Graph Connectors**, then select **Setup** for the connector from the menu. To learn about installed and draft connections, see [Managing connections added for Service Graph Connectors in SGC Central](#).

Procedure

1. Navigate to **Workspaces > CMDB Workspace**.
2. In the CMDB Workspace, select **SGC Central**.
3. On the Overview page, select **Create connection**.

Tip: Alternatively, you can select **Create connection** on the All connections page.
4. On the Create connection window, select the Kong Konnect connector type, and then select **Create connection**.
5. Complete the initial prerequisites when setting up a connection for the first time using a connector.

Note: This step is required only during the first-time setup. See [Perform initial setup tasks when creating a connection in SGC Central](#).

6. Enter connection details and test the API connection for importing Kong Konnect data.
 - a. In the **Setup** stage of the playbook, select the **Create and test connection** activity.
 - b. On the form, fill in the fields.

Create and test connection form

Field	Description
Connection name	Name to identify the Kong Konnect connection record. For example, Kong Konnect connection.
Personal access token	Token used to securely authenticate your identity and authorize access to your Kong Konnect account via the API

- c. Select **Create and test connection**.
 - d. Once the connection test is complete, select **Continue**.
7. Set the configuration properties for the connection.
 - a. In the **Setup** stage of the playbook, select the **Set configuration properties** activity.
 - b. Fill in the property details.

Kong Konnect configuration properties

Property	Description
Data retrieval configuration	
Gateway group IDs	Group IDs associated with a Kong Konnect gateway representing control plane groups consisting of self-managed control planes. For multiple IDs, separate them with commas. Note: The Gateway group IDs property is used if specified, and it overrides the Gateway IDs.
Gateway IDs	IDs of individual Kong Konnect gateways, each representing a control plane. For multiple IDs, separate them with commas. Note: The Gateway IDs property value is ignored if Gateway group IDs are specified.
Regions	List of comma-separated regions where the Kong Konnect gateway resides.
Expand HTTP method types	HTTP methods including GET, POST, PUT, PATCH, DELETE, OPTIONS, HEAD, CONNECT, and TRACE, to consider for routes. For multiple methods, separate them with commas. If left

Property	Description
Data retrieval configuration	
	blank, results in a single API Frontend being created with the <code>ALL</code> method, indicating support for all standard HTTP methods.
Tags settings	
Import tags	Option to ingest tags from the Kong Konnect gateway.
Tags value separator	Separator for key and value in tags.

- c. Select **Continue**.
8. Configure the import schedule to import data at regular intervals.
 - a. In the **Setup** stage of the playbook, select the **Configure import schedule** activity.
 - b. Expand the Parent scheduled data import within the Import schedules list to select the **Gateway** import schedule associated with your connection.

Note: The connection name is prefixed to the schedule name.

- c. In the Configure import schedule dialog box, select the **Active** check box, and then fill in the run schedule and time details.

For more information, see [Schedule a data import](#).

- d. Select **Save**.
Alternatively, select **Execute Now** to execute the import schedule immediately.
- e. Select **Continue**.

9. In the **Setup** stage of the playbook, select the **Confirm connection creation** activity to verify whether the connection was created.

What to do next

Select **View all connections** to review the connection details. The configured connection appears in the Installed connections list.

You can then manage connections from the SGC Central view of the CMDB Workspace. For more information, see [Managing connections added for Service Graph Connectors in SGC Central](#).

Related concepts

- [API Service Graph Connector for Kong Konnect](#)

Related reference

- [Target tables for storing API Service Graph Connector for Kong Konnect data](#)

Target tables for storing API Service Graph Connector for Kong Konnect data

When you complete setting up the connection, you can configure the integration to periodically pull data from a Kong Konnect application. The data is saved in tables that extend from the Configuration item [cmdb_ci] classes and other non-CMDB tables.

Kong Gateway [cmdb_ci_kong_gateway]

The following attributes in the Kong Gateway [cmdb_ci_kong_gateway] table are populated by collected data:

Attribute label	Attribute name
ID	id
Name	name
Asset tag	asset_tag

Attribute label	Attribute name
Correlation ID	correlation_id
Description	short_description
Operational status	operational_status

Relationships created for Kong Gateway

Parent class	Relationship type	Child class
Kong Gateway [cmdb_ci_kong_gateway]	Provides::Provided by	Kong Load Balancer [cmdb_ci_kong_lb]
Kong Gateway [cmdb_ci_kong_gateway]	Provides::Provided by	Managed API [cmdb_ci_managed_api]
Kong Gateway [cmdb_ci_kong_gateway]	Uses::Used by	DNS Alias [cmdb_ci_dns_alias]
Kong Gateway [cmdb_ci_kong_gateway]	Reference	Key Value [cmdb_key_value]
Kong Gateway [cmdb_ci_kong_gateway]	Reference	API Consumer [api_consumer]

Cloud Service Account [cmdb_ci_cloud_service_account]

The following attributes in the Cloud Service Account [cmdb_ci_cloud_service_account] table are populated by collected data:

Attribute label	Attribute name
Account Id	account_id

Attribute label	Attribute name
Name	name
Datacenter Type	datacenter_type
Operational status	operational_status

Logical Datacenter [cmdb_ci_logical_datacenter]

The following attributes in the Logical Datacenter [cmdb_ci_logical_datacenter] table are populated by collected data:

Attribute label	Attribute name
Name	name
Object ID	object_id
Region	region
Operational status	operational_status

Relationships created for Logical Datacenter

Parent class	Relationship type	Child class
Logical Datacenter [cmdb_ci_logical_datacenter]	Hosted on::Hosts	Kong Gateway [cmdb_ci_kong_gateway]
Logical Datacenter [cmdb_ci_logical_datacenter]	Hosted on::Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]

DNS Alias [cmdb_ci_dns_alias]

The following attributes in the DNS Alias [cmdb_ci_dns_alias] table are populated by collected data:

Attribute label	Attribute name
Name	name
Operational status	operational_status

Kong Load Balancer [cmdb_ci_kong_lb]

The following attributes in the Kong Load Balancer [cmdb_ci_kong_lb] table are populated by collected data:

Attribute label	Attribute name
ID	id
Name	name
Algorithm	algorithm
Description	short_description
Operational status	operational_status

Relationship created for Kong Load Balancer

Parent class	Relationship type	Child class
Kong Load Balancer [cmdb_ci_kong_lb]	Contains::Contained by	Kong Target [cmdb_ci_kong_target]

Kong Target [cmdb_ci_kong_target]

The following attributes in the Kong Target [cmdb_ci_kong_target] table are populated by collected data:

Attribute label	Attribute name
ID	id

Attribute label	Attribute name
Description	short_description
Name	name
Operational status	operational_status
Target	target

Managed API [cmdb_ci_managed_api]

The following attributes in the Managed API [cmdb_ci_managed_api] table are populated by collected data:

Attribute label	Attribute name
ID	id
Name	name
Base URL	base_url
Description	short_description
Operational status	operational_status
Life Cycle Stage Status	life_cycle_stage_status
Life Cycle Stage	life_cycle_stage
Type	type

Relationships created for Managed API

Parent class	Relationship type	Child class
Managed API [cmdb_ci_managed_api]	Uses::Used by	API Frontend [cmdb_ci_api_frontend]

Parent class	Relationship type	Child class
Managed API [cmdb_ci_managed_api]	Uses::Used by	API Backend [cmdb_ci_api_backend]

API Backend [cmdb_ci_api_backend]

The following attributes in the API Backend [cmdb_ci_api_backend] table are populated by collected data:

Attribute label	Attribute name
Host	host
ID	id
Path	path
URL	url
Name	name
Port	port
Protocol	protocol

Relationship created for API Backend

Parent class	Relationship type	Child class
API Backend [cmdb_ci_api_backend]	Uses::Used by	Kong Load Balancer [cmdb_ci_kong_lb]

API Frontend [cmdb_ci_api_frontend]

The following attributes in the API Frontend [cmdb_ci_api_frontend] table are populated by collected data:

Attribute label	Attribute name
Host	host
ID	id
Method	method
Path	path
URL	url
Description	short_description
Name	name
Operational status	operational_status
Protocol	protocol

Relationship created for API Frontend

Parent class	Relationship type	Child class
API Frontend [cmdb_ci_api_frontend]	Use End Point To::Use End Point From	API Backend [cmdb_ci_api_backend]

API Consumer [api_consumer]

The following attributes in the API Consumer [api_consumer] table are populated by collected data:

Attribute label	Attribute name
ID	id
Custom ID	custom_id
Email	email

Attribute label	Attribute name
Note: Fetched using the Developers data source only.	
Username	username
API Gateway	api_gateway

Relationship created for API Consumer

Parent class	Relationship type	Child class
API Consumer [api_consumer]	Reference	Kong Gateway [cmdb_ci_kong_gateway]

API Consumer Subscription [cmdb_ci_api_consumer_subscription]

The following attributes in the API Consumer Subscription [cmdb_ci_api_consumer_subscription] table are populated by collected data:

Attribute label	Attribute name
Operational status	operational_status
API Consumer	api_consumer
ID	id
Creation Date	creation_date
Description	short_description
Last Modified Date	last_modified_date
Name	name

Relationship created for API Consumer Subscription

Parent class	Relationship type	Child class
API Gateway [cmdb_ci_api_gateway]	Provides::Provided by	API Consumer Subscription [cmdb_ci_api_consumer_subscription]

API Consumer Access [api_consumer_access]

The following attributes in the API Consumer Access [api_consumer_access] table are populated by collected data:

Attribute label	Attribute name
API	api
API Consumer	api_consumer
State	state
API Consumer Subscription	api_consumer_subscription

API Policy [api_policy]

The following attributes in the API Policy [api_policy] table are populated by collected data:

Attribute label	Attribute name
Name	name
Managed API	managed_api
ID	id
Protocols	protocols
Frontend	frontend

Attribute label	Attribute name
Active	active
Consumer	consumer

Relationship created for API Policy

Parent class	Relationship type	Child class
API Policy [api_policy]	Reference	Managed API [cmdb_ci_managed_api]

Key Value [cmdb_key_value]

The following attributes in the Key Value [cmdb_key_value] table are populated by collected data:

Attribute label	Attribute name
Tag	tag
Configuration item	configuration_item
Key	key
Value	value

Accessing the connection details of API Service Graph Connector for Kong Konnect

You can access the connection details of the API Service Graph Connector for Kong Konnect in a single view using the common connection framework (CCF) included within the Integration Commons for CMDB (sn_cmdb_int_util) store app.

With the CCF, you can access all the connections used by the API Service Graph Connector for Kong Konnect. The connection details include the connection alias, connection properties, data sources, and scheduled data imports associated with a connection. You can also

test the connection. For more information, see [Accessing the connection details of Service Graph Connectors](#).

Access the details of a Kong Konnect connection

Access the details of a Kong Konnect connection configured for the API Service Graph Connector for Kong Konnect.

Before you begin

Role required: admin

Procedure

1. Navigate to **All > Service Graph Connectors > Kong Konnect > Connections**.
2. From the **Name** column of the Service Graph Connections list, select a connection.
3. On the Service Graph Connections page, view the connection details such as the connection name and alias.
4. Select a related list to view further details of the connection.
5. (Optional) Select the **Test Connection** related link to test the connection.