

Zurich ServiceNow AI Platform Capabilities

Last updated: January 16, 2026

Some examples and graphics depicted herein are provided for illustration only. No real association or connection to ServiceNow products or services is intended or should be inferred.

This PDF was created from content on docs.servicenow.com. The web site is updated frequently. For the most current ServiceNow product documentation, go to docs.servicenow.com.

Company Headquarters

2225 Lawson Lane
Santa Clara, CA 95054
United States
(408)501-8550

Service Graph Connector for Active Directory

The Service Graph Connector for Active Directory retrieves computer and software information from the Microsoft Active Directory (AD) product and imports it into the Configuration Management Database (CMDB) in your instance using Lightweight Directory Access Protocol (LDAP).

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Supported versions

- Microsoft Active Directory version: Last tested on
- Supported ServiceNow® versions:
 - Utah
 - Vancouver
 - Washington

Use cases

Import computer and software details about your assets from the Microsoft Active Directory product into your CMDB.

Guided setup

The guided setup for the Service Graph Connector for Active Directory provides an organized sequence of tasks to configure the integration on your instance. To access the guided setup, [Configure Service Graph Connector for Active Directory](#).

CMDB integrations dashboard

The Integration Commons for CMDB store app provides a dashboard with a central view of the status, processing results, and processing errors of all

installed integrations. You can see metrics for all integration runs. You can filter the view to a specific CMDB integration, a specific time duration, or a specific integration run. For more details about monitoring Microsoft Active Directory integrations in the CMDB Integrations Dashboard, see [Using the CMDB Integrations Dashboard](#).

Data mapping

Data from the Service Graph Connector for Active Directory data sources is mapped and transformed into the ServiceNow CMDB Configuration Item (CI) class definitions using the Robust Transform Engine (RTE). Data is inserted into the ServiceNow CMDB using the Identification and Reconciliation Engine (IRE).

After you complete the guided setup, you configure the integration to periodically pull data from the Active Directory. The data is loaded into the following tables.

You can use the Integration Hub ETL application to view the data maps.

Data sources and staging tables for Active Directory

Data source	Staging table
SGC Active Directory Import	SGC Active Directory Import [sn_sec_sgc_ad_active_directory_import]
Computer	Computer [cmdb_ci_computer]
Software	Software [cmdb_ci_spkg], [cmdb_software_instance], [cmdb_sam_sw_install]
SGC Active Directory Computer	SGC Active Directory Computer [sn_sec_sgc_ad_active_directory_computer]

Configure Service Graph Connector for Active Directory

Configure your Lightweight Directory Access Protocol (LDAP) connections and verify them, set up scheduled imports, and optionally add multiple instances with the Guided Setup.

Before you begin

To use this Service Graph Connector, you need a subscription to a Subscription Unit that is based in the IT Operations Management (ITOM) Visibility application or in the ITOM Discovery application. As defined in the section titled "Managed IT Resource Types" in [ServiceNow Subscription Unit Overview](#) for your subscription, for managed IT resources that are created or modified in the CMDB by this Service Graph Connector, but that aren't yet managed by [ITOM Visibility](#) or [ITOM Discovery](#), these resources will increase Subscription Unit consumption from that application. Review your current Subscription Unit consumption within ITOM Visibility or ITOM Discovery to ensure available capacity.

- The [Integration Commons for CMDB](#) store app, which is automatically installed.
- The CMDB CI class models store app, which is automatically installed. See [CMDB CI Class Models](#).
- The ITOM Discovery License plugin (com.snc.itom.discovery.license). You must activate this plugin.
- ITOM Licensing plugin (com.snc.itom.license). For more information, see [Request Discovery](#).
- The Datastream Action plugin (com.glide.hub.action_type.datastream), which is automatically installed.
- Observability Commons for CMDB (sn_observability), which is only required for event ingestion. This app must be installed prior to installing the connector for Event Management to work. For more information, see [Observability Commons for CMDB](#) on the ServiceNow Store.

After you have followed the instructions provided to you to download and activate the Service Graph Connector for Active Directory

application, refer to [Download an application from the ServiceNow Store for the first time](#) and [Install a Security Operations integration](#). There are a few steps you need to complete before you configure this integration.

Role required: admin

Procedure

1. Navigate to **All > Service Graph Connectors > Active Directory > Setup**.
2. On the Welcome to Guided Setup Home page, select **Continue**.
3. On the Experience page, select **Best Experience** followed by **Continue**.
The Service Graph Connector for Active Directory (AD) page is displayed with the following tasks:

- Configure LDAP Server
- Add Multiple Instances
- Set up scheduled import jobs

4. Select **Configure LDAP Server** to expand it.
The following steps are displayed in the left navigation panel:

- Configure Inactive threshold
- Update LDAP OU definition
- Configure LDAP Server Details
- Test LDAP Server Connection

A single LDAP server is supplied along with the application. This server includes a computer organizational (OU) unit that retrieves a computer's object information from the computers OU.

5. (Optional) Select **Configure Inactive threshold** to open the record.
The System Property `sn_sec_sgc_ad.inactive_threshold` form is displayed.
6. Select the **here** link in the message at the top of the form to edit the record.

7. (Optional) Alternatively, you can select the **Globe** icon in the upper right of the screen and select **Service Graph Connector for Active Directory** from the list to change the application scope so you can edit the form.
As you progress through the Guided Setup, follow any instructions you see at the top of the pages in for modifying the application scope so you can open, edit, and save the record.
8. Enter a threshold in the **Value** field.
The default value is 90 days. Before you modify this value, refer to the information about the threshold setting at the top of the page. With this setting, assets that match the day threshold value are excluded from import.
9. Right-click in the gray header titled System Property `sn_sec_sgc_ad.inactive_threshold` of the record and select **Save**.
10. Select **Mark as complete** followed by **Continue**.
The LDAP OU Definition Access record is displayed.
11. Update LDAP OU Definition Access.
 - a. Follow the steps listed at the top of the page and on the LDAP OU Definition record to verify or switch the application scope to 'Global' with the application picker.
 - b. Select the **LDAP OU Definition** record on the table to open it.
 - c. On the record, if not selected, select the **Application Access** tab.
 - d. If displayed, select the link to edit the record followed by the check boxes for the permission settings you want.
 - e. Right-click in the gray header of the Table LDAP OU Definition record and select **Save**.
 - f. Select **Mark as complete** followed by **Continue**.
The Configure LDAP Server Details page is displayed.
12. Provide the details for LDAP server connection.
 - a. Verify values or fill in the fields.

Field	Value
Name	Read-only: Unique name for the LDAP server for example SGC-AD-computer.
Application	Read-only: Service Graph Connector for Active Directory (AD).
Active	Check box selected.
Login distinguished name	Login name for the AD server.
Login password	Password for the AD server.
Starting search directory	Directory you want to search for example DC=Ops.
(Optional) MID Server	Dedicated MID Server for the connection, if available. Note: A MID Server is required for on-premise connections if the instance is not publicly accessible.
LDAP Server URLs	Add the URL for the server for example ldap://host-name:389/.

- b. Right-click in the gray header titled LDAP Server and select **Save**.
- c. Select **Mark as complete** followed by **Continue**.
The Test LDAP Server Connection page is displayed.

13. Test the LDAP Server Connection.

- a. Scroll to the Related links section on the form and select the **Test Connection** link

If the connection is successful, a Connected Successfully message is displayed. If your connection test fails, a message is displayed with information about why the connection failed. Review the Message field for how to proceed.

- b. If you edit the record to fix the connection, right-click in the gray header titled LDAP Server and select **Save**.
- c. Select **Mark as complete** followed by **Continue**.
Add Multiple Instances is displayed in the top header the tasks.

Adding Multiple instances is optional. If you don't want to add multiple instances, you can proceed to step 14 and the Set scheduled import jobs task.

14. (Optional) Add multiple instances.
To add multiple instances, you must update data source access. You must edit the permissions on the Datasource [sys_data_source] table to create a data source for the new connection in the Service Graph Connector for Active Directory.
15. Select **Add Multiple Instances** from the top header drop down list.
The following tasks are displayed:
 - Update Data Source Access
 - Update Scheduled Data Import Access
 - Add Another LDAP Server
 - List of configured LDAP servers
16. Select **Update Data Source Access**.
 - a. Follow the steps listed at the top of the page to switch the application scope with the application picker to open, edit, and save the record.
 - b. Select the Data Import record from the list to open it.
 - c. With the **Application Access** tab selected, follow the instructions to edit the record and modify the check boxes.
 - d. Right-click in the gray header titled Table Data Source and select **Save**.

- e. Select **Mark as complete** followed by **Continue**.
The Update scheduled data import access page is displayed.

17. Update scheduled data import access.

- a. Select the **Scheduled Data Import** record from the list to open it.
- b. (Optional) With the **Application Access** tab selected, follow the instructions to edit the record and modify the check boxes.
- c. Right-click in the gray header titled Table Scheduled Data Import and select **Save**.
- d. Select **Mark as complete** followed by **Continue**.
The Add Another LDAP Server page is displayed. There are two steps for this task:

- LDAP server configuration
- Basic LDAP server information

18. Provide LDAP server configuration information.

- a. Fill out the fields.

Field	Value
Type of LDAP server	Active Directory
Server name	Unique name of the LDAP server.
Server URL	URL for example ldap://host-name:389/.
Start search directory	Directory you want to search for example DC=SecOps.

- b. Select **Submit**.
After you submit these edits, complete the second configuration step.
- c. Fill in the fields for the basic LDAP server information.

Field	Value
Application	Read-only Service Graph Connector for Active Directory.
Active	Check box selected.
Login distinguished name	Login name for the AD server.
Login password	Password for the AD server.
Starting search directory	Directory you want to search for example <code>DC=SecOps</code> .
MID Server	Dedicated MID Server for the connection. Note: A MID Server is not required for the LDAP server.

- d. Right-click in the gray header titled LDAP Server and select **Save**.
- e. Select **Mark as complete** followed by **Continue**.
The List of configured LDAP server page is displayed.
- f. Select your new record from the list to open it and test the connection.
- g. (Optional) Edit information on the form.
- h. When you are satisfied with the information, scroll to the Related links and select the **Test Connection** link.
If the connection is successful, a message is displayed. If your connection test fails, review the Message and Suggestion fields for how to proceed.
- i. After a successful connection, right-click in the gray header titled LDAP Server and select **Save**.
- j. Select **Mark as complete** followed by **Continue**.

19. To set up scheduled jobs, select **Set up scheduled import jobs** from the drop down list in the top header.
You must activate a scheduled job from the configuration page.
 - a. On the Configure the scheduled jobs page, select a record from the Scheduled Data Imports list to open it.
 - b. Select the **Active** check box and fill in the fields.

Field	Value
Name	Unique name for the LDAP server, SGC-AD-computer.
Application	Read-only Service Graph Connector for Active Directory (AD).
Run	How often you want the job to run. If you want to run a test import prior to scheduling it, you might prefer to set this to Once .
Run as	Run the scheduled job with the credentials of another specified user.
Time	When you want the job to run.
Active	Select the check box.
Conditional	Specific conditions under which this job is run.
Use connection	Leave this deactivated for the first run. Specifies another connection and credentials for this job.
Concurrent import	Leave activated. Splits data into multiple imports sets.

Field	Value
	See the message for more information.
Partition Method	Leave as Custom size.
Partition size	15,000. Import set size for early scheduling.
Execute pre-import script	Leave activated. Specifies a script to run before the import is performed.
Execute post-import script	Leave activated. Specifies a script to run after the import is performed.

- c. (Optional) Select **Execute now** to run the job.
If you do not choose to run the job on-demand, the next job runs according to the schedule you set.
 - d. Right-click in the gray Scheduled Data Imports header and select **Save**.
 - e. Select **Mark as complete** followed by **Continue**.
20. On the Home page for Guided Setup, select **Complete** to finish the configuration.

CMDB classes targeted in Service Graph Connector for Active Directory

When you complete setting up the connection, you can configure the integration to periodically pull data. The data is saved in tables that extend from the Configuration item [cmdb_ci] table.

Computer [cmdb_ci_computer]

The following attributes in the Computer [cmdb_ci_computer] table are populated by collected data.

Attribute label	Attribute name
Name	name
Category	category
Object ID	object_id
Fully qualified domain name	fqdn
Checked out	check_out
Check in	check_in
First discovered	first_discovered
Operating System	os
OS Version	os_version

Software [cmdb_ci_spkg]

The following attributes in the Software [cmdb_ci_spkg] table are populated by collected data.

Attribute label	Attribute name
Name	name
Key	key
Version	version

Software Instance [cmdb_software_instance]

The following attributes in the Software Instance [cmdb_software_instance] table are populated by collected data.

Attribute label	Attribute name
Name	name
Install On	installed_on
Product Name	software

Software Installation [cmdb_sam_sw_install]

The following attributes in the Software Installation [cmdb_sam_sw_install] table are populated by collected data.

Attribute label	Attribute name
Display Name	display_name
Version	version
Discovery source	discovery_source

SGC Active Directory Computer [sn_sec_sgc_ad_active_directory_computer]

The following attributes in the SGC Active Directory Computer [sn_sec_sgc_ad_active_directory_computer] table are populated by collected data.

Attribute label	Attribute name
Account expires	account_expires
Bad password count	bad_pwd_count
Bad password time	bad_password_time
Code page	code_page

Attribute label	Attribute name
Common name	cn
Country code	country_code
Description	description
Display name	display_name
Distinguished name	distinguished_name
DN	dn
Dscorepropagation data	dscore_propagation_data
Instance type	instance_type
Is critical system object	iscritical_system_object
Keywords	keywords
Last logon	last_logon
Local policy flags	local_policy_flags
Logon count	logon_count
Member of	member_of
Ms-DS-Host service account	msds_host_service_account
Ms-DS-Supported encryption types	msds_support_ncryptiontypes
Name	name
Object class	object_class
Object GUID	object_guid
Other well known objects	other_well_known_objects

Attribute label	Attribute name
Password last set	pwd_last_set
Primary group id	primary_groupid
SamAccount name	sam_account_name
SamAccount type	sam_account_type
Service binding information	service_binding_information
Service class name	service_class_name
Service DNS name	service_dns_name
Service DNS name type	service_dns_name_type
Service principal name	service_principal_name
Show in advanced view only	show_in_advanced_view_only
Source	source
User account control	user_account_control
USN changed	usn_changed
USN created	usn_created
When changed	when_changed