

Zurich ServiceNow AI Platform Capabilities

Last updated: January 16, 2026

Some examples and graphics depicted herein are provided for illustration only. No real association or connection to ServiceNow products or services is intended or should be inferred.

This PDF was created from content on docs.servicenow.com. The web site is updated frequently. For the most current ServiceNow product documentation, go to docs.servicenow.com.

Company Headquarters

2225 Lawson Lane
Santa Clara, CA 95054
United States
(408)501-8550

Service Graph Connector for Akamai API Security

Use the Service Graph Connector for Akamai API Security to integrate the APIs discovered by Akamai into your ServiceNow instance to support various API management use cases.

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Supported versions

- Supported ServiceNow versions:
 - Xanadu
 - Yokohama
 - Zurich
- Supported Akamai API Security REST APIs:
 - /api/v3/apis
 - /api/v3/sources
 - /auth/token

Use cases

The Service Graph Connector for Akamai API Security brings data into the new API Insights capability of the ServiceNow platform, enabling the management of different APIs in one instance. The connector adds information discovered by Akamai API Security to the API Component CI class.

The Service Graph Connector for Akamai API Security populates attributes that are security- and risk-related, such as the request and response data types, whether an API endpoint is internet-facing, and the

type of authentication used for the endpoint. These data points enable risk and security use cases to be implemented for API security.

Configuring a connection for the connector

You can configure a connection for the connector by using the SGC Central view in the CMDB Workspace. The view enables you to discover and install connectors, and then effectively manage the full life cycle of creating, editing, monitoring, and debugging connections. To configure the connector using SGC Central, see [Configure Service Graph Connector for Akamai API Security using SGC Central](#).

CMDB integrations dashboard

The Integration Commons for CMDB store app provides a dashboard with a central view of the status, processing results, and processing errors of all installed integrations. You can see metrics for all integration runs. You can filter the view to a specific CMDB integration, a specific time duration, or a specific integration run. For more details about monitoring Akamai API Security integrations in the CMDB Integrations Dashboard, see [Using the CMDB Integrations Dashboard](#).

Data mapping

Data from the Akamai API Security data sources is mapped and transformed into the ServiceNow CMDB Configuration Item (CI) class definitions using the Robust Transform Engine (RTE). Data is inserted into the ServiceNow CMDB using the Identification and Reconciliation Engine (IRE).

The following table lists the data sources, the staging tables, and the target tables as CMDB CI and non-CMDB classes for Akamai API Security.

Data mapping for Akamai API Security

Data source	Staging table	Target tables
Sources	sn_akamai_api_sec_akamai_sources	Akamai API Security Sources [sn_akamai_source]
API Component	sn_akamai_api_sec_sga_akamai_api_component	API Component [cmdb_ci_api_component]

Data source	Staging table	Target tables
		Key Value [cmdb_key_value]

You can use the IntegrationHub ETL app to view the data maps. See [IntegrationHub ETL](#) for more information.

Scheduled script for full data load

The Service Graph Connector for Akamai API Security supports both full load and delta load data ingestion methods. A full data load retrieves all API-related data and populates the corresponding CMDB tables. Delta loads fetch only the data that changed since the previous execution.

During the initial scheduled data import, a full data load is executed. Subsequent data imports perform delta loads.

To run a full data load on a recurring basis, customize the execution schedule of the Reset Last Run Datetime for SG-Akamai scheduled script based on your requirements. To open the Scheduled Script Executions table, enter `sysauto_script.list` in the navigation filter.

Additional resource

[Management API Reference](#)

Related tasks

- [Configure Service Graph Connector for Akamai API Security using SGC Central](#)

Related concepts

- [Service Graph Connectors](#)

Related reference

- [CMDB classes targeted in Service Graph Connector for Akamai API Security](#)

Configure Service Graph Connector for Akamai API Security using SGC Central

Use the playbook available with the SGC Central application to set up the Service Graph Connector for Akamai API Security for pulling in Akamai API Security data into the CMDB.

Before you begin

- Install Service Graph Connector for Akamai API Security version 1.0.0 from the ServiceNow Store.

For ServiceNow Store installation steps, see [Install a ServiceNow Store application](#).

- Create a service account on the Akamai platform and generate client credentials to enable data retrieval using the Service Graph Connector for Akamai API Security.

The Akamai API Security platform supports client credentials-based authentication. Client credentials are required to authenticate and securely access API data.

Role required: SGC-Admin (sn_cmdb_int_util.sgc_admin)

Note: The admin user role is required to run background scripts and to provide table-level access to the SGC-Admin user.

About this task

The playbook experience for onboarding connectors is activated with SGC Central in the CMDB Workspace. To configure the SGC Central application, see [Configuring SGC Central](#) and for more information on how to interact with a playbook, see [Interact with Playbook](#).

Procedure

1. Navigate to **Workspaces > CMDB Workspace**.
2. In the CMDB Workspace, select **SGC Central**.
3. On the Dashboard page, select **Create connection**.

Tip: Alternatively, you can select **Create connection** on the All connections page.

4. On the Create connection window, select the Akamai connector type, and then select **Create connection**.
5. Complete the initial prerequisites when setting up a connection for the first time using a connector.

Note: This step is required only during the first-time setup. See [Perform initial setup tasks when creating a connection in SGC Central](#).

6. Complete the setup for configuring the connector for importing data.
 - a. Create and test a connection.
 - a. In the **Setup** stage of the playbook, select the **Create and test connection** activity.
 - b. On the form, fill in the fields.

Create and test connection form

Field	
Akamai Connection Name	Name to identify the Akamai connection record. For example, Akamai.
Connection URL	URL of the connection.
OAuth Client ID	Application (client) ID of your Akamai client application.
OAuth Client Secret	Client secret of your Akamai client application.
OAuth Token URL	Token URL of your Akamai client application.

- c. Select **Create and test connection**.
 - d. After the connection test is complete, select **Continue**.
- b. Set the configuration properties to import tags and to configure source-based filtering.
 - a. In the **Setup** stage of the playbook, select the **Set configuration properties** activity.
 - b. (Optional) In the **Data retrieval configuration** section, specify the **Source name** or **Source alias** as a comma-separated list to fetch API Component data from specific sources or gateways, respectively.

Note: When a value is specified or updated in the **Source name** or **Source alias** field, the `last_run_datetime` field for SG-Akamai data sources is reset. This triggers full data ingestion during the next scheduled import. Subsequent runs perform delta loads based on the configured filters.
 - c. In the **Tags settings** section, select the **Import tags** check box to import tags for the records.
 - d. In the **Tags value separator** field, specify `=` as the key-value pair separator.
 - e. Select **Continue**.
- c. Configure the import schedule to import data at regular intervals.
 - a. In the **Setup** stage of the playbook, select the **Configure import schedule** activity.
 - b. Expand the Parent scheduled data import within the Import schedules list, and select the Sources import schedule.
 - c. In the Configure import schedule dialog box, select the **Active** check box, and then fill in the run schedule and time details.

For more information, see [Schedule a data import](#).

- d. Select **Save**.

Alternatively, select **Execute Now** to execute the import schedule immediately.

- e. Select **Continue**.
- d. In the **Setup** stage of the playbook, select the **Confirm connection setup** activity to verify whether the connection was created.

What to do next

Select **View all connections** to review the connection details. The configured connection appears in the Installed connections list.

Related concepts

- [Service Graph Connector for Akamai API Security](#)

Related reference

- [CMDB classes targeted in Service Graph Connector for Akamai API Security](#)

CMDB classes targeted in Service Graph Connector for Akamai API Security

When you complete setting up the connection, you can configure the integration to periodically pull data from Akamai API Security. The data is saved in tables that extend from the Configuration item [cmdb_ci] table.

API Component [cmdb_ci_api_component]

The following attributes in the API Component [cmdb_ci_api_component] table are populated by collected data:

Attribute label	Attribute name
Host	host
Method	method

Attribute label	Attribute name
Path	path
URL	url
Attributes	attributes
Authorization	authorization
Correlation ID	correlation_id
Internet Facing	internet_facing
Name	name
Operational status	operational_status
Product instance identifier	product_instance_id
Request Data Types	request_data_types
Response Data Types	response_data_types

Relationship created for API Component

Parent class	Relationship type	Child class
API Component [cmdb_ci_api_component]	Reference	Key Value [cmdb_key_value]

Key Value [cmdb_key_value]

The following attributes in the Key Value [cmdb_key_value] table are populated by collected data:

Attribute label	Attribute name
Key	key
Value	value

Attribute label	Attribute name
Configuration item	configuration_item

Related concepts

- [Service Graph Connector for Akamai API Security](#)

Accessing the connection details of Service Graph Connector for Akamai API Security

You can access the connection details of the Service Graph Connector for Akamai API Security in a single view using the common connection framework (CCF) included within the Integration Commons for CMDB (sn_cmdb_int_util) store app.

With the CCF, you can access all the connections used by the Service Graph Connector for Akamai API Security. The connection details include the connection alias, connection properties, data sources, and scheduled data imports associated with a connection. You can also test the connection. For more information, see [Accessing the connection details of Service Graph Connectors](#).

Access the details of an Akamai API Security connection

Access the details of an Akamai API Security connection configured for the Service Graph Connector for Akamai API Security.

Before you begin

Role required: admin

Procedure

1. Navigate to **All > Service Graph Connectors > Akamai API Security > Connections**.
2. From the **Name** column of the Service Graph Connections list, select a connection.

3. On the Service Graph Connections page, view the connection details such as the connection name, alias, and data sources.
4. Select a related list to view further details of the connection.
5. (Optional) Select the **Test Connection** related link to test the connection.

Related concepts

- [Service Graph Connector for Akamai API Security](#)

Service Graph Connector for Akamai API Security properties

Service Graph Connector for Akamai API Security properties control the behavior of the connector.

Connection properties

These connection properties are available for the Service Graph Connector for Akamai API Security.

Note: To open the Service Graph Connection Properties [sn_cmdb_int_util_service_graph_connection_property] table for the connector, navigate to **All > Service Graph Connectors > Akamai API Security > Connections**, and select the connection name. The connection properties are displayed in the Service Graph Connection Properties related list.

Connection properties for Service Graph Connector for Akamai API Security

Property	Description
Import tags	Set the property to <code>true</code> to import API tags. • Type: <code>true</code> <code>false</code> • Default value: <code>false</code>

Property	Description
Tags storage type	Specify whether the tag values should be stored in the Key Value [cmdb_key_value] table or in the Attributes field of the API Component [cmdb_ci_api_component] table. • Type: cmdb_key_value attributes • Default value: cmdb_key_value
Tags value separator	Specify the delimiter to parse tag strings into key-value pairs. • Type: custom • Default value: null