

Zurich ServiceNow AI Platform Capabilities

Last updated: January 16, 2026

Some examples and graphics depicted herein are provided for illustration only. No real association or connection to ServiceNow products or services is intended or should be inferred.

This PDF was created from content on docs.servicenow.com. The web site is updated frequently. For the most current ServiceNow product documentation, go to docs.servicenow.com.

Company Headquarters

2225 Lawson Lane
Santa Clara, CA 95054
United States
(408)501-8550

Service Graph Connector for Google Console

Use the Service Graph Connector for Google Console to import device details from Chromebooks into the Configuration Management Database (CMDB).

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Key features

- Get visibility across Chromebook devices.
- Get started quickly with a streamlined onboarding process.
- Use only the credentials you need.

Supported versions

Versions

Google Console	ServiceNow
Last tested on July 05, 2024	• Xanadu • Washington DC • Vancouver • Utah

Use cases

You can use the Service Graph Connector for Google Console to get visibility into Google ChromeOS devices, enabling administrators to centrally manage enrollment, configuration, and monitoring these devices.

Guided setup

The guided setup for the Service Graph Connector for Google Console provides an organized sequence of tasks to configure the integration on your instance. To access the guided setup, see [Configure Service Graph Connector for Google Console](#).

CMDB integrations dashboard

The Integration Commons for CMDB store app provides a dashboard with a central view of the status, processing results, and processing errors of all installed integrations. You can see metrics for all integration runs. You can filter the view to a specific CMDB integration, a specific time duration, or a specific integration run. For more details about monitoring Google Console integrations in the CMDB Integrations Dashboard, see [Using the CMDB Integrations Dashboard](#).

Data mapping

Data from the Google Console data source is mapped and transformed into the ServiceNow CMDB Configuration Item (CI) class definitions using the Robust Transform Engine (RTE). Data is inserted into the ServiceNow CMDB using the Identification and Reconciliation Engine (IRE).

When you complete setting up the connection, you can configure the integration to periodically pull data from the Google Console application.

Note: For any discovered resources that were deleted later, the Service Graph Connector for Google Console automatically marks the corresponding records as no longer active or valid in CMDB.

The following table lists the data sources, the staging tables, and the target tables as CMDB CI classes as where data is stored for a Chromebook device within Google Console.

Data mapping for Google Console

Data source	Staging table	CMDB CI classes	Resource type
SG-GoogleConsole-ChromeDevices	SG-GoogleConsole-ChromeDevices [sn_googlecons	Computer IP Address	Chrome OS devices

Data source	Staging table	CMDB CI classes	Resource type
	ole_i_sg_google_console_chrome_devices]	Network Adapter When the Software Asset Management (SAM) and SAM Foundation applications are not installed: Software Software Instance When the SAM application, the SAM Foundation application, or both are installed: Software Installation	

For more information on where data is saved when pulling data from a Chromebook device, see [CMDB classes targeted in Service Graph Connector for Google Console](#).

You can use the IntegrationHub ETL app to view the data maps. See [IntegrationHub ETL](#) for more information.

Related concepts

- [Service Graph Connectors](#)

Configure Service Graph Connector for Google Console

Set up scheduled import jobs to pull in Chromebook device data from the Google Console into your CMDB.

Before you begin

To use this Service Graph Connector, you need a subscription to a Subscription Unit that is based in the IT Operations Management (ITOM) Visibility application or in the ITOM Discovery application. As defined in the section titled "Managed IT Resource Types" in [ServiceNow Subscription Unit Overview](#) for your subscription, for managed IT resources that are created or modified in the CMDB by this Service Graph Connector, but that aren't yet managed by [ITOM Visibility](#) or [ITOM Discovery](#), these resources will increase Subscription Unit consumption from that application. Review your current Subscription Unit consumption within ITOM Visibility or ITOM Discovery to ensure available capacity.

Dependencies and requirements:

- The Integration Commons for CMDB store app, which is automatically installed. See [Integration Commons for CMDB](#).
- The CMDB CI class models store app, which is automatically installed. See [CMDB CI Class Models](#).
- ITOM Licensing plugin (com.snc.itom.license). See [Request Discovery](#).

Role required: admin

Procedure

1. Verify that the application scope is set to the Service Graph Connector for Google Console application by using the application picker.
For more information, see [Application picker](#).
2. Navigate to **All > Service Graph Connectors > Google Console > Setup**.
3. On the Service Graph Connector for Google Console page, verify that the **Quick Start** option is selected and then select **Continue**.

4. Configure the authentication credentials to send requests to the Google Console API.
 - a. In the Configure the Connection and Credentials section of the Service Graph Connector for Google Console page, select **Start**.
 - b. Set up the Google Console environment.
 - a. Select the Google Console Setup Instructions task.
 - b. Select the link to the [Service Graph connector for Google Console - Setup Instructions \[KB1516892\]](#) article in the Now Support Knowledge Base and follow the instructions to set up the Google Console environment.

Note: Make a note of the destination keystore password. You need to specify this password while importing the Java Keystore (JKS) certificate into the Service Graph Connector for Google Console application.
 - c. Set the Google Console Setup Instructions task to complete by selecting the **Mark as complete** check box and then select **Continue**.
 - c. Create an X.509 certificate to associate the JKS certificate for the Google Console application with the Service Graph Connector for Google Console.
 - a. Select the Create X.509 certificate task.
 - b. In the X.509 Certificates list, select **New**.
 - c. On the form, fill in the fields.

X.509 Certificate form

Field	Description
Name	Name of the X.509 certificate. For example, sG-GoogleConsole-509Certificate.

Field	Description
Type	Certificate container. Select Java Key Store .
Key store password	Password to access the JKS certificate as noted down in the previous step .

Note: You can leave the value of other fields as-is.

- d. Select the manage attachments icon (📎).
 - e. Select **Choose file** to browse and upload the keystore.p12 file for the JKS certificate you created in the [previous step](#).
 - f. Close the dialog box.
 - g. Select the **Validate Stores/Certificates** related link.
 - h. On successful validation, select **Update** to return to the guided setup page.
 - i. Set the Create X.509 certificate task to complete by selecting the **Mark as complete** check box and then select **Continue**.
- d. Configure the connection.
- a. Verify that the application scope is set to the Service Graph Connector for Google Console application by using the application picker.
 - b. Select the Configure the Connection task and then select **Click Here**.
 - c. On the Connections page that opens in another browser tab, select **Edit** for the **SG-GoogleConsole** connection that is available by default.
 - d. On the form, fill in the fields.

Edit Connection form

Field	Description
Connection Name	Name to identify the connection record. For example, sG-GoogleConsole. Don't modify the name for the default connection alias sG-GoogleConsole.
Service Account Email	Email address of the service account in Google Console.
Keystore Password	The password that you used when you created the JKS file in the previous step .
Keystore	Select the name of the JKS file you created in the previous step .

- e. Select **Edit and Get OAuth Token**.
- f. After the OAuth token is generated, return to the guided setup.
- g. Set the Configure the Connection task to complete by selecting the **Mark as complete** check box and then select **Continue**.
- e. Set up the configuration properties.
 - a. Select the Add configuration properties task.
 - b. In the Service Graph Connections section, review and modify the property details by selecting a property from the **Property** column in the Service Graph Connection Properties related list.

You can configure the Customer ID property to pull Chromebook devices for the specified customer ID.

- c. Select **Update** in the Service Graph Connection Properties section.
 - d. Set the Add connection properties task to complete by selecting the **Mark as complete** check box and then select **Continue**.
 - f. Test the Google Console API connection to import data from the Google Console application.
 - a. Select the Test Connection task.
 - b. Test the connection by selecting the **Test Connection** related link.

Testing the connection might take a few moments. The page is refreshed to show the test results.
 - c. When the **Status** field is set to **Success**, select **Update**.

If any of the tests have errors, follow the suggestions for remediation.
 - d. Set the Test Connection task to complete by selecting the **Mark as complete** check box and then select **Continue**.
5. (Optional) Integrate with multiple Google Console instances.
 - a. Follow the instructions in the [Service Graph connector for Google Console - Setup Instructions \[KB1516892\]](#) article in the Now Support Knowledge Base to set up the Google Console environment.

Note: Make a note of the destination keystore password.
 - b. In the Add Multiple Instances section of the Service Graph Connector for Google Console page, select **Start**.
 - c. Create data sources for the new Google Console connection.
 - a. Ensure that you have edit permissions for the Datasource [sys_data_source] table.

- b. Select the Update Data Source Access task.
- c. To edit the record, select the **Global** application scope from the application picker.
- d. In the Application Access related list of the Data Source form that opens in a new tab, select the **Can create**, **Can update**, and **Can delete** check boxes.
- e. Select **Update**.
 - f. From the application picker, select the Service Graph Connector for Google Console application scope.
 - g. Set the Update Data Source Access task to complete by selecting the **Mark as complete** check box and then select **Continue**.
- d. Create a scheduled import job for the new Google Console connection.
 - a. Ensure that you have edit permissions for the Scheduled data import [scheduled_import_set] table.
 - b. Select the Update Scheduled Data Import task.
 - c. To edit the record, select the **Global** application scope from the application picker.
 - d. In the Application Access related list of the Scheduled Data Import form, select the **Can create**, **Can update**, and **Can delete** check boxes.
 - e. Select **Update**.
 - f. From the application picker, select the Service Graph Connector for Google Console application scope.
 - g. Set the Update Scheduled Data Import task to complete by selecting the **Mark as complete** check box and then select **Continue**.
- e. Create an X.509 certificate for the new Google Console instance by repeating the step 4.c, and then mark the Create X.509 certificate task to complete by selecting the **Mark as complete** check box and then select **Continue**.

- f. Add another connection for the new Google Console instance.
 - a. Verify that the application scope is set to the Service Graph Connector for Google Console application by using the application picker.
 - b. Select the Add Another Connection task and then select **Click Here**.
 - c. On the Connections page that opens in another browser tab, select **Add Connection**.
 - d. On the form, fill in the fields.

Create Connection form

Field	Description
Connection Name	Name to identify the connection record.
Service Account Email	Email address of the service account in Google Console.
Keystore Password	The password that you used when you created the JKS file in the previous step .
Keystore	Select the name of the JKS file you created in the previous step .

- e. Select **Create and Get OAuth Token**.
 - f. After the OAuth token is generated, return to the guided setup.
 - g. Set the Add Another Connection task to complete by selecting the **Mark as complete** check box and then select **Continue**.
- g. Add the configuration properties for the new Google Console instance.
 - a. Select the Add configuration properties task.

- b. Select the connection record you created in the [previous step](#).
- c. In the Service Graph Connections section, review and modify the property details by selecting a property from the **Property** column in the Service Graph Connection Properties related list.

You can configure the Customer ID property to pull Chromebook devices for the specified customer ID.

- d. Select **Update** in the Service Graph Connection Properties section.
 - e. Set the Add connection properties task to complete by selecting the **Mark as complete** check box and then select **Continue**.
 - h. Test the Google Console API connection to import data from new Google Console instance.
 - a. Select the Test New Connections task.
 - b. Select the connection record you created in the [previous step](#).
 - c. Test the connection by selecting the **Test Connection** related link.

Testing the connection might take a few moments. The page is refreshed to show the test results.

 - d. When the **Status** field is set to **Success**, select **Update**.
- If any of the tests have errors, follow the suggestions for remediation.
- e. Set the Test New Connections task to complete by selecting the **Mark as complete** check box and then select **Continue**.
6. Configure the scheduled job for the import of Google Console data.
 - a. In the Configure the scheduled jobs section of the Service Graph Connector for Google Console page, select **Start**.

- b. Select the **SG-GoogleConsole-ChromeDevices** scheduled job.
For a multiple instance setup, select the scheduled job created with the scheduled import in step 5.d for the new connection.
- c. On the Scheduled Data Import form, verify the field values.

For more information, see [Schedule a data import](#).
- d. Select the **Active** check box to activate the scheduled job.
- e. In the **Run** field, select **Periodically** to specify how often the job will run.
- f. Select **Update**.
- g. Set the Configure the scheduled jobs task to complete by selecting the **Mark as complete** check box and then select **Continue**.
7. On the Service Graph Connector for Google Console page, select **Complete** to save your changes.
8. In the Complete setup dialog box, select **Complete** to complete the setup.
9. In the message box that appears, select **Done**.

CMDB classes targeted in Service Graph Connector for Google Console

When you complete setting up the connection, you can configure the integration to periodically pull Google Console data from Chromebook devices. The data is saved in tables that extend from the Configuration item [cmdb_ci] table.

Computer [cmdb_ci_computer]

The following attributes in the Computer [cmdb_ci_computer] table are populated by collected data:

Attribute label	Attribute name	Google Console attribute
Install Status	install_status	status

Attribute label	Attribute name	Google Console attribute
Model number	model_number	model
Model ID	model_id	model
Manufacturer	manufacturer	model
Name	name	serialNumber
Serial number	serial_number	serialNumber
Assigned	assigned	lastEnrollmentTime
Operating System	os	os
Operational status	operational_status	status
OS Version	os_version	osVersion
Assigned to	assigned_to	annotatedUser

Relationships created for Computer

Parent class	Relationship type	Child class
Computer [cmdb_ci_computer]	Owns::Owned by	Network Adapter [cmdb_ci_network_adapter]
Computer [cmdb_ci_computer]	Owns::Owned by	IP Address [cmdb_ci_ip_address]
Computer [cmdb_ci_computer]	Reference	When the Software Asset Management (SAM) and SAM Foundation applications aren't installed:

Parent class	Relationship type	Child class
		Software [cmdb_ci_spkg] Software Instance [cmdb_software_instance] When the SAM or SAM Foundation application is installed: Software Installation [cmdb_sam_sw_install]

IP Address [cmdb_ci_ip_address]

The following attributes in the IP Address [cmdb_ci_ip_address] table are populated by collected data:

Attribute label	Attribute name	Google Console attribute
IP Address	ip_address	lastKnownNetwork.ipAddress
Name	name	lastKnownNetwork.ipAddress
Nic	nic	macAddress

Relationship created for IP Address

Parent class	Relationship type	Child class
IP Address [cmdb_ci_ip_address]	Reference	Network Adapter [cmdb_ci_network_adapter]

Network Adapter [cmdb_ci_network_adapter]

The following attributes in the Network Adapter [cmdb_ci_network_adapter] table are populated by collected data:

Attribute label	Attribute name	Google Console attribute
Configuration Item	cmdb_ci	serialNumber
MAC Address	mac_address	macAddress
Name	name	macAddress

Relationship created for Network Adapter

Parent class	Relationship type	Child class
Network Adapter [cmdb_ci_network_adapter]	Reference	Computer [cmdb_ci_computer]

Software [cmdb_ci_spkg]

The following attributes in the Software [cmdb_ci_spkg] table are populated by collected data when the Software Asset Management (SAM) and SAM Foundation applications are not installed:

Attribute label	Attribute name	Google Console attribute
Key	key	name-version
Name	name	name
Version	version	version

Relationship created for Software

Parent class	Relationship type	Child class
Software [cmdb_ci_spkg]	Reference	Software Instance [cmdb_software_instance]

Software Installation [cmdb_sam_sw_install]

The following attributes in the Software Installation [cmdb_sam_sw_install] table are populated by collected data when the SAM application, the SAM Foundation application, or both are installed:

Attribute label	Attribute name	Google Console attribute
Discovery source	discovery_source	None
Display name	display_name	Name
Installed on	installed_on	serialNumber
Version	version	Version

Relationship created for Software Installation

Parent class	Relationship type	Child class
Software Installation [cmdb_sam_sw_install]	Reference	Computer [cmdb_ci_computer]

Software Instance [cmdb_software_instance]

The following attributes in the Software Instance [cmdb_software_instance] table are populated by collected data when the SAM and SAM Foundation applications are not installed:

Attribute label	Attribute name	Google Console attribute
Installed on	installed_on	serialNumber
Name	name	name, version, serialNumber

Relationship created for Software Instance

Parent class	Relationship type	Child class
Software Instance [cmdb_software_instance]	Reference	Computer [cmdb_ci_computer]