

Zurich ServiceNow AI Platform Capabilities

Last updated: January 16, 2026

Some examples and graphics depicted herein are provided for illustration only. No real association or connection to ServiceNow products or services is intended or should be inferred.

This PDF was created from content on docs.servicenow.com. The web site is updated frequently. For the most current ServiceNow product documentation, go to docs.servicenow.com.

Company Headquarters

2225 Lawson Lane
Santa Clara, CA 95054
United States
(408)501-8550

Service Graph Connector for Infoblox

Use the Service Graph Connector for Infoblox to pull data from an Infoblox instance into your ServiceNow instance.

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Supported versions

- Supported versions: Infoblox API v2.11.2
- Supported ServiceNow versions:
 - Xanadu
 - Yokohama
 - Zurich

Use cases

The following example use cases describe how you can use the Service Graph Connector for Infoblox for different ServiceNow® applications:

- Configure the Infoblox connection for connecting to an Infoblox instance.
- Create IP address management (IPAM) tasks when subnets are added or deleted.
- Schedule periodic synchronization of IPAM CIs by configuring scheduled data imports jobs.
- View imported IPAM CIs and IPAM tasks.

Configuring a connection for the connector

You can configure a connection for the connector by using the SGC Central view in the CMDB Workspace. The view enables you to

discover and install connectors, and then effectively manage the full life cycle of creating, editing, monitoring, and debugging connections. To configure the connector using SGC Central, see [Configure Service Graph Connector for Infoblox using SGC Central](#).

Important: Unless there are configuration issues, use the SGC Central view in the CMDB Workspace to configure the connection for the connector, as the guided setup method is being deprecated.

CMDB integrations dashboard

The Integration Commons for CMDB store app provides a dashboard with a central view of the status, processing results, and processing errors of all installed integrations. You can see metrics for all integration runs. You can filter the view to a specific CMDB integration, a specific time duration, or a specific integration run. For more details about monitoring Infoblox integrations in the CMDB Integrations Dashboard, see [Using the CMDB Integrations Dashboard](#).

Data mapping

Data from the Infoblox data source is mapped and transformed into the ServiceNow CMDB configuration item (CI) class definitions using the Robust Transform Engine (RTE). Data is inserted into the ServiceNow CMDB using the Identification and Reconciliation Engine (IRE).

When you complete setting up the connection, you can configure the integration to pull data periodically from Infoblox.

The following data sources are included for the Infoblox app:

SG-Infoblox IP Pool

Imports all the network containers from the Infoblox instance, loads the imported data in the SG-Infoblox IP Pool [sn_infoblox_integ_sg_infoblox_ip_pool] table, and then populates the IP Pool [cmdb_ci_ip_pool] target table. The SG-Infoblox Network data source runs after the SG-Infoblox IP Pool data source does.

SG-Infoblox Network

Runs after the SG-Infoblox IP Pool data source, imports the IPv4 and IPv6 networks and subnets data from the Infoblox instance, loads the imported data in the SG-Infoblox Detailed Subnetwork

[sn_infoblox_integ_sg_infoblox_detailed_subnetwork] table, and then populates the IP Network Subnet [cmdb_ci_ip_network_subnet] and Managed Network [cmdb_ci_managed_network] target tables. The SG-Infoblox IP Address data source runs after the SG-Infoblox Network data source does.

The Detailed Subnetwork

[sn_infoblox_integ_sg_infoblox_detailed_subnetwork] table determines which IP addresses are imported based on the value of the Get Ip Address field. To import an IP address, set the Get Ip Address field value to `true`. Alternatively, you can specify the list of IP addresses to be imported in pipe-delimited string format in the **Value** field of the sn_infoblox_integ.included_network_regex system property.

Note: IP addresses will not be imported during the first run of the Service Graph Connector for Infoblox unless you update the sn_infoblox_integ.included_network_regex system property because the Get Ip Address field value is set to `false` by default.

SG-Infoblox IP Address

Runs after the SG-Infoblox Network data source, imports the IPv4 and IPv6 IP addresses from the Infoblox instance, loads the imported data in the SG-Infoblox IP Address [sn_infoblox_integ_sg_infoblox_ip_address] table, and then populates the Allocated IP Address [cmdb_ci_allocated_ip_address], IP Network Subnet [cmdb_ci_ip_network_subnet], and Managed Network [cmdb_ci_managed_network] target tables.

SG-Infoblox DNS Alias

Imports all the canonical name (CNAME) records from the Infoblox instance, loads the imported data in the SG-Infoblox DNS Alias [sn_infoblox_integ_sg_infoblox_dns_alias] table, and then populates the DNS Alias [cmdb_ci_dns_alias] target table.

For more information on where data is saved when pulling data from Infoblox, see [CMDB classes targeted in Service Graph Connector for Infoblox](#).

You can use the IntegrationHub ETL app to view the data maps. See [IntegrationHub ETL](#) for more information.

Parallel data loading

Starting with the Service Graph Connector for Infoblox 1.3.0 version, parallel data loading can be enabled for the SG-Infoblox Network and SG-Infoblox IP Address data sources by setting the partition size in the `sn_infoblox_integ.parallel_loading_partition_size` system property. This system property determines the maximum number of networks that each partition processes. The maximum value that you can set for the partition size is 150.

- For the SG-Infoblox Network data source, the partition size is based on network views.
- For the SG-Infoblox IP Address data source, the partition size is based on the number of networks.

Related concepts

- [Service Graph Connectors](#)

Configure Service Graph Connector for Infoblox using SGC Central

Use the playbook available with the SGC Central application to set up the Service Graph Connector for Infoblox for pulling in Infoblox data into the CMDB.

Before you begin

Install Service Graph Connector for Infoblox version 1.2.0 or later from the ServiceNow Store. For ServiceNow Store installation steps, see [Install a ServiceNow Store application](#).

Role required: SGC-Admin (sn_cmdb_int_util.sgc_admin)

Note: The admin user role is required to run background scripts and to provide table-level access to the SGC-Admin user.

About this task

The playbook experience for onboarding connectors is activated with SGC Central in the CMDB Workspace. To configure the SGC Central

application, see [Configuring SGC Central](#) and for more information on how to interact with a playbook, see [Interact with Playbook](#).

Procedure

1. Navigate to **Workspaces > CMDB Workspace**.
2. In the CMDB Workspace, select **SGC Central**.
3. On the Overview page, select **Create connection**.

Tip: Alternatively, you can select **Create connection** on the All connections page.
4. On the Create connection window, select the Infoblox connector type and then select **Configure connection**.
A default connection, SG_Infoblox_Connection, for Infoblox is available within the application. As the Service Graph Connector for Infoblox supports only a single instance, you can configure the default connection for the first time or resume editing it thereafter.
5. Complete the initial prerequisites when setting up a connection for the first time using a connector.

Note: This step is required only during the first-time setup. See [Perform initial setup tasks when creating a connection in SGC Central](#).
6. Enter connection details and test the API connection for importing Infoblox data.
 - a. In the **Setup** stage of the playbook, select the **Configure and test connection** activity.
 - b. On the form, fill in the fields.

Configure and test connection form

Field	Description
Connection name	Name to identify the Infoblox connection record.

Field	Description
Connection URL	Infoblox base URL in the following format: <base-URL>.
User name	User name for authenticating the HTTP request.
Password	Password for the user name used for authenticating the HTTP request.
Use MID Server	Option to use the MID Server for connecting to the Infoblox instance. Note: A MID Server is required only if a direct connection between the ServiceNow and Infoblox instances isn't possible.
Mid Selection	MID Server for the connection. This field appears only when you select the Use MID Server check box.

- c. Select **Update and test connection**.
 - d. Once the connection test is complete, select **Continue**.
7. (Optional) Specify network views and the API version for connecting to the Infoblox instance by setting the configuration properties.

Note: To skip this step, select **Continue** for the **Set configuration properties** activity. If you skip this step, the default values of the Network view and API version properties are considered.

- a. In the **Setup** stage of the playbook, select the **Set configuration properties** activity.

- b. In the **Network view** field, enter the network views for which data is to be imported.
For multiple views, separate them with commas. For example: `view1,view2`.

If you leave this field empty or set it to **Default**, the data sources within the connector import data from all the network views.

- c. In the **API version** field, enter the [version of WAPI](#) you're using.

For more information about the Infoblox API, see the [Infoblox Developer documentation](#).

- d. Select **Save properties**.

- e. Select **Continue**.

8. (Optional) Opt for task creation on network insertion or deletion.

Note: To skip this step, select **Continue** for the **Configure task preferences** activity.

- a. In the **Setup** stage of the playbook, select the **Configure task preferences** activity.
- b. Select the **Create task on network insertion** check box to enable creating a task when a network is inserted.
- c. Select the **Create task on network deletion** to enable creating a task when a network is deleted.
- d. In the Task user group list, select the user group assigned to tasks created on network insertion or deletion.
- e. Select **Save preferences**.
- f. Select **Continue**.

9. Configure the import schedule to import data at regular intervals.

- a. In the **Setup** stage of the playbook, select the **Configure import schedule** activity.
- b. Select **Configure import schedule**.

- c. Expand the Parent scheduled data import within the Import schedules list to select the **SG-Infoblox IP Pool** import schedule.
- d. In the Configure import schedule dialog box, select the **Active** check box, and then fill in the run schedule and time details.

For more information, see [Schedule a data import](#).

- e. Select **Save**.
Alternatively, select **Execute Now** to execute the import schedule immediately.
 - f. Select **Continue**.
10. In the **Setup** stage of the playbook, select the **Confirm connection setup** activity to verify whether the connection was configured.

What to do next

Select **View all connections** to review the connection details. The configured connection appears in the Installed connections list.

Related concepts

- [Service Graph Connector for Infoblox](#)
- [Accessing the connection details of Service Graph Connector for Infoblox](#)

Related reference

- [CMDB classes targeted in Service Graph Connector for Infoblox](#)

Configure Service Graph Connector for Infoblox using the guided setup

Pull in data from Infoblox into your CMDB.

Before you begin

Important: Unless there are configuration issues, use the SGC Central view in the CMDB Workspace to configure the connection for the connector, as the guided setup method is being deprecated.

To use this Service Graph Connector, you need a subscription to a Subscription Unit that is based in the IT Operations Management (ITOM) Visibility application or in the ITOM Discovery application. As defined in the section titled "Managed IT Resource Types" in [ServiceNow Subscription Unit Overview](#) for your subscription, for managed IT resources that are created or modified in the CMDB by this Service Graph Connector, but that aren't yet managed by [ITOM Visibility](#) or [ITOM Discovery](#), these resources will increase Subscription Unit consumption from that application. Review your current Subscription Unit consumption within ITOM Visibility or ITOM Discovery to ensure available capacity.

Dependencies and requirements:

- The [Integration Commons for CMDB](#) store app, which is automatically installed.
- The CMDB CI class models store app, which is automatically installed. See [CMDB CI Class Models](#).
- The ITOM Discovery License plugin (com.snc.itom.discovery.license). You must activate this plugin.
- ITOM Licensing plugin (com.snc.itom.license). For more information, see [Request Discovery](#).
- The Datastream Action plugin (com.glide.hub.action_type.datastream), which is automatically installed.
- Observability Commons for CMDB (sn_observability), which is only required for event ingestion. This must be installed prior to installing the connector for Event Management to work. For more information, see [Observability Commons for CMDB](#) on the ServiceNow Store.

Note: If you have an earlier version of the Service Graph Connector for Infoblox, then don't migrate data from the old connector. You must uninstall the previous version and run the new integration.

Role required: SGC-Admin (sn_cmdb_int_util.sgc_admin)

Note: The admin user role is required to run background scripts and to provide table-level access to the SGC-Admin user.

Procedure

1. Ensure that the application scope is set to the Service Graph Connector for Infoblox application by using the application picker. For more information, see [Application picker](#).
2. Navigate to **All > Service Graph Connectors > Infoblox > Setup**.
3. On the Getting started page, select **Get Started**.
4. Configure the authentication credentials and HTTP connection details for sending requests to the Infoblox API.
 - a. Configure your Infoblox authentication credentials.
 - a. In the Configure the connection section of the Service Graph Connector for Infoblox page, select **Get Started**.
 - b. For the Configure Infoblox authentication credentials task, select **Configure** to open the Basic Auth Credentials page opens in a new browser tab.
 - c. In the **Name** field, enter a name for the authentication.
For example, `Infoblox Credential`.
 - d. In the **User name** field, enter the user name that is used to authenticate the HTTP request when this authentication profile is enabled.
 - e. In the **Password** field, enter the password for the user name that is used to authenticate the HTTP request.
 - f. Select **Update** to return to the guided setup page.

- For multiple views, separate the views with commas. For example: `view1,view2`. If you leave this field empty, the data sources import data from all the network views.

- c. Configure the connection properties.
 - a. For the Configure connection properties task, select **Configure** to open the Service Graph Connections page in a new browser tab.
 - b. To review and modify the property details, select a property from the **Property** column in the Service Graph Connection Properties related list.

- c. Select **Update** on the Service Graph Connection Properties page.
 - d. Select **Update** on the Service Graph Connections page to return to the guided setup page.
 - e. Set the Configure connection properties task to complete by selecting **Mark as Complete**.
- d. Test the Infoblox API connection to import data from the Infoblox application.
 - a. In the Configure the connection section of the Service Graph Connector for Infoblox page, select **Continue**.
 - b. For the Test the connection task, select **Configure** to open the Service Graph Connections page in a new browser tab.
 - c. Select **Test Connection**.
 - d. When the **Status** field is set to **Success**, select **Update** to close the Test the connection dialog box and return to the guided setup page.

If any of the tests have errors, follow the suggestions for remediation.

 - e. Set the Test the connection task to complete by selecting **Mark as Complete**.
5. (Optional) Add multiple instances.

Note: If you don't need to add multiple instances, you can skip this step.

 - a. In the Add Multiple Instances section of the Service Graph Connector for Infoblox page, select **Get Started**.
 - b. For the Update Data Source Access task, select **Configure**.
 - c. Select the Data Source [sys_data_source] table.
 - d. Select the **Global** application scope by using the application picker.

- e. In the Application Access related list, select the **Can create**, **Can update**, and **Can delete** check boxes, if not already selected.
- f. Select **Update** to close the tab and return to the guided setup.
- g. Modify the application scope again to **Service Graph Connector for Infoblox** by using the application picker.
- h. Set the Update Data Source Access task to complete by selecting **Mark as Complete**.
- i. For the Update Scheduled Data Import Access task, select **Configure**.
- j. Select the Scheduled data import [scheduled_import_set] table.
- k. Repeat steps 5.d to 5.g.
- l. Set the Update Scheduled Data Import Access task to complete by selecting **Mark as Complete**.
- m. Clear the cache for the new connection.
 - a. For the Clear Cache for Data Source and Scheduled Data Imports tables task, select **Configure**.
 - b. Select the **Global** application scope by using the application picker.
 - c. In the **Run script** text box of the background script page, enter the following script:


```
GlideTableManager.invalidateTable("sys_data_source");
GlideCacheManager.flushTable("sys_data_source");

GlideTableManager.invalidateTable("scheduled_import_set");
GlideCacheManager.flushTable("scheduled_import_set");

GlideTableManager.invalidateTable("sys_db_object");
GlideCacheManager.flushTable("sys_db_object");
```
 - d. Select **Run Script** to run the background script.

The script may take several minutes to execute.

- e. After the script is executed, select **Close**.
- f. Modify the application scope again to **Service Graph Connector for Infoblox** by using the application picker.
- g. Set the Clear Cache for Data Source and Scheduled Data Imports tables task to complete by selecting **Mark as complete**.
- n. Add a basic authentication connection to the new Infoblox instance.
 - a. For the Add Another Basic Auth Connection task, select **Configure**.
 - b. To create a new connection, select **Add Connection**.
 - c. In the Connection Information section of the Create Connection window, fill in the fields.

Connection Information

Field	Description
Connection name	Name to identify the Infoblox connection record.
Connection URL	Infoblox base URL in the following format: <base - URL>.
Use MID Server	Option to use a MID Server. Note: Use of a MID Server is optional.
MID Selection	Name of the MID Server used by the connector.

Field	Description
	This field appears only when the Use MID server check box is selected.
MID Application	Name of the MID application used by the connector. This field appears only when the Use MID server check box is selected.

- d. In the Credential Information section of the Create Connection window, fill in the fields.

Credential Information

Field	Description
Username	Infoblox account user name that is used to authenticate the connection request.
Password	Password that is used to authenticate the connection request.

- e. Select **Create Connection**.
- f. Navigate back to the guided setup, and set the Add Another Basic Auth Connection task to complete by selecting **Mark as Complete**.
- o. Test the newly added connections.
- a. For the Test connections task, select **Configure**.
- b. From the **Name** column, select the new connection.

- c. Select the **Test Connection** related link to start the testing process.
 - d. When the **Status** field is set to **Success**, return to the guided setup page.
Note: If any of the tests have errors, follow the suggestions for remediation.
 - e. Set the Test connections task to complete by selecting **Mark as Complete**.
6. Configure the IP address management tasks and user groups.
 - a. Enable properties to create an IP address management task when deleting or inserting a network.
 - a. In the Configure IP address management tasks section of the Service Graph Connector for Infoblox page, select **Get Started**.
 - b. For Enable creating a task, select **Configure** to open the Enable create Task page in a new browser tab.
 - c. Select the **Create a task when a network is deleted** and **Create a task when a network is inserted** check boxes to enable properties for creating IP address management tasks when deleting and inserting a network, respectively.
 - d. Select **Save**.
 - e. Close the Enable create Task page tab and return to the guided setup page.
 - f. Set Enable creating a task to complete by selecting **Mark as Complete**.
 - b. Configure the user group for IP address management tasks.
 - a. For the Configure the user group for IP address management tasks task, select **Configure** to open the SG Infoblox Connection page in a new browser tab.
 - b. In the **Connection alias** field, review and change the connection alias.

- c. In the **Task user group** field, change the assignment group for the connection alias.

Note: By default, the user group for the IP address management tasks is assigned to the IP Address Management user group. To change the default assignment group, change the task user group for the connection alias.

- d. Select **Update** to return to the guided setup page.
- e. Set the Configure the user group for IP address management tasks task to complete by selecting **Mark as Complete**.

7. Configure the scheduled jobs to import data from the Infoblox application.

- a. In the Set up scheduled import jobs section of the Service Graph Connector for Infoblox page, select **Get started**.
- b. For the Configure the scheduled jobs task, select **Configure** to open the Scheduled Data Imports page in a new browser tab.
- c. From the **Name** column, select the scheduled job that you want to activate.
- d. On the Scheduled Data Import form, verify the field values for the scheduled job.
For more information, see [Schedule a data import](#).
- e. Select **Update**.
- f. Repeat the steps 7.c to 7.e for each scheduled job for data import.
- g. Close the Scheduled Data Imports page tab and return to the guided setup page.
- h. Set the Configure the scheduled jobs task to complete by selecting **Mark as Complete** in the guided setup.

CMDB classes targeted in Service Graph Connector for Infoblox

When you complete setting up the connection, you can configure the integration to pull data periodically from Infoblox. The data is saved in tables that extend from the Configuration item [cmdb_ci] table.

Allocated IP Address [cmdb_ci_allocated_ip_address]

The following attributes in the Allocated IP Address [cmdb_ci_allocated_ip_address] table are populated by collected data:

Attribute label	Attribute name
IP Address	ip_address
Managed Network	managed_network
Is Broadcast	is_broadcast
Is Conflict	is_conflict
Is DHCP	is_dhcp
Is DNS	is_dns
Is Managed	is_managed
Is Reserved	is_reserved
Name	name

Relationship created for Allocated IP Address

Parent class	Relationship type	Child class
Allocated IP Address [cmdb_ci_allocated_ip_address]	Reference	Managed Network [cmdb_ci_managed_network]

DNS Alias [cmdb_ci_dns_alias]

The following attribute in the DNS Alias [cmdb_ci_dns_alias] table is populated by collected data:

Attribute label	Attribute name
Name	name

IP Network Subnet [cmdb_ci_ip_network_subnet]

The following attributes in the IP Network Subnet [cmdb_ci_ip_network_subnet] table are populated by collected data:

Attribute label	Attribute name
Name	name
Parent Pool	parent_pool
CIDR	cidr

Relationships created for IP Network Subnet

Parent class	Relationship type	Child class
IP Network Subnet [cmdb_ci_ip_network_subnet]	Members::Member of	Allocated IP Address [cmdb_ci_allocated_ip_address]
IP Network Subnet [cmdb_ci_ip_network_subnet]	Reference	SG-Infoblox Detailed Subnetwork [sn_infoblox_integ_sg_infoblox_detailed_subnetwork]

IP Pool [cmdb_ci_ip_pool]

The following attributes in the IP Pool [cmdb_ci_ip_pool] table are populated by collected data:

Attribute label	Attribute name
Name	name
Parent Pool	parent_pool
CIDR	cidr

Managed Network [cmdb_ci_managed_network]

The following attribute in the Managed Network [cmdb_ci_managed_network] table is populated by collected data:

Attribute label	Attribute name
Name	name

SG-Infoblox Detailed Subnetwork [sn_infoblox_integ_sg_infoblox_detailed_subnetwork]

The following attributes in the SG-Infoblox Detailed Subnetwork [sn_infoblox_integ_sg_infoblox_detailed_subnetwork] table are populated by collected data:

Attribute label	Attribute name
Connection ID	connection_id
Get Ip Address	list_ip_address
Network	network
Network Type	network_type
Network View	network_view

Accessing the connection details of Service Graph Connector for Infoblox

You can access the connection details of the Service Graph Connector for Infoblox in a single view using the common connection framework (CCF) included within the Integration Commons for CMDB (sn_cmdb_int_util) store app.

With the CCF, you can access all the connections used by the Service Graph Connector for Infoblox. The connection details include the connection alias, connection properties, data sources, and scheduled data imports associated with a connection. You can also test the connection. For more information, see [Accessing the connection details of Service Graph Connectors](#).

Access the details of an Infoblox connection

Access the details of an Infoblox connection configured for the Service Graph Connector for Infoblox.

Before you begin

Role required: admin

Procedure

1. Navigate to **All > Service Graph Connectors > Infoblox > Connections**.
2. From the **Name** column of the Service Graph Connections list, select a connection.
3. On the Service Graph Connections page, view the connection details such as the connection name, alias, and data sources.
4. Select a related list to view further details of the connection.
5. (Optional) Select the **Test Connection** related link to test the connection.