

Zurich ServiceNow AI Platform Capabilities

Last updated: January 16, 2026

Some examples and graphics depicted herein are provided for illustration only. No real association or connection to ServiceNow products or services is intended or should be inferred.

This PDF was created from content on docs.servicenow.com. The web site is updated frequently. For the most current ServiceNow product documentation, go to docs.servicenow.com.

Company Headquarters

2225 Lawson Lane
Santa Clara, CA 95054
United States
(408)501-8550

Service Graph Connector for Microsoft Defender Endpoint

Use the Service Graph Connector for Microsoft Defender Endpoint to pull data from machines protected by the Microsoft Defender for Endpoint security solution into your ServiceNow instance.

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Supported versions

- Supported Microsoft Defender for Endpoint versions:
 - Microsoft Defender for Endpoint Plan 1
 - Microsoft Defender for Endpoint Plan 2
- Supported ServiceNow versions:
 - Washington DC
 - Xanadu
 - Yokohama

Use cases

The ServiceNow Security Operations applications have features that interact with the Service Graph Connector to gain insights into machines utilizing the Microsoft Defender for Endpoint security solution.

Important Information for upgrading Service Graph Connector for Microsoft Defender Endpoint

After you upgrade to Service Graph Connector for Microsoft Defender Endpoint 1.2.0, migrate data from the Server [cmdb_ci_server] CI class to the Computer [cmdb_ci_computer] CI class. For more information, see the [Service Graph Connector for Microsoft Defender Endpoint - Data](#)

[migration after upgrade to version 1.2.0 \[KB2096769\]](#) article in the Now Support Knowledge Base.

Configuring a connection for the connector

You can configure a connection for the connector by using the SGC Central view in the CMDB Workspace. The view enables you to discover and install connectors, and then effectively manage the full life cycle of creating, editing, monitoring, and debugging connections. To configure the connector using SGC Central, see [Configure Service Graph Connector for Microsoft Defender Endpoint using SGC Central](#).

Important: Unless there are configuration issues, use the SGC Central view in the CMDB Workspace to configure the connection for the connector, as the guided setup method is being deprecated.

CMDB integrations dashboard

The Integration Commons for CMDB store app provides a dashboard with a central view of the status, processing results, and processing errors of all installed integrations. You can see metrics for all integration runs. You can filter the view to a specific CMDB integration, a specific time duration, or a specific integration run. For more details about monitoring Microsoft Defender for Endpoint integrations in the CMDB Integrations Dashboard, see [Using the CMDB Integrations Dashboard](#).

Data mapping

Data from the Microsoft Defender for Endpoint data source is mapped and transformed into the ServiceNow CMDB configuration item (CI) class definitions using the Robust Transform Engine (RTE). Data is inserted into the ServiceNow CMDB using the Identification and Reconciliation Engine (IRE).

When you complete setting up the connection, you can configure the integration to pull data periodically from the machines utilizing the Microsoft Defender for Endpoint security solution.

The following data source is included for the Microsoft Defender for Endpoint security solution:

SG-Defender Machines

Imports all the machine-related data from the machines utilizing the Microsoft Defender for Endpoint security solution, loads the imported data in the SG-Defender Machines [sn_defender_integ_sg_defender_machines] staging table, and then populates the following target tables:

- IP Address [cmdb_ci_ip_address]
- Software Installation [cmdb_sam_sw_install] (If the Software Asset Management (SAM) application is installed.)
- Software Instance [cmdb_software_instance] (If the SAM application is not installed.)
- Software [cmdb_ci_spkg] (If the SAM application is not installed.)
- SG-Defender Machines Related [sn_defender_integ_sg_defender_machines_related]
- Network Adapter [cmdb_ci_network_adapter]
- Computer [cmdb_ci_computer]
- Windows Server [cmdb_ci_win_server]

Note: Only operating system details are populated in the Software Installation [cmdb_sam_sw_install], Software Instance [cmdb_software_instance], and Software [cmdb_ci_spkg] tables.

For more information on where data is saved when pulling data from the Microsoft Defender for Endpoint security solution, see [CMDB classes targeted in Service Graph Connector for Microsoft Defender Endpoint](#).

You can use the IntegrationHub ETL app to view the data maps. See [IntegrationHub ETL](#) for more information.

Related concepts

- [Service Graph Connectors](#)

Configure Service Graph Connector for Microsoft Defender Endpoint using SGC Central

Set up scheduled import jobs to pull in Microsoft Defender for Endpoint data into your Configuration Management Database (CMDB).

Before you begin

Complete the following tasks:

- Install Service Graph Connector for Microsoft Defender Endpoint version 1.1.0 or later from the ServiceNow Store. For ServiceNow Store installation steps, see [Install a ServiceNow Store application](#).
- Verify that you have an active subscription to Microsoft Defender for Endpoint.
- Verify that you have created an Azure application to get programmatic access to Microsoft Defender for Endpoint. See [Create an app to access Microsoft Defender for Endpoint without a user](#) in the Microsoft 365 documentation.
- Obtain the tenant ID, client ID, and client secret details for the Microsoft Defender for Endpoint administrator account.
- Enable the Machine.Read.All and Machine.ReadWrite.All permissions in Microsoft Defender for Endpoint. See [Permissions](#) for the List machines API in the Microsoft 365 documentation.

Role required: SGC-Admin (sn_cmdb_int_util.sgc_admin)

Note: The admin user role is required to run background scripts and to provide table-level access to the SGC-Admin user.

About this task

The playbook experience for onboarding connectors is activated with SGC Central in the CMDB Workspace. To configure the SGC Central application, see [Configuring SGC Central](#) and for more information on how to interact with a playbook, see [Interact with Playbook](#).

Procedure

1. Navigate to **Workspaces > CMDB Workspace**.
2. In the CMDB Workspace, select **SGC Central**.
3. On the Overview page, select **Create connection**.

Tip: Alternatively, you can select **Create connection** on the All connections page.

4. On the Create connection window, select the Microsoft Defender connector type, and then select **Configure connection**.
A default connection, SG Defender OAuth2.0 connection, for Microsoft Defender for Endpoint is available within the application. As the Service Graph Connector for Microsoft Defender Endpoint supports only a single instance, you can configure the default connection for the first time or resume editing it thereafter.
5. Complete the initial prerequisites when setting up a connection for the first time using a connector.

Note: This step is required only during the first-time setup. See [Perform initial setup tasks when creating a connection in SGC Central](#).

6. Enter connection details and test the API connection for importing Microsoft Defender for Endpoint data.
 - a. In the **Setup** stage of the playbook, select the **Configure and test connection** activity.
 - b. On the form, fill in the fields.

Configure and test connection form

Field	Description
Connection Name	Name to identify the Microsoft Defender for Endpoint connection record.

Field	Description
	Note: This field is automatically set to sG Defender OAuth2.0 connection. Leave the field value as is.
OAuth Client ID	Application (client) ID of your Microsoft Defender for Endpoint as described in the Before you begin section.
OAuth Client Secret	Client Secret of your Microsoft Defender for Endpoint as described in the Before you begin section.
OAuth token URL	Token URL of your Microsoft Defender for Endpoint. Enter the token URL in the following format: <code>https://login.microsoftonline.com/<tenantid>/oauth2/v2.0/token</code> Where <tenantid> is the tenant ID of your Microsoft Defender for Endpoint as described in the Before you begin section.
Use MID Server	Option to use a MID Server. Note: Use of a MID Server is optional.
Mid Selection	Name of the MID Server used by the connector.

Field	Description
	This field appears only when the Use MID Server check box is selected.

- c. Select **Update and test connection**.
 - d. Once the connection test is complete, select **Continue**.
7. Configure the import schedule to import data at regular intervals.
 - a. In the **Setup** stage of the playbook, select the **Configure import schedule** activity.
 - b. Select **Configure import schedule**.
 - c. Expand the Parent scheduled data import within the Import schedules list to select the **SG-Defender Machines** import schedule.
 - d. In the Configure import schedule dialog box, select the **Active** check box, and then fill in the run schedule and time details.

For more information, see [Schedule a data import](#).
 - e. Select **Save**.
Alternatively, select **Execute Now** to execute the import schedule immediately.
 - f. Select **Continue**.
8. In the **Setup** stage of the playbook, select the **Confirm connection setup** activity to verify whether the connection was configured.

What to do next

Select **View all connections** to review the connection details. The configured connection appears in the Installed connections list.

Related concepts

- [Service Graph Connector for Microsoft Defender Endpoint](#)

- [Accessing the connection details of Service Graph Connector for Microsoft Defender Endpoint](#)

Related reference

- [CMDB classes targeted in Service Graph Connector for Microsoft Defender Endpoint](#)

Configure Service Graph Connector for Microsoft Defender Endpoint using the guided setup

Pull in data from machines using the Microsoft Defender for Endpoint security solution into your Configuration Management Database (CMDB).

Before you begin

Important: Unless there are configuration issues, use the SGC Central view in the CMDB Workspace to configure the connection for the connector, as the guided setup method is being deprecated.

To use this Service Graph Connector, you need a subscription to a Subscription Unit that is based in the IT Operations Management (ITOM) Visibility application or in the ITOM Discovery application. As defined in the section titled "Managed IT Resource Types" in [ServiceNow Subscription Unit Overview](#) for your subscription, for managed IT resources that are created or modified in the CMDB by this Service Graph Connector, but that aren't yet managed by [ITOM Visibility](#) or [ITOM Discovery](#), these resources will increase Subscription Unit consumption from that application. Review your current Subscription Unit consumption within ITOM Visibility or ITOM Discovery to ensure available capacity.

Dependencies and requirements:

- The [Integration Commons for CMDB](#) store app, which is automatically installed.
- The CMDB CI class models store app, which is automatically installed. See [CMDB CI Class Models](#).
- The ITOM Discovery License plugin (com.snc.itom.discovery.license). You must activate this plugin.

- ITOM Licensing plugin (com.snc.itom.license). For more information, see [Request Discovery](#).
- The Datastream Action plugin (com.glide.hub.action_type.datastream), which is automatically installed.
- Observability Commons for CMDB (sn_observability), which is only required for event ingestion. For Event Management to work, the Observability Commons for CMDB (sn_observability) app must be installed prior to installing the connector. For more information, see [Observability Commons for CMDB](#) on the ServiceNow Store.

Complete the following tasks:

- Install the Service Graph Connector for Microsoft Defender Endpoint application (sn_defender_integ). For more information, see [Install a ServiceNow Store application](#).
- Ensure that you have an active subscription to Microsoft Defender for Endpoint.
- Ensure that you have created an Azure application to get programmatic access to Microsoft Defender for Endpoint. See [Create an app to access Microsoft Defender for Endpoint without a user](#) in the Microsoft 365 documentation.
- Obtain the tenant ID, client ID, and client secret details for the Microsoft Defender for Endpoint administrator account.
- Enable the Machine.Read.All and Machine.ReadWrite.All permissions in Microsoft Defender for Endpoint. See [Permissions](#) for the List machines API in the Microsoft 365 documentation.

Role required: SGC-Admin (sn_cmdb_int_util.sgc_admin)

Note: The admin user role is required to run background scripts and to provide table-level access to the SGC-Admin user.

Procedure

1. Ensure that the application scope is set to the Service Graph Connector for Microsoft Defender Endpoint application by using the application picker.

For more information, see [Application picker](#).

2. Navigate to **All > Service Graph Connectors > Microsoft Defender > Setup**.
3. On the Getting started page, select **Get Started**.
4. Configure the authentication credentials details for sending requests to the List machines API in Microsoft Defender for Endpoint.
 - a. Configure your Microsoft Defender for Endpoint authentication credentials.
 - a. In the Configure the connection section of the Service Graph Connector for Microsoft Defender page, select **Get Started**.
 - b. For the Configure the credentials task, select **Configure**.
 - c. On the form, review and modify the fields.

Application Registries form

Field	Description
Connection Name	Name to identify the connection record. Note: This field is automatically set to the sG Defender OAuth connection record. Leave the field value as is.
Client ID	Application (client) ID of your Microsoft Defender for Endpoint as described in the Before you begin section.
Client Secret	Client Secret of your Microsoft Defender for Endpoint as described in the Before you begin section.

Field	Description
OAuth Token URL	Token URL of your Microsoft Defender for Endpoint. Enter the token URL in the following format: <pre>https://login.microsoftonline.com/<tenantid>/oauth2/v2.0/token</pre> Where <tenantid> is the tenant ID of your Microsoft Defender for Endpoint as described in the Before you begin section.

- d. Select **Update** to return to the guided setup page.
 - e. Set the Configure the credentials task to complete by selecting **Mark as Complete**.
- b. Test the List machines API connection to import machine-related data from Microsoft Defender for Endpoint.
 - a. For the Test the connection task, select **Configure**.
 - b. On the Service Graph Connections page, select **Test Connection**.
 - c. When the **Status** field is set to **Success**, select **Update** to close the Test the connection dialog box and return to the guided setup page.

If any of the tests have errors, follow the suggestions for remediation.

 - d. Set the Test the connection task to complete by selecting **Mark as Complete**.
5. Configure the scheduled jobs to import machine-related data from Microsoft Defender for Endpoint.
 - a. In the Set up scheduled import jobs section of the Service Graph Connector for Microsoft Defender page, select **Get Started**.

- b. For the Configure scheduled jobs task, select **Configure**.
- c. From the **Name** column, select the scheduled job that you want to activate.
By default, the SG-Defender Machines scheduled job is available to run the SG-Defender Machines data source.
- d. On the Scheduled Data Import form, verify the field values for the scheduled job.
For more information, see [Schedule a data import](#).
- e. Select **Update**.
- f. Select the back button of your browser to return to the guided setup page.
- g. Set the Configure the scheduled jobs task to complete by selecting **Mark as Complete** in the guided setup.

Related concepts

- [Accessing the connection details of Service Graph Connector for Microsoft Defender Endpoint](#)

CMDB classes targeted in Service Graph Connector for Microsoft Defender Endpoint

When you complete setting up the connection, you can configure the integration to pull data periodically from machines utilizing the Microsoft Defender for Endpoint security solution. The data is saved in tables that extend from the Configuration item [cmdb_ci] table.

Computer [cmdb_ci_computer]

The following attributes in the Computer [cmdb_ci_computer] table are populated by collected data:

Attribute label	Attribute name
Class	sys_class_name
Discovery source	discovery_source

Attribute label	Attribute name
Install Status	install_status
Name	name
Operating System	os
OS Version	os_version

Relationships created for Computer

Parent class	Relationship type	Child class
Computer [cmdb_ci_computer]	Owns::Owned by	IP Address [cmdb_ci_ip_address]
Computer [cmdb_ci_computer]	Owns::Owned by	Network Adapter [cmdb_ci_network_adapter]
Computer [cmdb_ci_computer]	Reference	SG-Defender Machines Related [sn_defender_integ_sg_defender_machines_related]
Computer [cmdb_ci_computer]	Reference	Software Installation [cmdb_sam_sw_install]

IP Address [cmdb_ci_ip_address]

The following attributes in the IP Address [cmdb_ci_ip_address] table are populated by collected data:

Attribute label	Attribute name
Install Status	install_status
IP Address	ip_address
IP version	ip_version

Attribute label	Attribute name
Name	name
Nic	nic

Relationship created for IP Address

Parent class	Relationship type	Child class
IP Address [cmdb_ci_ip_address]	Reference	Network Adapter [cmdb_ci_network_adapter]

SG-Defender Machines Related [sn_defender_integ_sg_defender_machines_related]

The following attributes in the SG-Defender Machines Related [sn_defender_integ_sg_defender_machines_related] table are populated by collected data:

Attribute label	Attribute name
Agent Version	agent_version
Device Id	device_id
Exposure Level	exposure_level
First Seen	first_seen_date
Health Status	health_status
IsAadJoined	isaadjoined
Last Reported	last_reported
Managed by	managed_by
Onboarding Status	onboarding_status

Network Adapter [cmdb_ci_network_adapter]

The following attributes in the Network Adapter [cmdb_ci_network_adapter] table are populated by collected data:

Attribute label	Attribute name
Discovery source	discovery_source
Install Status	install_status
MAC Address	mac_address
Name	name

Relationships created for Network Adapter

Parent class	Relationship type	Child class
Network Adapter [cmdb_ci_network_adapter]	Reference	Server [cmdb_ci_server]
Network Adapter [cmdb_ci_network_adapter]	Reference	Computer [cmdb_ci_computer]

Software [cmdb_ci_spkg]

The following attributes in the Software [cmdb_ci_spkg] table are populated by collected data when the Software Asset Management (SAM) application isn't installed:

Attribute label	Attribute name
Key	key
Name	name
Version	version

Relationship created for Software

Parent class	Relationship type	Child class
Software [cmdb_ci_spkg]	Reference	Software Instance [cmdb_software_instance]

Software Installation [cmdb_sam_sw_install]

The following attributes in the Software Installation [cmdb_sam_sw_install] table are populated by collected data when the SAM application is installed:

Attribute label	Attribute name
Discovery source	discovery_source
Display name	display_name
Version	version

Software Instance [cmdb_software_instance]

The following attributes in the Software Instance [cmdb_software_instance] table are populated by collected data when the SAM application isn't installed:

Attribute label	Attribute name
Installed on	installed_on
Name	name

Relationship created for Software Instance

Parent class	Relationship type	Child class
Software Instance [cmdb_software_instance]	Reference	Server [cmdb_ci_server]

Windows Server [cmdb_ci_win_server]

The following attributes in the Windows Server [cmdb_ci_win_server] table are populated by collected data when the SAM application isn't installed:

Attribute label	Attribute name
Class	sys_class_name
Discovery source	discovery_source
Install Status	install_status
Name	name
Operating System	os
OS Version	os_version

Relationships created for Windows Server

Parent class	Relationship type	Child class
Windows Server [cmdb_ci_win_server]	Owns::Owned by	Network Adapter [cmdb_ci_network_adapter]
Windows Server [cmdb_ci_win_server]	Owns::Owned by	IP Address [cmdb_ci_ip_address]
Windows Server [cmdb_ci_win_server]	Reference	SG-Defender Machines Related [sn_defender_integ_sg_defender_machines_related]
Windows Server [cmdb_ci_win_server]	Reference	Software Installation [cmdb_sam_sw_install]

Properties

Service Graph Connector for Microsoft Defender Endpoint properties control the behavior of the connector.

System properties

These system properties are available for Service Graph Connector for Microsoft Defender Endpoint.

Note: To open the System Properties [sys_properties] table, enter `sys_properties.list` in the navigation filter.

System properties for Service Graph Connector for Microsoft Defender Endpoint

Property	Description
sn_defender_integ.pagination_record_count	Enter the maximum number of rows fetched in the List machines API response from the machine resource type. - Type: integer - Default value: 500 - Location: System Property [sys_properties] table

Accessing the connection details of Service Graph Connector for Microsoft Defender Endpoint

You can access the connection details of the Service Graph Connector for Microsoft Defender Endpoint in a single view using the common connection framework (CCF) included within the Integration Commons for CMDB (sn_cmdb_int_util) store app.

With the CCF, you can access all the connections used by the Service Graph Connector for Microsoft Defender Endpoint. The connection

details include the connection alias, data sources, and scheduled data imports associated with a connection. You can also test the connection.

Access the details of a Microsoft Defender for Endpoint connection

Access the details of a Microsoft Defender for Endpoint connection configured for the Service Graph Connector for Microsoft Defender Endpoint.

Before you begin

Role required: admin

Procedure

1. Navigate to **All > Service Graph Connectors > Microsoft Defender > Connections**.
2. From the **Name** column of the Service Graph Connections list, select a connection.
3. On the Service Graph Connections page, view the connection details such as the connection name, alias, and data sources.
4. Select a related list to view further details of the connection.
5. (Optional) Select the **Test Connection** related link to test the connection.

Related concepts

- [Accessing the connection details of Service Graph Connectors](#)

Life cycle management of records in Service Graph Connector for Microsoft Defender Endpoint

Life cycle management in the Service Graph Connector for Microsoft Defender Endpoint monitors and updates the statuses of Microsoft Defender for Endpoint resources throughout their entire life cycle, from creation to deletion.

The life cycle management process helps maintain the accuracy and integrity of data in the Configuration Management Database (CMDB).

Life cycle management for CIs in Service Graph Connector for Microsoft Defender Endpoint

The following table lists the configuration items (CIs) in CMDB and other non-CMDB tables for which life cycle management is available in the Service Graph Connector for Microsoft Defender Endpoint. The Install Status [install_status] attribute of the CIs is updated to installed or retired according to the state of the CI.

Supported tables for life cycle management

Data source	CIs	Life cycle management available
SG-Defender Machines	Windows Server [cmdb_ci_win_server]	Yes
SG-Defender Machines	IP Address [cmdb_ci_ip_address]	Yes
SG-Defender Machines	Network Adapter [cmdb_ci_network_adapter]	Yes
SG-Defender Machines	Computer [cmdb_ci_computer]	Yes