

Zurich ServiceNow AI Platform Capabilities

Last updated: January 16, 2026

Some examples and graphics depicted herein are provided for illustration only. No real association or connection to ServiceNow products or services is intended or should be inferred.

This PDF was created from content on docs.servicenow.com. The web site is updated frequently. For the most current ServiceNow product documentation, go to docs.servicenow.com.

Company Headquarters

2225 Lawson Lane
Santa Clara, CA 95054
United States
(408)501-8550

Service Graph Connector for Microsoft Intune

Use the Service Graph Connector for Microsoft Intune to pull data from the Microsoft Intune application into your ServiceNow instance.

The Service Graph Connector for Microsoft Intune pulls data from mobile devices, computers and software applications into the ServiceNow® Configuration Management Database (CMDB) application. The integration provides greater visibility into mobile devices, computers and related software applications that run on them.

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Supported versions

Versions

Microsoft Intune	ServiceNow
- Microsoft Intune Graph API v1.0 - Microsoft Intune Graph API Beta	- Xanadu - Yokohama - Zurich

Use cases

The following are examples on how you can use the Service Graph Connector for different ServiceNow® applications:

- IT Operations Management (ITOM) Visibility
 - Detailed hardware and application inventory for Android, Apple, and Windows mobile devices. The inventory can be used with or without Software Asset Management (SAM).

- Compliance tracking for mobile devices. You can build your own device (BYOD) or use corporate-owned devices.
- [IT Service Management \(ITSM\)](#)
 - Incidents, problems, and changes on discovered configuration items (CI).
 - Ownership tracking and assignment for mobile devices.

You can also do the following types of administrative actions:

- Device Management: You can report on various aspects of the device.
- Integration with Azure Monitor: Delta notification.

Configuring a connection for the connector

You can configure a connection for the connector by using the SGC Central view in the CMDB Workspace. The view enables you to discover and install connectors, and then effectively manage the full life cycle of creating, editing, monitoring, and debugging connections. To configure the connector using SGC Central, see [Configure Service Graph Connector for Microsoft Intune using SGC Central](#).

Important: Starting with the Service Graph Connector for Microsoft Intune version 2.7.0, the guided setup method is deprecated. Use the SGC Central view in the CMDB Workspace to configure the connection for the connector.

CMDB integration dashboards

The Integration Commons for CMDB store app provides a dashboard with a central view of the status, processing results, and processing errors of all installed integrations. You can see metrics for all integration runs. You can filter the view to a specific CMDB integration, a specific time duration, or a specific integration run. For more details about monitoring Microsoft Intune integrations in the CMDB Integrations Dashboard, see [Using the CMDB Integrations Dashboard](#).

Data mapping

Data from data sources in the Microsoft Intune application is mapped and transformed into the ServiceNow CMDB Configuration Item (CI) class definitions using the Robust Transform Engine (RTE). Data is inserted into

the ServiceNow CMDB using the Identification and Reconciliation Engine (IRE).

The following table describes the data sources, the staging tables, and the target tables as CMDB CI classes, and the resource types imported for a Microsoft Intune application.

Data mapping for Microsoft Intune

Data source	Staging table	CMDB CI classes	Resource types	Data source type
SG-Intune Computer	SG-Intune Computer [sn_intune_integrat_computer]	Computer SG-Intune Computer Related IP Address Serial Number When the Software Asset Management (SAM) application isn't installed: Software Software Instance When the SAM application is installed: Software Installation	Computers	Regular

Data source	Staging table	CMDB CI classes	Resource types	Data source type
SG-Intune Devices	SG-Intune Devices [sn_intune_integrat_devices]	Handheld Computing Device Serial Number Network Adapter SG-Intune Device Related IP Address When the Software Asset Management (SAM) application isn't installed: Software Software Instance When the SAM application is installed: Software Installation	Mobile devices	Regular
SG-Intune Software	SG-Intune Software [sn_intune_in	Software	Discovered apps	Regular

Data source	Staging table	CMDB CI classes	Resource types	Data source type
	tegrat_software]			
SG-Intune Device Reports	SG-Intune Device Reports [sn_intune_in_tegrat_device_reports]	Computer or Handheld Computing Device Serial Number Network adapter SG-Intune Computer Related SG-Intune Device Related IP Address Note: Imports Wireless (Wi-Fi) IPv4 Address of a device only. When the Software Asset Management (SAM)	Computers and mobile devices	Advanced

Data source	Staging table	CMDB CI classes	Resource types	Data source type
		application isn't installed: Software Software Instance When the SAM application is installed: Software Installation		
SG-Intune Software Reports	SG-Intune Software Reports [sn_intune_integrat_software_reports]	When the Software Asset Management (SAM) application isn't installed: Software Software Instance When the SAM application is installed: Software Installation	Discovered apps	Advanced

Starting with the Service Graph Connector for Microsoft Intune 2.7.0 version, the SG-Intune Device Reports and SG-Intune Software Reports advanced data sources are not available by default. To use these

advanced data sources, you must select the **Advanced data sources** option while configuring the connection using SGC Central. See [Configure Service Graph Connector for Microsoft Intune using SGC Central](#).

Configure the SG-Intune Device Reports and SG-Intune Software Reports advanced data sources for faster data import, better performance, and inclusion of software publisher details. Compared to the regular data sources (SG-Intune Computer, SG-Intune Devices, and SG-Intune Software), the advanced data sources help resolve server errors and performance issues caused by having a large number of Microsoft Intune devices.

For more information, see [Service Graph Connector For Microsoft Intune - Advanced \(Configure advanced Data sources\) \[KB1641546\]](#).

Note: The SG-Intune Device Reports advanced data source is an alternative to the SG-Intune Computer and SG-Intune Devices regular data sources. The SG-Intune Software Reports advanced data source is an alternative to the SG-Intune Software data source. The data imported by the advanced data sources is similar to the data imported by the corresponding regular data sources.

After you complete setting up the connection, you can configure the integration to periodically pull data from the Microsoft Intune application.

Note:

- For any discovered software applications that were deleted later in the Microsoft Intune application, the Service Graph Connector automatically deletes the corresponding records in CMDB.
- To view more details about a handheld computing device or computer in the Computer [cmdb_ci_computer] class, enable the related lists SG-Intune Device Related and SG-Intune Computer Related.

You can add these related lists by configuring the Related Lists view on the form that opens when you select a handheld computing device or computer configuration item (CI) in the Computer [cmdb_ci_computer] class. Computer CIs are displayed in the Computers list, accessed by navigating to **All > Configuration > Base Items > Computers**. For more information about adding related lists to a form, see [Configuring the form layout](#).

For more information on where data is saved when pulling data from a Microsoft Intune application, see [CMDB classes targeted in Service Graph Connector for Microsoft Intune](#).

You can use the IntegrationHub ETL app to view the data maps. See [IntegrationHub ETL](#) for more information.

Additional resources

- [Service Graph Connector for Microsoft Intune - Troubleshooting connection issues](#) article on the ServiceNow Community site
- [Service Graph Connector For Microsoft Intune - Advanced \(Configure advanced Data sources\) \[KB1641546 \]](#) article in the Now Support Knowledge Base

Related tasks

- [Configure Service Graph Connector for Microsoft Intune using SGC Central](#)

Related concepts

- [Service Graph Connectors](#)

Configure Service Graph Connector for Microsoft Intune using SGC Central

Use the playbook available with the SGC Central application to set up the Service Graph Connector for Microsoft Intune for pulling in Microsoft Intune data into the CMDB.

Before you begin

Install Service Graph Connector for Microsoft Intune version 2.5.0 or later from the ServiceNow Store. For ServiceNow Store installation steps, see [Install a ServiceNow Store application](#).

Obtain the following information from your Microsoft Intune administrator:

- Client ID
- Client Secret
- Token URL

For the connector to access the data in Microsoft Intune, the credential information is required to use the Microsoft Graph API. Therefore, you must grant the following Graph API permissions from the App registrations page in the Microsoft portal:

- DeviceManagementManagedDevices.Read.All (Type: Application)
- DeviceManagementApps.Read.All (Type: Application)
- User.Read.All (Type: Application)

Dependencies and requirements:

- The [Integration Commons for CMDB](#) store app, which is automatically installed.
- The CMDB CI class models store app, which is automatically installed. See [CMDB CI Class Models](#).

- Datastream Action plugin (com.glide.hub.action_type.datastream), which is automatically installed.
- ITOM Licensing plugin (com.snc.itom.license). For more information, see [Request Discovery](#).
- ServiceNow IntegrationHub Zip step (com.glide.hub.action_step.zip), which is automatically installed.
- ServiceNow IntegrationHub JSON Parser step (com.glide.hub.action_step.jsonparser), which is automatically installed.
- The SGC Central application (sn_sgc_central), which is automatically installed.

Role required: SGC-Admin (sn_cmdb_int_util.sgc_admin)

Note: The admin user role is required to perform the following tasks:

- Run background scripts.
- Configure advanced data sources.
- Provide table-level access to the SGC-Admin user.

About this task

The playbook experience for onboarding connectors is activated with SGC Central in the CMDB Workspace. To configure the SGC Central application, see [Configuring SGC Central](#) and for more information on how to interact with a playbook, see [Interact with Playbook](#).

For more details on permissions, see [Service Graph Connector for Microsoft Intune - Troubleshooting connection issues](#) on ServiceNow Community and [Microsoft Graph permissions reference](#) on the Microsoft documentation site.

Procedure

1. Navigate to **Workspaces > CMDB Workspace**.
2. In the CMDB Workspace, select **SGC Central**.
3. On the Overview page, select **Create connection**.

Tip: Alternatively, you can select **Create connection** on the All connections page.

4. On the Create connection window, select the Microsoft Intune connector type and then select **Create connection**.
5. Complete the initial prerequisites when setting up a connection for the first time using a connector.

Note: This step is required only during the first-time setup. See [Perform initial setup tasks when creating a connection in SGC Central](#).

6. Select the data source type.
 - a. In the **Setup** stage of the playbook, select the **Select data source type** activity.
 - b. Select a data source type:
 - **Advanced data sources:** Advanced data sources offer faster data import and better performance, and include software publisher details. Select this option if you have a large number of Microsoft Intune devices.

Note:

- The admin role is required to configure advanced data sources.
- The response for advanced data sources is returned in ZIP file format. Ensure that the value of the glide.attachment.extensions system property either is empty or includes `zip`, `bin`, `json`.
- **Regular data sources:** The standard option, which doesn't include software publisher details.

- c. Select **Continue**.
7. Enter connection details and test the API connection for importing Microsoft Intune data.

- a. In the **Setup** stage of the playbook, select the **Create and test connection** activity.
- b. On the form, fill in the fields.

Create and test connection form

Field	Description
Connection Name	Name to identify the Microsoft Intune connection record. For example, SG-Intune connection.
Connection URL	Base URL to connect to your Microsoft Intune application. Based on the region of your Microsoft Intune application, enter the connection URL in one of the following formats: - Global https://graph.microsoft.com - US Government https://graph.microsoft.us - China https://microsoftgraph.chinacloudapi.cn - Germany https://graph.cloudapi.de/

Field	Description
OAuth Client ID	Client ID of the Microsoft Intune application as noted in the Before you begin section.
OAuth Client Secret	Client secret of the Microsoft Intune application as noted in the Before you begin section.
OAuth Token URL	Callback URL for the Microsoft Intune application. Based on the region of your Microsoft Intune application, enter the token URL in one of the following formats: - Global https://login.microsoftonline.com/<tenantid>/oauth2/v2.0/token - US Government https://login.microsoftonline.us/<tenantid>/oauth2/v2.0/token - China https://login.partner.microsoftonline.cn/<tenantid>/oauth2/v2.0/token - Germany https://login.microsoftonline.de/<tenantid>/oauth2/v2.0/token

Field	Description
	Where <tenantid> is the tenant ID of your Microsoft Intune application.
Use MID server	Option to use the MID Server for connecting to the Microsoft Intune instance. Note: A MID Server is required only if a direct connection between the ServiceNow and Microsoft Intune instances isn't possible.
Mid Selection	MID Server for the connection. This field appears only when you select the Use MID Server check box.

- c. Select **Create and test connection**.
- d. Once the connection test is complete, select **Continue**.
8. Configure the connection properties to enable the connector to access resources.
 - a. In the **Setup** stage of the playbook, select the **Configure properties** activity.
 - b. In the **Configure properties** section, update the connection properties for advanced and regular data sources if required.
 - c. Select **Continue**.
9. Configure the report trigger job for advanced data sources. The **Activate report trigger job** activity appears only if you selected **Advanced data sources** in step 6.b. The advanced data sources require device reports and software reports to be triggered in the

Microsoft environment before related jobs and scheduled imports are run.

- a. In the **Setup** stage of the playbook, select the **Activate report trigger job** activity.
- b. Fill in the fields on the **Scheduled Script Execution** form.

Scheduled Script Execution form

Field	Description
Name	Specify a name for the report trigger job.
Active	Select this check box to activate the report trigger job.
Run	Specify the schedule for the job to be run.
Time	Specify the time when the job should run.
Run as	Specify the user role required to run the report trigger job.

Note: After you configure the report trigger job, all related jobs and the device and software reports scheduled imports are automatically scheduled to run in a specific sequence a few hours later (typically 3–4 hours). You can review the scheduled imports that are already activated and their scheduled time in step 10.

- c. Select **Continue**.
10. Configure the import schedule to import data at regular intervals.
- a. In the **Setup** stage of the playbook, select the **Configure import schedule** activity.
 - b. Expand the Parent scheduled data import within the Import schedules list to select the **Connection Name-SG-Intune Devices** import schedule.

- c. Select the **Active** check box, and then fill in the run schedule and time details.

For more information, see [Schedule a data import](#).

- d. Select **Save**.
Alternatively, select **Execute Now** to execute the import schedule immediately.
- e. Select **Continue**.

11. In the **Setup** stage of the playbook, select the **Confirm connection setup** activity to verify whether the connection was configured.

What to do next

Select **View all connections** to review the connection details. The configured connection appears in the Installed connections list.

Related concepts

- [Service Graph Connector for Microsoft Intune](#)
- [Accessing the connection details of Service Graph Connector for Microsoft Intune](#)

Related reference

- [CMDB classes targeted in Service Graph Connector for Microsoft Intune](#)

Configure Service Graph Connector for Microsoft Intune using the guided setup

Set up authentication credentials and a scheduled job to import Microsoft Intune data into your CMDB.

Before you begin

Important: Starting with the Service Graph Connector for Microsoft Intune version 2.7.0, the guided setup method is deprecated. Use the SGC Central view in the CMDB Workspace to configure the connection for the connector.

To use this Service Graph Connector, you need a subscription to a Subscription Unit that is based in the IT Operations Management (ITOM) Visibility application or in the ITOM Discovery application. As defined in the section titled "Managed IT Resource Types" in [ServiceNow Subscription Unit Overview](#) for your subscription, for managed IT resources that are created or modified in the CMDB by this Service Graph Connector, but that aren't yet managed by [ITOM Visibility](#) or [ITOM Discovery](#), these resources will increase Subscription Unit consumption from that application. Review your current Subscription Unit consumption within ITOM Visibility or ITOM Discovery to ensure available capacity.

Obtain the following information from your Microsoft Intune administrator:

- Client ID
- Client Secret
- Token URL

For the connector to access the data in Microsoft Intune, the credential information is required to use the Microsoft Graph API. Therefore, you must grant the following Graph API permissions from the App registrations page in the Microsoft portal:

- DeviceManagementManagedDevices.Read.All (Type: Application)
- DeviceManagementApps.Read.All (Type: Application)
- User.Read.All (Type: Application)

For more details on permissions, see [Service Graph Connector for Microsoft Intune - Troubleshooting connection issues](#) on ServiceNow Community and [Microsoft Graph permissions reference](#) on the Microsoft documentation site.

Dependencies and requirements:

- The [Integration Commons for CMDB](#) store app, which is automatically installed.
- The CMDB CI class models store app, which is automatically installed. See [CMDB CI Class Models](#).
- Datastream Action plugin (com.glide.hub.action_type.datastream), which is automatically installed.
- ITOM Licensing plugin (com.snc.itom.license). For more information, see [Request Discovery](#).
- ServiceNow IntegrationHub Zip step (com.glide.hub.action_step.zip), which is automatically installed.
- ServiceNow IntegrationHub JSON Parser step (com.glide.hub.action_step.jsonparser), which is automatically installed.

Starting with Service Graph Connector for Microsoft Intune 2.1.1 release, the multi-instance support is available to import data from multiple Microsoft Intune instances. This feature involves dynamically creating data sources and scheduled imports; thus, requires the granting of additional permissions. The guided setup includes additional steps for this feature.

Role required: SGC-Admin (sn_cmdb_int_util.sgc_admin)

Note: The admin user role is required to run background scripts and to provide table-level access to the SGC-Admin user.

Procedure

1. Navigate to **All > Service Graph Connectors > Intune > Setup**.
2. On the Getting Started page, select **Get started**.
3. Configure the credentials.
 - a. On the Service Graph Connector for Microsoft Intune page, in the Configure the connection section, select the task **Configure credentials**.
 - b. On the next page, in the Configure credentials task section, select **Configure**.

c. On the form, fill in the fields.

Edit Connection form

Field	Description
Connection Name	Name of the Microsoft Intune application. This field is automatically set.
Connection URL	Connection URL for the connection. Based on the region of your Microsoft Intune application, enter the connection URL in one of the following formats: - Global <code>https://graph.microsoft.com</code> - US Government <code>https://graph.microsoft.us</code> - China <code>https://microsoftgraph.chinacloudapi.cn</code> - Germany <code>https://graph.cloudapi.de/</code>
OAuth Client ID	The client ID of the Microsoft Intune application.
OAuth Client Secret	The client secret of the Microsoft Intune application.
OAuth Token URL	Callback URL for the Microsoft Intune application.

Field	Description
	Based on the region of your Microsoft Intune application, enter the token URL in one of the following formats: - Global https://login.microsoftonline.com/<tenantid>/oauth2/v2.0/token - US Government https://login.microsoftonline.us/<tenantid>/oauth2/v2.0/token - China https://login.partner.microsoftonline.cn/<tenantid>/oauth2/v2.0/token - Germany https://login.microsoftonline.de/<tenantid>/oauth2/v2.0/token Where <tenantid> is the tenant ID of your Microsoft Intune application.

d. Select **Edit and Get OAuth Token**.

e. Go back to the guided setup page and for the Configure credentials task, select **Mark as Complete**.

4. (Optional) If needed, configure the MID Server.

- a. In the Configure MID Server section, select **Configure**.
- b. Select the **Use MID server** check box.
- c. Select **Update** to save the record.

Note: You do not need to update the other fields.

5. Test the connection to the Microsoft Intune API.

- a. In the Test the connection section, select **Configure**.
- b. On the form, review the fields.

Data Source form

Field	Description
Name	Unique name for this data source.
Import set table label	Label of the table that will be created for this data source.
Import set table name	Name of the table that will be created for this data source.
Data in single column	Option to set to data in single column.
Type	Data storage type of the data to be imported.
Application	Application containing this record.

- c. (Optional) Modify the properties in the Service Graph Connection Properties related list of the connection record.

Note: Try to retain the default value of the software_path property to ensure the proper retrieval of software details.

- d. Select the **Test Connection** related link to start the testing process.

- e. When the **Status** field is set to **Success**, return to the guided setup page.
If any of the tests have errors, follow the suggestions for remediation.
 - f. In the Test the connection task section, select **Mark as Complete**.
6. Add multiple instances.
 - a. On the left sidebar, select the Add Multiple Instances icon
 - b. On the Service Graph Connector for Microsoft Intune page, in the Add Multiple Instances section, select the Update Data Source Access task.
 - c. Select the **Global** application scope by using the application picker.
 - d. In the Application Access related list, select the **Can create**, **Can update**, and **Can delete** check boxes, if not already selected.
 - e. Select **Update** to close the tab and return to the guided setup.
 - f. Modify the application scope again to **Service Graph Connector for Microsoft Intune** by using the application picker.
 - g. Set the Update Data Source Access task to complete by selecting **Mark as Complete**.
 - h. Repeat the steps 6.c to 6.f for the Update Scheduled data import access task with the Scheduled data import [scheduled_data_set] table and set the task to complete by selecting **Mark as Complete**.
7. Clear the cache for the new connection.
 - a. In the Clear Cache for Datasource and Import set section, select **Configure**.

- b. In the **Run script** text box of the background script page, enter the following script:

```
GlideTableManager.invalidateTable("sys_data_source");
GlideCacheManager.flushTable("sys_data_source");

GlideTableManager.invalidateTable("scheduled_import_set");
GlideCacheManager.flushTable("scheduled_import_set");

GlideTableManager.invalidateTable("sys_db_object");
GlideCacheManager.flushTable("sys_db_object");
```

- c. Select **Run Script** to run the background script in the **global** scope.
The script may take several minutes to execute.
- d. After the script is executed, select **Close**.
- e. From the application picker, select the **Service Graph Connector for Microsoft Intune** application.
- f. Select **Mark as Complete**.
8. To either add or save the connection, select **Configure** for the Create or Edit connection task.
- To add a connection, select **Add Connection**.
 - To save the edits for the existing connection, select **Edit**.

Note: Obtain the following information from your Microsoft Intune administrator:

- Client ID
- Client Secret
- Token URL

When a Microsoft Intune administrator registers an application, the Client ID, Client Secret, and Token URL will be available. To get more information about how to register an application, see the [Microsoft Intune documentation site](#).

- On the form, fill in the fields or edit as needed.

Create Connection form

Field	Description
Connection Name	Display name for the connection.
Connection URL	Connection URL for the new connection. Based on the region of your Microsoft Intune application, enter the connection URL in one of the following formats: • Global <code>https://graph.microsoft.com</code> • US Government <code>https://graph.microsoft.us</code> • China <code>https://microsoftgraph.chinacloudapi.cn</code>

Field	Description
	Germany https://graph.cloudapi.de/
OAuth Client ID	Client ID for the Microsoft Intune application.
OAuth Client Secret	Client Secret for the Microsoft Intune application.
OAuth Token URL	Callback URL for the Microsoft Intune application. Based on the region of your Microsoft Intune application, enter the token URL in one of the following formats: - Global https://login.microsoftonline.com/<tenantid>/oauth2/v2.0/token - US Government https://login.microsoftonline.us/<tenantid>/oauth2/v2.0/token - China https://login.partner.microsoftonline.cn/<tenantid>/oauth2/v2.0/token - Germany https://login.microsoftonline.de/<tenantid>/oauth2/v2.0/token

Field	Description
	id>/oauth2/v2.0/token Where <tenantid> is the tenant ID of your Microsoft Intune application.

- b. Either add or save the connection.
 - To create the new connection, select **Create and Get OAuth Tokens**.
 - To save the edits for the existing connection, select **Edit and Get OAuth Token**.
- c. Navigate back to the guided setup and select **Mark as Complete**.
- d. (Optional) Set up the MID Server for the connection you created.
 - a. In the Configure Mid Servers section, select **Configure**.
 - b. Select the name of the connection you created.
 - c. Select the **Use MID server** check box.
 - d. Select **Update**.
 - e. When you're finished with the task, select **Mark as Complete**
9. Test the API connection to import data from the Microsoft Intune application.
 - a. Test the connection, in the Test New Connections section, by selecting **Configure**.
 - a. Select the name of the data source associated with the newly created connection.
 - b. Select the **Test Connection** related link to start the process.
 - c. Optionally modify the properties in the Service Graph Connection Properties related list.

Microsoft Intune connection properties

Property	Description
api_version	The version of the Microsoft Intune Graph API.
software_path	The path of the software code for finding apps and associated devices or vice versa. Leave the property value as is.
include_primary_user_details	Enable retrieving the details of the primary user during import and populating the assigned_to attribute in the records of the cmdb_ci table by setting the property value to <code>true</code>. For retrieving the enrolled user details, set the property value to <code>false</code>. Retrieving primary user details increases the time for importing data because of additional API calls. Note: When a user is assigned to a device initially, the enrolled and primary users are the same. If the device is reassigned to another user, the primary user name is reassigned to the new user, but the enrolled user is still the original enrolled user name.

Property	Description
include_ip_address_details	Enable retrieving the IP addresses of devices during import and populate the records in the cmdb_ci_ip_address table by setting the property value to <code>true</code>. To skip retrieving IP addresses, set the property to <code>false</code>. Retrieving IP addresses increases the time for importing data because of additional API calls.

Note: The properties in the Service Graph Connection Properties related list of the connection record are modifiable. However, try to retain the default value of the `software_path` property to ensure the proper retrieval of software details.

- d. When the **Status** field is set to **Success**, return to the guided setup page.

Note: If any of the tests have errors, follow the suggestions for remediation.

- e. Return to the guided setup and select **Mark as Complete** for the Test New Connections task.

10. Set up the scheduled import jobs.

- a. For the Configure scheduled jobs task in the Set up scheduled import jobs section, select **Configure**.
- b. Select the name of the scheduled import you want to run.
- c. On the Scheduled Data Import form, verify the field values for the scheduled job and select the **Active** check box.

For more information, see [Schedule a data import](#).

- d. Select **Update**.
 - e. Set the Configure scheduled jobs task to complete by selecting **Mark as Complete**.
11. Use advanced options to resolve server errors and improve performance with the SG-Intune Computer, SG-Intune Devices, and SG-Intune Software data sources while importing a large number of devices into the Microsoft Intune portal.

Note:

- The SG-Intune Device Reports data source serves as an alternative to the SG-Intune Computer and SG-Intune Devices data sources, importing the same information while optimizing the data retrieval process by minimizing API calls and reducing import time.
- The SG-Intune Software Reports data source serves as an alternative to the SG-Intune Software data source.
- Both the SG-Intune Device Reports and SG-Intune Software Reports data sources require the paid ServiceNow IntegrationHub Professional Pack Installer (com.glide.hub.integrations.professional) plugin.
- To enable the creation of attachments, the glide.attachment.extensions system property must be set to either null or bin, zip, json.

For more information, see the [Service Graph Connector For Microsoft Intune – Advanced \[KB1641546\]](#) article in the Now Support Knowledge Base.

- a. Configure the scheduled jobs to import data using the SG-Intune Device Reports and SG-Intune Software Reports data sources.
 - a. In the Advanced [Beta] section, for the Configure scheduled jobs for advanced data sources task, select **Configure**.
 - b. In the Scheduled jobs list, select **SG-Intune Trigger Device Reports** job.

- c. On the Scheduled Script Execution form, verify the field values for the scheduled job and select the **Active** check box.

For more information, see [Schedule script execution form](#).

- d. Select **Update**.
- e. To activate the scheduled job for the SG-Intune Software Reports data source, repeat steps 11.a.ii to 11.a.iv by selecting the **SG-Intune Trigger Software Reports** scheduled job.
- f. Return to the guided setup page and set the Configure scheduled jobs for advanced data sources task to complete by selecting **Mark as Complete**.

Important:

- Deactivate the SG-Intune Computer and SG-Intune Devices scheduled imports after setting up the SG-Intune Trigger Device Reports scheduled job for the SG-Intune Device Reports data source.
- Deactivate the SG-Intune Software scheduled import after setting up the SG-Intune Trigger Software Reports scheduled job.
- Activate the ServiceNow IntegrationHub Professional Pack Installer (com.glide.hub.integrations.professional) plugin on your instance.

For more information, see the [Service Graph Connector For Microsoft Intune – Advanced \[KB1641546\]](#) article in the Now Support Knowledge Base.

- b. Configure the scheduled import for the SG-Intune Device Reports and SG-Intune Software Reports data sources.
 - a. In the Advanced [Beta] section, for the Configure the scheduled import for advanced data sources task, select **Configure**.
 - b. In the Scheduled Data Imports list, select the **SG-Intune Device Reports** scheduled import.

- c. On the Scheduled Data Import form, verify the field values for the scheduled data import and select the **Active** check box.

For more information, see [Schedule a data import](#).

- d. Select **Update**.
 - e. Return to the guided setup page and set the Configure the scheduled import for advanced data sources task to complete by selecting **Mark as Complete**.
- Important:** Verify that the SG-Intune Device Reports scheduled import is configured to run 3 hours after the SG-Intune Trigger Device Reports and SG-Intune Trigger Software Reports scheduled jobs.

Example: If the SG-Intune Trigger Device Reports job is set for 9 a.m. and SG-Intune Trigger Software Reports for 10 a.m. daily, schedule the SG-Intune Device Reports scheduled import for 1 p.m. daily.

- c. When using multiple instances, update the permissions on the Scheduled Script Execution [sys_autoscript] table so that you can add scheduled jobs for the new connections.
 - a. For the Update scheduled job access task, select **Configure**.
 - b. Select the **Global** application scope from the application picker.
 - c. In the Application Access related list, select the **Can create**, **Can update**, and **Can delete** check boxes.
 - d. Select **Update**.
 - e. Switch back to the Service Graph Connector for Microsoft Intune application scope using the application picker.
 - f. Return to the guided setup page and set the Update scheduled job access task to complete by selecting **Mark as Complete**.

- d. When using multiple instances, clear the Scheduled Script Execution (sysauto_script) table cache to configure scheduled jobs for the new connections.
 - a. For the Clear cache for scheduled job task, select **Configure**.
 - b. Select the **Global** application scope from the application picker.
 - c. In the **Run script** field, enter the following code:

```
GlideTableManager.invalidateTable("sysauto_script");
GlideCacheManager.flushTable("sysauto_script");
GlideTableManager.invalidateTable("sys_db_object");
GlideCacheManager.flushTable("sys_db_object");
```
 - d. Select **Run Script**.
 - e. Switch back to the Service Graph Connector for Microsoft Intune application scope using the application picker.
 - f. Return to the guided setup page and set the Clear cache for scheduled job task to complete by selecting **Mark as Complete**.
- e. When using multiple instances, create advanced data sources, scheduled jobs, and scheduled imports for the new connections.

Tip: You can create additional connections for multiple instances by following the instructions in the [Add Multiple Instances](#) section of the guided setup.

- a. For the Set up advanced data sources for multiple instances task, select **Configure**.
- b. On the form, fill in the fields to configure your scheduled job details for the new connection.

Field	Description
Instance Prefix to Data source and Scheduled data import sets	Identifier that is used in all of the data source and scheduled import names for this distinct SG-Intune connection. In a multiple instance deployment, keep prefix short, meaningful identifier that enables you to identify a set of related data sources. Note: Try to keep the prefix the same as your connection name.
Connection and Credentials Alias	Connection alias that was created in the previous step.
Run Scheduled Import as User	User to populate the field on the scheduled data import.

- c. Select **Submit** to create scheduled imports for your new connection.
- d. To activate any newly created scheduled jobs, repeat steps [11.a.ii](#) to [11.a.iv](#).
- e. To activate any newly created parent scheduled import, repeat steps [11.b.ii](#) to [11.b.iv](#).
- f. Return to the guided setup page and set the Set up advanced data sources for multiple instances task to complete by selecting **Mark as Complete**.

CMDB classes targeted in Service Graph Connector for Microsoft Intune

When you complete setting up the connection, you can configure the integration to periodically pull data from Microsoft Intune. The data from

the regular data sources (SG-Intune Computer, SG-Intune Devices, and SG-Intune Software) and the advanced data sources (SG-Intune Device Reports and SG-Intune Software Reports) is saved in tables that extend from the Configuration item [cmdb_ci] table.

Computer [cmdb_ci_computer]

The following attributes in the Computer [cmdb_ci_computer] table are populated by collected data:

Attribute label	Attribute name
Name	name
Serial number	serial_number
Description	short_description
Disk space (GB)	disk_space
Manufacturer	manufacturer
Operating System	os
OS Version	os_version
Model ID	model_id
Assigned to	assigned_to
Chassis type	chassis_type

Relationships created for Computer

Parent class	Relationship type	Child class
Computer [cmdb_ci_computer]	Owns::Owned by	Network Adapter [cmdb_ci_network_adapter]
Computer [cmdb_ci_computer]	Owns::Owned by	IP Address [cmdb_ci_ip_address]

Parent class	Relationship type	Child class
Computer [cmdb_ci_computer]	Reference	SG-Intune Computer Related [sn_intune_integrat_computer_related]
Computer [cmdb_ci_computer]	Reference	Software Installation [cmdb_sam_sw_install]

Handheld Computing Device [cmdb_ci_handheld_computing]

The following attributes in the Handheld Computing Device [cmdb_ci_handheld_computing] table are populated by collected data:

Attribute label	Attribute name
Name	name
Serial number	serial_number
Description	short_description
Disk space (GB)	disk_space
IMEI	imei
MEID	meid
Operating System	os
OS Version	os_version
Phone Number	phone_number
Root Access	root_access
Model ID	model_id
Carrier	carrier

Attribute label	Attribute name
Assigned to	assigned_to
Manufacturer	manufacturer

Relationships created for Handheld Computing Device

Parent class	Relationship type	Child class
Handheld Computing Device [cmdb_ci_handheld_computing]	Owns::Owned by	Network Adapter [cmdb_ci_network_adapter]
Handheld Computing Device [cmdb_ci_handheld_computing]	Owns::Owned by	IP Address [cmdb_ci_ip_address]
Handheld Computing Device [cmdb_ci_handheld_computing]	Reference	SG-Intune Device Related [sn_intune_integrat_device_related]
Handheld Computing Device [cmdb_ci_handheld_computing]	Reference	Software Installation [cmdb_sam_sw_install]

Software Installation [cmdb_sam_sw_install]

The following attributes in the Software Installation [cmdb_sam_sw_install] table are populated by collected data:

Attribute label	Attribute name
Display name	display_name
Version	version
Discovery source	discovery_source

Attribute label	Attribute name
Publisher	publisher
Installed on	installed_on

Note: The Publisher attribute is populated by the SG-Intune Software Reports data source only.

Relationships created for Software Installation

Parent class	Relationship type	Child class
Software Installation [cmdb_sam_sw_install]	Reference	Handheld Computing Device [cmdb_ci_handheld_computing] Computer [cmdb_ci_computer]

Network Adapter [cmdb_ci_network_adapter]

The following attributes in the Network Adapter [cmdb_ci_network_adapter] table are populated by collected data:

Attribute label	Attribute name
MAC Address	mac_address
Name	name
Configuration Item	cmdb_ci

Relationships created for Network Adapter

Parent class	Relationship type	Child class
Network Adapter [cmdb_ci_network_adapter]	Reference	Handheld Computing Device

Parent class	Relationship type	Child class
		[cmdb_ci_handheld_computing]
Network Adapter [cmdb_ci_network_adapter]	Reference	Computer [cmdb_ci_computer]

IP Address [cmdb_ci_ip_address]

The following attributes in the IP Address [cmdb_ci_ip_address] table are populated by collected data:

Attribute label	Attribute name
IP version	ip_version
Owned By Configuration Item	owned_by_cmdb_ci
IP Address	ip_address
Name	name

Relationships created for IP Address

Parent class	Relationship type	Child class
IP Address [cmdb_ci_ip_address]	Reference	Handheld Computing Device [cmdb_ci_handheld_computing]
IP Address [cmdb_ci_ip_address]	Reference	Computer [cmdb_ci_computer]

Serial Number [cmdb_serial_number]

The following attributes in the Serial Number [cmdb_serial_number] table are populated by collected data:

Attribute label	Attribute name
Serial Number	serial_number
Serial Number Type	serial_number_type
Valid	valid

Relationships created for Serial Number

Parent class	Relationship type	Child class
Serial Number [cmdb_serial_number]	Reference	Handheld Computing Device [cmdb_ci_handheld_computing]
Serial number [cmdb_serial_number]	Reference	Computer [cmdb_ci_computer]

SG-Intune Computer Related [sn_intune_integrat_computer_related]

The following attributes in the SG-Intune Computer Related [sn_intune_integrat_computer_related] table are populated by collected data:

Attribute label	Attribute name
Device ID	device_id
Azure AD Registered	azure_ad_registered
Compliance State	compliance_state
Device Enrollment Type	device_enrollment_type
Email Address	email_address
Encrypted	is_encrypted

Attribute label	Attribute name
Managed Device Owner Type	managed_device_owner_type
Management Agent	management_agent
Supervised	is_supervised

SG-Intune Device Related [sn_intune_integrat_device_related]

The following attributes in the SG-Intune Device Related [sn_intune_integrat_device_related] table are populated by collected data:

Attribute label	Attribute name
Device ID	device_id
Azure AD Registered	azure_ad_registered
Compliance State	compliance_state
Device Category	device_category
Device Enrollment Type	device_enrollment_type
Device State	device_state
Email Address	email_address
Encrypted	is_encrypted
Managed Device Owner Type	managed_device_owner_type
Management Agent	management_agent
Security Patch Level	security_patch_level
Supervised	is_supervised
System Management Bios Version	system_management_bios_version

Attribute label	Attribute name
Wifi Subnet ID	wifi_subnet_id

Note: The attributes Device Category, Device State, Security Patch Level, System Management Bios Version, and Wifi Subnet ID are populated by the SG-Intune Device Reports data source only.

The attributes Azure AD Registered, Device Enrollment Type, and Management Agent aren't populated by the SG-Intune Device Reports data source.

Software [cmdb_ci_spkg]

The following attributes in the Software [cmdb_ci_spkg] table are populated by collected data:

Attribute label	Attribute name
Key	key
Name	name
Version	version

Relationship created for Software

Parent class	Relationship type	Child class
Software [cmdb_ci_spkg]	Reference	Software Instance [cmdb_software_instance]

Software Instance [cmdb_software_instance]

The following attributes in the Software Instance [cmdb_software_instance] table are populated by collected data:

Attribute label	Attribute name
Name	name

Attribute label	Attribute name
Installed on	installed_on

Relationships created for Software Instance

Parent class	Relationship type	Child class
Software Instance [cmdb_software_instance]	Reference	Handheld Computing Device [cmdb_ci_handheld_computing]
Software Instance [cmdb_software_instance]	Reference	Computer [cmdb_ci_computer]

Accessing the connection details of Service Graph Connector for Microsoft Intune

You can access the connection details of the Service Graph Connector for Microsoft Intune in a single view using the common connection framework (CCF) included within the Integration Commons for CMDB (sn_cmdb_int_util) store app.

With the CCF, you can access all the connections used by the Service Graph Connector for Microsoft Intune. The connection details include the connection alias, connection properties, data sources, and scheduled data imports associated with a connection. You can also test the connection. For more information, see [Accessing the connection details of Service Graph Connectors](#).

Access the details of a Microsoft Intune connection

Access the details of a Microsoft Intune connection configured for the Service Graph Connector for Microsoft Intune.

Before you begin

Role required: admin

Procedure

1. Navigate to **All > Service Graph Connectors > Intune > Connections**.
2. From the **Name** column of the Service Graph Connections list, select a connection.
3. On the Service Graph Connections page, view the connection details such as the connection name, alias, and data sources.
4. Select a related list to view further details of the connection.
5. (Optional) Select the **Test Connection** related link to test the connection.

Service Graph Connector for Microsoft Intune properties

Service Graph Connector for Microsoft Intune properties control the behavior of the connector.

Connection properties

These connection properties are available for Service Graph Connector for Microsoft Intune.

Note: To open the Service Graph Connection Properties [sn_cmdb_int_util_service_graph_connection_property] table for the connector, navigate to **All > Service Graph Connectors > Intune > Connections** and select the connection name. The connection properties are displayed in the Service Graph Connection Properties related list.

Connection properties for Service Graph Connector for Microsoft Intune

Property	Description	Data source type
include_primary_user_details	Set the property to true to retrieve primary user details during import and add the assigned_to	Regular data sources (SG-Intune Computer, SG-Intune Devices, and SG-Intune Software)

Property	Description	Data source type
	attribute to the Configuration item [cmdb_ci] table. Set the property to <code>false</code> to retrieve the enrolled user details. Retrieving primary user details increases the time for importing data because of additional API calls. Note: When a user is assigned to a device initially, the enrolled and primary users are the same. If the device is reassigned to another user, the primary user name is reassigned to the new user, but the enrolled user is still the original enrolled user name. • Type: <code>true</code> <code>false</code> • Default value: <code>true</code>	

Property	Description	Data source type
include_ip_address_details	Set the property to <code>true</code> to retrieve IP address details during import and add the records to the IP Address [cmdb_ci_ip_address] table. Set the property to <code>false</code> to skip retrieving IP addresses. Retrieving IP addresses increases the time for importing data because of additional API calls. • Type: <code>true</code> <code>false</code> • Default value: <code>true</code>	Regular data sources (SG-Intune Computer, SG-Intune Devices, and SG-Intune Software)
api_version	Enter the version of the Microsoft Intune Graph API. Note: This property is specific to the regular data sources (SG-Intune Computer, SG-Intune Devices, and SG-Intune Software). • Type: <code>string</code>	Regular data sources (SG-Intune Computer, SG-Intune Devices, and SG-Intune Software)

Property	Description	Data source type
	Default value: v1.0	
software_path	Set the path of the software code for finding apps and associated devices for regular data sources (SG-Intune Computer, SG-Intune Devices, and SG-Intune Software). Set the property to null value to enable the logic to determine the path of the software code. - Type: device app - Default value: device	Regular data sources (SG-Intune Computer, SG-Intune Devices, and SG-Intune Software)
device_report_chunks_count	Set the number of device report chunks. The value must be a power of 16 (1, 16, or 256). - Type: integer - Default value: 1	Advanced data sources (SG-Intune Device Reports and SG-Intune Software Reports)
software_report_chunks_count	Set the number of software report chunks. The value must be a power of 16 (1, 16, or 256).	Advanced data sources (SG-Intune Device Reports and SG-Intune Software Reports)

Property	Description	Data source type
	- Type: integer - Default value: 16	
export_apis_max_calls_before_wait	Set the maximum number of API calls that can be made consecutively before a waiting period is enforced. - Type: integer - Default value: 8	Advanced data sources (SG-Intune Device Reports and SG-Intune Software Reports)
export_apis_wait_time_in_ms	Set the duration (in milliseconds) for the waiting period after the specified number of consecutive API calls is reached. - Type: integer - Default value: 120000	Advanced data sources (SG-Intune Device Reports and SG-Intune Software Reports)