

Zurich ServiceNow AI Platform Capabilities

Last updated: January 16, 2026

Some examples and graphics depicted herein are provided for illustration only. No real association or connection to ServiceNow products or services is intended or should be inferred.

This PDF was created from content on docs.servicenow.com. The web site is updated frequently. For the most current ServiceNow product documentation, go to docs.servicenow.com.

Company Headquarters

2225 Lawson Lane
Santa Clara, CA 95054
United States
(408)501-8550

Service Graph Connector for Observability - Datadog

Use the Service Graph Connector for Observability - Datadog to ingest CMDB data from a Datadog installation using REST APIs. Push events from Datadog into ServiceNow with Event Management.

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Supported versions

Supported ServiceNow versions:

- Washington DC
- Xanadu
- Yokohama

Guided setup

The guided setup for the Service Graph Connector for Observability - Datadog provides an organized sequence of tasks to configure the integration on your instance. To access the guided setup, see [Configure Service Graph Connector for Observability - Datadog](#).

CMDB integrations dashboard

The Integration Commons for CMDB store app provides a dashboard with a central view of the status, processing results, and processing errors of all installed integrations. You can see metrics for all integration runs. You can filter the view to a specific CMDB integration, a specific time duration, or a specific integration run. For more details about monitoring Observability Datadog integrations in the CMDB Integrations Dashboard, see [Using the CMDB Integrations Dashboard](#).

Data mapping

Data from the Datadog data sources is mapped and transformed into the ServiceNow CMDB Configuration Item (CI) class definitions using the Robust Transform Engine (RTE). Data is inserted into the ServiceNow CMDB using the Identification and Reconciliation Engine (IRE).

The Datadog data source includes SGO-Datadog Hosts [sn_datadog_integra_datadog_hosts].

For more information on where data is saved when pulling data from Datadog, see [CMDB classes targeted in Service Graph Connector for Observability - Datadog](#).

When you complete setting up the connection, the data from Datadog is automatically loaded into staging tables and then inserted into the following target tables:

- Cloud DataBase [cmdb_ci_cloud_database]
- Cloud Load Balancer [cmdb_ci_cloud_load_balancer]
- Cloud Service Account [cmdb_ci_cloud_service_account]
- IP Address [cmdb_ci_ip_address]
- Key Value [cmdb_key_value]
- Logical Datacenter [cmdb_ci_logical_datacenter]
- Network Adapter [cmdb_ci_network_adapter]
- Server [cmdb_ci_server]

You can use the IntegrationHub ETL app to view the data maps. See [IntegrationHub ETL](#) for more information.

Related tasks

- [Configure Service Graph Connector for Observability - Datadog](#)

Related concepts

- [Service Graph Connectors](#)

- [Accessing the connection details of Service Graph Connector for Observability - Datadog](#)

Related reference

- [CMDB classes targeted in Service Graph Connector for Observability - Datadog](#)

Configure Service Graph Connector for Observability - Datadog

Pull in data from Datadog into your Configuration Management Database (CMDB).

Before you begin

To use this Service Graph Connector, you need a subscription to a Subscription Unit that is based in the IT Operations Management (ITOM) Visibility application or in the ITOM Discovery application. As defined in the section titled "Managed IT Resource Types" in [ServiceNow Subscription Unit Overview](#) for your subscription, for managed IT resources that are created or modified in the CMDB by this Service Graph Connector, but that aren't yet managed by [ITOM Visibility](#) or [ITOM Discovery](#), these resources will increase Subscription Unit consumption from that application. Review your current Subscription Unit consumption within ITOM Visibility or ITOM Discovery to ensure available capacity.

Dependencies and requirements:

- The [Integration Commons for CMDB](#) store app, which is automatically installed.
- The CMDB CI class models store app, which is automatically installed. See [CMDB CI Class Models](#).
- The ITOM Discovery License plugin (com.snc.itom.discovery.license). You must activate this plugin.
- ITOM Licensing plugin (com.snc.itom.license). For more information, see [Request Discovery](#).

- The Datastream Action plugin (com.glide.hub.action_type.datastream), which is automatically installed.
- Observability Commons for CMDB (sn_observability), which is only required for event ingestion. This must be installed prior to installing the connector for Event Management to work. For more information, see [Observability Commons for CMDB](#) on the ServiceNow Store.

Note: If you have an earlier version of the Service Graph Connector for Observability - Datadog, then don't migrate data from the old connector. You must uninstall the previous version and run the new integration.

Role required: SGC-Admin (sn_cmdb_int_util.sgc_admin)

Note: The admin user role is required to run background scripts and to provide table-level access to the SGC-Admin user.

Procedure

1. Navigate to **All > Service Graph Connectors > Observability Datadog > Setup**.
2. On the Getting started page, select **Get Started**.
3. Configure the authentication credentials and the host name to send requests to the Datadog API.
 - a. Configure your Datadog credentials.
 - a. In the Configure the Connection section of the Datadog Integration with CMDB page, select **Get Started**.
 - b. For the Configure the Credentials task, select **Configure**.
 - c. In the **Connection name** field, enter a name for the connection.

Note: Do not modify the name of the default connection.
 - d. In the **Connection URL** field, enter the base URL or IP address for Datadog.

- e. In the **API key** field, enter the Datadog API token.
 - f. In the **Application key** field, enter the application key used for connecting to the Datadog API.
 - g. Select **Update**.
 - h. Set the Configure the Credentials task to complete by selecting **Mark as Complete**.
- b. Test the connection.
 - a. For the Test Connection task, select **Configure**.
 - b. Test the connection by selecting the **Test Connection** related link.

Testing the connection might take a few moments. The page is refreshed to show the test results.
 - c. When the **Status** field is set to **Success**, select **Update**.

If any of the tests have errors, follow the suggestions for remediation.
 - d. Set the Test Connection task to complete by selecting **Mark as complete**.
 - c. (Optional) Add a filter for the SGO-Datadog Hosts [sn_datadog_integra_datadog_hosts] data source.
 - a. For the Create Hosts Filter task, select **Configure**.
 - b. Enter a comma-separated list of host tags in **key:value** format in the **Value** field to define a filter for pulling host data from Datadog.

For example, `datadog:monitored,env:production`.
 - c. Select **Update**.
 - d. Set the Create Hosts Filter task to complete by selecting **Mark as complete**.
4. Configure the webhook and monitors for Observability Datadog.

- a. In the Configure Observability section of the Datadog Integration with CMDB page, select **Get started**.
- b. For the Configure the Webhooks and Monitors task, select **Configure**.
- c. In the Datadog Webhooks list, select **New** to add a Datadog webhook.
- d. Fill in the fields.

New record form

Field	Description
Name	Name of the Datadog webhook.
Connection Alias	Search for and select the connection and credential alias that you created in step 3 .

- e. Select **Submit**.
- f. Populate the Datadog Webhooks list by selecting the **Synchronize Monitors** related link on the Datadog Webhook page.

Note: In the Datadog Webhooks list, don't select **New** to add a monitor as this option is not used in this scenario.
- g. In the **Name** column of the Datadog Webhooks list, select a monitor.
- h. On the Datadog Monitors page, select the **Webhook Active** check box, and then select **Update**.
- i. Repeat steps [4.g](#) and [4.h](#) for all the monitors in the Datadog Webhooks list.
- j. On the Datadog Webhook page, select **Update** to save your changes.

- k. Set the Configure the Webhooks and Monitors task to complete by selecting **Mark as Complete**.
5. Set up scheduled import jobs.
 - a. Navigate to **All > Service Graph Connectors > Observability Datadog > Import Schedules**.
 - b. Select the name of the scheduled import that you want to activate.
 - c. On the Scheduled Data Import form, verify the field values for the scheduled job and select the **Active** check box.

For more information, see [Schedule a data import](#).
 - d. Select **Update**.

Related concepts

- [Service Graph Connector for Observability - Datadog](#)
- [Accessing the connection details of Service Graph Connector for Observability - Datadog](#)

Related reference

- [CMDB classes targeted in Service Graph Connector for Observability - Datadog](#)

CMDB classes targeted in Service Graph Connector for Observability - Datadog

When you complete setting up the connection, the data is automatically pulled from Datadog. The data is saved in target tables.

Cloud DataBase [cmdb_ci_cloud_database]

The following attributes in the Cloud DataBase [cmdb_ci_cloud_database] table are populated by collected data:

Attribute label	Attribute name
Object ID	object_id
Fully qualified domain name	fqdn
Name	name
Type	type
Version	version

Relationships created for Cloud DataBase

Parent class	Relationship type	Child class
Cloud DataBase [cmdb_ci_cloud_data base]	Hosted on::Hosts	Logical Datacenter [cmdb_ci_logical_dat acenter]
Cloud DataBase [cmdb_ci_cloud_data base]	Reference	Key Value [cmdb_key_value]

Cloud Load Balancer [cmdb_ci_cloud_load_balancer]

The following attributes in the Cloud Load Balancer [cmdb_ci_cloud_load_balancer] table are populated by collected data:

Attribute label	Attribute name
Name	name
Object ID	object_id

Relationships created for Cloud Load Balancer

Parent class	Relationship type	Child class
Cloud Load Balancer [cmdb_ci_cloud_load_balancer]	Hosted on::Hosts	Logical Datacenter [cmdb_ci_logical_datacenter]
Cloud Load Balancer [cmdb_ci_cloud_load_balancer]	Reference	Key Value [cmdb_key_value]

Cloud Service Account [cmdb_ci_cloud_service_account]

The following attributes in the Cloud Service Account [cmdb_ci_cloud_service_account] table are populated by collected data:

Attribute label	Attribute name
Account Id	account_id
Name	name
Object ID	object_id
Datacenter Type	datacenter_type

IP Address [cmdb_ci_ip_address]

The following attributes in the IP Address [cmdb_ci_ip_address] table are populated by collected data:

Attribute label	Attribute name
IP Address	ip_address
Nic	nic
Name	name

Relationship created for IP Address

Parent class	Relationship type	Child class
IP Address [cmdb_ci_ip_address]	Reference	Network Adapter [cmdb_ci_network_adapter]

Key Value [cmdb_key_value]

The following attributes in the Key Value [cmdb_key_value] table are populated by collected data:

Attribute label	Attribute name
Key	key
Value	value

Logical Datacenter [cmdb_ci_logical_datacenter]

The following attributes in the Logical Datacenter [cmdb_ci_logical_datacenter] table are populated by collected data:

Attribute label	Attribute name
Name	name
Object ID	object_id
Region	region

Relationship created for Logical Datacenter

Parent class	Relationship type	Child class
Logical Datacenter [cmdb_ci_logical_datacenter]	Hosted on::Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]

Network Adapter [cmdb_ci_network_adapter]

The following attributes in the Network Adapter [cmdb_ci_network_adapter] table are populated by collected data:

Attribute label	Attribute name
Configuration Item	cmdb_ci
MAC Address	mac_address
Name	name

Relationship created for Network Adapter

Parent class	Relationship type	Child class
Network Adapter [cmdb_ci_network_adapter]	Reference	Server [cmdb_ci_server]

Server [cmdb_ci_server]

The following attributes in the Server [cmdb_ci_server] table are populated by collected data:

Attribute label	Attribute name
Class	sys_class_name
CPU core thread	cpu_core_thread
CPU count	cpu_count
CPU speed (MHz)	cpu_speed
CPU type	cpu_type
Disk space (GB)	disk_space
DNS Domain	dns_domain

Attribute label	Attribute name
Fully qualified domain name	fqdn
Name	name
Operating System	os
RAM (MB)	ram

Relationships created for Server

Parent class	Relationship type	Child class
Server [cmdb_ci_server]	Owns::Owned by	Network Adapter [cmdb_ci_network_adapter]
Server [cmdb_ci_server]	Owns::Owned by	IP Address [cmdb_ci_ip_address]
Server [cmdb_ci_server]	Reference	Key Value [cmdb_key_value]

Related concepts

- [Service Graph Connector for Observability - Datadog](#)

Accessing the connection details of Service Graph Connector for Observability - Datadog

You can access the connection details of the Service Graph Connector for Observability - Datadog in a single view using the common connection framework (CCF) included within the Integration Commons for CMDB (sn_cmdb_int_util) store app.

With the CCF, you can access all the connections used by the Service Graph Connector for Observability - Datadog. The connection details include the connection alias, connection properties, data sources, and scheduled data imports associated with a connection. You can also

test the connection. For more information, see [Accessing the connection details of Service Graph Connectors](#).

Access the details of a Datadog connection

Access the details of a Datadog connection configured for the Service Graph Connector for Observability - Datadog.

Before you begin

Role required: admin

Procedure

1. Navigate to **All > Service Graph Connectors > Datadog > Connections**.
2. From the **Name** column of the Service Graph Connections list, select a connection.
3. On the Service Graph Connections page, view the connection details such as the connection name, alias, and data sources.
4. Select a related list to view further details of the connection.
5. (Optional) Select the **Test Connection** related link to test the connection.

Related concepts

- [Service Graph Connector for Observability - Datadog](#)