

Zurich ServiceNow AI Platform Capabilities

Last updated: January 16, 2026

Some examples and graphics depicted herein are provided for illustration only. No real association or connection to ServiceNow products or services is intended or should be inferred.

This PDF was created from content on docs.servicenow.com. The web site is updated frequently. For the most current ServiceNow product documentation, go to docs.servicenow.com.

Company Headquarters

2225 Lawson Lane
Santa Clara, CA 95054
United States
(408)501-8550

Service Graph Connector for Observability - Dynatrace

Use the Service Graph Connector for Observability - Dynatrace to ingest CI data, events, metrics, and logs from Dynatrace into your ServiceNow instance.

Note: The Service Graph Connector for Observability - Dynatrace provided by ServiceNow is different from the Service Graph Connector for Dynatrace provided by Dynatrace.

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Supported versions

- Supported versions:
 - Minimum version supported: Dynatrace SaaS; Version 1.284
- Supported ServiceNow versions:
 - Xanadu
 - Yokohama
 - Zurich

Important information for upgrading Service Graph Connector for Observability - Dynatrace

Before upgrading the Service Graph Connector for Observability - Dynatrace to version 1.10.0 or later, disable the reconciliation rules for tables extending the Application [cmdb_ci_appl] table. See the [Reconciliation rules\(ServiceNow, ServiceWatch\) on multiple table like Apache web server stopping other discovery source to update fields on those tables \[KB1649455\]](#) article in the Now Support Knowledge Base.

Configuring a connection for the connector

You can configure a connection for the connector by using the SGC Central view in the CMDB Workspace enables you to discover and install connectors, and then effectively manage the full life cycle of creating, editing, monitoring, and debugging connections. To configure the connector using SGC Central, see [Configure Service Graph Connector for Observability - Dynatrace using SGC Central](#).

Important: Unless there are configuration issues, use the SGC Central view in the CMDB Workspace to configure the connection for the connector, as the guided setup method is being deprecated.

CMDB integrations dashboard

The Integration Commons for CMDB store app provides a dashboard with a central view of the status, processing results, and processing errors of all installed integrations. You can see metrics for all integration runs. You can filter the view to a specific CMDB integration, a specific time duration, or a specific integration run. For more details about monitoring Dynatrace integrations in the CMDB Integrations Dashboard, see [Using the CMDB Integrations Dashboard](#).

Data mapping

Data from the Dynatrace data sources is mapped and transformed into the ServiceNow CMDB Configuration Item (CI) class definitions using the Robust Transform Engine (RTE). Data is inserted into the ServiceNow CMDB using the Identification and Reconciliation Engine (IRE).

The following table describes the data sources, the staging tables, the target tables as CMDB CI classes, and the Dynatrace entities imported by each data source.

Data mapping for Dynatrace entities

Data source	Description	Staging table	CMDB CI classes	Entities
SGO-Dynatrace Hosts	Ingests host data from Dynatrace.	SGO-Dynatrace Hosts [sn_dynatrace_integ_sg_d	Computer IP Address [cmdb_ci_ip_address]	Host

Data source	Description	Staging table	CMDB CI classes	Entities
	Contains computer data.	ynatrace_hosts]	Key value When the Software Asset Management (SAM) application isn't installed: Software Software Instance When the SAM application is installed: Software Installation	

Data source	Description	Staging table	CMDB CI classes	Entities
			Note: Only the operating system data is stored in the Software Packages, Software Instance, and Software Installation CI classes.	
SGO-Dynatrace Processes	Ingests process data from Dynatrace. Contains running process data.	SGO-Dynatrace Processes [sn_dynatrace_integ_sg_dynatrace_processes]	The target table is populated using Application Dependency Mapping (ADM). The ADM adapter analyzes the imported data and command-line arguments, identifies the appropriate	Process

Data source	Description	Staging table	CMDB CI classes	Entities
			table based on the conditions included in Discovery Process Classification s list, and inserts the data into the table, which extends the Application [cmdb_ci_app] table. To learn about process classification , see Discovery classifiers .	

Data source	Description	Staging table	CMDB CI classes	Entities
			Note: The addition of unclassified processes to the Application [cmdb_ci_appl] table depends on the value of the sn_dynatrace_integ.createUnmatchedApplicationCIs system property. For more information, see Service Graph Connector for Observability - Dynatrace properties.	

Data source	Description	Staging table	CMDB CI classes	Entities
SGO-Dynatrace Process Groups	Ingests process group data from Dynatrace. Contains a group of similar running processes.	SGO-Dynatrace Process Groups [sn_dynatrace_integ_sg_dynatrace_process_groups]	Group	Process Group
SGO-Dynatrace Services	Ingests service data from Dynatrace. Contains information related to services that are detected via the Dynatrace agent. Can be filtered using advanced settings properties.	SGO-Dynatrace Services [sn_dynatrace_integ_sg_dynatrace_services]	Calculated Application Service Key value	Service
SGO-Dynatrace Applications	Ingests application data from Dynatrace.	SGO-Dynatrace Applications [sn_dynatrace_integ_sg_d	Calculated Application Service Key value	Application

Data source	Description	Staging table	CMDB CI classes	Entities
	Contains information related to the applications defined manually. Applications are parents to services representing a higher level, logical group of services.	ynatrace_applications]		
SGO-Dynatrace Application Rels	Ingests application relationships from Dynatrace. Returns the same data as the SGO-Dynatrace Services data source. Maps relationships between applications and processes that could have been skipped due	SGO-Dynatrace Application Relationships [sn_dynatrace_integ_sg_dynatrace_application_relationships]	Calculated Application Service	Service

Data source	Description	Staging table	CMDB CI classes	Entities
	to filtered services.			
SGO-Dynatrace AWS Application Network LB	Ingests cloud load balancer data from Dynatrace. Contains information related to AWS application and network load balancer.	SGO-Dynatrace AWS Application Network LB [sn_dynatrace_integ_sgo_dynatrace_aws_application_network_lb]	Cloud Load Balancer Key Value	AWS Network Load Balancer AWS Application Load Balancer
SGO-Dynatrace AWS Datacenters	Ingests AWS datacenter and availability zone data from Dynatrace. Contains information related to AWS datacenters and availability zones.	SGO-Dynatrace AWS Availability Zone [sn_dynatrace_integ_sgo_dynatrace_aws_availability_zone]	AWS Datacenter Availability Zone	AWS Availability Zone
SGO-Dynatrace	Ingests AWS virtual machine	SGO-Dynatrace AWS EC2	Virtual Machine Instance	EC2 Instance

Data source	Description	Staging table	CMDB CI classes	Entities
AWS EC2 Instance	instance data from Dynatrace. Contains information related to virtual machine instances, server details, cloud hardware type, cloud image, and tags.	Instance [sn_dynatrace_integ_sg_dynatrace_aws_ec2_instance]	Server Cloud Hardware Type Hardware Type Image Key Value	
SGO-Dynatrace AWS Elastic Loadbalancer	Ingests cloud load balancer data from Dynatrace. Contains load balancer details and tags.	SGO-Dynatrace AWS Elastic Loadbalancer [sn_dynatrace_integ_sgo_dynatrace_aws_elastic_loadbalancer]	Cloud Load Balancer Key Value	Elastic Load Balancer
SGO-Dynatrace AWS Service Account	Ingests cloud service account data from Dynatrace. Contains information related to	SGO-Dynatrace AWS Service Account [sn_dynatrace_integ_sgo_dynatrace_aws_service_account]	Cloud Service Account	AWS Credentials

Data source	Description	Staging table	CMDB CI classes	Entities
	AWS account IDs.			
SGO-Dynatrace Azure Load Balancer	Ingests Azure load balancer data from Dynatrace. Contains Azure load balancer and cloud load balancer IP address and tag details.	SGO-Dynatrace Azure Load Balancer [sn_dynatrace_integ_sgo_dynatrace_azure_load_balancer]	Cloud Load Balancer Cloud LB IPAddress Key Value	Azure Load Balancer
SGO-Dynatrace Azure Region	Ingests Azure datacenter data from Dynatrace. Contains Azure datacenter information.	SGO-Dynatrace Azure Region [sn_dynatrace_integ_sgo_dynatrace_azure_region]	Azure Datacenter	Azure Region
SGO-Dynatrace Azure Storage Accounts	Ingests Azure cloud storage account data from Dynatrace. Contains information related to	SGO-Dynatrace Azure Storage Accounts [sn_dynatrace_integ_sgo_dynatrace_azure_storage_accounts]	Cloud Storage Account	Azure Storage Account

Data source	Description	Staging table	CMDB CI classes	Entities
	cloud storage accounts.			
SGO-Dynatrace Azure Strg Acnts v2	Ingests Azure cloud storage account data from Dynatrace using v2 API. Contains information related to cloud storage accounts.	SGO-Dynatrace Azure Storage Accounts v2 [sn_dynatrace_integ_sgo_dynatrace_azure_storage_accounts_v2]	Cloud Storage Account	cloud:azure:storage:storageaccounts
SGO-Dynatrace Azure Subscriptions	Ingests Azure subscription data from Dynatrace. Contains Azure subscription details.	SGO-Dynatrace Azure Subscriptions [sn_dynatrace_integ_sg_dynatrace_azure_subscriptions]	Cloud Service Account	Azure Subscription
SGO-Dynatrace Azure VM	Ingests Azure virtual machine instance data from Dynatrace. Contains information	SGO-Dynatrace Azure VM [sn_dynatrace_integ_sgo_dynatrace_azure_vm]	Virtual Machine Instance	Azure VM

Data source	Description	Staging table	CMDB CI classes	Entities
	related to Azure virtual machine instances.			
SGO-Dynatrace Docker Container	Ingests Docker container data from Dynatrace. Contains information related to the Docker container image.	SGO-Dynatrace Docker Container [sn_dynatrace_integ_sgo_dynatrace_docker_container]	Docker Container Application Docker Image Computer [cmdb_ci_computer]	Container Group Instance
SGO-Dynatrace Kubernetes Cluster	Ingests Kubernetes cluster data from Dynatrace. Contains information related to Kubernetes clusters.	SGO-Dynatrace Kubernetes Cluster [sn_dynatrace_integ_sgo_dynatrace_kubernetes_cluster]	Kubernetes Cluster Key Value	Kubernetes Cluster
SGO-Dynatrace Kubernetes Namespace	Ingests Kubernetes namespace data from Dynatrace. Contains information	SGO-Dynatrace Kubernetes Namespace [sn_dynatrace_integ_sgo_dynatrace_k]	Kubernetes Namespace Key Value	Cloud Application Namespace

Data source	Description	Staging table	CMDB CI classes	Entities
	related to Kubernetes namespaces	ubernetes_namespace]		
SGO-Dynatrace Kubernetes Node	Ingests Kubernetes node data from Dynatrace. Contains information related to Kubernetes nodes.	SGO-Dynatrace Kubernetes Node [sn_dynatrace_integ_sgo_dynatrace_kubernetes_node]	Kubernetes Node Key Value	Kubernetes Node
SGO-Dynatrace Kubernetes Pod	Ingests Kubernetes pod data from Dynatrace. Contains information related to Kubernetes pods.	SGO-Dynatrace Kubernetes Pod [sn_dynatrace_integ_sgo_dynatrace_kubernetes_pod]	Kubernetes Pod Key Value	Cloud Application Instance
SGO-Dynatrace Kubernetes Service	Ingests Kubernetes service data from Dynatrace. Contains information related to	SGO-Dynatrace Kubernetes Service [sn_dynatrace_integ_sgo_dynatrace_kubernetes_service]	Kubernetes Service Key Value	Kubernetes Service

Data source	Description	Staging table	CMDB CI classes	Entities
	Kubernetes services.			
SGO-Dynatrace Azure Cosmos DB v1	Ingests Azure Cosmos DB data from Dynatrace. Contains information related to Azure Cosmos DB.	SGO-Dynatrace Azure Cosmos DB v1 [sn_dynatrace_integ_sgo_dynatrace_azure_cosmos_db_v1]	Cloud DataBase Azure Datacenter Cloud Service Account Key value	AZURE_COSMOS_DB
SGO-Dynatrace Azure Cosmos DB V2	Ingests Azure Cosmos DB data from Dynatrace. Contains information related to Azure Cosmos DB.	SGO-Dynatrace Azure Cosmos DB V2 [sn_dynatrace_integ_sgo_dynatrace_azure_cosmos_db_v2]	Cloud DataBase Azure Datacenter Cloud Service Account Key value	cloud:azure:documentdb:databaseaccounts:global cloud:azure:documentdb:databaseaccounts:mongo
SGO-Dynatrace Azure SQL Server V2	Ingests Azure SQL Server data from Dynatrace. Contains information related to Azure SQL Server.	SGO-Dynatrace Azure SQL Server V2 [sn_dynatrace_integ_sgo_dynatrace_azure_sql_server_v2]	Cloud DataBase Azure Datacenter Key value	cloud:azure:sql:servers:databases:dtu cloud:azure:sql:servers:databases:vcore

Data source	Description	Staging table	CMDB CI classes	Entities
				cloud:azure: sql:servers:d atabases:hy perscale
SGO- Dynatrace Azure Function App	Ingests Azure Functions app data from Dynatrace. Contains information related to Azure Functions app.	SGO- Dynatrace Azure Function App [sn_dynatrac e_integ_sgo_ dynatrace_a zure_funcio n_app]	Cloud Function Azure Datacenter Cloud Service Account Key value	AZURE_FUNC TION_APP
SGO- Dynatrace Azure Scale Sets VM	Ingests Azure Virtual Machine Scale Sets (VMSS) data from Dynatrace. Contains information related to Azure VMSS.	SGO- Dynatrace Azure Scale Sets VM [sn_dynatrac e_integ_sgo_ dynatrace_a zure_scale_s ets_vm]	Instance Scale Set Azure Datacenter Cloud Service Account Key value	AZURE_VM_S CALE_SET
SGO- Dynatrace AWS RDS V1	Ingests Amazon Relational Database Service (RDS) data from Dynatrace.	SGO- Dynatrace AWS RDS V1 [sn_dynatrac e_integ_sgo_ dynatrace_a ws_rds_v1]	Cloud DataBase AWS Datacenter Key value	RELATIONAL_ DATABASE_S ERVICE

Data source	Description	Staging table	CMDB CI classes	Entities
	Contains information related to Amazon RDS.			
SGO-Dynatrace AWS RDS V2	Ingests Amazon Relational Database Service (RDS) data from Dynatrace. Contains information related to Amazon RDS.	SGO-Dynatrace AWS RDS V2 [sn_dynatrace_integ_sgo_dynatrace_aws_rds_v2]	Cloud DataBase AWS Datacenter Key value	cloud:aws:rds
SGO-Dynatrace AWS Dynamo DB v1	Ingests Amazon Dynamo DB data from Dynatrace. Contains information related to Amazon Dynamo DB.	SGO-Dynatrace AWS Dynamo DB v1 [sn_dynatrace_integ_sgo_dynatrace_aws_dynamo_db_v1]	DynamoDB Table AWS Datacenter Key value	DYNAMO_DB_TABLE
SGO-Dynatrace AWS Dynamo DB v2	Ingests Amazon Dynamo DB data from Dynatrace.	SGO-Dynatrace AWS Dynamo DB v2 [sn_dynatrac	DynamoDB Table AWS Datacenter	cloud:aws:dynamodb

Data source	Description	Staging table	CMDB CI classes	Entities
	Contains information related to Amazon Dynamo DB.	e_integ_sgo_dynatrace_aws_dynamo_db_v2]	Key value	
SGO-Dynatrace AWS Lambda Func V1	Ingests AWS Lambda Function data from Dynatrace. Contains information related to AWS Lambda Function.	SGO-Dynatrace AWS Lambda Func V1 [sn_dynatrace_integ_sgo_dynatrace_aws_lambda_func_v1]	Cloud Function Azure Datacenter Key value	AWS_LAMBDA_FUNCTION
SGO-Dynatrace AWS Lambda Func V2	Ingests AWS Lambda Function data from Dynatrace. Contains information related to AWS Lambda Function.	SGO-Dynatrace AWS Lambda Func V2 [sn_dynatrace_integ_sgo_dynatrace_aws_lambda_func_v2]	Cloud Function Azure Datacenter Key value	cloud:aws:lambda
SGO-Dynatrace AWS S3 Bucket V2	Ingests Amazon S3 bucket data from Dynatrace.	SGO-Dynatrace AWS S3 Bucket V2 [sn_dynatrace_integ_sgo_	Cloud Object Storage AWS Datacenter	cloud:aws:s3

Data source	Description	Staging table	CMDB CI classes	Entities
	Contains information related to Amazon S3 bucket.	dynatrace_aws_s3_bucket_v2]	Key value	
SGO-Dynatrace Custom Applications	Ingests custom application data from Dynatrace. Contains information related to custom applications.	SGO-Dynatrace Custom Applications [sn_dynatrace_integ_sgo_dynatrace_custom_applications]	Calculated Application Service Configuration Item [cmdb_ci] Key value	CUSTOM_APPLICATION
SGO-Dynatrace AWS Auto Scaling Group V1	Ingests AWS autoscaling group data from Dynatrace using V1 API. Contains information related to AWS autoscaling group.	SGO-Dynatrace AWS Auto Scaling Group V1 [sn_dynatrace_integ_sgo_dynatrace_aws_auto_scaling_group_v1]	Cloud Resource AWS Datacenter Key value	AUTO_SCALING_GROUP

When you complete setting up the connection, you can configure the integration to pull data from Dynatrace periodically. The data is loaded into the staging tables, and then inserted into the target tables.

For more information on where data is saved when pulling data from Dynatrace, see [CMDB classes targeted in Service Graph Connector for Observability - Dynatrace](#).

You can use the IntegrationHub ETL app to view the data maps. See [IntegrationHub ETL](#) for more information.

Additional resources

- [Introduction to Service Graph Connector for Observability Dynatrace](#) article on the ServiceNow Community site
- [How do I configure the Dynatrace Service Graph Connector?](#) article on the ServiceNow Community site

Related concepts

- [Service Graph Connectors](#)

Related reference

- [Service Graph Connector for Observability - Dynatrace properties](#)

Configure Service Graph Connector for Observability - Dynatrace using SGC Central

Set up scheduled import jobs to pull in Dynatrace data into your Configuration Management Database (CMDB).

Before you begin

Install Service Graph Connector for Observability - Dynatrace version 1.11.0 or later from the ServiceNow Store. For ServiceNow Store installation steps, see [Install a ServiceNow Store application](#).

Role required: SGC-Admin (sn_cmdb_int_util.sgc_admin)

Note: The admin user role is required to run background scripts and to provide table-level access to the SGC-Admin user.

About this task

The playbook experience for onboarding connectors is activated with SGC Central in the CMDB Workspace. To configure the SGC Central application, see [Configuring SGC Central](#) and for more information on how to interact with a playbook, see [Interact with Playbook](#).

Procedure

1. Navigate to **Workspaces > CMDB Workspace**.
2. In the CMDB Workspace, select **SGC Central**.
3. On the Overview page, select **Create connection**.

Tip: Alternatively, you can select **Create connection** on the All connections page.
4. On the Create connection window, select the Dynatrace connector type, and then select **Configure connection**.
5. Complete the initial prerequisites when setting up a connection for the first time using a connector.
 - a. (Optional) Install the Observability Commons for CMDB application (sn_observability) for event ingestion.

Note: The **Install Observability Commons for CMDB** activity appears only when the Observability Commons for CMDB application (sn_observability) isn't already installed. If event ingestion isn't needed, you can skip this step by selecting **Continue** for the **Install Observability Commons for CMDB** activity.
 - a. In the **Prerequisites** stage of the playbook, select the **Install Observability Commons for CMDB** activity.
 - b. Install the [Observability Commons for CMDB](#) application (sn_observability) from the ServiceNow Store.
 - c. After you have installed the application, select **Continue**.
- b. Create data sources for the connection.

Note: This step is required when configuring the connector for the first time only.

- a. Verify that you have edit permissions for the Datasource [sys_data_source] table.
- b. In the **Prerequisites** stage of the playbook, select the **Update data source access** activity.
- c. Select **Update access**.
- d. To edit the record, select the **Global** application scope from the application picker.
- e. In the Application Access related list of the Data Source form, select the **Can create**, **Can update**, and **Can delete** check boxes.
- f. Select **Update**.
- g. From the application picker, select the application scope of the connector.
- h. After completing the **Update data source access** activity, select **Continue**.
- c. Enable creating scheduled jobs for the connection by updating the scheduled data import access.

Note: This step is required when configuring the connector for the first time only.

- a. Verify that you have edit permissions for the Scheduled Data Import [scheduled_import_set] table.
- b. In the **Prerequisites** stage of the playbook, select the **Update scheduled data import access** activity.
- c. Select **Update access**.
- d. To edit the record, select the **Global** application scope from the application picker.

- e. In the Application Access related list of the Data Source form, select the **Can create**, **Can update**, and **Can delete** check boxes.
 - f. Select **Update**.
 - g. From the application picker, select the application scope of the connector.
 - h. After completing the **Update scheduled data import access** activity, select **Continue**.
- d. Enable creating values for the connection by updating the variable value access.
- Note:** This step is required when configuring the connector for the first time only.
- a. Verify that you have edit permissions for the Value [sys_variable_value] table.
 - b. In the **Prerequisites** stage of the playbook, select the **Update variable value access** activity.
 - c. Select **Update access**.
 - d. To edit the record, select the **Global** application scope from the application picker.
 - e. In the Application Access related list of the Data Source form, select the **Can create**, **Can update**, and **Can delete** check boxes.
 - f. Select **Update**.
 - g. From the application picker, select the application scope of the connector.
 - h. After completing the **Update variable value access** activity, select **Continue**.
- e. Clear the cache on the Data Source [sys_data_source] table.
- Note:** This step is required when configuring the connector for the first time only.

- a. In the **Prerequisites** stage of the playbook, select the **Clear cache** activity.
- b. Select **Run clear cache**.
- c. In the **Run script** text box of the background script page, enter the following script:

```
GlideTableManager.invalidateTable("sys_data_source");
    GlideCacheManager.flushTable("sys_data_source");

    GlideTableManager.invalidateTable("scheduled_import_set");
    GlideCacheManager.flushTable("scheduled_import_set");

    GlideTableManager.invalidateTable("sys_variable_value");
    GlideCacheManager.flushTable("sys_variable_value");

    GlideTableManager.invalidateTable("sys_db_object");
    GlideCacheManager.flushTable("sys_db_object");
```

- d. Select **Run Script** to run the background script in the **global** scope.

The script may take several minutes to execute.

- e. After the script is executed, select **Close**.
- f. From the application picker, select the application scope of the connector.
- g. After completing the **Clear cache** activity, select **Continue**.
- f. Verify that the Event Management application works properly with the Dynatrace environment by copying the EvtMgmtImpactManagerMediator script to the Global application scope.

Note: This step is displayed only when the Observability Commons for CMDB plugin (sn_observability) is already installed and is required when configuring the connector for the first time only.

- a. In the **Prerequisites** stage of the playbook, select the **Enable script access for event management** activity.
 - b. Select **Enable script access**.
 - c. Select the **Global** application scope from the application picker.
 - d. From the context menu, select **Insert and Stay**.
 - e. Verify that the EvtMgmtImpactManagerMediator script was copied to the Global application scope and the **Accessible from** field was set to All application scopes.
 - f. Select **Update**.
 - g. From the application picker, select the application scope of the connector.
 - h. After completing the **Enable script access for event management** activity, select **Continue**.
6. Enter connection details and test the API connection for importing Dynatrace data.
- a. In the **Setup** stage of the playbook, select the **Create and test connection** activity.
 - b. On the form, fill in the fields.

Create and test connection form

Field	Description
Connection name	Name to identify the Dynatrace connection record.
Hostname	Hostname of your Dynatrace environment.

Field	Description
API Key	Dynatrace API Key. Note: The API Key must be prefixed with <code>api - token</code> .

- c. Select **Create and test connection**.
 - d. Once the connection test is complete, select **Continue**.
7. (Optional) Configure the connection and connector properties to map attributes and manage data imports.

Note: To skip this step, select **Continue** for the **Set configuration properties** activity.

- a. In the **Setup** stage of the playbook, select the **Set configuration properties** activity.
- b. Fill in the form.

Configuration properties

Field	Description
Management zone IDs	List of the management zone IDs to fetch from your Dynatrace environment. For multiple entries, separate the zone IDs with commas.
Management zone names	List of the management zones to fetch from your Dynatrace environment. For multiple entries, separate the zone names with commas.
Service types	List of the Dynatrace service types from where to ingest the data into the CMDB. For

Field	Description
	multiple entries, separate the service types with commas.

Field	Description
	Note: All service types except for DATABASE_SERVICE are mapped to the Calculated Application Service [cmdb_ci_service_calculated] CMDB table. The DATABASE_SERVICE service type is mapped to the Database Instance [cmdb_ci_db_instance] CMDB table. Valid values are: • BACKGROUND_ACTIVITY • CICS_SERVICE • CUSTOM_SERVICE • DATABASE_SERVICE • ENTERPRISE_SERVICE_BUS_SERVICE • EXTERNAL • IBM_INTEGRATION_BUS_SERVICE • IMS_SERVICE • MESSAGING_SERVICE • QUEUE_LISTENER_SERVICE • RMI_SERVICE • RPC_SERVICE • WEB_REQUEST_SERVICE

Field	Description
Tags	List of the tag names to fetch from your Dynatrace environment. For multiple entries, separate the tags with commas.

- c. To manage data source failures during import, select the **Save REST response as attachment** check box to save each response as an attachment temporarily.
 - d. Select **Continue**.
8. (Optional) To enable Dynatrace notifications as events in your ServiceNow instance, trigger the workflow to create a problem notification and alerting profile in your Dynatrace environment.
- Note:** This step is displayed only when the Observability Commons for CMDB plugin (sn_observability) is already installed. To skip this step, select **Skip** for the **Configure observability** activity.
- a. In the **Setup** stage of the playbook, select the **Configure observability** activity.
 - b. Select **Create problem notification**.

Note: The created records appear in the Dynatrace application under the display name ServiceNow default Problem notification and can be customized.
 - c. Dismiss any success alerts and select **Continue**.
9. Configure the import schedule to import data at regular intervals.
- a. In the **Setup** stage of the playbook, select the **Configure import schedule** activity.
 - b. Expand the Parent scheduled data import within the Import schedules list to select the **SGO-Dynatrace Hosts - Connection Name** import schedule.

- c. Select the **Active** check box, and then fill in the run schedule and time details.

For more information, see [Schedule a data import](#).

- d. Select **Save**.
Alternatively, select **Execute Now** to execute the import schedule immediately.
- e. Select **Continue**.

10. In the **Setup** stage of the playbook, select the **Confirm connection creation** activity to verify whether the connection was created.

What to do next

Select **View all connections** to review the connection details. The created connection appears in the Installed connections list.

Related concepts

- [Service Graph Connector for Observability - Dynatrace](#)

Related reference

- [CMDB classes targeted in Service Graph Connector for Observability - Dynatrace](#)
- [Service Graph Connector for Observability - Dynatrace properties](#)

Configure Service Graph Connector for Observability - Dynatrace using guided setup

Use the Service Graph Connector for Observability - Dynatrace to ingest Configuration Management Database (CMDB) data from Dynatrace using REST APIs. This connector is the second generation of the Service Graph Connector for Observability - Dynatrace application developed by ServiceNow.

Before you begin

Important: Unless there are configuration issues, use the SGC Central view in the CMDB Workspace to configure the connection for the connector, as the guided setup method is being deprecated.

To use this Service Graph Connector, you need a subscription to a Subscription Unit that is based in the IT Operations Management (ITOM) Visibility application or in the ITOM Discovery application. As defined in the section titled "Managed IT Resource Types" in [ServiceNow Subscription Unit Overview](#) for your subscription, for managed IT resources that are created or modified in the CMDB by this Service Graph Connector, but that aren't yet managed by [ITOM Visibility](#) or [ITOM Discovery](#), these resources will increase Subscription Unit consumption from that application. Review your current Subscription Unit consumption within ITOM Visibility or ITOM Discovery to ensure available capacity.

Dependencies and requirements:

- The [Integration Commons for CMDB](#) store app, which is automatically installed.
- The CMDB CI class models store app, which is automatically installed. See [CMDB CI Class Models](#).
- The ITOM Discovery License plugin (com.snc.itom.discovery.license). You must activate this plugin.
- ITOM Licensing plugin (com.snc.itom.license). For more information, see [Request Discovery](#).
- The Datastream Action plugin (com.glide.hub.action_type.datastream), which is automatically installed.
- Observability Commons for CMDB (sn_observability), which is only required for event ingestion and will need to be installed prior to installing the connector for Event Management to work. For more information, see [Observability Commons for CMDB](#) on the ServiceNow Store.

Note: To access the Dynatrace API, you need an access token with Read entities (entities.read) scope.

Role required: SGC-Admin (sn_cmdb_int_util.sgc_admin)

Note: The admin user role is required to run background scripts and to provide table-level access to the SGC-Admin user.

Procedure

1. Navigate to **All > Service Graph Connectors > Dynatrace Observability > Setup**.
2. On the Getting started page, select **Get Started**.
3. Set impact values for clusters and have the connector get access to the SNC.ImpactManager API.

Note: This step appears when Observability Commons is installed.

- a. On the Setup page, in the Enable Access To SNC.Impact Manager section, select the **Copy Script to Global Scope** task.
- b. In the Copy Script to Global Scope section, copy the script.
 - a. Select **Configure**.
 - b. Switch to the global scope.



- c. Select the Additional actions icon ().
- d. Select **Insert and Stay**.
- e. Select **Mark as Complete**.
- c. In the Verify script is copied properly section, verify the script.
 - a. Select **Configure**.

- b. Select the EvtMgmtImpactManagerMediator script and verify it was copied to the global scope.
 - c. In the **Accessible from** field, ensure it is set to **All application scopes**.
 - d. Select **Mark as Complete**.
 4. Configure the basic setup.
 - a. On the Setup page, in the Basic section, select the **Configure Auth Token for Dynatrace** task.
 - b. On the next page, in the Configure Auth Token for Dynatrace section, configure the authentication token.
 - a. Select **Configure**.
 - b. In the **API Key** field, enter api-token <your api token>.

For example, api-token mytokenid.
 - c. Select **Mark as Complete**.
 - c. In the Configure HTTP Connection for Dynatrace section, configure the HTTP connection.
 - a. Select **Configure**.
 - b. Update the **Host** field with a fully qualified hostname for your Dynatrace instance.

For example, abc123.live.dynatrace.com.

The hostname is automatically filled in the **Connection URL** field.
 - c. Enable the use of a MID Server, select the **Use MID Server** check box.

Note: The HTTP connection will be pre-configured to use the API key that was configured during the previous setup task.
 - d. Select **Mark as Complete**.

d. Test the HTTP connection.

a. In the Test Connection section, select **Configure**.

b. To test the connection configuration, select **Test Connection**.

Note: If any of the tests have errors, follow the suggestions for remediation.

c. Set the Test Connection task to complete by selecting **Mark as Complete**.

e. In the Create Default Notification Payload Template section, select **Configure**.

Note: You need an access token with the following scopes:

- Read configuration (ReadConfig)
- Write configuration (WriteConfig)
- Read log content (LogExport)
- Read metrics (metrics.read)
- Read settings (settings.read)
- Write settings (settings.write)
- Read logs (logs.read)

a. Update the name of the payload template, if needed.

b. Select **Problem Notification Setup**.

c. Set the Create Default Notification Payload Template task to complete by selecting **Mark as Complete**.

f. (Optional) If you want to support multiple instances, in the Upgrade Source Native Keys section, select **Configure**.

a. In the **Run script** text box of the background script page, enter the following script:

```
var gr = new GlideRecord("sys_object_source");
gr.addQuery("name", "SGO-Dynatrace");
```

```
var grOR = gr.addQuery("id", "STARTSWITH", "HOST-");
grOR.addOrCondition("id", "STARTSWITH", "PROCESS_GROUP_INSTANCE-");
grOR.addOrCondition("id", "STARTSWITH", "PROCESS_GROUP-");
grOR.addOrCondition("id", "STARTSWITH", "SERVICE-");
grOR.addOrCondition("id", "STARTSWITH", "APPLICATION-");
gr.query();
while (gr.next()) {
    gr.setValue("id", "f379137e075820107add6a77c4a93538||" + gr.getValue("id"));
    gr.update();
}
```

- b. Select **Run Script** to run the background script in the **global** scope.

The script may take several minutes to execute.

- c. After the script is executed, select **Close**.
 - d. From the application picker, select the **Service Graph Connector for Observability Dynatrace** application.
 - e. Select **Mark as Complete**.
5. For a Grail-enabled tenant, configure the OAuth 2.0 client credentials and test the connection.
For more information on Dynatrace OAuth credentials, see [Authentication for the Account Management API](#) on the Dynatrace documentation site.
 - a. Set the Dynatrace Grail status to indicate whether using the Grail-enabled tenant.

Note:

You can check Grail enablement by contacting your Dynatrace administrator.

- a. In the Configure Dynatrace Grail OAuth section of the Service Graph Connector for Observability Dynatrace Setup page, select **Get Started**.
 - b. For the Set Dynatrace Grail status task, select **Configure** and review or modify the property settings for a Grail-enabled tenant.
 - c. If you've Grail-enabled tenant, set the **Value** field of the `grailEnabled` property to `true`.

Else, leave the value set to `false`.
 - d. Set the Configure Dynatrace Grail OAuth task to complete by selecting **Mark as Complete**.
- b. Add a new OAuth connection.
- Note:** You need an OAuth token with the following scope permissions in Grail:
- `storage:logs:read`
 - `storage:buckets:read`
- a. In the Configure OAuth credentials section, select **Configure**.
 - b. On the Workflow Studio page that opens in a new browser tab, select **Add Connection**.
 - c. Enter a name, the connection URL, OAuth client ID, and OAuth client secret details.
 - d. Select **Create and Get OAuth Token**.
 - e. Return to the guided setup page.
 - f. Set the Configure OAuth credentials task to complete by selecting **Mark as Complete**.
- c. Test the new OAuth connection.
- a. In the Test Connection section, select **Configure**.
 - b. To test the connection configuration, select **Test Connection**.

- c. When the **Status** field is set to **Success**, select **Update** to close the Test the connection dialog box and return to the guided setup page.

If any of the tests have errors, follow the suggestions for remediation.

- d. Set the Test Connection task to complete by selecting **Mark as Complete**.

6. Set up the additional configurations.

- a. On the Guided setup page, in the Advanced section, select the **Advanced settings** task.

- b. In the Advanced Settings section, select **Configure** and review or modify the existing settings for a custom configuration.

You can configure the following settings:

- Review the page size used in REST API requests to fetch Dynatrace entities.
- Define number of days a configuration item (CI) can be inactive before it is ignored.
- Enter the percentage of an application cluster's nodes that need to be in a state to raise that state to its parent in the service map.

For example, you can define the percentage of nodes that need to go critical for the parent of a cluster to be in a critical state. If there are 10 nodes in a cluster, setting the property value to 70 would require at least 7 out of the 10 nodes in the cluster to go into a critical state to reflect up to the parent service of the cluster.

- Enable ingesting events that do not have a matching CI in the CMDB.
- Enable populating the Application (cmdb_ci_appl) CIs from Dynatrace (Dynatrace processes) during scheduled imports.

- c. Select **Save**.

- d. Select **Mark as Complete** for the Advanced Settings task.

- e. Configure connection properties for the Dynatrace connection.
 - a. In the Configure Instance Settings section, select **Configure**.
 - b. In the Service Graph Connection Properties related list, configure the properties of the connection record.

Dynatrace connection properties

Property	Description
managementZoneNames	Enter the name of the management zone to fetch from your Dynatrace environment. For multiple entries, separate the zone names with commas.
tags	Enter the name of the tags to fetch from your Dynatrace environment. For multiple entries, separate the tags with commas.
serviceTypes	Enter the list of Dynatrace service types from where to ingest the data into CMDB. For multiple entries, separate the service types with commas.

Property	Description
	Note: All service types except for DATABASE_SERVICE are mapped to the Calculated Application Service [cmdb_ci_service_calculated] CMDB table. The DATABASE_SERVICE service type is mapped to the Database Instance [cmdb_ci_db_instance] CMDB table. Valid values are: - BACKGROUND_ACTIVITY - CICS_SERVICE - CUSTOM_SERVICE - DATABASE_SERVICE - ENTERPRISE_SERVICE_BUS_SERVICE - EXTERNAL - IBM_INTEGRATION_BUS_SERVICE - IMS_SERVICE - MESSAGING_SERVICE - QUEUE_LISTENER_SERVICE - RMI_SERVICE - RPC_SERVICE

Property	Description
managementZoneIds	Enter the management zone ID to fetch from your Dynatrace environment. For multiple entries, separate the zone IDs with commas.

c. Select **Update**.

d. Complete the Configure Instance Settings task by selecting **Mark as Complete**.

f. Execute the Fix Older Ids fix script to migrate the IDs of the imported data from the previous format to the latest format of the object IDs.

Note: Beginning with the 1.9.0 version of the Service Graph Connector for Observability - Dynatrace, the latest format of the object IDs, which is Base64 Encoding, is used for data import. The Fix Older Ids fix script migrates any existing data with previous object IDs to the latest format.

g. Configure the notification settings.

The setup enables pulling ITOM events from Dynatrace into the ServiceNow instance.

a. In the Configure Problem Notification section, select **Configure**.

b. To push the configuration to Dynatrace, select **Problem Notification Setup**.

c. To receive the configuration from Dynatrace, select **Fetch Notification Setup**.

d. Complete the Configure Problem Notification task by selecting **Mark as Complete**.

7. Clean up records from the previous instance.

Note: If you are not migrating from the previous Dynatrace version, you can skip this step.

- a. On the Setup page, in the Clean Up Records From Previous Integration section, select the **Execute the New Integration** task.
- b. On the next page, in the Execute the New Integration section, select **Configure** and select **Update**.
- c. Select **Mark as Complete**.
- d. In the Verify Integration Execution Has Completed section, verify the integration execution.

- a. Select **Configure**.

- b. In the **State** field, wait for the field to change to **Complete** or **Complete with errors**.

It is normal to have errors during the migration from an older version.

- c. To refresh the list, select and hold (or right-click) the header and select **Refresh List**.

- d. Select **Mark as Complete**.

- e. In the Delete Application Services Left Over From Previous Version section, select **Configure** to delete any application services that you no longer need from the previous integration.

- f. Select **Mark as Complete**.

- g. In the Cleanup Identification Remnants - Copy Script section, copy the script.

- a. Select **Configure**.

- b. Change the current scope to **Global**.



- c. Select the menu icon ().

- d. Select **Insert and Stay**.

- e. Select **Mark as Complete**.

- h. In the Cleanup Identification Remnants - Execute Script section, execute the script.
 - a. Select **Configure**.
 - b. Select the record of the script you copied.
 - c. Select **Update**.
8. (Optional) Add multiple instances.

Note: If you do not need to add multiple instances, you can skip this step.

 - a. In the Add Multiple Instances section of the Service Graph Connector for Observability - Dynatrace page, select **Get Started**.
 - b. Update the data source access to create a data source for the new connection.
 - a. Ensure that you have edit permissions for the Datasource [sys_data_source] table.
 - b. For the Update Data Source Access task, select **Configure**.
 - c. To edit the record, select the **Global** application scope from the application picker.
 - d. In the Application Access related list of the Data Source form that opens in a new tab, select the **Can create**, **Can update**, and **Can delete** check boxes.
 - e. Select **Update** to return to the guided setup page.
 - f. Select the **Service Graph Connector for Observability Dynatrace** application scope from the application picker.
 - g. Set the Update Data Source Access task to complete by selecting **Mark as Complete**.
 - c. Update the scheduled data import access to create a scheduled import for the new connection.
 - a. Ensure that you have edit permissions for the Scheduled data import [scheduled_import_set] table.

- b. For the Update Scheduled Data Import Access task, select **Configure**.
 - c. To edit the record, select the **Global** application scope from the application picker.
 - d. In the Application Access related list of the Data Source form that opens in a new tab, select the **Can create**, **Can update**, and **Can delete** check boxes.
 - e. Select **Update** to return to the guided setup page.
 - f. Select the **Service Graph Connector for Observability Dynatrace** application scope from the application picker.
 - g. Set the Update Scheduled Data Import Access task to complete by selecting **Mark as Complete**.
- d. Update the value access to create the data source for the new connection.
- a. Ensure that you have edit permissions for the Value [sys_variable_value] table.
 - b. For the Update Value Access task, select **Configure**.
 - c. To edit the record, select the **Global** application scope from the application picker.
 - d. In the Application Access related list of the Data Source form that opens in a new tab, select the **Can create**, **Can update**, and **Can delete** check boxes.
 - e. Select **Update** to return to the guided setup page.
 - f. Select the **Service Graph Connector for Observability Dynatrace** application scope from the application picker.
 - g. Set the Update Value Access task to complete by selecting **Mark as Complete**.
- e. Clear the data source and import set cache for the new connection.
- a. For the Clear Cache for Datasource and Import set task, select **Configure**.

- b. In the **Run script** text box of the background script page, enter the following script:

```

        GlideTableManager.invalidateTable("sys_data_source");
        GlideCacheManager.flushTable("sys_data_source");

        GlideTableManager.invalidateTable("scheduled_import_set");
        GlideCacheManager.flushTable("scheduled_import_set");

        GlideTableManager.invalidateTable("sys_variable_value");
        GlideCacheManager.flushTable("sys_variable_value");

        GlideTableManager.invalidateTable("sys_db_object");
        GlideCacheManager.flushTable("sys_db_object");

```

- c. Select **Run Script** to run the background script in the **global** scope.

The script may take several minutes to execute.

- d. After the script is executed, select **Close**.
- e. Select the **Service Graph Connector for Observability Dynatrace** application scope from the application picker.
- f. Set the Clear Cache for Datasource and Import set task to complete by selecting **Mark as Complete**.
- f. Add another connection.
- a. Ensure that the application scope is set to **Service Graph Connector for Observability** in the application picker.
- b. For the Add Another Connection task, select **Configure**.

- c. On the Workflow Studio page that opens in a new browser tab, select **Add Connection**.
- d. On the form, fill in the fields.

Connection form

Field	Description
Connection Name	Display name for the connection.
Connection Hostname	Host name of the Dynatrace instance.
API Key	Dynatrace API Key. Note: The API Key must be prefixed with <code>api -</code> token.

- e. Select **Create Connection**.
 - f. Return to the guided setup page.
 - g. Set the Add Another Connection task to complete by selecting **Mark as Complete**.
- g. If using a Grail-enabled tenant, configure additional OAuth 2.0 connections.
- a. For the Add another OAuth connection task, select **Configure**.
 - b. On the Workflow Studio page that opens in a new browser tab, select **Add Connection**.
 - c. Enter a name, the connection URL, OAuth client ID, and OAuth client secret details.
 - d. Select **Create and Get OAuth Token**.
 - e. Return to the guided setup page.

- PDF generated on January 16, 2026

- k. Test the new connections.
 - a. For the Test Connections task, select **Configure**.
 - b. Select the name of the connection you want to test.
 - c. To validate the data source configuration, select **Test Load 20 Records**.
 - d. When the **Status** field is set to **Success**, select **Update** to close the Test the connection dialog box and return to the guided setup page.

If any of the tests have errors, follow the suggestions for remediation.
 - e. Set the Test Connections task to complete by selecting **Mark as Complete**.
- l. Create default notification payload templates.
 - a. Ensure that you have the access token with the following scopes:
 - Read configuration (ReadConfig)
 - Write configuration (WriteConfig)
 - Read log content (LogExport)
 - Read metrics (metrics.read)
 - b. For the Create Default Notification Payload Templates task, select **Configure**.
 - c. Select the connection you want to create a default notification payload template for.
 - d. Update the name of the payload template, if needed.
 - e. Select **Problem Notification Setup**.

The notification is created with the payload parameters as described in the following table.

Notification payload parameters

Parameter	Description
name	Name of the notification. The name is automatically prefixed with ServiceNow Default Problem Notification and the instance name is added to it.
alertingProfile	ID of the alerting profile in Dynatrace.
type	Type of payload that is automatically set to webhook .
url	Webhook URL in the format <code>https://https://<instance name>.service-now.com/ /api/sn_em_connector/em/inbound_event?source=SG0-Dynatrace</code> .
payload	Custom payload created for notification in the following format: <pre>{ "ImpactedEntities": { "ImpactedEntities": { "ImpactedEntity": "{ImpactedEntity}", "PID": "{PID}", "ProblemDetailsHTML"</pre>

Parameter	Description
	<pre> : "{ProblemDetailsHTML }", "ProblemDetailsJSON" : {ProblemDetailsJSON} , "ProblemDetailsMarkd own": "{ProblemDetails Markdown}" , "ProblemDetailsText" : "{ProblemDetailsText }", "ProblemID": "{Probl emID}" , "ProblemImpact": "{P roblemImpact}" , "ProblemSeverity": " {ProblemSeverity}" , "ProblemTitle": "{Pr oblemTitle}" , "ProblemURL": "{Prob lemURL}" , "State": "{State}" , "Tags": "{Tags}" } </pre>

- f. Repeat the steps for each connection.
- g. Set the Create Default Notification Payload Templates task to complete by selecting **Mark as Complete**.

9. Set up scheduled import jobs.
 - a. In the Set up scheduled import jobs section of the Service Graph Connector for Observability - Dynatrace page, select **Get Started**.
 - b. For the Configure the scheduled import jobs task, select **Configure**.
 - c. Select the name of the scheduled import you want to run.
 - d. On the Scheduled Data Import form, verify the field values for the scheduled job and select the **Active** check box.

For more information, see [Schedule a data import](#).
 - e. Select **Update**.
 - f. Set the Set up scheduled import jobs task to complete by selecting **Mark as Complete**.

CMDB classes targeted in Service Graph Connector for Observability - Dynatrace

When you complete setting up the connection, you can configure the integration to periodically pull data from Dynatrace. The data is saved in tables that extend from the Configuration item [cmdb_ci] table.

Application [cmdb_ci_appl]

The following attributes in the Application [cmdb_ci_appl] table are populated by collected data.

Attribute label	Attribute name
Class	sys_class_name
Configuration file	config_file
Installation directory	install_directory

Attribute label	Attribute name
Name	name
Operational status	operational_status
Running process command	running_process_command
Running process key parameters	running_process key parameters
Version	version

Relationships created for Application

Parent class	Relationship type	Child class
Application [cmdb_ci_appl]	Runs on::Runs	Computer [cmdb_ci_computer]
Application [cmdb_ci_appl]	Runs on::Runs	Docker Container [cmdb_ci_docker_container]
Application [cmdb_ci_appl]	Reference	Key value [cmdb_key_value]

Note: Based on the Discovery Process Classifications list, the tables that extend the Application [cmdb_ci_appl] table are populated by the SGO-Dynatrace Processes [sn_dynatrace_integ_sg_dynatrace_processes] data source.

Availability Zone [cmdb_ci_availability_zone]

The following attributes in the Availability Zone [cmdb_ci_availability_zone] table are populated by collected data.

Attribute label	Attribute name
Name	name

Attribute label	Attribute name
Object ID	object_id

AWS Datacenter [cmdb_ci_aws_datacenter]

The following attributes in the AWS Datacenter [cmdb_ci_aws_datacenter] table are populated by collected data.

Attribute label	Attribute name
Name	name
Object ID	object_id
Region	region

Relationships created for AWS Datacenter

Parent class	Relationship type	Child class
AWS Datacenter [cmdb_ci_aws_datacenter]	Hosted on::Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]
AWS Datacenter [cmdb_ci_aws_datacenter]	Contains::Contained by	Availability Zone [cmdb_ci_availability_zone]

Azure Datacenter [cmdb_ci_azure_datacenter]

The following attributes in the Azure Datacenter [cmdb_ci_azure_datacenter] table are populated by collected data.

Attribute label	Attribute name
Install Status	install_status

Attribute label	Attribute name
Name	name
Object ID	object_id
Region	region

Relationship created for Azure Datacenter

Parent class	Relationship type	Child class
Azure Datacenter [cmdb_ci_azure_data center]	Hosted on::Hosts	Cloud Service Account [cmdb_ci_cloud_servi ce_account]

Calculated Application Service [cmdb_ci_service_calculated]

The following attributes in the Calculated Application Service [cmdb_ci_service_calculated] table are populated by collected data.

Attribute label	Attribute name
Comments	comments
Correlation ID	correlation_id
Hide from dashboard	hide_from_dashboard
Metadata	metadata
Name	name
Operational status	operational_status
Service Populator	service_populator
Service Populator Status	populator_status

Attribute label	Attribute name
Service Type	type

Note: The Comments attribute includes the following information:

- Service Type
- Edition
- TCP Port

Relationships created for Calculated Application Service

Parent class	Relationship type	Child class
Calculated Application Service [cmdb_ci_service_calculated]	Depends on::Used by	Configuration Item [cmdb_ci]
Calculated Application Service [cmdb_ci_service_calculated]	Runs on::Runs	Computer [cmdb_ci_computer]
Calculated Application Service [cmdb_ci_service_calculated]	Contains::Contained by	Cloud Load Balancer [cmdb_ci_cloud_load_balancer]
Calculated Application Service [cmdb_ci_service_calculated]	Contains::Contained by	Group [cmdb_ci_group]
Calculated Application Service [cmdb_ci_service_calculated]	Reference	Key value [cmdb_key_value]

Cloud DataBase [cmdb_ci_cloud_database]

The following attributes in the Cloud DataBase [cmdb_ci_cloud_database] table are populated by collected data.

Attribute label	Attribute name
Fully qualified domain name	fqdn
Install Status	install_status
Name	name
Object ID	object_id
State	state
TCP port(s)	tcp_port
Type	type
Version	version

Relationships created for Cloud DataBase

Parent class	Relationship type	Child class
Cloud DataBase [cmdb_ci_cloud_database]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Cloud DataBase [cmdb_ci_cloud_database]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Cloud DataBase [cmdb_ci_cloud_database]	Reference	Key Value [cmdb_key_value]

Cloud Function [cmdb_ci_cloud_function]

The following attributes in the Cloud Function [cmdb_ci_cloud_function] table are populated by collected data.

Attribute label	Attribute name
Code Size	code_size
Fully qualified domain name	fqdn
Install Status	install_status
Language	language
Name	name
Object ID	object_id
Version	version

Relationships created for Cloud Function

Parent class	Relationship type	Child class
Cloud Function [cmdb_ci_cloud_function]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Cloud Function [cmdb_ci_cloud_function]	Reference	Key Value [cmdb_key_value]

Cloud Hardware Type [cmdb_ci_cloud_hardware_type]

The following attributes in the Cloud Hardware Type [cmdb_ci_cloud_hardware_type] table are populated by collected data.

Attribute label	Attribute name
Name	name
Object ID	object_id
Provider	provider

Relationship created for Cloud Hardware Type

Parent class	Relationship type	Child class
Cloud Hardware Type [cmdb_ci_cloud_hardware_type]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]

Cloud LB IPAddress [cmdb_ci_cloud_lb_ipaddress]

The following attributes in the Cloud LB IPAddress [cmdb_ci_cloud_lb_ipaddress] table are populated by collected data.

Attribute label	Attribute name
Install Status	install_status
Name	name
Object ID	object_id

Cloud Load Balancer [cmdb_ci_cloud_load_balancer]

The following attributes in the Cloud Load Balancer [cmdb_ci_cloud_load_balancer] table are populated by collected data.

Attribute label	Attribute name
Install Status	install_status

Attribute label	Attribute name
Name	name
Object ID	object_id
Operational status	operational_status

Relationships created for Cloud Load Balancer

Parent class	Relationship type	Child class
Cloud Load Balancer [cmdb_ci_cloud_load_balancer]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Cloud Load Balancer [cmdb_ci_cloud_load_balancer]	Owns::Owned by	Cloud LB IPAddress [cmdb_ci_cloud_lb_ipaddress]
Cloud Load Balancer [cmdb_ci_cloud_load_balancer]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Cloud Load Balancer [cmdb_ci_cloud_load_balancer]	Reference	Key Value [cmdb_key_value]

Cloud Object Storage [cmdb_ci_cloud_object_storage]

The following attributes in the Cloud Object Storage [cmdb_ci_cloud_object_storage] table are populated by collected data.

Attribute label	Attribute name
Cloud Provider	cloud_provider
Install Status	install_status
Name	name

Attribute label	Attribute name
Object ID	object_id
Service Name	service_name

Relationships created for Cloud Object Storage

Parent class	Relationship type	Child class
Cloud Object Storage [cmdb_ci_cloud_object_storage]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Cloud Object Storage [cmdb_ci_cloud_object_storage]	Reference	Key Value [cmdb_key_value]

Cloud Resource [cmdb_ci_cmp_resource]

The following attributes in the Cloud Resource [cmdb_ci_cmp_resource] table are populated by collected data.

Attribute label	Attribute name
Install Status	install_status
Name	name
Object ID	object_id

Relationships created for Cloud Resource

Parent class	Relationship type	Child class
Cloud Resource [cmdb_ci_cmp_resource]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]

Parent class	Relationship type	Child class
Cloud Resource [cmdb_ci_cmp_resource]	Reference	Key Value [cmdb_key_value]

Cloud Service Account [cmdb_ci_cloud_service_account]

The following attributes in the Cloud Service Account [cmdb_ci_cloud_service_account] table are populated by collected data.

Attribute label	Attribute name
Account Id	account_id
Datacenter Type	datacenter_type
Install Status	install_status
Name	name
Object ID	object_id
Operational status	operational_status

Cloud Storage Account [cmdb_ci_cloud_storage_account]

The following attributes in the Cloud Storage Account [cmdb_ci_cloud_storage_account] table are populated by collected data.

Attribute label	Attribute name
Name	name
Install Status	install_status
Object ID	object_id

Attribute label	Attribute name
Sku Name	sku_name

Relationships created for Cloud Storage Account

Parent class	Relationship type	Child class
Cloud Storage Account [cmdb_ci_cloud_storage_account]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Cloud Storage Account [cmdb_ci_cloud_storage_account]	Reference	Key Value [cmdb_key_value]

Computer [cmdb_ci_computer]

The following attributes in the Computer [cmdb_ci_computer] table are populated by collected data.

Attribute label	Attribute name
Class	sys_class_name
CPU core count	cpu_core_count
DNS Domain	dns_domain
Fully qualified domain name	fqdn
Is Virtual	virtual
Name	name
Operating System	os
OS Version	os_version

Attribute label	Attribute name
RAM (MB)	ram

Relationships created for Computer

Parent class	Relationship type	Child class
Computer [cmdb_ci_computer]	Owns::Owned by	IP Address [cmdb_ci_ip_address]
Computer [cmdb_ci_computer]	Reference	Key Value [cmdb_key_value]
Computer [cmdb_ci_computer]	Reference	Software Installation [cmdb_sam_sw_install]

Docker Container [cmdb_ci_docker_container]

The following attributes in the Docker Container [cmdb_ci_docker_container] table are populated by collected data.

Attribute label	Attribute name
Container id	container_id
Install Status	install_status
Name	name

Note: The Install Status value is based on the value of the `properties.containerStatus.state` field in the incoming payload.

- If the `properties.containerStatus.state` value is `running`, the Install Status value is set to 1 (Installed).
- If the `properties.containerStatus.state` value is `terminated` or is empty, or if there are any errors, the Install Status value is set to 7 (Retired).
- For all other `properties.containerStatus.state` values, the Install Status value isn't updated.

Docker Image [cmdb_ci_docker_image]

The following attributes in the Docker Image [cmdb_ci_docker_image] table are populated by collected data.

Attribute label	Attribute name
Image id	image_id
Image digest	image_digest
Name	name

Relationship created for Docker Image

Parent class	Relationship type	Child class
Docker Image [cmdb_ci_docker_image]	Instantiates::Instantiated by	Docker Container [cmdb_ci_docker_container]

DynamoDB Table [cmdb_ci_dynamodb_table]

The following attributes in the DynamoDB Table [cmdb_ci_dynamodb_table] table are populated by collected data.

Attribute label	Attribute name
Name	name
Install Status	install_status
Object ID	object_id

Relationships created for DynamoDB Table

Parent class	Relationship type	Child class
DynamoDB Table [cmdb_ci_dynamodb_table]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
DynamoDB Table [cmdb_ci_dynamodb_table]	Reference	Key Value [cmdb_key_value]

Group [cmdb_ci_group]

The following attribute in the Group [cmdb_ci_group] table is populated by collected data.

Attribute label	Attribute name
Name	name

Relationship created for Group

Parent class	Relationship type	Child class
Group [cmdb_ci_group]	Contains::Contained by	Application [cmdb_ci_appl]

Hardware Type [cmdb_ci_compute_template]

The following attributes in the Hardware Type [cmdb_ci_compute_template] table are populated by collected data.

Attribute label	Attribute name
Name	name
Object ID	object_id

Relationship created for Hardware Type

Parent class	Relationship type	Child class
Hardware Type [cmdb_ci_compute_template]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]

Image [cmdb_ci_os_template]

The following attributes in the Image [cmdb_ci_os_template] table are populated by collected data.

Attribute label	Attribute name
Name	name
Object ID	object_id

Relationship created for Image

Parent class	Relationship type	Child class
Image [cmdb_ci_os_template]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]

Instance Scale Set [cmdb_ci_instance_scale_set]

The following attributes in the Instance Scale Set [cmdb_ci_instance_scale_set] table are populated by collected data.

Attribute label	Attribute name
Name	name
Install Status	install_status
Object ID	object_id

Relationships created for Instance Scale Set

Parent class	Relationship type	Child class
Instance Scale Set [cmdb_ci_instance_scale_set]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Instance Scale Set [cmdb_ci_instance_scale_set]	Reference	Key Value [cmdb_key_value]

IP Address [cmdb_ci_ip_address]

The following attributes in the IP Address [cmdb_ci_ip_address] table are populated by collected data.

Attribute label	Attribute name
IP Address	ip_address
IP version	ip_version
Name	name

Key value [cmdb_key_value]

The following attributes in the Key value [cmdb_key_value] table are populated by collected data.

Attribute label	Attribute name
Key	key
Value	value

Kubernetes Cluster [cmdb_ci_kubernetes_cluster]

The following attributes in the Kubernetes Cluster [cmdb_ci_kubernetes_cluster] table are populated by collected data.

Attribute label	Attribute name
Cluster Resource ID	cluster_resource_id
Install Status	install_status
Name	name

Relationships created for Kubernetes Cluster

Parent class	Relationship type	Child class
Kubernetes Cluster [cmdb_ci_kubernetes_cluster]	Contains::Contained by	Kubernetes Namespace [cmdb_ci_kubernetes_namespace]
Kubernetes Cluster [cmdb_ci_kubernetes_cluster]	Cluster of::Cluster	Kubernetes Node [cmdb_ci_kubernetes_node]
Kubernetes Cluster [cmdb_ci_kubernetes_cluster]	Contains::Contained by	Kubernetes Service [cmdb_ci_kubernetes_service]
Kubernetes Cluster [cmdb_ci_kubernetes_cluster]	Contains::Contained by	Kubernetes Pod [cmdb_ci_kubernetes_pod]

Kubernetes Namespace [cmdb_ci_kubernetes_namespace]

The following attributes in the Kubernetes Namespace [cmdb_ci_kubernetes_namespace] table are populated by collected data.

Attribute label	Attribute name
Install Status	install_status
Kubernetes UID	k8s_uid
Name	name

Kubernetes Node [cmdb_ci_kubernetes_node]

The following attributes in the Kubernetes Node [cmdb_ci_kubernetes_node] table are populated by collected data.

Attribute label	Attribute name
Install Status	install_status
Kubernetes UID	k8s_uid
Name	name

Kubernetes Pod [cmdb_ci_kubernetes_pod]

The following attributes in the Kubernetes Pod [cmdb_ci_kubernetes_pod] table are populated by collected data.

Attribute label	Attribute name
Install Status	install_status
Kubernetes UID	k8s_uid

Attribute label	Attribute name
Name	name
Namespace	namespace

Relationships created for Kubernetes Pod

Parent class	Relationship type	Child class
Kubernetes Pod [cmdb_ci_kubernetes_pod]	Runs on::Runs	Kubernetes Node [cmdb_ci_kubernetes_node]
Kubernetes Pod [cmdb_ci_kubernetes_pod]	Contains::Contained by	Docker Container [cmdb_ci_docker_container]

Kubernetes Service [cmdb_ci_kubernetes_service]

The following attributes in the Kubernetes Service [cmdb_ci_kubernetes_service] table are populated by collected data.

Attribute label	Attribute name
Install Status	install_status
Kubernetes UID	k8s_uid
Name	name
Namespace	namespace

Server [cmdb_ci_server]

The following attributes in the Server [cmdb_ci_server] table are populated by collected data.

Attribute label	Attribute name
DNS Domain	dns_domain
Fully qualified domain name	fqdn
Is Virtual	virtual
Name	name
Object ID	object_id

Relationships created for Server

Parent class	Relationship type	Child class
Server [cmdb_ci_server]	Virtualized by::Virtualizes	Virtual Machine Instance [cmdb_ci_vm_instanc e]
Server [cmdb_ci_server]	Reference	Key Value [cmdb_key_value]

Software [cmdb_ci_spkg]

The following attributes in the Software [cmdb_ci_spkg] table are populated by collected data.

Attribute label	Attribute name
Key	key
Name	name
Version	version

Relationship created for Software

Parent class	Relationship type	Child class
Software [cmdb_ci_spkg]	Reference	Software Instance [cmdb_software_instance]

Software Installation [cmdb_sam_sw_install]

The following attributes in the Software Installation [cmdb_sam_sw_install] table are populated by collected data.

Attribute label	Attribute name
Discovery source	discovery_source
Display name	display_name
Version	version

Software Instance [cmdb_software_instance]

The following attributes in the Software Instance [cmdb_software_instance] table are populated by collected data.

Attribute label	Attribute name
Installed on	installed_on
Name	name

Relationship created for Software Instance

Parent class	Relationship type	Child class
Software Instance [cmdb_software_instance]	Reference	Computer [cmdb_ci_computer]

Virtual Machine Instance [cmdb_ci_vm_instance]

The following attributes in the Virtual Machine Instance [cmdb_ci_vm_instance] table are populated by collected data.

Attribute label	Attribute name
Install Status	install_status
IP Address	ip_address
Name	name
Object ID	object_id
Operational status	operational_status
VM Instance ID	vm_inst_id

Relationships created for Virtual Machine Instance

Parent class	Relationship type	Child class
Virtual Machine Instance [cmdb_ci_vm_instance]	Provisioned From::Provisioned	Hardware Type [cmdb_ci_compute_template]
Virtual Machine Instance [cmdb_ci_vm_instance]	Hosted on::Hosts	Azure Datacenter [cmdb_ci_azure_datacenter]
Virtual Machine Instance [cmdb_ci_vm_instance]	Provisioned From::Provisioned	Cloud Hardware Type [cmdb_ci_cloud_hardware_type]
Virtual Machine Instance	Provisioned From::Provisioned	Image [cmdb_ci_os_template]

Parent class	Relationship type	Child class
[cmdb_ci_vm_instance]		
Virtual Machine Instance [cmdb_ci_vm_instance]	Hosted on::Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
Virtual Machine Instance [cmdb_ci_vm_instance]	Reference	Key Value [cmdb_key_value]

Set up push notifications from Dynatrace

Set up push notifications of events from Dynatrace into a ServiceNow instance that has the Service Graph Connector for Observability - Dynatrace installed.

Before you begin

If you don't have an alerting profile in Dynatrace, then complete the following steps to create one:

1. Navigate to **Settings > Alerting > Alerting Profiles**.
2. Set up an alerting profile according to your business needs.

Note: For more information about how to set up an alerting profile, see [Alerting profiles](#) on the Dynatrace documentation site.

You must have Observability Commons for CMDB installed.

Role required: admin

Procedure

1. In the Dynatrace instance, navigate to **Settings > Integration > Problem notifications**.

- 2. Click **Add Notification**.
- 3. On the form, fill in the fields.

Melde	
Notification Category	Custom Integration
Display Name	Name of the notification
Webhook URL	Use the following URL: https://<name_of_your_servicenow_instance_name> /api/sn_em. inbound_event?source=SG0-Dynatrace

Melde

R

L

A

d

d

i

t

i

o

n

a

I

H

T

Ta. In the ServiceNow instance, set a password for the pre-created Dynatrace API user by doing

P

H

e

a

d

e

r

s

>

C

r

e

α

t

e

b

a

s

i

c

a

u

t

h

o

r

a. In the ServiceNow instance, set a password for the pre-created Dynatrace API user by doing

a. Navigate to **System Security > Users**.

b. Select the Dynatrace API user.

c. Set the **Password** field with a new password.

d. Clear the **Password needs reset** check box.

e. Update or save the user.

b. Set the **Username** field to DynatraceAPI.

c. Set the **Password** field to the password that you had created.

d. Click **Add**.

Melde

i
z
a
t
i
o
n

Use the following payload:

```
{
  "connectionId": <connections_alias_sys_id>,
  "ImpactedEntities": {ImpactedEntities},
  "ImpactedEntity": "{ImpactedEntity}",
  "PID": "{PID}",
  "ProblemDetailsHTML": "{ProblemDetailsHTML}",
  "ProblemDetailsJSONv2": {ProblemDetailsJSONv2},
  "ProblemDetailsMarkdown": "{ProblemDetailsMarkdown}",
  "ProblemDetailsText": "{ProblemDetailsText}",
  "ProblemID": "{ProblemID}",
  "ProblemImpact": "{ProblemImpact}",
  "ProblemSeverity": "{ProblemSeverity}",
  "ProblemTitle": "{ProblemTitle}",
  "ProblemURL": "{ProblemURL}",
  "State": "{State}",
  "Tags": "{Tags}"
}
```

Melde

Note: For the <connections_alias_sys_id>:

- Navigate to **All > IntegrationHub > Connection & Credentials > Connection & Credentials**
- Select to open the connector for which you want to get the <connections_alias_sys_id>

Name	Type	ID
ACME Godaddy	Connection and Credential	sn_disco_certmgmt.ACME_Godaddy
CICD	Credential	sn_cicd_spoke.CICD
Digicert	Credential	sn_disco_certmgmt.Digicert
Docker	Connection and Credential	sn_docker_spoke.Docker
Dynatrace AWS Connection 1	Connection and Credential	sn_dynatrace_integ.Dynatrace_AWS_1
Dynatrace Connection	Connection and Credential	sn_dynatrace_integ.Dynatrace_Conne
GoDaddy	Credential	sn_disco_certmgmt.GoDaddy
linuxAdmin	Credential	sn_em_connector.linuxAdmin
MicrosoftImageAnalysis	Connection and Credential	MicrosoftImageAnalysis
MicrosoftReceiptScanner	Connection and Credential	MicrosoftReceiptScanner
MicrosoftSensitiveDataMasking	Connection and Credential	MicrosoftSensitiveDataMasking
SGO-Dynatrace OAuth 2.0 Connection alias	Connection and Credential	sn_dynatrace_integ.SGO_Dynatrace_
Sidebar Teams Graph Credentials	Connection and Credential	sn_oe_sfs.Sidebar_Teams_Graph_Cred
windowsAdmin	Credential	sn_em_connector.windowsAdmin

- Right-click the context menu (☰) and then select **Copy sys_id**.

Properties from parent alias sn_dynatrace_integ.Dynatrace_Connection. Click [here](#) for more information about configuring child aliases.

Name	Dynatrace AWS Connection 1	Application	Service Graph Connector for Observability - I
ID	sn_dynatrace_integ.Dynatrace_AWS_Connection_1	Parent Alias	sn_dynatrace_integ.Dynatrace_Connection
Type	Connection and Credential	Connection type	HTTP
Support Multiple Active Connections	☐	Default Retry Policy	Default HTTP Retry Policy
Configuration Template	Dynatrace Connection Template		

Related Links
[Create New Connection & Credential](#)

Connections (1)

Name	Connection type	Active	Credential	Use MID server	Protocol	Host
Dynatrace AWS Connection 1	HTTP(S) Connection	true	DynatraceConnection.Dynatrace AWS Conn	false	https	qat87636.live.dynatrace.com

Melde

A
l
e
r
t
i
n
g
P
r
o
f
i
l
e

Select the alerting profile created in the Before you begin section or another alerting profile.

S
e
n
d
i
n
g
T
e
s
t
N
o
t
i
f
i
c
a
t
i
o
n

Click to send a test notification, and verify that the response status is 200.

Service Graph Connector for Observability - Dynatrace properties

Service Graph Connector for Observability - Dynatrace properties control the behavior of the connector.

Connection properties

These connection properties are available for Service Graph Connector for Observability - Dynatrace.

Note: To open the Service Graph Connection Properties [sn_cmdb_int_util_service_graph_connection_property] table for the connector, navigate to **All > Service Graph Connectors > Dynatrace Observability > Connections** and select the connection name. The connection properties are displayed in the Service Graph Connection Properties related list.

Connection properties for Service Graph Connector for Observability - Dynatrace

Property	Description
managementZonelds	Enter a list of management zone IDs to fetch from Dynatrace. For multiple entries, separate the IDs with commas.
managementZoneNames	Enter a list of management zones to fetch from Dynatrace. For multiple entries, separate the names with commas.
tags	Enter a list of tags to fetch from Dynatrace. For multiple entries, separate the tags with commas.
grailEnabled	Set the property to <code>true</code> for a Grail-enabled tenant.

Property	Description
OAuth Connection	View the Sys ID of the OAuth connection and credential alias linked to the Service Graph connection record.
serviceTypes	Enter a list of Dynatrace service types from where to ingest the data into CMDB. For multiple entries, separate the service types with commas.

Property	Description
	Note: All service types except for DATABASE_SERVICE are mapped to the Calculated Application Service [cmdb_ci_service_calculated] CMDB table. The DATABASE_SERVICE service type is mapped to the Database Instance [cmdb_ci_db_instance] CMDB table. Valid values are: • BACKGROUND_ACTIVITY • CICS_SERVICE • CUSTOM_SERVICE • DATABASE_SERVICE • ENTERPRISE_SERVICE_BUS_SERVICE • EXTERNAL • IBM_INTEGRATION_BUS_SERVICE • IMS_SERVICE • MESSAGING_SERVICE • QUEUE_LISTENER_SERVICE • RMI_SERVICE • RPC_SERVICE • WEB_REQUEST_SERVICE • WEB_SERVICE

PDF generated on January 16, 2026

©2026 ServiceNow. All rights reserved.

[Terms of Use Privacy Statement](#)

ServiceNow, the ServiceNow logo, Now, and other ServiceNow marks are trademarks and/or registered trademarks of ServiceNow, Inc., in the United States and/or other countries. Other company and product names may be trademarks of the respective companies with which they are associated.

Property	Description
saveRESTResponseAsAttachment	Set the property to true to use the SGO-Dynatrace Fetch Entities For Larger Payload action flow and save the response from Dynatrace as an attachment with a .json extension. Set the property to false to use the dedicated action flow and consume the response from Dynatrace as a data stream for processing. • Type: true false • Default value: false

System properties

These system properties are available for Service Graph Connector for Observability - Dynatrace.

Note: To open the System Properties [sys_properties] table, enter `sys_properties.list` in the navigation filter.

System properties for Service Graph Connector for Observability - Dynatrace

Property	Description
sn_dynatrace_integ.critical_cluster_threshold	Enter the percentage of an application cluster's nodes that need to be in a state to raise that state to its parent in the service map. • Type: integer • Default value: 75

Property	Description
	Location: System Property [sys_properties] table
sn_dynatrace_integ.default_from_value_days	Enter the number of days a configuration item (CI) can be inactive before it is ignored. - Type: integer - Default value: 300 - Location: System Property [sys_properties] table
sn_dynatrace_integ.events_for_unmatched_ci.enabled	Set the property to true to ingest events that don't have a matching CI in CMDB. - Type: true false - Default value: false - Location: System Property [sys_properties] table
sn_dynatrace_integ.page_size	Enter the page size used in REST requests to fetch Dynatrace entities. - Type: integer - Default value: 50 - Location: System Property [sys_properties] table

Property	Description
sn_dynatrace_integ.populate_applications	Set the property to true to populate the Application [cmdb_ci_appl] CIs from Dynatrace processes. Set the property to false to ignore the Application [cmdb_ci_appl] CIs. • Type: true false • Default value: false • Location: System Property [sys_properties] table Note: This property is read via scheduled imports. The manual execution of the SGO-Dynatrace Processes and SGO-Dynatrace Process Groups data sources will not consider this property.
sn_dynatrace_integ.createUnmatchedApplicationCIs	Set the property to true to add unclassified processes to the Application [cmdb_ci_appl] table. Set the property to false to ignore unclassified processes. • Type: true false • Default value: true • Location: System Property [sys_properties] table

Property	Description
	Note: Classified processes are added to the corresponding child application classes in the Application [cmdb_ci_appl] table regardless of the value of this property.

Accessing the connection details of Service Graph Connector for Observability - Dynatrace

You can access the connection details of the Service Graph Connector for Observability - Dynatrace in a single view using the common connection framework (CCF) included within the Integration Commons for CMDB (sn_cmdb_int_util) store app.

With the CCF, you can access all the connections used by the Service Graph Connector for Observability - Dynatrace. The connection details include the connection alias, connection properties, data sources, and scheduled data imports associated with a connection. You can also test the connection.

Access the details of a Dynatrace connection

Access the details of a Dynatrace connection configured for the Service Graph Connector for Observability - Dynatrace.

Before you begin

Role required: admin

Procedure

1. Navigate to **All > Service Graph Connectors > Dynatrace Observability > Connections**.
2. From the **Name** column of the Service Graph Connections list, select a connection.

3. On the Service Graph Connections page, view the connection details such as the connection name, alias, and data sources.
4. Select a related list to view further details of the connection.
5. (Optional) Select the **Test Connection** related link to test the connection.

Related concepts

- [Accessing the connection details of Service Graph Connectors](#)

Related reference

- [Service Graph Connector for Observability - Dynatrace properties](#)