

Zurich ServiceNow AI Platform Capabilities

Last updated: January 16, 2026

Some examples and graphics depicted herein are provided for illustration only. No real association or connection to ServiceNow products or services is intended or should be inferred.

This PDF was created from content on docs.servicenow.com. The web site is updated frequently. For the most current ServiceNow product documentation, go to docs.servicenow.com.

Company Headquarters

2225 Lawson Lane
Santa Clara, CA 95054
United States
(408)501-8550

Service Graph Connector for Observability - New Relic

Use the Service Graph Connector for Observability - New Relic to ingest CMDB data from a New Relic installation using REST APIs. Push events from New Relic into ServiceNow with Event Management.

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Supported versions

- New Relic version: Last tested on July 01, 2025
- Supported ServiceNow versions:
 - Xanadu
 - Yokohama
 - Zurich

Configuring a connection for the connector

You can configure a connection for the connector by using the SGC Central view in the CMDB Workspace. The view enables you to discover and install connectors, and then effectively manage the full life cycle of creating, editing, monitoring, and debugging connections. To configure the connector using SGC Central, see [Configure Service Graph Connector for Observability - New Relic using SGC Central](#).

Important: Unless there are configuration issues, use the SGC Central view in the CMDB Workspace to configure the connection for the connector, as the guided setup method is being deprecated.

CMDB integrations dashboard

The Integration Commons for CMDB store app provides a dashboard with a central view of the status, processing results, and processing errors of all installed integrations. You can see metrics for all integration runs. You can

filter the view to a specific CMDB integration, a specific time duration, or a specific integration run. For more details about monitoring Observability New Relic integrations in the CMDB Integrations Dashboard, see [Using the CMDB Integrations Dashboard](#).

Data mapping

Data from the New Relic data sources is mapped and transformed into the ServiceNow CMDB Configuration Item (CI) class definitions using the Robust Transform Engine (RTE). Data is inserted into the ServiceNow CMDB using the Identification and Reconciliation Engine (IRE).

The following data sources are included for New Relic:

- SG-New Relic Application Services
- SG-New Relic Applications
- SG-New Relic Disks
- SG-New Relic Hosts
- SG_New Relic Networks

When you complete setting up the connection, you can configure the integration to periodically pull data from the New Relic application. The data is loaded into the following staging tables:

- SG-New Relic Applications
[sn_newrelic_integ_sg_new_relic_applications]
- SG-New Relic Application Services
[sn_newrelic_integ_application_services]
- SG-New Relic Disks [sn_newrelic_integ_disks]
- SG-New Relic Hosts [sn_newrelic_integ_hosts]
- SG_New Relic Networks [sn_newrelic_integ_networks]

The data is then inserted into the following target tables:

- Application [cmdb_ci_appl]
- Application service [cmdb_ci_service_calculated]

- Disk [cmdb_ci_disk]
- IP Address[cmdb_ci_ip_address]
- Network Adapter [cmdb_ci_network_adapter]
- Running Process [cmdb_running_process]
- Server [cmdb_ci_server]
- Software Installation [cmdb_sam_sw_install] (If the Software Asset Management (SAM) application is installed.)
- Software Instance [cmdb_software_instance] (If the SAM application is not installed.)
- Software [cmdb_ci_spkg] (If the SAM application is not installed.)

For more information on where data is saved when pulling data from New Relic, see [CMDB classes targeted in Service Graph Connector for Observability - New Relic](#).

You can use the IntegrationHub ETL app to view the data maps. See [IntegrationHub ETL](#) for more information.

System property

The sn_newrelic_integ.alerts_for_unmatched_ci.enabled system property determines whether to ingest events that don't have a matching CMDB CI class. Set the value of this system property to true to ingest unmatched events. The default value is false.

Related concepts

- [Service Graph Connectors](#)

Configure Service Graph Connector for Observability - New Relic using SGC Central

Use the playbook available with the SGC Central application to set up the Service Graph Connector for Observability - New Relic for pulling in New Relic project data into the CMDB.

Before you begin

Dependencies and requirements:

- Install Service Graph Connector for Observability - New Relic version 1.3.0 or later from the ServiceNow Store. For ServiceNow Store installation steps, see [Install a ServiceNow Store application](#).
- Install Observability Commons for CMDB (sn_observability), which is only required for event ingestion. This must be installed prior to installing the connector for Event Management to work. For more information, see [Observability Commons for CMDB](#) on the ServiceNow Store.

Role required: SGC-Admin (sn_cmdb_int_util.sgc_admin)

Note: The admin user role is required to run background scripts and to provide table-level access to the SGC-Admin user.

About this task

The playbook experience for onboarding connectors is activated with SGC Central in the CMDB Workspace. To configure the SGC Central application, see [Configuring SGC Central](#) and for more information on how to interact with a playbook, see [Interact with Playbook](#).

Procedure

1. Navigate to **Workspaces > CMDB Workspace**.
2. In the CMDB Workspace, select **SGC Central**.
3. On the Overview page, select **Create connection**.

Tip: Alternatively, you can select **Create connection** on the All connections page.
4. On the Create connection window, select the New Relic connector type, and then select **Create connection**.
5. Complete the initial prerequisites when setting up a connection for the first time using a connector.

Note: This step is required only during the first-time setup. See [Perform initial setup tasks when creating a connection in SGC Central](#).

6. Enter connection details and test the API connection for importing New Relic data.
 - a. In the **Setup** stage of the playbook, select the **Create and test connection** activity.
 - b. On the form, fill in the fields.

Configure and test connection form

Field	Description
Connection Name	Name to identify the New Relic connection record.
Connection URL	New Relic base URL in the following format: <base-URL>.
API Key	New Relic API key or tenant code.
Account ID	New Relic account ID.

- c. Select **Update and test connection**.
 - d. After the connection test is complete, select **Continue**.
7. For the Configure Observability activity, select **Continue**.
New Relic creates the destination, channel, and workflow required to enable alerts for all configuration items (CIs).
8. Configure the import schedule to import data at regular intervals.
 - a. In the **Setup** stage of the playbook, select the **Configure import schedule** activity.
 - b. Select **Configure import schedule**.
 - c. Expand the Parent scheduled data import within the Import schedules list to select the **SG-New Relic Hosts** import schedule.

- d. In the Configure import schedule dialog box, select the **Active** check box, and then fill in the run schedule and time details.

For more information, see [Schedule a data import](#).

- e. Select **Save**.
Alternatively, select **Execute Now** to execute the import schedule immediately.
 - f. Select **Continue**.
9. In the **Setup** stage of the playbook, select the **Confirm connection creation** activity to verify whether the connection was configured.
 10. Enable alerts for configuration items (CIs) that aren't available in the CMDB.
 - a. Navigate to **Workspaces > CMDB Workspace > SGC Central**.
 - b. Select **Settings**.
 - c. Select **New Relic system properties**.
 - d. On the System Properties form, select the `sn_newrelic_integ.alerts_for_unmatched_ci.enabled` system property.
 - e. Set the **Value** of the system property to `true`.
 - f. Select **Submit**.

What to do next

Select **View all connections** to review the connection details. The configured connection appears in the Installed connections list.

Related concepts

- [Service Graph Connector for Observability - New Relic](#)

Configure Service Graph Connector for Observability - New Relic using the guided setup

Set up scheduled import jobs to pull in data from New Relic into your CMDB.

Before you begin

To use this Service Graph Connector, you need a subscription to a Subscription Unit that is based in the IT Operations Management (ITOM) Visibility application or in the ITOM Discovery application. As defined in the section titled "Managed IT Resource Types" in [ServiceNow Subscription Unit Overview](#) for your subscription, for managed IT resources that are created or modified in the CMDB by this Service Graph Connector, but that aren't yet managed by [ITOM Visibility](#) or [ITOM Discovery](#), these resources will increase Subscription Unit consumption from that application. Review your current Subscription Unit consumption within ITOM Visibility or ITOM Discovery to ensure available capacity.

Dependencies and requirements:

- The [Integration Commons for CMDB](#) store app, which is automatically installed.
- The CMDB CI class models store app, which is automatically installed. See [CMDB CI Class Models](#).
- The ITOM Discovery License plugin (com.snc.itom.discovery.license). You must activate this plugin.
- ITOM Licensing plugin (com.snc.itom.license). For more information, see [Request Discovery](#).
- The Datastream Action plugin (com.glide.hub.action_type.datastream), which is automatically installed.
- Observability Commons for CMDB (sn_observability), which is only required for event ingestion. This must be installed prior to installing the connector for Event Management to work. For more information, see [Observability Commons for CMDB](#) on the ServiceNow Store.

Note: If you have an earlier version of the Service Graph Connector for Observability - New Relic, then don't migrate data from the old connector. You must uninstall the previous version and run the new integration.

Role required: SGC-Admin (sn_cmdb_int_util.sgc_admin)

Note: The admin user role is required to run background scripts and to provide table-level access to the SGC-Admin user.

Procedure

1. Ensure that the application scope is set to the Service Graph Connector for Observability - New Relic application by using the application picker.
For more information, see [Application picker](#).
2. Navigate to **All > Service Graph Connectors > New Relic > Setup**.
3. On the Getting started page, select **Get Started**.
4. Configure the authentication credentials to send requests to the New Relic application.
 - a. Configure your New Relic connection and credentials.
 - a. In the Configure the Connection section of the New Relic Integration with CMDB page, select **Get Started**.
 - b. For the Configure connection and credentials task, select **Configure**.
 - c. On the Connections page of the Workflow Studio, select **Configure** for the **NewRelicConnectionAlias** connection that is available by default.
 - d. On the form, review and modify the fields.

Configure Connection form

Field	Description
Connection Information	

Field	Description
Connection Name	Name to uniquely identify the connection record. For example, NewRelicConnectionAlias .
Connection URL	Base URL to connect to the New Relic application in the following format: https://api.newrelic.com/graphql Note: This field is automatically set to the URL to connect to the NerdGraph API in the New Relic application. Leave the field value as is.
Credential Information	
API Key	NerdGraph API token used for authentication on the New Relic application.
Account ID	Account ID associated with the New Relic credential.

e. Select **Configure Connection**.

Note: The Service Graph Connector for Observability - New Relic supports connection to a single New Relic instance only. So, you can use the single default connection only.

f. Return to the Configure the connection task page using the back button for your browser.

- Testing the connection might take a few moments. The page is refreshed to show the test results.

New record form

Field	Description
Name	Name of the New Relic configuration. The destination, channel, and workflow strings are appended to the configuration name when the configuration is created.
Connection and Credential Alias	Select the connection alias that you created in step 4.

- e. Select **Submit**.
- f. Set the Configure destination, channel and workflow task to complete by selecting **Mark as Complete**.
- b. Enable alerts for configuration items (CIs) that aren't available in the CMDB.
 - a. In the Configure Observability section of the New Relic Integration with CMDB page, select **Continue**.
 - b. For the Turn on alerts for unmatched CI task, select **Configure**.
 - c. On the System Properties form, select the `sn_newrelic_integ.alerts_for_unmatched_ci.enabled` system property.
 - d. Set the **Value** of the system property to `true`.
 - e. Select **Submit**.
 - f. Set the Turn on alerts for unmatched CI task to complete by selecting **Mark as Complete**.
6. Configure the scheduled jobs to import data from the New Relic application.

- a. In the Set up scheduled data imports section of the New Relic Integration with CMDB page, select **Get started**.
- b. For the Configure Scheduled Data Imports task, select **Configure**.
- c. Select the scheduled job that you want to activate.
- d. On the Scheduled Data Import form, verify the field values for the scheduled job.
For more information, see [Schedule a data import](#).
- e. Select the **Active** check box to activate the scheduled job.
- f. Select **Update**.
- g. Repeat steps [6.c](#) to [6.f](#) for each scheduled job for data import.
- h. Navigate back to the guided setup page.
- i. Set the Configure Scheduled Data Imports task to complete by selecting **Mark as Complete**.

CMDB classes targeted in Service Graph Connector for Observability - New Relic

When you complete setting up the connection, you can configure the integration to periodically pull data from New Relic. The data is saved in tables that extend from the Configuration item [cmdb_ci] table.

Server [cmdb_ci_server]

The following attributes in the Server [cmdb_ci_server] table are populated by collected data:

Attribute label	Attribute name
CPU core count	cpu_core_count
Disk space (GB)	disk_space
DNS Domain	dns_domain
Fully qualified domain name	fqdn

Attribute label	Attribute name
Host name	host_name
Operating System	os

Relationships created for Server

Parent class	Relationship type	Child class
Server [cmdb_ci_server]	Contains::Contained by	Disk [cmdb_ci_disk]
Server [cmdb_ci_server]	Owens::Owned by	IP Address [cmdb_ci_ip_address]
Server [cmdb_ci_server]	Owens::Owned by	Network Adapter [cmdb_ci_network_adapter]

Calculated Application Service [cmdb_ci_service_calculated]

The following attributes in the Calculated Application Service [cmdb_ci_service_calculated] table are populated by collected data:

Attribute label	Attribute name
Name	name
Metadata	metadata
Service Populator Status	populator_status
Service Type	type

IP Address [cmdb_ci_ip_address]

The following attributes in the IP Address [cmdb_ci_ip_address] table are populated by collected data:

Attribute label	Attribute name
IP Address	ip_address
IP version	ip_version
Name	name
Nic	nic

Relationship created for IP Address

Parent class	Relationship type	Child class
IP Address [cmdb_ci_ip_address]	Reference	Network Adapter [cmdb_ci_network_adapter]

Software Instance [cmdb_software_instance]

The following attributes in the Software Instance [cmdb_software_instance] table are populated by collected data:

Attribute label	Attribute name
Installed on	installed_on
Name	name

Relationship created for Software Instance

Parent class	Relationship type	Child class
Software Instance [cmdb_software_instance]	Reference	Server [cmdb_ci_server]

Software [cmdb_ci_spkg]

The following attributes in the Software [cmdb_ci_spkg] table are populated by collected data:

Attribute label	Attribute name
Key	key
Nic	nic
Name	name

Relationship created for Software

Parent class	Relationship type	Child class
Software [cmdb_ci_spkg]	Reference	Software Instance [cmdb_software_instance]

Disk [cmdb_ci_disk]

The following attributes in the Disk [cmdb_ci_disk] table are populated by collected data:

Attribute label	Attribute name
Device ID	device_id
Free disk space (GB)	free_space
Computer	computer
Name	name
Disk space (GB)	disk_space
File system	file_system

Relationship created for Disk

Parent class	Relationship type	Child class
Disk [cmdb_ci_disk]	Hosted on::Hosts	Server [cmdb_ci_server]

Network Adapter [cmdb_ci_network_adapter]

The following attributes in the Network Adapter [cmdb_ci_network_adapter] table are populated by collected data:

Attribute label	Attribute name
Configuration Item	cmdb_ci
MAC Address	mac_address
Name	name

Relationship created for Network Adapter

Parent class	Relationship type	Child class
Network Adapter [cmdb_ci_network_adapter]	Reference	Server [cmdb_ci_server]

Application [cmdb_ci_appl]

The following attributes in the Application [cmdb_ci_appl] table are populated by collected data:

Attribute label	Attribute name
Class	sys_class_name
Name	name
Running process command	running_process_command

Relationship created for Application

Parent class	Relationship type	Child class
Application [cmdb_ci_appl]	Runs on::Runs	Server [cmdb_ci_server]

Accessing the connection details of Service Graph Connector for Observability - New Relic

You can access the connection details of the Service Graph Connector for Observability - New Relic in a single view using the common connection framework (CCF) included within the Integration Commons for CMDB (sn_cmdb_int_util) store app.

With the CCF, you can access all the connections used by the Service Graph Connector for Observability - New Relic. The connection details include the connection alias, connection properties, data sources, and scheduled data imports associated with a connection. You can also test the connection. For more information, see [Accessing the connection details of Service Graph Connectors](#).

Access the details of a Service Graph Connector for Observability - New Relic connection

Access the details of a New Relic connection configured for the Service Graph Connector for Observability - New Relic.

Before you begin

Role required: admin

Procedure

1. Navigate to **All > Service Graph Connectors > New Relic > Connections**.
2. From the **Name** column of the Service Graph Connections list, select a connection.
3. On the Service Graph Connections page, view the connection details such as the connection name, alias, and data sources.
4. Select a related list to view further details of the connection.
5. (Optional) Select the **Test Connection** related link to test the connection.