

Zurich ServiceNow AI Platform Capabilities

Last updated: January 16, 2026

Some examples and graphics depicted herein are provided for illustration only. No real association or connection to ServiceNow products or services is intended or should be inferred.

This PDF was created from content on docs.servicenow.com. The web site is updated frequently. For the most current ServiceNow product documentation, go to docs.servicenow.com.

Company Headquarters

2225 Lawson Lane
Santa Clara, CA 95054
United States
(408)501-8550

Service Graph Connector for OpenTelemetry

Use the Service Graph Connector for OpenTelemetry to ingest Configuration Management Database (CMDB) data from the ServiceNow Cloud Observability (formerly Lightstep) application using REST APIs. Push events from the Cloud Observability application into ServiceNow with Event Management.

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Supported ServiceNow versions

- Utah
- Vancouver
- Washington DC

Use cases

The following examples describe how you can use the Service Graph Connector for OpenTelemetry:

- Import project topologies from Cloud Observability so that the site reliability engineering (SRE) teams can have a single view for triage with other ServiceNow data points (such as a change request, an incident) from a single view.
- Import events created by Cloud Observability against monitored projects to pinpoint SRE triage activities.

Guided setup

The guided setup for the Service Graph Connector for OpenTelemetry provides an organized sequence of tasks to configure the integration on your instance. To access the guided setup, see [Configure Service Graph Connector for OpenTelemetry](#).

CMDB integrations dashboard

The Integration Commons for CMDB store app provides a dashboard with a central view of the status, processing results, and processing errors of all installed integrations. You can see metrics for all integration runs. You can filter the view to a specific CMDB integration, a specific time duration, or a specific integration run. For more details about monitoring Cloud Observability integrations in the CMDB Integrations Dashboard, see [Using the CMDB Integrations Dashboard](#).

Data mapping

Data from the Cloud Observability data sources is mapped and transformed into the ServiceNow CMDB configuration item (CI) class definitions using the Robust Transform Engine (RTE). Data is inserted into the ServiceNow CMDB using the Identification and Reconciliation Engine (IRE).

When you complete setting up the connection, you can configure the integration to pull data from the application periodically.

The following table describes the data sources, the scheduled jobs, the staging tables, and the target tables as CMDB CI classes for the Cloud Observability application.

Data mapping for Cloud Observability

Data source	Description	Scheduled job	Staging table	CMDB CI classes
OpenTelemetry Resources	Imports all the Kubernetes clusters, workloads, and application services from the OpenTelemetry traces.	OpenTelemetry Resources OpenTelemetry Delta Resources	OpenTelemetry Resources [sn_sg_lightstep_resource]	Calculated Application Service Kubernetes Cluster Kubernetes Deployment Kubernetes Node

Data source	Description	Scheduled job	Staging table	CMDB CI classes
				Kubernetes Pod Kubernetes StatefulSet Kubernetes ReplicaSet Kubernetes DaemonSet Kubernetes Job Kubernetes Cronjob Kubernetes Namespace Server Key Value
OpenTelemetry Pods	Imports all the Kubernetes pods from the containers.	OpenTelemetry Pods OpenTelemetry Delta Pods	OpenTelemetry K8s Pods [sn_sg_lightstep_pods]	Kubernetes Cluster Kubernetes Pod
OpenTelemetry Containers	Imports all the containers from the OpenTelemetry traces.	OpenTelemetry Containers	OpenTelemetry docker containers [sn_sg_lightstep_containers]	Docker Container

Data source	Description	Scheduled job	Staging table	CMDB CI classes
		OpenTelemetry Delta Containers		
OpenTelemetry Container Images	Imports all the container images from the OpenTelemetry traces.	OpenTelemetry Container Images OpenTelemetry Delta Container Images	Opentelemetry container images [sn_sg_lightstep_container_images]	Docker Image
OpenTelemetry Services	Imports all the Kubernetes services from the OpenTelemetry traces.	OpenTelemetry Delta Services OpenTelemetry Services	OpenTelemetry K8s Services [sn_sg_lightstep_kubernetes_services]	Kubernetes Service
OpenTelemetry Dependency Map	Imports the dependency maps to get an aggregate view of the traced data. The data source also imports and loads any inferred services and their related services data in the Inferred	OpenTelemetry Dependency Map	OpenTelemetry Dependency Map [sn_sg_lightstep_dependency_map]	Calculated Application Service

Data source	Description	Scheduled job	Staging table	CMDB CI classes
	service [sn_sg_lightstep_inferred_service] staging table. Note: You need to link the imported inferred services with a CI manually. See Inferred service linking.			

For more information on where data is saved when pulling data from Cloud Observability, see [CMDB classes targeted in Service Graph Connector for OpenTelemetry](#).

You can use the IntegrationHub ETL app to view the data maps. See [IntegrationHub ETL](#) for more information.

Inferred service linking

The ServiceNow Cloud Observability application can infer the presence of an inferred service when the span calling the remote service has the necessary information. Service Graph Connector for OpenTelemetry provides the linking of inferred services and their related services with CIs in the CMDB. For more information, see [Linking inferred services with CIs](#).

Related concepts

- [Service Graph Connectors](#)

Configure Service Graph Connector for OpenTelemetry

Set up scheduled import jobs to pull in data from ServiceNow Cloud Observability (formerly Lightstep) into your Configuration Management Database (CMDB).

Before you begin

To use this Service Graph Connector, you need a subscription to a Subscription Unit that is based in the IT Operations Management (ITOM) Visibility application or in the ITOM Discovery application. As defined in the section titled "Managed IT Resource Types" in [ServiceNow Subscription Unit Overview](#) for your subscription, for managed IT resources that are created or modified in the CMDB by this Service Graph Connector, but that aren't yet managed by [ITOM Visibility](#) or [ITOM Discovery](#), these resources will increase Subscription Unit consumption from that application. Review your current Subscription Unit consumption within ITOM Visibility or ITOM Discovery to ensure available capacity.

Dependencies and requirements:

- The [Integration Commons for CMDB](#) store app, which is automatically installed.
- The CMDB CI class models store app, which is automatically installed. See [CMDB CI Class Models](#).
- The ITOM Discovery License plugin (com.snc.itom.discovery.license). You must activate this plugin.
- ITOM Licensing plugin (com.snc.itom.license). For more information, see [Request Discovery](#).
- The Datastream Action plugin (com.glide.hub.action_type.datastream), which is automatically installed.
- Observability Commons for CMDB (sn_observability), which is only required for event ingestion. For Event Management to work, the Observability Commons for CMDB app must be installed prior to

installing the connector. For more information, see [Observability Commons for CMDB](#) on the ServiceNow Store.

Note: If you have an earlier version of the Service Graph Connector for OpenTelemetry, then don't migrate data from the old connector. You must uninstall the previous version and run the new integration.

Role required: SGC-Admin (sn_cmdb_int_util.sgc_admin)

Note: The admin user role is required to run background scripts and to provide table-level access to the SGC-Admin user.

Procedure

1. Ensure that the application scope is set to Service Graph Connector for OpenTelemetry by using the application picker.
For more information, see [Application picker](#).
2. Navigate to **All > Service Graph Connectors > OpenTelemetry > Setup**.
3. On the Getting started page, select **Get Started**.
4. Configure the application properties to set up your organization and authentication credentials for sending requests to the ServiceNow Cloud Observability APIs.
 - a. In the Configure the connection section of the Service Graph Connector for OpenTelemetry page, select **Get started**.
 - b. For the Use OpenTelemetry task, ensure that the Cloud Observability application meets the conditions as discussed in the [ServiceNow Cloud Observability setup \[KB1527588\]](#) article in the Now Support Knowledge Base.

Important: Note down your projects, organization, and API key details of the Cloud Observability application to be used later during the installation of the connector.

After you have set up the OpenTelemetry environment in the Cloud Observability application, return to the guided setup and mark the Use OpenTelemetry task to complete by selecting **Mark as Complete**.

- c. Enter your Cloud Observability organization details from where you want to retrieve the projects, resources, and dependency-mapping information.
 - a. For the Set up your organization task, select **Configure**.
 - b. In the **Value** field of the Service Graph Connection Properties form, enter the name of your Cloud Observability organization.
 - c. Select **Update**.
 - d. Mark the Set up your organization task to complete by selecting **Mark as Complete**.
- d. Enter the API key details associated with the Cloud Observability application.
 - a. For the Set up the API key task, select **Configure**.
 - b. In the **API Key** field of the API Key Credentials form, enter the API key associated with the Cloud Observability application that you noted down in step 4.b.
 - c. Select **Update**.
 - d. Set the Set up the API key task to complete by selecting **Mark as Complete**.
- e. Test the Cloud Observability API connection to import data from the Cloud Observability application.
 - a. For the Test the connection task, select **Configure**.
 - b. Select the **Test Connection** related link.
 - c. When the **Status** field is set to **Success**, select **X** to close the Test the connection dialog box and return to the guided setup page.

If any of the tests have errors, follow the suggestions for remediation.
 - d. Set the Test the connection task to complete by selecting **Mark as Complete**.

- f. Retrieve all the projects included in your Cloud Observability organization.
 - a. For the Get projects task, select **Configure**.
 - b. Select **Get Projects**.
 - c. When the Project properties related list is populated with all the projects included in the organization you specified in step [4.c.ii](#), select **X** to close the Get projects dialog box and return to the guided setup page.
 - d. Set the Get projects task to complete by selecting **Mark as Complete**.
5. (Optional) Configure additional configurations to set up lookback time, add excluded projects, run project diagnostics, and configure integration settings for service maps and stale configuration items (CIs).
 - a. In the Advanced settings section of the Service Graph Connector for OpenTelemetry page, select **Continue**.
 - b. Set up the lookback time from when you want to retrieve resources from the projects.

Lookback time is used to calculate the start and end time for retrieving resources from a project of an organization and should match the scheduled job frequency setting. For example, if the lookback time is set to 12 hours, resources are retrieved from the start time calculated as the current time minus 12 hours and until the end time that is the current time.

- a. For the Set up lookback time task, select **Configure**.
 - b. In the **Value** field of the Service Graph Connection Properties form, enter the lookback time in hours.
 - c. Select **Update**.
 - d. Set the Set up lookback time task to complete by selecting **Mark as Complete**.
- c. Select the projects from which you don't want to retrieve resources.

- a. For the Add excluded projects task, select **Configure**.
 - b. Select a project from the **Project** column.
 - c. Select the **Exclude project** check box.
 - d. Select **Update**.
 - e. Repeat steps from 5.c.ii to 5.c.iv for each project that you want to exclude.
 - f. Select **X** to close the Add excluded projects dialog box and return to the guided setup page.
 - g. Set the Add excluded projects task to complete by selecting **Mark as Complete**.
- d. Run project diagnostics to test the Resource API response and ensure that the API contains the Kubernetes cluster name, Kubernetes namespace, and Kubernetes nodes.
- a. For the Run project diagnostics task, select **Configure**.
 - b. Select a project from the **Project** column.
 - c. Select **Run diagnostics**.
 - d. When the **Diagnostics status** field set to **Success**, select **X** to close the Run project diagnostics dialog box and return to the guided setup page.
- If any of the Diagnostic tests have errors, follow the instructions in the **Diagnostics message** field to resolve the errors.
- e. Repeat the steps 5.d.ii to 5.d.iv for each project that you want to run diagnostics.
 - f. Set the Run project diagnostics task to complete by selecting **Mark as Complete**.
- e. Configure the system properties for service maps and stale CIs.
- a. For the Configure system properties for the connector task, select **Configure**.

- b. Verify the default values for the properties or fill in the values for a custom configuration.
 - c. Select **Save**.
 - d. Set the Configure system properties for the connector task to complete by selecting **Mark as Complete**.
6. Configure the scheduled jobs to import complete or incremental data from the Cloud Observability application.
 - a. In the Configure the scheduled import jobs section of the Service Graph Connector for OpenTelemetry page, select **Continue**.
 - b. Activate the scheduled job for full data import.

By default, the OpenTelemetry Resources scheduled job is available for full data import. However, you must activate the job.

- a. For the Configure the scheduled job for full import task, select **Configure**.
- b. On the Scheduled Data Import form for the OpenTelemetry Resources scheduled job, verify the field values for the scheduled job and select the **Active** check box.

For more information, see [Schedule a data import](#).

- c. Select **Update**.
 - d. Set the Configure the scheduled job for full import task to complete by selecting **Mark as Complete** in the guided setup.
- c. (Optional) Activate the scheduled job for delta data import.

By default, the OpenTelemetry Delta Resources scheduled job is available for delta data import. However, you must activate the job.

Note: The delta data pull doesn't occur in the following scenarios:

- The full data import is scheduled at the same time.
 - The **Last Run Datetime** field of a data source is empty.
 - The last delta data pull period is more than 3 days.
- a. For the Configure the scheduled job for delta import task, select **Configure**.
 - b. On the Scheduled Data Import form for the OpenTelemetry Delta Resources scheduled job, verify the field values for the scheduled job and select the **Active** check box.

For more information, see [Schedule a data import](#).

- c. Select **Update**.
- d. Set the Configure the scheduled job for delta import task to complete by selecting **Mark as Complete** in the guided setup.

Note: When adding a new project to retrieve resources, be sure to perform a full import before running a delta import to avoid partial data and populate the CMDB accurately.

7. Manage alerts and events by sending events from the Cloud Observability application to the ServiceNow Event Management application.

You can manage alerts and events only when the Observability Commons for CMDB application is installed.

Note: Enabling this feature requires a paid Cloud Observability license, but the feature is also available to free accounts for the purpose of evaluating the product in non-production environments. You can reach out to your ServiceNow account representative for more information.

- a. In the Manage alerts and events section of the Service Graph Connector for OpenTelemetry page, select **Continue**.
- b. Create a webhook destination for a project.

- a. For the Create a webhook task, select **Configure**.
- b. Select a project that is not excluded from the **Project** column.
- c. Select **Create Webhook** to create a webhook destination in the Cloud Observability application.
- d. After a success message appears, select **X** to close the Create a webhook dialog box and return to the guided setup page.

When the webhook is created successfully:

- The system automatically creates a user record for each webhook destination in your ServiceNow instance.
 - The user name of the user record starts with `ls_api_<project_name>` and the user is assigned the `evt_mgmt_integration` role.
- e. Repeat the steps 7.b.ii to 7.b.iv for each project for which you want to create a webhook.
 - f. Set the Create a webhook task to complete by selecting **Mark as Complete** in the guided setup.
- c. Configure the system property for ingesting events that don't have matching CIs in the CMDB.
 - a. For the Configure the property for unmatched CIs task, select **Configure**.
 - b. In the **Value** field, enter **true**.
 - c. Select **Update**.
 - d. Set the Configure the property for unmatched CIs task to complete by selecting **Mark as Complete** in the guided setup.

Related concepts

- [Accessing the connection details of Service Graph Connector for OpenTelemetry](#)

Related reference

- [Service Graph Connector for OpenTelemetry properties](#)
- [Linking inferred services with CIs](#)

CMDB classes targeted in Service Graph Connector for OpenTelemetry

When you complete setting up the connection, you can configure the integration to periodically pull data from ServiceNow Cloud Observability (formerly Lightstep). The data is saved in tables that extend from the Configuration item [cmdb_ci] table.

Calculated Application Service [cmdb_ci_service_calculated]

The following attributes in the Calculated Application Service [cmdb_ci_service_calculated] table are populated by collected data:

Attribute label	Attribute name
Service Populator	service_populator
Name	name
Hide from dashboard	hide_from_dashboard
Operational status	operational_status
Service Populator Status	populator_status
Service Type	type

Relationships created for Calculated Application Service

Parent class	Relationship type	Child class
Calculated Application Service [cmdb_ci_service_calculated]	Connects to::Connected by	Kubernetes Deployment [cmdb_ci_kubernetes_deployment]

Parent class	Relationship type	Child class
Calculated Application Service [cmdb_ci_service_calculated]	Connects to::Connected by	Calculated Application Service [cmdb_ci_service_calculated]
Calculated Application Service [cmdb_ci_service_calculated]	Reference	Key Value [cmdb_key_value]

Docker Container [cmdb_ci_docker_container]

The following attributes in the Docker Container [cmdb_ci_docker_container] table are populated by collected data:

Attribute label	Attribute name
Container id	container_id
Install Status	install_status
Name	name

Docker Image [cmdb_ci_docker_image]

The following attributes in the Docker Image [cmdb_ci_docker_image] table are populated by collected data:

Attribute label	Attribute name
Image id	image_id
Install Status	install_status
Name	name

Key Value [cmdb_key_value]

The following attributes in the Key Value [cmdb_key_value] table are populated by collected data:

Attribute label	Attribute name
Key	key
Value	value

Kubernetes Cluster [cmdb_ci_kubernetes_cluster]

The following attributes in the Kubernetes Cluster [cmdb_ci_kubernetes_cluster] table are populated by collected data:

Attribute label	Attribute name
Name	name
Namespace	namespace
Install Status	install_status
Kubernetes UID	k8s_uid

Relationships created for Kubernetes Cluster

Parent class	Relationship type	Child class
Kubernetes Cluster [cmdb_ci_kubernetes_cluster]	Cluster of::Cluster	Kubernetes Node [cmdb_ci_kubernetes_node]
Kubernetes Cluster [cmdb_ci_kubernetes_cluster]	Contains::Contained by	Kubernetes Pod [cmdb_ci_kubernetes_pod]
Kubernetes Cluster [cmdb_ci_kubernetes_cluster]	Contains::Contained by	Kubernetes Namespace [cmdb_ci_kubernetes_namespace]
Kubernetes Cluster [cmdb_ci_kubernetes_cluster]	Contains::Contained by	Kubernetes Service [cmdb_ci_kubernetes_service]

Kubernetes Cronjob [cmdb_ci_kubernetes_cronjob]

The following attributes in the Kubernetes Cronjob [cmdb_ci_kubernetes_cronjob] table are populated by collected data:

Attribute label	Attribute name
Kubernetes Cluster	cluster
Name	name
Namespace	namespace
Install Status	install_status

Relationships created for Kubernetes Cronjob

Parent class	Relationship type	Child class
Kubernetes Cronjob [cmdb_ci_kubernetes_cronjob]	Hosted on::Hosts	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]
Kubernetes Cronjob [cmdb_ci_kubernetes_cronjob]	Reference	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]

Kubernetes DaemonSet [cmdb_ci_kubernetes_daemonset]

The following attributes in the Kubernetes DaemonSet [cmdb_ci_kubernetes_daemonset] table are populated by collected data:

Attribute label	Attribute name
Kubernetes Cluster	cluster
Name	name
Namespace	namespace
Install Status	install_status

Relationships created for Kubernetes DaemonSet

Parent class	Relationship type	Child class
Kubernetes DaemonSet [cmdb_ci_kubernetes_daemonset]	Hosted on::Hosts	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]
Kubernetes DaemonSet [cmdb_ci_kubernetes_daemonset]	Reference	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]

Kubernetes Deployment [cmdb_ci_kubernetes_deployment]

The following attributes in the Kubernetes Deployment [cmdb_ci_kubernetes_deployment] table are populated by collected data:

Attribute label	Attribute name
Kubernetes Cluster	cluster
Name	name
Namespace	namespace
Install Status	install_status

Relationships created for Kubernetes Deployment

Parent class	Relationship type	Child class
Kubernetes Deployment [cmdb_ci_kubernetes_deployment]	Hosted on::Hosts	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]
Kubernetes Deployment	Connects to::Connected by	Kubernetes Node [cmdb_ci_kubernetes_node]

Parent class	Relationship type	Child class
[cmdb_ci_kubernetes_deployment]		
Kubernetes Deployment [cmdb_ci_kubernetes_deployment]	Connects to::Connected by	Kubernetes ReplicaSet [cmdb_ci_kubernetes_replicaset]
Kubernetes Deployment [cmdb_ci_kubernetes_deployment]	Reference	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]

Kubernetes Job [cmdb_ci_kubernetes_job]

The following attributes in the Kubernetes Job [cmdb_ci_kubernetes_job] table are populated by collected data:

Attribute label	Attribute name
Kubernetes Cluster	cluster
Kubernetes UID	k8s_uid
Name	name
Namespace	namespace
Install Status	install_status

Relationships created for Kubernetes Job

Parent class	Relationship type	Child class
Kubernetes Job [cmdb_ci_kubernetes_job]	Hosted on::Hosts	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]

Parent class	Relationship type	Child class
Kubernetes Job [cmdb_ci_kubernetes_job]	Reference	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]

Kubernetes Namespace [cmdb_ci_kubernetes_namespace]

The following attributes in the Kubernetes Namespace [cmdb_ci_kubernetes_namespace] table are populated by collected data:

Attribute label	Attribute name
Kubernetes Cluster	cluster
Name	name
Install Status	install_status

Relationship created for Kubernetes Namespace

Parent class	Relationship type	Child class
Kubernetes Namespace [cmdb_ci_kubernetes_namespace]	Reference	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]

Kubernetes Node [cmdb_ci_kubernetes_node]

The following attributes in the Kubernetes Node [cmdb_ci_kubernetes_node] table are populated by collected data:

Attribute label	Attribute name
Kubernetes UID	k8s_uid
Name	name
Install Status	install_status

Attribute label	Attribute name
Namespace	namespace
Kubernetes Cluster	cluster

Relationships created for Kubernetes Node

Parent class	Relationship type	Child class
Kubernetes Node [cmdb_ci_kubernetes_node]	Hosted on::Hosts	Server [cmdb_ci_server]
Kubernetes Node [cmdb_ci_kubernetes_node]	Reference	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]

Kubernetes Pod [cmdb_ci_kubernetes_pod]

The following attributes in the Kubernetes Pod [cmdb_ci_kubernetes_pod] table are populated by collected data:

Attribute label	Attribute name
Name	name
Install Status	install_status
Kubernetes Cluster	cluster
Kubernetes UID	k8s_uid
Namespace	namespace
IP Address	ip_address
Start date	start_date

Relationships created for Kubernetes Pod

Parent class	Relationship type	Child class
Kubernetes Pod [cmdb_ci_kubernetes_pod]	Contains::Contained by	Docker Image [cmdb_ci_docker_image]
Kubernetes Pod [cmdb_ci_kubernetes_pod]	Contains::Contained by	Docker Container [cmdb_ci_docker_container]
Kubernetes Pod [cmdb_ci_kubernetes_pod]	Reference	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]

Kubernetes ReplicaSet [cmdb_ci_kubernetes_replicaset]

The following attributes in the Kubernetes ReplicaSet [cmdb_ci_kubernetes_replicaset] table are populated by collected data:

Attribute label	Attribute name
Kubernetes UID	k8s_uid
Name	name
Namespace	namespace
Install Status	install_status
Kubernetes Cluster	cluster

Relationships created for Kubernetes ReplicaSet

Parent class	Relationship type	Child class
Kubernetes ReplicaSet [cmdb_ci_kubernetes_replicaset]	Hosted on::Hosts	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]

Parent class	Relationship type	Child class
Kubernetes ReplicaSet [cmdb_ci_kubernetes_replicaset]	Connects to::Connected by	Kubernetes Node [cmdb_ci_kubernetes_node]
Kubernetes ReplicaSet [cmdb_ci_kubernetes_replicaset]	Reference	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]

Kubernetes Service [cmdb_ci_kubernetes_service]

The following attributes in the Kubernetes Service [cmdb_ci_kubernetes_service] table are populated by collected data:

Attribute label	Attribute name
Name	name
Namespace	namespace
Install Status	install_status

Kubernetes StatefulSet [cmdb_ci_kubernetes_statefulset]

The following attributes in the Kubernetes StatefulSet [cmdb_ci_kubernetes_statefulset] table are populated by collected data:

Attribute label	Attribute name
Name	name
Kubernetes Cluster	cluster
Namespace	namespace
Install Status	install_status

Relationship created for Kubernetes StatefulSet

Parent class	Relationship type	Child class
Kubernetes StatefulSet [cmdb_ci_kubernetes_statefulset]	Hosted on::Hosts	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]
Kubernetes StatefulSet [cmdb_ci_kubernetes_statefulset]	Reference	Kubernetes Cluster [cmdb_ci_kubernetes_cluster]

Server [cmdb_ci_server]

The following attribute in the Server [cmdb_ci_server] table is populated by collected data:

Attribute label	Attribute name
Name	name

Related concepts

- [Kubernetes extension classes](#)
- [CI relationships in the CMDB](#)

Service Graph Connector for OpenTelemetry properties

Service Graph Connector for OpenTelemetry properties control the behavior of the connector.

Connection properties

These connection properties are available for Service Graph Connector for OpenTelemetry.

Note: To open the Service Graph Connection Properties [sn_cmdb_int_util_service_graph_connection_property] table for the connector, navigate to **All > Service Graph Connectors > OpenTelemetry > Connections** and select the connection name. The connection properties are displayed in the Service Graph Connection Properties related list.

Connection properties for Service Graph Connector for OpenTelemetry

Property	Description
Organization	Enter the name of an OpenTelemetry organization. - Type: string - Default value: None - Location: Service Graph Connection Properties [sn_cmdb_int_util_service_graph_connection_property] table
Lookback Time	Enter time in hours to retrieve OpenTelemetry resources. - Type: integer - Default value: 12 - Location: Service Graph Connection Properties [sn_cmdb_int_util_service_graph_connection_property] table

System properties

These system properties are available for Service Graph Connector for OpenTelemetry.

Note: To open the System Properties [sys_properties] table, enter `sys_properties.list` in the navigation filter.

System properties for Service Graph Connector for OpenTelemetry

Property	Description
<code>sn_sg_lightstep.classes_to_inactivate_stale_records</code>	Enter a list of configuration item (CI) classes to be inactivated as stale records. For multiple entries, separate the CI classes with commas. - Type: string - Default value: None - Location: System Property [sys_properties] table
<code>sn_sg_lightstep.events_for_unmatched_ci.enabled</code>	Set the property to <code>true</code> to ingest events that don't have a matching CI in CMDB. - Type: true false - Default value: false - Location: System Property [sys_properties] table
<code>sn_sg_lightstep.resource_api_num_rows</code>	Enter the maximum number of rows fetched in the Resource API response from OpenTelemetry resources. - Type: integer - Default value: 2500

Property	Description
	Location: System Property [sys_properties] table
sn_sg_lightstep.service_map_classes_to_exclude	Enter a list of CI classes to be excluded from the service map. For multiple entries, separate the CI classes with commas. - Type: string - Default value: None - Location: System Property [sys_properties] table
sn_sg_lightstep.service_map_max_levels	Enter the maximum hierarchy level of CIs to be included in the service map. - Type: integer - Default value: 5 - Location: System Property [sys_properties] table
sn_sg_lightstep.service_map_relationship_types_to_exclude	Enter a list of CI relationship types to be excluded from the service map. For multiple entries, separate the CI relationship types with commas. - Type: string - Default value: None - Location: System Property [sys_properties] table

Linking inferred services with CIs

Create inferred services relationships in your ServiceNow instance with other Cloud Observability application services as originally configured in the application by linking an inferred service configuration item (CI) in CMDB with an inferred service from the Cloud Observability application.

Inferred services

The inferred services in the Cloud Observability application are referred to as external services, libraries, or dependencies such as a database or a third-party API that haven't been instrumented with OpenTelemetry. These types of technologies are manually defined in the Cloud Observability application, and you can import them into your ServiceNow instance through the Service Graph Connector for OpenTelemetry.

For information about adding inferred services in the Cloud Observability application, see [Add inferred services](#) in the Cloud Observability documentation.

Storing inferred services data

The OpenTelemetry Dependency Map [sn_sg_lightstep_dependency_map] data source available with the Service Graph Connector for OpenTelemetry iterates through all the included projects in a Cloud Observability organization and pulls in the inferred services details. Inferred services details include mapping of related services. The data source saves these details in the Inferred service [sn_sg_lightstep_inferred_service] table.

The following attributes in the Inferred service [sn_sg_lightstep_inferred_service] table are populated by the OpenTelemetry Dependency Map [sn_sg_lightstep_dependency_map] data source.

Attribute label	Attribute name
Project	project
Organization	organization
ID	id

Attribute label	Attribute name
Inferred service	inferred_service
Inferred service CI	inferred_service_ci
Active	active
Last scan	last_scan
Cloud Observability CI	cloud_observability_ci

Due to insufficient information for defining identification rules, the pulled in inferred services don't automatically bind to a CI in CMDB. However, as a user with the `cmdb_inst_admin` role, you can manually link a CI to an inferred service. The linking creates appropriate relationships with the related services and generates the inferred service mapping in the respective application service maps of your ServiceNow instance.

Link an inferred service

Link a Cloud Observability inferred service with a CI to create relationships between the inferred service and other Cloud Observability services in your ServiceNow instance.

Before you begin

Role required: `cmdb_inst_admin`

Procedure

1. Navigate to **All > Service Graph Connectors > OpenTelemetry > Inferred services**.
2. Review the inferred services available from the Cloud Observability app in the **Inferred service** column.
3. For an inferred service, double-click the **Inferred service CI** column cell.

4. Select the lookup using list icon () to search for and select an inferred service CI available within the Configuration item [cmdb_ci] table.
5. Select the save icon ().
6. Repeat the steps 3 to 5 for each inferred service that you want to link with a CI.

Result

The Update CI relationship business rule is triggered that creates appropriate relationships for the inferred service with the related services and generates the inferred service mapping in the respective application service maps.

Note:

- If you remove any mapping later, the Delete CI relationship business rule is triggered to delete any relationships between the inferred service CIs and the Cloud Observability inferred services.
- For any inferred services that were not last scanned in the Cloud Observability app, the Service Graph Connector automatically deactivates the corresponding records in CMDB and deletes the relationship for the inactive records.

Accessing the connection details of Service Graph Connector for OpenTelemetry

You can access the connection details of the Service Graph Connector for OpenTelemetry in a single view using the common connection framework (CCF) included within the Integration Commons for CMDB (sn_cmdb_int_util) store app.

With the CCF, you can access all the connections used by the Service Graph Connector for OpenTelemetry. The connection details include the connection alias, connection properties, data sources, and scheduled data imports associated with a connection. You can also test the connection.

Access the details of an OpenTelemetry connection

Access the details of an OpenTelemetry connection configured for the Service Graph Connector for OpenTelemetry.

Before you begin

Role required: admin

Procedure

1. Navigate to **All > Service Graph Connectors > OpenTelemetry > Connections**.
2. From the **Name** column of the Service Graph Connections list, select a connection.
3. On the Service Graph Connections page, view the connection details such as the connection name, alias, and data sources.
4. Select a related list to view further details of the connection.
5. (Optional) Select the **Test Connection** related link to test the connection.

Related concepts

- [Accessing the connection details of Service Graph Connectors](#)

Related reference

- [Service Graph Connector for OpenTelemetry properties](#)