

Zurich ServiceNow AI Platform Capabilities

Last updated: January 16, 2026

Some examples and graphics depicted herein are provided for illustration only. No real association or connection to ServiceNow products or services is intended or should be inferred.

This PDF was created from content on docs.servicenow.com. The web site is updated frequently. For the most current ServiceNow product documentation, go to docs.servicenow.com.

Company Headquarters

2225 Lawson Lane
Santa Clara, CA 95054
United States
(408)501-8550

Service Graph Connector for Rapid7

The Service Graph Connector for Rapid7 pulls in asset inventory data (hardware and software) from the Rapid7 database into the Configuration Management Database (CMDB) application in your ServiceNow AI Platform® instance.

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Supported versions

- Version 4.0 of the Rapid7 InsightVM application.
- Utah, Vancouver, and Washington ServiceNow® family releases.

Use cases

- Complement the data from the Rapid7 InsightVM discovery product.
- Import hardware data and details about your assets from the Rapid7 InsightVM integration and store them in appropriate configuration item (CI) classes in your CMDB.

CMDB integrations dashboard

The Integration Commons for CMDB store app provides a dashboard with a central view of the status, processing results, and processing errors of all installed integrations. You can see metrics for all integration runs. You can filter the view to a specific CMDB integration, a specific time duration, or a specific integration run. For more details about monitoring Rapid7 integrations in the CMDB Integrations Dashboard, see [Using the CMDB Integrations Dashboard](#).

Guided setup

Use the guided setup feature for the Service Graph Connector for Rapid7 to help you configure your integration in an organized sequence of tasks.

Note: The API token requires the InsightIDR viewer role.

Configure the Service Graph Connector for Rapid7

After you have followed the instructions provided to you to download and activate the Service Graph Connector for Rapid7 application, refer to [Download an application from the ServiceNow Store for the first time](#) and [Install a Security Operations integration](#). There are a few steps you need to complete before you configure this integration.

Configure the Service Graph Connector for Rapid7

Configure your connections, set up scheduled imports, verify successful connections and optionally add multiple instances in the Guided Setup.

Before you begin

To use this Service Graph Connector, you need a subscription to a Subscription Unit that is based in the IT Operations Management (ITOM) Visibility application or in the ITOM Discovery application. As defined in the section titled "Managed IT Resource Types" in [ServiceNow Subscription Unit Overview](#) for your subscription, for managed IT resources that are created or modified in the CMDB by this Service Graph Connector, but that aren't yet managed by [ITOM Visibility](#) or [ITOM Discovery](#), these resources will increase Subscription Unit consumption from that application. Review your current Subscription Unit consumption within ITOM Visibility or ITOM Discovery to ensure available capacity.

- The [Integration Commons for CMDB](#) store app, which is automatically installed.
- The CMDB CI class models store app, which is automatically installed. See [CMDB CI Class Models](#).
- The ITOM Discovery License plugin (com.snc.itom.discovery.license). You must activate this plugin.
- ITOM Licensing plugin (com.snc.itom.license). For more information, see [Request Discovery](#).
- The Datastream Action plugin (com.glide.hub.action_type.datastream), which is automatically installed.

- Observability Commons for CMDB (sn_observability), which is only required for event ingestion. This app must be installed prior to installing the connector for Event Management to work. For more information, see [Observability Commons for CMDB](#) on the ServiceNow Store.

Roles required:

- admin for tasks in the Guided Setup
- insightIDR viewer role for the API token

Procedure

1. Navigate to **All > Service Graph Connectors > Rapid7 > Setup** in the navigation panel in your instance.
2. On the Welcome to Guided Setup Home page, select **Continue**.
3. On the Experience page that is displayed, select **Best Experience** followed by **Continue**.
On the Service Graph Connector for Rapid7 page, there are three tasks displayed:
 - Configure the connection
 - Add multiple instances
 - Set up scheduled imports
4. Select **Configure the connection** to expand it.
There are three steps:
 - Configure Rapid7 authentication credentials
 - Configure Rapid7 HTTP Connection
 - Test Connection
5. Select **Configure Rapid7 authentication credentials** and fill in the fields.
 - a. Enter a name for the credentials, for example **SGRapid7.Credential**.
 - b. Verify the **Active** check box is selected.

- c. In the API Key field, enter your Rapid7 InsightVM API key.
 - d. Leave the other field values in their current settings.
 - e. Right-click in the gray header titled API Key Credentials and select **Save**.
 - f. Select **Mark as complete** followed by **Continue**.
The Configure Rapid7 HTTP Connection page is displayed.
6. Configure Rapid7 HTTP Connection.
- a. Fill in the fields,

Field	Value
Name	Connection name, sGRapid7, for example.
Active	Selected.
Credential	Credentials to use for the connection. Select one from the list.
Connection alias	Select one from the list. sn_sec_sgc_rapid7.SGRapid7 , for example
URL builder	Select the check box. Fill in the new fields.
Connection URL	URL that includes 'https', for example, https://us.api.insight.rapid7.com
Host	Rapid7 domain part of the URL without the 'https'. An example might be us.api.insight.rapid7.com .
Protocol	https

- b. Right-click in the gray header titled HTTP(s) Connection and select **Save**.
 - c. Select **Mark as complete** followed by **Continue**.
The Test Connection page is displayed.
 7. Test the connection.
 - a. Select the **Test Connection** link under Related Links.
If the connection is successful, 200 is displayed in the Status Code field and a message is displayed. If your connection test fails, review the Message and Suggestion fields for how to proceed.
 - b. Right-click in the gray header titled Service Graph Connections and select **Save**.
 - c. Select **Mark as complete** followed by **Continue**.
The steps for Add Multiple Instances is displayed. This step is optional and you might prefer to wait after you confirm you can import data before setting up multiple instances.
 8. To configure the scheduled job, navigate back to the Guided Setup page and select **Set up scheduled import jobs**.
 - a. Follow the steps listed at the top of the page to switch the application scope with the application picker to open, edit, and save the record.
You must select the Active check box to activate the scheduled job.
 - b. Select a record.
 - c. Fill in the fields.

Field	Value
Name	Unique Name for scheduled job.
Application	Read-only: Service Graph Connector for Rapid7.
Data source	Data source used.

Field	Value
Run	How often you want the job to run. If you want to run a test import prior to scheduling it, you might prefer to select Once .
Run as	Run the scheduled job with the credentials of another specified user.
Time	When you want the job to run.
Active	Select the check box to activate the job.
Conditional	Specific conditions under which this job is run.
Use connection	Leave this check box deactivated for the first run. Specifies another connection and credentials for this job.
Concurrent import	Leave check box activated. Splits data into multiple imports sets. See the field message for more information.
Partition Method	Leave as Custom size.
Partition size	15,000. Leave this value for the import set size for early scheduling.
Execute pre-import script	Leave check box activated. Specifies a script to run before the import is performed.

Field	Value
Execute post-import script	Leave check box activated. Specifies a script to run after the import is performed.

- d. (Optional) Select **Execute now** to run the job.
If you do not choose to run the job on-demand, the next job runs according to the schedule you set.
 - e. Right-click in the gray header titled Scheduled Data Imports and select **Save**.
 - f. Select **Mark as complete** followed by **Continue**.
9. (Optional) Return to Guided setup and add multiple instances.
When indicated, follow the steps listed at the top of the page to switch the application scope with the application picker to open, edit, and save the record.
10. Select **Update Data Sources**.
- a. On the Update Data Source Access page, select **Data Source**.
 - b. On the page that is displayed, select the **Application Access** tab.
 - c. Review the access settings and update as needed.
 - d. Right-click in the gray header titled Table and select **Save**.
 - e. Select **Mark as complete** followed by **Continue**.
 - f. Select Schedule **Update Schedule Data Import**.
 - g. Select the **Application Access** tab to view the permission settings.
 - h. When you are satisfied with the settings, right-click in the gray header titled Tables and select **Save**.
 - i. Select **Mark as complete** followed by **Continue**.
 - j. Follow the steps listed at the top of the page to switch the application scope with the application picker to open, edit, and save the record.

- k. On the Add Another Connection page, select the **Click here** link. The Workflow Studio connection page is displayed and you can create a new connection.
- l. From this page, select **Add Connection**.
- m. Fill in the fields with your connection information.

Field	Description
Rapid7 Connection name	Unique name for your connection.
Rapid7 Connection URL	Connection URL.
API Key	Rapid7 API key.

- n. Select **Create Connection**.
Your connections are displayed on the Rapid7 page.
- o. Select **Mark as complete** followed by **Continue**.
The Test New Connections page is displayed. Locate your new connection and note the status is 'Pending'.
- p. Scroll and select the **Test Connection** link.
If the connection is successful, 200 is displayed in the Status Code field and a message is displayed. If your connection test fails, review the Message and Suggestion fields for how to proceed.
- q. Right-click in the gray header titled Service Graph Connections and select **Save**.
- r. Select **Mark as complete** followed by **Continue**.
The Configure the scheduled jobs page is displayed.
- s. Repeat the steps listed previously in step 8.
- t. On the Service Graph Connector for Rapid7 page for Guided Setup, select **Complete** to finish the configuration.

CMDB classes targeted in the Service Graph Connector for Rapid7

When you complete setting up the connection, you can configure the integration to periodically pull data. The data is saved in tables that extend from the Configuration item [cmdb_ci] table.

Hardware [cmdb_ci_hardware]

The following attributes in the Hardware [cmdb_ci_hardware] table are populated by collected data.

Attribute label	Attribute name
Name	name
Correlation ID	correlation_id
MAC Address	mac_address
Install Status	install_status
Operational Status	operational_status

IP Address [cmdb_ci_ip_address]

The following attributes in the IP Address [cmdb_ci_ip_address] table are populated by collected data.

Attribute label	Attribute name
Name	name
IP Address	ip_address
Owned By Configuration Item	owned_by_cmdb_ci

SGC Rapid7 Asset [sn_sec_sgc_rapid7_sgc_rapid7_asset]

The following attributes in the SGC Rapid7 Asset [sn_sec_sgc_rapid7_sgc_rapid7_asset] table are populated by collected data.

Attribute label	Attribute name
Assessed for policies	assessed_for_policies
Assessed for vulnerabilities	assessed_for_vulnerabilities
Configuration item	configuration_item
Credential assessments	credential_assessments
Critical vulnerabilities	critical_vulnerabilities
Exploits	exploits
Last assessed for vulnerabilities	last_assessed_for_vulnerabilities
Last scan end	last_scan_end
Last scan start	last_scan_start
Malware kits	malware_kits
Moderate vulnerabilities	moderate_vulnerabilities
New	new
OS architecture	os_architecture
OS description	os_description
OS family	os_family
OS name	os_name
OS system name	os_system_name

Attribute label	Attribute name
OS type	os_type
OS vendor	os_vendor
OS version	os_version
Remediated	remediated
Risk score	risk_score
Same	same
Severe vulnerabilities	severe_vulnerabilities
Tags	tags
Total vulnerabilities	total_vulnerabilities
Type	type
Unique identifiers	unique_identifiers
Configuration item	configuration_item

Relationships created for Hardware

Parent class	Relationship type	Child class
Hardware [cmdb_ci_hardware]	Owns::Owned by	IP Address [cmdb_ci_ip_address]
Hardware [cmdb_ci_hardware]	Reference	SGC Rapid7 Asset [sn_sec_sgc_rapid7_sg c_rapid7_asset]

Relationships created for IP Address

Parent class	Relationship type	Child class
IP Address [cmdb_ci_ip_address]	Reference	Hardware [cmdb_ci_hardware]

Relationships created by SGC Rapid7 Asset

Parent class	Relationship type	Child class
SGC Rapid7 Asset [sn_sec_sgc_rapid7_sg c_rapid7_asset]	Reference	Hardware [cmdb_ci_hardware]