

Zurich ServiceNow AI Platform Capabilities

Last updated: January 16, 2026

Some examples and graphics depicted herein are provided for illustration only. No real association or connection to ServiceNow products or services is intended or should be inferred.

This PDF was created from content on docs.servicenow.com. The web site is updated frequently. For the most current ServiceNow product documentation, go to docs.servicenow.com.

Company Headquarters

2225 Lawson Lane
Santa Clara, CA 95054
United States
(408)501-8550

Service Graph Connector for SentinelOne

The Service Graph Connector for SentinelOne pulls in asset inventory data (hardware and software) from the SentinelOne database into the Configuration Management Database (CMDB) application in your ServiceNow AI Platform® instance.

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Supported Versions

- Supported SentinelOne API versions: Get Agents- V2.1
- Supported ServiceNow AI Platform® versions:
 - Xanadu
 - Washington
 - Vancouver

Use cases

- Import SentinelOne agent information and store it in appropriate configuration item (CI) classes in your CMDB.
- Configure multiple instances of SentinelOne in the Service Graph Connector.

Guided setup

Use the guided setup feature to help you configure your integration in an organized sequence of tasks.

CMDB integrations dashboard

The Integration Commons for CMDB store app provides a dashboard with a central view of the status, processing results, and processing errors of all

installed integrations. You can see metrics for all integration runs. You can filter the view to a specific CMDB integration, a specific time duration, or a specific integration run. For more details about monitoring SentinelOne integrations in the CMDB Integrations Dashboard, see [Using the CMDB Integrations Dashboard](#).

Configure the Service Graph Connector for SentinelOne

The guided setup for the Service Graph Connector for SentinelOne provides an organized sequence of tasks to configure the integration on your ServiceNow AI Platform instance.

Before you begin

To use this Service Graph Connector, you need a subscription to a Subscription Unit that is based in the IT Operations Management (ITOM) Visibility application or in the ITOM Discovery application. As defined in the section titled "Managed IT Resource Types" in [ServiceNow Subscription Unit Overview](#) for your subscription, for managed IT resources that are created or modified in the CMDB by this Service Graph Connector, but that aren't yet managed by [ITOM Visibility](#) or [ITOM Discovery](#), these resources will increase Subscription Unit consumption from that application. Review your current Subscription Unit consumption within ITOM Visibility or ITOM Discovery to ensure available capacity.

Dependencies and requirements:

- The Integration Commons for CMDB store app, which is automatically installed.
- The CMDB CI Class Models store app store app, which is automatically installed.
- Discovery Core plugin (com.snc.discovery.core), which is automatically installed by Discovery.
- The ITOM Discovery License plugin (com.snc.itom.discovery.license). You must activate this plugin.
- ITOM Licensing plugin (com.snc.itom.license). For more information, see Request Discovery.

- Guided Setup (com.sn.ads.setup).
- Data Stream (com.glide.hub.action_type.datastream).
- ITOM Patterns.

Roles required:

- SentinelOne Role - viewer
- ServiceNow AI Platform® Role - admin

Guided Setup

The guided setup for the Service Graph Connector for SentinelOne provides an organized sequence of tasks to configure the integration on your instance.

Procedure

1. Navigate to **Service Graph Connectors > SentinelOne > Setup**.
2. On the Home page, select **Continue**.
3. On the Experience page, select the **Best Experience** from it.
4. On the Service Graph Connector for SentinelOne page in the Configure the connection page, select the **Configure SentinelOne Authentication Credentials** task and follow these steps:
 - a. In the API Key field, enter your SentinelOne API Key and update the credential record.
 - b. Select the **Mark as Complete** checkbox and select **Continue**.
5. In the **Configure SentinelOne HTTP Connection** task follow these steps:
 - a. Add the SentinelOne base URL (Uniform Resource Locator).
 - b. Select the **Mark as Complete** checkbox and select **Continue**.
6. In the **Test Connection** task follow these steps:
 - a. Select the **Test Connection** link.

The Status code field displays 200 if the connection is successful.

- b. Select the **Mark as Complete** checkbox and select **Continue**.
7. (Optional) To create another connection, select the **Update Data Source Access** section and follow these steps:
 - a. Give permission to create and update the data source.
 - b. Select the **Mark as Complete** checkbox and select **Continue**.
 - c. Give permission to create and update the Scheduled Import Sets.
 - d. Select the **Mark as Complete** checkbox and select **Continue**.
 - e. Clear the cache with the code snippet mentioned previously using Scripts-Background.
 - f. Select the **Mark as Complete** checkbox and select **Continue**.
 - g. Add a new connection by clicking the link.
 - h. After you add a new connection, select the **Mark as Complete** checkbox and select **Continue**.
 - i. Select the new connection record and select the **Test Connection link**.

The Status code field displays 200 if the connection is successful.
 - j. Select the **Mark as Complete** checkbox and select **Continue**.
8. Fill out the fields on the Scheduled Data Import form:

Field	Description
Name	Name of the scheduled job.
Data source	Data source record that defines the data to import.
Run as	Option to run the scheduled job with the credentials of the specified user.

Field	Description
Active	Option to activate the scheduled job. Select this option.
Concurrent Import	Function that loads the data from multiple import sets. The function then processes and transforms the data concurrently.
Partition Method	Partition method for the concurrent import set.
Partition Size	Import set size for early scheduling.
Execute pre-import script	Option to specify a script to run before the import is performed.
Execute post-import script	Option to specify a script to run after the import is performed.
Application	Application that contains this scheduled job.
Run	Frequency of running the import.
Conditional	Conditions under which this job is executed.

9. Click **Execute Now**.

10. In the Help task bar, select **Mark as Complete**.

CMDB classes targeted in the Service Graph Connector for SentinelOne

When you complete setting up the connection, you can configure the integration to periodically pull data. The data is saved in tables that extend from the Configuration item [cmdb_ci] table.

AWS Datacenter [cmdb_ci_aws_datacenter]

The following attributes in the AWS Datacenter [cmdb_ci_aws_datacenter] table are populated by collected data.

Attribute label	Attribute name
Object Id	object_id
Region	region
Name	name

Relationships for AWS Datacenter

Parent Class	Relationship Type	Child Class
AWS Datacenter [cmdb_ci_aws_datacenter]	Hosted On: Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]

Azure Datacenter [cmdb_ci_azure_datacenter]

The following attributes in the Azure Datacenter [cmdb_ci_azure_datacenter] table are populated by collected data.

Attribute label	Attribute name
Object Id	region
Name	name
Region	region

Relationships for Azure Data Center

Parent Class	Relationship Type	Child Class
Azure Datacenter [cmdb_ci_azure_datacenter]	Hosted On: Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]

Availability Zone [cmdb_ci_availability_zone]

The following attributes in the Availability Zone [cmdb_ci_availability_zone] table are populated by collected data.

Relationships for Availability Zone

Parent Class	Relationship Type	Child Class
Azure Datacenter [cmdb_ci_azure_datacenter]	Contains:Contained by	Availability Zone [cmdb_ci_availability_zone]

Attribute label	Attribute name
Name	name
Object Id	object_id
Region	region

GCP Datacenter [cmdb_ci_google_datacenter]

The following attributes in the GCP Datacenter [cmdb_ci_google_datacenter] table are populated by collected data.

Attribute label	Attribute name
Name	name
Object Id	object_id

Attribute label	Attribute name
Account Id	account_id
Datacenter Type	datacenter_type

Relationships for GCP Datacenter

Parent Class	Relationship Type	Child Class
GCP Datacenter [cmdb_ci_google_datacenter]	Hosted On: Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]

Cloud Service Account [cmdb_ci_cloud_service_account]

The following attributes in the Cloud Service Account [cmdb_ci_cloud_service_account] table are populated by collected data.

Attribute label	Attribute name
Name	name
Object Id	object_id
Account Id	account_id
Datacenter Type	datacenter_type

Relationships for Cloud Service Account

Parent Class	Relationship Type	Child Class
Network [cmdb_ci_network]	Hosted On: Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]

Cloud Subnets [cmdb_ci_cloud_subnet]

The following attributes in the Cloud Subnets [cmdb_ci_cloud_subnet] table are populated by collected data.

Attribute label	Attribute name
Object Id	object_id
Name	name

Relationships for Cloud Subnets

Parent Class	Relationship Type	Child Class
Network [cmdb_ci_network]	Contains:Contained by	Cloud Subnets [cmdb_ci_cloud_subnet]

Hardware Type [cmdb_ci_compute_template]

The following attributes in the Hardware Type [cmdb_ci_compute_template] table are populated by collected data.

Attribute label	Attribute name
Name	name
Object Id	object_id

Relationships for Hardware Type

Parent Class	Relationship Type	Child Class
Compute Template [cmdb_ci_compute_template]	Hosted On: Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]

Parent Class	Relationship Type	Child Class
VM Instance [cmdb_ci_vm_instance]	Provisioned From::Provisioned	Compute Template [cmdb_ci_compute_template]

Cloud Network [cmdb_ci_network]

The following attributes in the Cloud Network [cmdb_ci_network] table are populated by collected data.

Attribute label	Attribute name
Object Id	object_id
Name	name

Relationships for Cloud network

Parent Class	Relationship Type	Child Class
Network [cmdb_ci_network]	Hosted on::Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]

Virtual Machine Instance [cmdb_ci_vm_instance]

The following attributes in the Virtual Machine Instance [cmdb_ci_vm_instance] table are populated by collected data.

Attribute label	Attribute name
Object Id	object_id
Name	name
VM Instance ID	vm_inst_id

Relationships for VM Instance

Parent Class	Relationship Type	Child Class
VM Instance [cmdb_ci_vm_instance]	Hosted On: Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]
VM Instance [cmdb_ci_vm_instance]	Virtualized by::Virtualizes	Server [cmdb_ci_server]
VM Instance [cmdb_ci_vm_instance]	Hosted On: Hosts	AWS Datacenter [cmdb_ci_aws_datacenter]

Key Value [cmdb_key_value]

The following attributes in the Key Value [cmdb_key_value] table are populated by collected data.

Attribute label	Attribute name
Key	key
Value	value
Tag	tag

Image [cmdb_ci_os_template]

The following attributes in the Image [cmdb_ci_os_template] table are populated by collected data.

Attribute label	Attribute name
Object Id	object_id
Name	name

Relationships for Image

Parent Class	Relationship Type	Child Class
Image [cmdb_ci_os_template]	Hosted on::Hosts	Cloud Service Account [cmdb_ci_cloud_service_account]

Server [cmdb_ci_server]

The following attributes in the Server [cmdb_ci_server] table are populated by collected data.

Attribute label	Attribute name
Name	name
Serial number	serial_number
CPU speed (MHz)	cpu_speed
CPU count	cpu_count
RAM (MB)	ram
OS Address Width (bits)	os_address_width
Operating System	os
CPU core count	cpu_core_count
Fully qualified domain name	fqdn
CPU name	cpu_name
First Discovered	first_discovered

Computer [cmdb_ci_computer]

The following attributes in the Computer [cmdb_ci_computer] table are populated by collected data.

Attribute label	Attribute name
Name	name
Serial number	serial_number
CPU speed (MHz)	cpu_speed
CPU count	cpu_count
RAM (MB)	ram
OS Address Width (bits)	os_address_width
Operating System	os
CPU core count	cpu_core_count
Fully qualified domain name	fqdn
CPU name	cpu_name
First Discovered	first_discovered

SentinelOne Asset Tags [sn_sec_sgc_sntlone_asset_tags]

The following attributes in the SentinelOne Asset Tags [sn_sec_sgc_sntlone_asset_tags] table are populated by collected data.

Attribute label	Attribute name
ID	tags_id
Key	tags_key

Attribute label	Attribute name
Value	tags_value
Assigned At	tags_assignedat
Assigned By	tags_assignedby
Assigned By ID	assigned_by_id

IP Address [cmdb_ci_ip_address]

The following attributes in the IP Address [cmdb_ci_ip_address] table are populated by collected data.

Attribute label	Attribute name
IP Address	ip_address
Name	name
Nic	nic
IP version	ip_version

Relationships for IP Address

Parent Class	Relationship Type	Child Class
Server [cmdb_ci_server]	Owns:Owned by	IP Address [cmdb_ci_ip_address]

Network Adapter [cmdb_ci_network_adapter]

The following attributes in the Network Adapter [cmdb_ci_network_adapter] table are populated by collected data.

Attribute label	Attribute name
Mac Address	mac_address
Name	name
Ip Default Gateway	ip_default_gateway
Discovery Source	discovery_source

Relationships for Network Adapter

Parent Class	Relationship Type	Child Class
Server [cmdb_ci_server]	Owns:Owned by	Network Adapter [cmdb_ci_network_adapter]

SentinelOne Additional Attributes [sn_sec_sgc_sntlone_additional_attributes]

The following attributes in the SentinelOne Additional Attributes [sn_sec_sgc_sntlone_additional_attributes] table are populated by collected data.

Attribute label	Attribute name
NetworkInterfaces Name	networkinterfaces_name
NetworkInterfaces GatewayMacAddress	networkinterfaces_gatewaymacaddress
UUID	uuid
Configuration item	configuration_item
Network Quarantine Enabled	network_quarantine_enabled
Last Successful Scan Date	last_successful_scan_date

Attribute label	Attribute name
License_Key	license_key
First Discovered	first_discovered
Location Enabled	location_enabled
Ad ComputerDistinguishedName	ad_computerdistinguishedname
Agent Version	agent_version
Scan Status	scan_status
Scan Started At	scan_started_at
ID	id
IP Address Subnet	ip_address_subnet
Mitigation Mode Suspicious	mitigation_mode_suspicious
Last Scan Finished At	last_scan_finished_at
Firewall Enabled	firewall_enabled
Console Migration Status	console_migration_status
Group ID	group_id
Operational State Expiration	operational_state_expiration
Last IP To Mgmt	last_ip_to_mgmt
Threat Reboot Required	threat_reboot_required
Machine Type	machine_type
Is Pending Uninstall	is_pending_uninstall ranger_status

Attribute label	Attribute name
Ranger Status	
Ad LastUserDistinguishedName	ad_lastuserdistinguishedname
Agent Up To Date	agent_up_to_date
Ranger Version	ranger_version
Last Boot Time	last_boot_time
Disk Encryption Status	disk_encryption_status
Mitigation Mode	mitigation_mode
Last Full Scan	last_full_scan
Agent Uninstalled	agent_uninstalled
Extenal Id	extenal_id
Updated At	updated_at
Last Scan Aborted At	last_scan_aborted_at
Network Status	network_status
Show Alert Icon	show_alert_icon
Subscribed On	subscribed_on
Account ID	account_id
Recently Active	recently_active
Active Threats	active_threats
Allow Remote Shell	allow_remote_shell
Site Name	site_name

Attribute label	Attribute name
First Full Mode Time	first_full_mode_time
Infected	infected
App Vulnerability Status	app_vulnerability_status
Site ID	site_id
Agent Installer Type	agent_installer_type
Account Name	account_name
NetworkInterfaces Name	networkinterfaces_name
NetworkInterfaces GatewayMacAddress	networkinterfaces_gatewaymacaddress
NetworkInterfaces ID	networkinterfaces_id
user_actions_needed	user_actions_needed
aws_security_group	aws_security_group
proxyState_console	proxyState_console
proxyState_deepVisibility	proxyState_deepVisibility
Ad UserPrincipalName	ad_userPrincipalName
Ad ComputerMemberOf	ad_computerMemberOf
Ad ComputerDistinguishedName	ad_computerDistinguishedName
Ad LastUserMemberOf	ad_lastUserMemberOf
Ad LastUserDistinguishedName	ad_lastUserDistinguishedName
Ad Mail	ad_mail
Agent Decommissioned	agent_decommissioned

Attribute label	Attribute name
Agent Operational State	agent_operational_state
Last Active Date	last_active_date
Group Updated At	group_updated_at
Missing Permissions	missing_permissions

Service Graph Connector for SentinelOne Properties

Property	Description
sn_sec_sgc_sntlone.api_page_size	Enter the number of records per page to retrieve. • Type: string • Default value: 1000 • Location: System Property [sys_properties] table

Note: To open the System Properties [sys_properties] table, enter sys_properties.LIST in the navigation filter.