

Zurich ServiceNow AI Platform Capabilities

Last updated: January 16, 2026

Some examples and graphics depicted herein are provided for illustration only. No real association or connection to ServiceNow products or services is intended or should be inferred.

This PDF was created from content on docs.servicenow.com. The web site is updated frequently. For the most current ServiceNow product documentation, go to docs.servicenow.com.

Company Headquarters

2225 Lawson Lane
Santa Clara, CA 95054
United States
(408)501-8550

Service Graph Connector for Splunk

The Service Graph Connector for Splunk pulls in asset inventory data (hardware and software) from the Splunk database into the Configuration Management Database (CMDB) application in your ServiceNow AI Platform® instance.

Request apps on the Store

Visit the [ServiceNow Store](#) website to view all the available apps and for information about submitting requests to the store. For cumulative release notes information for all released apps, see the [ServiceNow Store version history release notes](#).

Supported versions

Supported versions:

- Xanadu
- Washingtondc
- Vancouver

Use cases

By default, the Service Graph Connector for Splunk pulls the following basic forwarding details:

- Forwarder's version
- Forwarder's type
- Forwarder's last check-in time
- OS
- Host
- Host IP address

With the [Service Graph Connector for Splunk add-on](#), you have the option to import extended data for your Windows and Linux assets

with the Service Graph Connector for Splunk that includes the following details:

- MAC address
- Operating system details
- Asset name
- Software details
- File system
- Last logon date
- Open ports

This data is stored in the Configuration Management Database (CMDB) and Splunk Asset Details extension attributes custom tables. To import these extended asset details, the add-on is required. See [Install the add-on for the Service Graph Connector for Splunk](#).

Guided setup

The guided setup for the Service Graph Connector for Splunk provides an organized sequence of tasks to configure the integration on your instance. To access the guided setup, see the section titled Configure the Service Graph Connector for Splunk.

CMDB integrations dashboard

The Integration Commons for CMDB store app provides a dashboard with a central view of the status, processing results, and processing errors of all installed integrations. You can see metrics for all integration runs. You can filter the view to a specific CMDB integration, a specific time duration, or a specific integration run. For more details about monitoring integrations in the CMDB Integrations Dashboard, see [Using the CMDB Integrations Dashboard](#).

Configure the Service Graph Connector for Splunk

Configure your connections, set up scheduled imports, verify successful connections and optionally add multiple instances in the Guided Setup.

Before you begin

To use this Service Graph Connector, you need a subscription to a Subscription Unit that is based in the IT Operations Management (ITOM) Visibility application or in the ITOM Discovery application. As defined in the section titled "Managed IT Resource Types" in [ServiceNow Subscription Unit Overview](#) for your subscription, for managed IT resources that are created or modified in the CMDB by this Service Graph Connector, but that aren't yet managed by [ITOM Visibility](#) or [ITOM Discovery](#), these resources will increase Subscription Unit consumption from that application. Review your current Subscription Unit consumption within ITOM Visibility or ITOM Discovery to ensure available capacity.

- The [Integration Commons for CMDB](#) store app, which is automatically installed.
- The CMDB CI class models store app, which is automatically installed. See [CMDB CI Class Models](#).
- The ITOM Discovery License plugin (com.snc.itom.discovery.license). You must activate this plugin.
- ITOM Licensing plugin (com.snc.itom.license). For more information, see [Request Discovery](#).
- The Datastream Action plugin (com.glide.hub.action_type.datastream), which is automatically installed.
- Optional: Only required for event ingestion. Observability Commons for CMDB (sn_observability). If used, this app must be installed prior to installing the connector for Event Management to work. For more information, see [Observability Commons for CMDB](#) on the ServiceNow Store.

Role required: admin

Procedure

1. Navigate to **All > Service Graph Connectors > Splunk > Setup** in the navigation panel in your instance.
2. On the Welcome to Guided Setup Home page, select **Continue**.

3. On the Experience page that is displayed, select **Best Experience** followed by **Continue**.

On the Service Graph Connector for Splunk page, there are three tasks displayed:

- Configure the connection
- Add multiple instances
- Set up scheduled import jobs

4. Select **Configure the connection** to expand it.
There are three tasks:

- Configure Splunk authentication credentials
- Configure Splunk HTTP Connection
- Test Connection

5. Select **Configure Splunk authentication credentials** and fill in the fields.

- a. Enter a name for the credentials, for example **SG-Splunk Credentials**.
- b. Verify the **Active** check box is selected.
- c. Enter your User name and Password for your Splunk instance.
- d. Leave the other field values in their current settings.
- e. Right-click in the gray header titled Basic Auth Credentials and select **Save**.
- f. Select **Mark as complete** followed by **Continue**.
The Configure Splunk HTTP Connection page is displayed.

6. Configure the Splunk HTTP connection.

- a. Fill in the fields.

Field	Value
Name	Connection name, sG-splunk Connection, for example.
Active	Selected.
Credential	Credentials to use for the connection. Select one from the list.
Domain	global.
Connection alias	Select one from the list. sn_sec_sgc_splunk.SGSplunk , for example
URL builder	Select the check box. Fill in the new fields.
Host	Splunk domain part of the URL without the 'https'. An example might be splunk3.com or an IP address.
Override default port	The Splunk instance port,8089, for example.
Protocol	https.
(Optional) Use MID server	Select the check box for a dedicated MID Server for the connection, if available. a. Select Specific MID Server from the MID Selection drop down list. b. Select a MID Server from the list.

Field	Value
	Note: A MID Server is required for on-premise connections if the connection is not publicly accessible.

- b. Right-click in the gray header titled HTTP(s) Connection and select **Save**.
- c. Select **Mark as complete** followed by **Continue**.
The Test Connection page is displayed.
- d. (Optional) Set the flag for the **is the servicenow addon installed** (is_snow_addon_installed).
By default, the property on the Service Graph Connection Properties tab is set to **false**.

Option	Description
false	The default query is set to extract only essential information about the forwarder that includes the host name and the operating system.
true	The query offers more information about the forwarder along with extensive asset details via the ServiceNow add-on. This data is imported only if the add-on is installed on the Splunk instance.

7. Test the connection.

- a. Select the **Test Connection** link under Related Links.

If the connection is successful, 201 is displayed in the Status Code field and a message is displayed after a few moments. If your connection test fails, review the Message and Suggestion fields for how to proceed.

- b. After a successful test, right-click in the gray header titled Service Graph Connections and select **Save**.
 - c. Select **Mark as complete** followed by **Continue**.
The steps for Add Multiple Instances is displayed. To add multiple instances, proceed to step 9. This step is optional and you might prefer to wait after you confirm you can import data before setting up multiple instances. To set the import schedule, follow the steps below.
8. To configure the scheduled job, select **Set up scheduled import jobs** from the drop down list under Add Multiple Instances in the header.
- a. On the Configure the scheduled jobs page, select a record under Scheduled Data Imports.
 - b. Select the frequency from the list for the Run field.
If you want to run a test import prior to scheduling it, you might prefer to select **Once**.
 - c. Select the **Active** box to activate the scheduled job.
 - d. (Optional) Edit the fields as required.

You might prefer to leave these fields in their default settings for the first few runs to confirm data imports.

Field	Value
Name	Unique Name for scheduled job.
Application	Read-only: Service Graph Connector for Splunk
Data source	Data source used.

Field	Value
Run as	Run the scheduled job with the credentials of another specified user.
Time	When you want the job to run.
Conditional	Specific conditions under which this job is run.
Use connection	Leave this check box deactivated for the first run. Specifies another connection and credentials for this job.
Concurrent import	Leave check box activated. Splits data into multiple imports sets. See the field message for more information.
Partition Method	Leave as Custom size.
Partition size	15,000. Leave this value for the import set size for early scheduling.
Execute pre-import script	Leave check box activated. Specifies a script to run before the import is performed.
Execute post-import script	Leave check box activated. Specifies a script to run after the import is performed.

- e. (Optional) Select **Execute now** to run the job.
If you do not choose to run the job on-demand, the next job runs according to the schedule you set.
- f. Right-click in the gray header titled Scheduled Data Import and select **Save**.
- g. Select **Mark as complete** followed by **Continue**.

The main task page is displayed.

9. (Optional) To add multiple instances, select **Update Data Sources**.

When indicated, follow the steps listed at the top of the page to switch the application scope with the application picker to open, edit, and save the record.

- a. On the Update Data Source Access page, select **Data Source**.
- b. On the page that is displayed, select the **Application Access** tab.
- c. Review the access settings and update as needed.
- d. Right-click in the gray header titled Table and select **Save**.
- e. Select **Mark as complete** followed by **Continue**.
- f. On the **Update Schedule Data Import** record, select **Schedule Data Import** to open it.
- g. Select the **Application Access** tab to view the permission settings.
- h. When you are satisfied with the settings, right-click in the gray header titled Tables and select **Save**.
- i. Select **Mark as complete** followed by **Continue**.
- j. Follow the steps listed at the top of the page to switch the application scope with the application picker to open, edit, and save the record.
- k. On the Add Another Connection page, select the **Click here** link. The Flow Designer connection page is displayed and you can create a new connection.
- l. From this page, select **Add Connection**.
- m. Fill in the fields with your connection information.

Field	Description
Splunk Connection name	Unique name for your connection.

Field	Description
Splunk Connection URL	Connection URL in https format.
User name	Splunk user name.
Password	Splunk password.

- n. Select **Create Connection**.
Your connections are displayed on the page.
 - o. On the Add Multiple Instance page, select **Mark as complete** followed by **Continue**.
The Configure MID Server for New HTTP Connection page is displayed.
 - p. Locate your new connection and select it to open the record.
The connection URL is displayed in the Connection URL field.
 - q. (Optional) Select the Use MID server check box to add a MID Server.
 - a. Select **Specific MID Server** from the MID Selection drop down list.
 - b. Select a MID Server from the list.
 - r. Right-click in the gray header titled HTTP(s) Connection and select **Save**.
 - s. Select **Mark as complete** followed by **Continue**.
The Test New Connections page is displayed.
10. Test the new connection.
- a. Scroll and select the connection you want to test.
 - b. Select the **Test Connection** link under Related Links.
If the connection is successful, 201 is displayed in the Status Code field and a message is displayed after a few moments. If your connection test fails, review the Message and Suggestion fields for how to proceed.

- c. After a successful test, right-click in the gray header titled Service Graph Connections and select **Save**.
- d. Select **Mark as complete** followed by **Continue**.
The Configure the scheduled jobs page is displayed
- e. On the Service Graph Connector for Splunk page for Guided Setup, select **Complete** to finish the configuration.

Service Graph Connector for Splunk add-on

Import more detailed asset data with the Service Graph Connector for Splunk with an add-on developed by ServiceNow engineering. The add-on permits you to import data about your Windows and Linux assets.

Service Graph Connector for Splunk

The Service Graph Connector for Splunk retrieves computer and software information from the Splunk product and imports it into the Configuration Management Database (CMDB) in your instance. By default, the following basic data is imported:

- Forwarder's version (agent)
- Forwarder's type (agent)
- Forwarder's last check-in time (agent)
- OS
- Host
- Host IP address

The service graph connector for Splunk is available on the ServiceNow® Store.

The ServiceNow Add-on for Windows and Linux assets

With the Windows and Linux Assets add-on, you have the option to import more detailed asset data with the Service Graph Connector for Splunk that includes the following data:

- MAC address

- Operating system details
- Asset name
- Installed software details
- File system
- Last logon date
- Open ports
- Running processes
- Running services

This add-on is available for download into your Splunk console from [splunkbase](#).

Downloading and installing the add-on

Prior to installing this add-on, you must verify you have installed and activated the following applications and add-ons:

- Service Graph Connector Splunk
- Splunk_TA_nix version 9.0.0 (Linux) or later
- Splunk_TA_windows version 8.9.0 or later add-ons available from [splunkbase](#).

These add-ons permit you to identify and import more specific data related to your Linux and Windows assets with your imports with the Splunk Service Graph Connector API.

For example, searches from these add-ons might provide you with data you want about Windows drivers, Windows Network Adaptors, Linux Hardware, and other OS Details.

Target workloads

In the app.manifest, individual agents on a specific machine send information to a central hub (server) where data is collected, stored, and managed. This central machine is where the apps are installed.

To adjust workloads to specify resources for a search, indexing, or other workloads, in Splunk Web, select **Settings > Workload Management > Workload Rules**.

In the Status column, select the toggle to activate or deactivate individual workload rules.

Supported deployments

This add-on supports the following types of deployments:

- standalone
- distributed
- search head clustering

See Splunk documentation for more information about their supported workloads.

Install the add-on for the Service Graph Connector for Splunk

Install the Splunk add-on developed by ServiceNow® engineering from splunkbase to search for Windows and Linux Assets.

Before you begin

Role required: admin or security_admin

Procedure

1. Navigate to **splunkbase** ([splunkbase](#)) and log in.
2. In your Splunk console, select **Apps > Find More Apps**.
3. Locate the **ServiceNow Add-on for Windows and Linux Assets** app and select **Install**.

Note: You can upgrade from within the app.

4. Follow the prompts.

5. (Optional) Navigate to **Settings > Searches, reports and alerts** to view when searches are scheduled.

Note:

You can change the schedules, but since the schedules run in a specific order and require successful completion before the next search in the list is initiated, you might prefer to leave the settings in their defaults.

After all the searches are completed, the data is grouped from each search into a few coalesced key-value pairings (kvstores) for import into your instance: asset details, asset process details, asset service details, and asset software details.

6. Select **App: Search and Reporting (search) > ServiceNow Add-on for Windows and Linux Assets**.

By default, search data is stored in the following key definitions:

- Asset_index_macro: Index="internal"
- Asset_linux_Index_macro: index="main"
- Asset_windows_index="main"

If you are storing the search data for Linux and Windows in custom indexes, you must update your search macros.

7. To update your search macros, navigate to **Settings > Advanced search > Search macros > Search & Reporting (Search) > ServiceNow Add-on for Windows and Linux Assets ServiceNow_TA_windows_linux_assets**
8. On the Search macros page, update the index as required in the Definition column.
9. (Optional) Adjust workloads to specify resources for search, indexing, and other workloads.
 - a. In Splunk Web, select **Settings > Workload Management > Workload Rules**.
 - b. In the Status column, select the toggle to activate or deactivate individual workload rules.

See [Service Graph Connector for Splunk add-on](#) for more information about target workloads and supported deployments.

CMDB classes targeted in the Service Graph Connector for Splunk

When you complete setting up the connection, you can configure the integration to periodically pull data. The data is saved in tables that extend from the Configuration item [cmdb_ci] table.

Computer [cmdb_ci_computer]

The following attributes in the Hardware [cmdb_ci_computer] table are populated by collected data.

Attribute label	Attribute name
Name	name
Serial Number	serial_number
Operating System	os
OS Version	os_version
CPU name	cpu_name
CPU manufacturer	cpu_manufacturer
CPU type	cpu_type
CPU speed (MHz)	cpu_speed
CPU core count	cpu_core_count
CPU count	cpu_count
Manufacturer	manufacturer

IP Address [cmdb_ci_ip_address]

The following attributes in the IP Address [cmdb_ci_ip_address] table are populated by collected data.

Attribute label	Attribute name
Name	name
IP Address	ip_address

Network Adapter [cmdb_ci_network_adapter]

The following attributes in the Network Adapter [cmdb_ci_network_adapter] table are populated by collected data.

Attribute label	Attribute name
Name	name
MAC Address	mac_address
Manufacturer	manufacturer

Software [cmdb_ci_spkg]

The following attributes in the Software [cmdb_ci_spkg] table are populated by collected data.

Attribute label	Attribute name
Name	name
Version	version

Software Instance [cmdb_software_instance]

The following attributes in the Software Instance [cmdb_software_instance] table are populated by collected data.

Attribute label	Attribute name
Name	name
Product name	software
Installed On	installed_on

Software Installation [cmdb_sam_sw_install]

The following attributes in the Software Installation [cmdb_sam_sw_install] table are populated by collected data. This table is populated only when the Software Asset Management applications are installed.

Attribute label	Attribute name
Display Name	display_name
Version	version
Discovery Source	discovery_source

Splunk Asset Details [sn_sec_sgc_splunk_asset_details]

The following attributes in the Splunk Asset Details [sn_sec_sgc_splunk_asset_details] table are populated by collected data.

Attribute label	Attribute name
Configuration Item	configuration_item
Forwarder GUID	forwarder_guid
Forwarder Type	forwarder_type
Forwarder Version	forwarder_version

Attribute label	Attribute name
Host Name	host_name
Host Status	host_status
Host type	host_type
Last logon date	last_check_in
Model Name	model_name
OS Architecture	os_architecture
OS Build Number	os_build_number
OS Family	os_family

Relationships created for Computer

Parent class	Relationship type	Child class
Computer [cmdb_rel_ci]	Owns::Owned by	IP Address [cmdb_ci_ip_address]
Computer [cmdb_rel_ci]	Owns::Owned by	Network Adapter [cmdb_ci_network_adapter]
Computer [cmdb_rel_ci]	Contains::Contained by	File system [cmdb_ci_file_system]